

HDMI HDBaseT Extender with POH

VE1812

- The VE1812 HDMI HDBaseT Extender with POH is the ideal solution for connecting equipment in remote locations up to 100m over a single Cat 5e / 6 / 6a cable. With Long Reach Mode enabled, the VE1812 can extend HDMI signal up to 150m @1080p.


The VE1812 supports RS-232 and IR signaling pass-through, allowing you to control the HDMI source device from the receiver unit (VE1812R) while also accessing the HDMI display device from the transmitter unit (VE1812T). The IR signals can also be extended in both directions.

The VE1812 features Power over HDBaseT (POH) which sends power from Tx to Rx over Cat 5e / 6 / 6a cable without any additional power supply. The VE1812 is HDMI (3D, Deep Color, 4kx2k) and HDCP compatible. When transmitting HDMI / 4K with a Cat 6a or ATEN 2L-2910 Cat 6 cable, the maximum distance can reach up to 100 meters. The VE1812 is perfect for digital classrooms, video conference rooms, gaming or any installation that requires superior video quality.



Features

- HDBaseT Connectivity – extends an HDMI connection over a long distance via one Cat 5e / 6 / 6a cable
- Supports HDBaseT Long Reach Mode – Up to a maximum range of 150 meters @ 1080p
- 4k x 2k HDMI transmission distance up to 100m over Cat 6a or ATEN 2L-2910 Cat 6 cable
- HDBaseT Anti-jamming – resists signal interference during high-quality video transmission using HDBaseT technology
- POH (Power over HDBaseT) – supplies power from Transmitter to Receiver over a long distance via one Cat 5e / 6 / 6a cable
- Bi-directional RS-232 channel – allows you to connect to serial terminals or serial devices, such as touch screens and barcode scanners
- Bi-directional IR channel – Two way IR protocol delivery by one IR port; IR transmission is processed one direction at a time
- Rack- Mountable



Specifications

Function	VE1812R	VE1812T
Video Input		
Interfaces	N/A	1 x HDMI Type A Female (Black)
Impedance	N/A	100 Ω
Max. Distance	N/A	1.8 m
Video Output		
Interfaces	1 x HDMI Type A Female (Black)	N/A
Impedance	100 Ω	N/A
Video		
Max. Data Rate	10.2Gbps (3.4Gbps per lane)	
Max. Pixel Clock	340 MHz	
Compliance	HDMI (3D, Deep Color, 4K); HDCP Compatible Consumer Electronics Control (CEC)	
Max. Resolutions / Distance	Up to 4K@70m (Cat 5e/6) / 100m (Cat 6a); 1080p@100m (Cat 5e/6/6a) *4K supported: 4096 x 2160 / 3840 x 2160 @ 60Hz (4:2:0); 4096 x 2160 / 3840 x 2160 @ 30Hz (4:4:4)	
Audio		
Input	N/A	1 x HDMI Type A Female (Black)
Output	1 x HDMI Type A Female (Black)	N/A
Control		
RS-232	Connector: 1 x Terminal Block, 3 pole Baud Rate: 19200, Data Bits:8, Stop Bits: 1, no parity and flow control	
IR	1 x Mini Stereo Jack Female (Black)	
Switches		
Long Reach Mode Switch	1 x Slide Switch - ON/OFF	
Firmware Upgrade	1 x Slide Switch - ON/OFF	
Power		
Connectors	1 x DC Jack (Black) with locking	
Consumption	DC 5V, 6.4W	DC 5V, 4.3W
Environmental		
Operating Temperature	0° to 40° C	
Storage Temperature	-20° to 60° C	
Humidity	0 - 80% RH, Non-Condensing	
Physical Properties		
Housing	Metal	Metal
Weight	0.45 kg	0.45 kg
Dimensions (L x W x H) with bracket	14.04 x 12.30 x 3.00 cm	14.04 x 12.30 x 3.00 cm
Dimensions (L x W x H) without bracket	13.60 x 10.10 x 2.90 cm	13.60 x 10.10 x 2.90 cm

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com

Publish Date: 08/2017 V1.0



© Copyright 2017 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.