




Datenblatt - Fiche technique - Data sheet

21.15.1527




ROLINE UTP-Patchkabel Kat.6, orange, 0,5 m

Cordon ROLINE Cat.6 UTP, orange, 0,5 m

ROLINE UTP Patch Cord, Cat.6, orange, 0.5 m

Total length (optional)



Remark : SCABAXX013X XXX XE1201

- (1) XX : Jacket Color
- 01=Black(RAL9011), 02=Gray(RAL7035), 03=Red(RAL3031)
- 05=White(RAL9010), 06=Yellow(RAL1021), 07=Blue(RAL5015)
- 08=Green(RAL6029), 09=Orange(RAL2003), 10=Purple(RAL4005)
- 11=Pink(RAL4003)
- (2) X : Wiring
- 1=T568A, 2=T568B, 3=T568A & T568B combination
- (3) XXX : Length
- (4) Length Unit : 1=cm, 2=meter, 3=feet.
- (3)(4) : 0501=0.5meter(50cm), 0012=1meter, 0102=10meter
- 0033=3feet, 0103=10feet

Specification :

- Material :
- 1. RJ45 Plug : (P/N : PU8850)
- 1-1. Housing : Polycarbonate, UL 94V-2, Transparent color.
- 1-2. Contact material : Phosphor Bronze with 50-60 micro-inch Nickel plated.
- 1-3. Contact finished : Min. 50 micro-inch Gold plated.
- 2. Narrow PVC Molded.
- 3. Cable : UTP UnShielded and Twisted, 4 pair Stranded wire UL material approved. 24 AWG conductor and PVC jacket.
- 4. length mark(latch side) : 0.3M,0.5M,0.75M,1M,1.5M,2M,3M,5M,7M,7.5M, 10M,15M,20M,25M,30M.
- 5. Print : roline UTP PATCH CABLE 24AWG 4PR EIA/TIA-568B.2-1 CAT.6 XXXXXXX-X

DRAWING		17.MAR.2009		Connie	
CHECK	17.MAR.2009	KLi			
APPROVAL	17.MAR.2009	Yty			
SCALE	1/1 (A4)	UNIT	mm	ITEM NO.: 21.15.XXXX	
		DRAWING NO. 21.15.XXXX(SAT)		DES.: C6 UTP Patch Cord	
		DRAWING CLASSIFICATION		SHEET 1 OF 1	

rotronic