

Product Highlights

Rugged Construction

IP55/IP67-rated to safeguard against dust and water to operate in harsh outdoor environments and temperature ranging from -40 up to 50°C

D-Link Nuclias Cloud Management

Extensive range of management functions can be performed centrally and hassle-free, through the Nuclias cloud management platform

Zero-Touch Deployment

Cloud-based auto-configuration allows for swift plug-and-play installation and eliminates the need for on-site setup



DBA-3620P / DBA-3621P

Wireless AC1300 Wave 2 Outdoor Cloud-Managed Access Points

Features

Built for Outdoors

- Protection ratings (IP55 for DBA-3620P and IP67 for DBA-3621P) to safeguard against dust and water
- Wide operating temperature range of -40 to 50 °C

High Performance Wi-Fi


- IEEE 802.11ac Wave 2 wireless standard
- Up to 1.3 Gbps combined throughput²
- MU-MIMO with 2 spatial streams
- 192-bit Enterprise and 128-bit Personal encryption (802.11i)

D-Link Nuclias Cloud Management (1-year license included)

- Centralised cloud-based management
- Zero-touch deployment
- Unlimited scalability with no limitation on the number of supported APs
- Intuitive web and app-based interface
- Real-time at-a-glance network information
- Management of multiple sites and devices through single pane of glass
- Over-the-air firmware updates
- Instant alerts and notifications

The DBA-3620P / DBA-3621P Nuclias Wireless AC1300 Wave 2 Outdoor Cloud-Managed Access Points are high-performance outdoor access points designed specifically for SMB, retail, hospitality, campus, as well as managed service providers. They offer impressive protection ratings to withstand harsh outdoor environments, high combined data rates of up to 1,300 Mbps over two dedicated wireless bands and the latest 192-bit wireless encryption.

The DBA-3620P / DBA-3621P can be easily deployed with zero-touch provisioning and controlled through Nuclias Cloud Management¹ via the web-browser portal or the Nuclias mobile app for tablets. Once connected, the DBA-3620P / DBA-3621P automatically retrieves configuration settings, enabling deployment at remote locations without an on-site network administrator. With D-Link Nuclias, businesses can now more effectively organise their entire wireless network, manage multiple APs simultaneously, and monitor live network statistics. This allows network administrators to focus more on providing reliable connectivity and services and spend less time managing devices.



D-Link Assist

Next Business Day Service

Complimentary Next Business Day Service, as Standard

Your network is the backbone of your business. Keeping it running is essential, even if the unexpected happens. D-Link Assist is a rapid-response technical support service that replaces faulty equipment quickly and efficiently. Maximising your uptime and giving you the confidence that instant support is only a phone call away.

All D-Link products with 5-year or Limited Lifetime warranty come with complimentary Next Business Day Service. D-Link will send out a replacement product to you on the next business day after acceptance of a product failure. On receipt of the replacement product, you simply arrange the return of the defective product to us. Any products with a 2-year/3-year warranty can also benefit from the Next Business Day advance replacement service when the optional 3-year warranty extension has been purchased.

Find out more at eu.dlink.com/services



is a complete cloud-managed networking solution for small to medium-sized organisations with one or more sites.

How it works

Wi-Fi coverage and network capacity are provided by high-performance Access Points and Managed Switches deployed on site, while configuration and ongoing management can be carried out remotely through a web browser or tablet.

Zero-touch provisioning and centralised cloud-based control make the network simpler to install and easier to manage.

With Nuclias, network configurations and software updates are pushed to remote devices through the cloud, without the need to have specialised equipment or personnel onsite.

SSL encrypted, out-of-band network monitoring and management ensures secure connectivity whilst minimising bandwidth requirement.

Main features

- Zero-touch provisioning
- Role-based administration
- Auditable change logs
- Authentication via customisable captive portal, 802.1x and RADIUS server
- Social login for Wi-Fi access supported
- Advanced traffic report and data analysis
- Intuitive web-based interface with multilingual support
- Automatic monitoring and alerts
- Over-the-web firmware upgrades
- Searchable network-wide event log
- Intuitive VLAN Configuration
- Cloud based RF Optimisation

Simpler to install and easier to manage



Unlimited scalability of supported APs



Reporting and analytics









Zero-touch provisioning









Pay-as-you grow Subscription

Technical Specifications		
General	DBA-3620P	DBA-3621P
Interfaces	<ul style="list-style-type: none"> • 1 x 10/100/1000 Mbps Ethernet port <ul style="list-style-type: none"> • 1 x RJ45 Console port • IEEE 802.11a/b/g/n/ac Wave 2 wireless 	
Ethernet Interface	<ul style="list-style-type: none"> • 1 x 10/100/1000 BASE-T LAN Port 	
Standards	<ul style="list-style-type: none"> • IEEE 802.11a/b/n/g/ac Wave 2 • IEEE 802.3az Energy-Efficient Ethernet (EEE) • IEEE 802.3af Power over Ethernet (PoE) <ul style="list-style-type: none"> • IEEE 802.3i/u/ab • IEEE 802.3x Flow Control 	
Antenna	<ul style="list-style-type: none"> • Built-in internal omnidirectional antenna <ul style="list-style-type: none"> » 2.4 GHz: 3.5 dBi » 5 GHz: 5 dBi • 2 x R-SMA connectors for external antennas 	<ul style="list-style-type: none"> • 2 x external Type-N antennas <ul style="list-style-type: none"> » 2.4 GHz: 3.5 dBi » 5 GHz: 5 dBi
Data Signal Rate ²	<ul style="list-style-type: none"> • 2.4 GHz: Up to 400 Mbps • 5 GHz: Up to 867 Mbps 	
Functionality		
Security	<ul style="list-style-type: none"> • Latest 128/192-bit Personal/Enterprise wireless encryption <ul style="list-style-type: none"> • MAC address filtering • SSID isolation • Guest isolation • Captive portal • Station isolation <ul style="list-style-type: none"> • SAE • AES 	
Maximum SSIDs	<ul style="list-style-type: none"> • Up to 16 SSIDs per device • Up to 8 SSIDs per wireless band 	
Physical		
Dimensions	• 291.9 x 115 x 65.5 mm	• 460 x 160 x 79.5 mm
Weight	<ul style="list-style-type: none"> • 0.822 kg without bracket • 0.853 kg with bracket 	• 1.38kg without bracket
Power Input	<ul style="list-style-type: none"> • IEEE 802.3af Power over Ethernet (PoE) 	
Power Consumption	<ul style="list-style-type: none"> • PoE: 13.5 W 	
Temperature	<ul style="list-style-type: none"> • Operating: -40 to 50 °C (-40 to 122 °F) • Storage: -40 to 65 °C (-40 to 149 °F) 	
Humidity	<ul style="list-style-type: none"> • Operating: 10% to 90% non-condensing • Storage: 5% to 95% non-condensing 	
Mean Time Between Failure (MTBF)	• 1,142,136 hours	• 1,305,297 hours
Mounting Options	<ul style="list-style-type: none"> • Pole mount • Wall mount 	<ul style="list-style-type: none"> • Pole mount • Wall mount
Certifications	<ul style="list-style-type: none"> • CE Class B • FCC Class B • UL • IC Class B 	<ul style="list-style-type: none"> • CE Class B • FCC Class B • UL • IC Class B

Antenna Pattern - DBA-3620P

Orientation	H-Plane	E-Plane
<p>2.4 GHz Antenna Wall Mounted</p> 		
<p>5 GHz Antenna Wall Mounted</p> 		

Antenna Pattern - DBA-3621P

Orientation	H-Plane	E-Plane
<p>2.4 GHz Antenna Wall Mounted</p> 		
<p>5 GHz Antenna Wall Mounted</p> 		

Nuclias Wireless AC1300 Wave 2 Outdoor Cloud-Managed Access Points

Nuclias Cloud Network Solution Features		
Scalability	<ul style="list-style-type: none"> • Unlimited number of APs can be supported 	
Out-of-band Cloud Architecture	<ul style="list-style-type: none"> • Allows only device management control packets between cloud controller and devices. This allows the network to stay up if the connection to the controller is lost. • Client data traffic flows directly to the destination on the LAN or across the WAN. 	
Setup Highlights	<ul style="list-style-type: none"> • Zero-touch provisioning • Centralised management of all network devices 	<ul style="list-style-type: none"> • Flexible WLAN group creation
Wi-Fi Highlights	<ul style="list-style-type: none"> • Enterprise-class 802.11ac support • Band steering 	<ul style="list-style-type: none"> • PSK (WPA/WPA2), 802.1x/RADIUS authentication • SSID scheduling
Guest Wi-Fi	<ul style="list-style-type: none"> • Open, click-through, PSK, captive portal • Social login with Facebook and Google • Multiple admin portal access privileges 	<ul style="list-style-type: none"> • SSID scheduling • Free Wi-Fi access with time limit
RF Features	<ul style="list-style-type: none"> • Channel and power control per device group • Background scan of APs and clients 	<ul style="list-style-type: none"> • Client isolation • Selected auto channel for both 2.4 and 5 GHz bands
Security	<ul style="list-style-type: none"> • IP and MAC Filtering • Rogue AP detection • All traffic from AP to cloud is encrypted • Client data traffic is locally terminated (not sent to the cloud) 	
Network Health Monitoring and Troubleshooting	<ul style="list-style-type: none"> • Single pane dashboard view of all connected devices and clients, with usage details • Email notifications for network alerts • Track individual Wi-Fi client data: signal strength, speed, association history • Event logs sorted by venue, SSID, AP, client 	<ul style="list-style-type: none"> • Event logs for client joining, firmware upgrade, channel change, device online, device registration etc. • Alarms generated for AP status • Integrated ping and traceroute tools • Visual LED to check for cloud connectivity • Remotely reboot APs
Reporting	<ul style="list-style-type: none"> • Complete traffic report (per device group, AP, SSID, radio) • Unique client report (tracking 2.4 vs 5 GHz clients over time) • Report duration: up to 2 months (archived report duration can be customized based on local regulations) 	
IPv6 Readiness	<ul style="list-style-type: none"> • Future ready with full support for IPv6 	
Other Highlights	<ul style="list-style-type: none"> • Customisable management console • Schedule-based over-the-web firmware upgrade • Import floor plan to venue to visualize physical location of APs 	<ul style="list-style-type: none"> • Google Maps integration • Multi-language support • Responsive console design that auto fits viewing in different devices (laptops, tablets, mobile phones)
Supported Hardware	<ul style="list-style-type: none"> • Access Points <ul style="list-style-type: none"> • DBA-1210P (Dual-Band AC1300) • DBA-2520P (Dual-Band AC1900) • DBA-2820P (Dual-Band AC2600) • DBA-X1230P (Dual-Band AX1800)³ • DBA-X2830P (Dual-Band AX3600) • DBA-3620P (IP55 Outdoor Dual-Band AC1300) • DBA-3621P (IP67 Outdoor Dual-Band AC1300) 	<ul style="list-style-type: none"> • Switches <ul style="list-style-type: none"> • DBS-2000-10MP (10-Port Gigabit, Max PoE) • DBS-2000-28 (28-Port Gigabit) • DBS-2000-28MP (28-Port Gigabit, Max PoE) • DBS-2000-28P (28-Port Gigabit, PoE) • DBS-2000-52 (52-Port Gigabit) • DBS-2000-52MP (52-Port Gigabit, Max PoE)
Subscription Licenses	<ul style="list-style-type: none"> • DBA-WW-Y1-LIC • Nuclias 1 Year Cloud Managed Access Point License 	<ul style="list-style-type: none"> • DBA-WW-Y3-LIC • Nuclias 3 Year Cloud Managed Access Point License

¹ Active D-Link Nuclias account and valid device license required. 1-year license included.

² Maximum wireless signal rate derived from the IEEE Standard 802.11ac specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental factors may adversely affect wireless signal range.

³ Available Q4 2020



For more information: www.dlink.com

D-Link European Headquarters. D-Link (Europe) Ltd., First Floor, Artemis Building, Odyssey Business Park, West End Road, South Ruislip HA4 6QE, United Kingdom. Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2020 D-Link Corporation. All rights reserved. E&OE.

Updated July 2020

