# User Manual

## Command Line Interface

### Managed Switch Software

© 2026, Shenzhen Cudy Technology Co., Ltd.

# USING THIS DOCUMENT

This document is intended for the software engineer's general information on the usage of switch source files for the chip development of the switch team.

Though every effort has been made to ensure that this document is current and accurate, more information may have become available subsequent to the production of this guide.

# Content


1. AAA ..... - 1 -
aaa authentication ..... - 1 -
login authentication ..... - 3 -
ip http login authentication ..... - 4 -
enable authentication ..... - 5 -
show aaa authentication ..... - 6 -
show line lists ..... - 7 -
tacacs default-config ..... - 8 -
tacacs host ..... - 9 -
show tacacs default-config ..... - 11 -
show tacacs ..... - 11 -
show default-config ..... - 12 -
radius host ..... - 13 -
show radius default-config ..... - 15 -
show radius ..... - 15 -

2.ACL ..... - 16 -
mac acl ..... - 16 -
permit (MAC) ..... - 17 -
deny (MAC) ..... - 19 -
ip acl ..... - 20 -
permit (IP) ..... - 21 -
deny (IP) ..... - 24 -
ipv6 acl ..... - 26 -
Permil(IPv6) ..... - 27 -
deny (IPv6) ..... - 30 -
bind acl ..... - 32 -
show acl ..... - 33 -
show acl utilization ..... - 34 -

3.Administration ..... - 35 -
configure ..... - 35 -
clear arp ..... - 36 -
clear line ..... - 37 -
enable ..... - 37 -
end ..... - 39 -
exit ..... - 40 -
history ..... - 41 -
hostname ..... - 42 -
interface ..... - 43 -
ip address ..... - 44 -
ip default-gateway ..... - 45 -
ip dhcp ..... - 46 -
ip domain lookup ..... - 47 -
ipv6 autoconfig ..... - 48 -
ipv6 address ..... - 49 -
ipv6 default-gateway ..... - 50 -
ipv6 dhcp ..... - 51 -
ip name-server ..... - 51 -
ip service ..... - 52 -
ip session-timeout ..... - 53 -
ip ssh ..... - 55 -
line ..... - 56 -
reboot ..... - 57 -
enable password ..... - 57 -
exec-timeout ..... - 59 -
password-thresh ..... - 60 -

ping ..... - 62 -
traceroute ..... - 63 -
silent-time ..... - 64 -
system name ..... - 65 -
system contact ..... - 66 -
system location ..... - 67 -
terminal length ..... - 68 -
username ..... - 69 -
show arp ..... - 70 -
show cpu utilization ..... - 71 -
show history ..... - 72 -
show info ..... - 73 -
show ip ..... - 74 -
show ip dhcp ..... - 74 -
show ip http ..... - 75 -
show ipv6 ..... - 76 -
show line ..... - 77 -
show memory statistics ..... - 78 -
show privilege ..... - 79 -
show username ..... - 79 -
show users ..... - 80 -
show version ..... - 81 -

4.Authentication Manager ..... - 82 -
authentication ..... - 82 -
authentication(Interface) ..... - 83 -
authentication mac radius ..... - 84 -
authentication mac local ..... - 85 -
authentication guest-vlan ..... - 86 -
authentication guest-vlan (Interface) ..... - 87 -
authentication host-mode ..... - 88 -
authentication max-hosts ..... - 89 -
authentication port-control ..... - 90 -
clear authentication sessions ..... - 91 -
show authentication ..... - 92 -
show authentication sessions ..... - 94 -

5. Diagnostic ..... - 95 -
show cable-diag ..... - 95 -
show fiber-transceiver ..... - 96 -

6. DHCP Servre ..... - 98 -
dhcp-client ..... - 98 -
dhcp-relay ..... - 99 -
dhcp-server ..... - 100 -
dhcp-server group (Global) ..... - 100 -
dhcp-server group (Interface) ..... - 101 -
ip pool ..... - 102 -
show dhcp-server clients ..... - 103 -

7. DHCP Snooping ..... - 104 -
ip dhcp snooping ..... - 104 -
ip dhcp snooping vlan ..... - 104 -
ip dhcp snooping trust ..... - 106 -
ip dhcp snooping verify ..... - 107 -
ip dhcp snooping rate-limit ..... - 107 -
clear ip dhcp snooping statistics ..... - 108 -
show ip dhcp snooping ..... - 109 -

8. DOS ..... - 110 -
dos ..... - 110 -
dos(interface) ..... - 113 -
show dos ..... - 114 -

9. Dynamic ARP Inspection ..... - 115 -
ip arp inspection ..... - 115 -
ip arp inspection vlan ..... - 116 -
ip arp inspection trust ..... - 117 -
ip arp inspection validate ..... - 118 -
ip arp inspection rate-limit ..... - 119 -
clear ip arp inspection statistics ..... - 120 -
show ip arp inspection ..... - 121 -
show ip arp inspeciton interface ..... - 121 -

10. GVRP ..... - 122 -
gvrp (Global) ..... - 123 -
gvrp (Interface) ..... - 123 -
gvrp registration-mode ..... - 124 -
gvrp vlan-create-forbid ..... - 125 -
clear gvrp statistics ..... - 126 -
show gvrp statistics ..... - 127 -
show gvrp ..... - 129 -
show gvrp configuration ..... - 130 -

11. IGMP Snooping ..... - 130 -
ip igmp snooping ..... - 131 -
ip igmp snooping version ..... - 131 -
ip igmp snooping querier ..... - 132 -
ip igmp snooping vlan ..... - 133 -
ip igmp snooping vlan fastleave ..... - 134 -
ip igmp snooping vlan query-interval ..... - 135 -
ip igmp snooping vlan response-time ..... - 135 -
ip igmp snooping vlan router ..... - 136 -
ip igmp snooping vlan forbidden-port ..... - 137 -
ip igmp snooping vlan static-port ..... - 138 -
ip igmp snooping vlan static-router-port ..... - 139 -
ip igmp snooping vlan static-group ..... - 140 -
ip igmp snooping vlan group ..... - 141 -
ip igmp profile ..... - 141 -
profile range ..... - 142 -
ip igmp filter ..... - 143 -
ip igmp max-groups ..... - 144 -
ip igmp max-groups action ..... - 145 -
clear ip igmp snooping groups ..... - 145 -
clear ip igmp snooping statistics ..... - 146 -
show ip igmp snooping groups counters ..... - 148 -
show ip igmp snooping groups ..... - 148 -
show ip igmp snooping router ..... - 149 -
show ip igmp snooping querier ..... - 150 -
show ip igmp snooping ..... - 151 -
show ip igmp snooping vlan ..... - 152 -
show ip igmp snooping forward-all ..... - 153 -
show ip igmp profile ..... - 154 -
show ip igmp filter ..... - 155 -
show ip igmp max-group ..... - 156 -
show ip igmp max-group action ..... - 157 -

12. IP Source Guard ..... - 158 -
ip source verify ..... - 158 -
ip source binding ..... - 159 -
show ip source interface ..... - 160 -
show ip source binding ..... - 161 -

13. Link Aggregation ..... - 162 -
lag ..... - 162 -
lag load-balance ..... - 164 -
lacp port-priority ..... - 164 -

lacp system-priority ..... - 165 -
show lacp ..... - 166 -
show lag ..... - 167 -

14. LLDP ..... - 168 -
lldp ..... - 168 -
lldp rx ..... - 169 -
lldp tx ..... - 170 -
lldp lldpdu ..... - 170 -
lldp tlv-select ..... - 172 -
lldp tlv-select pvid ..... - 173 -
lldp tlv-select vlan-name ..... - 174 -
show lldp ..... - 176 -
show lldp local-device ..... - 177 -
show lldp neighbor ..... - 178 -

15.Logging ..... - 179 -
logging ..... - 179 -
logging host ..... - 180 -
logging severity ..... - 181 -
show logging ..... - 183 -
clear logging ..... - 184 -

16.MAC Address Table ..... - 185 -
mac address-table aging-time ..... - 185 -
mac address-table static ..... - 186 -
clear mac address-table ..... - 187 -
show mac address-table ..... - 188 -
show mac address-table counters ..... - 189 -
show mac address-table aging-time ..... - 189 -

17.MAC VLAN ..... - 190 -
vlan mac-vlan group (Global) ..... - 190 -
vlan mac-vlan group (Interface) ..... - 191 -
show vlan mac-vlan groups ..... - 192 -
show vlan mac-vlan interfaces ..... - 193 -

18.Management ACL ..... - 194 -
management access-list ..... - 194 -
management access-class ..... - 194 -
deny ..... - 195 -
permit ..... - 196 -
no sequence ..... - 198 -
show management access-list ..... - 198 -
show management access-class ..... - 199 -

19.MLD Snooping ..... - 200 -
ipv6 mld snooping ..... - 200 -
ipv6 mld snooping report-suppression ..... - 201 -
ipv6 mld snooping version ..... - 202 -
ipv6 mld snooping unknown-multicast action ..... - 203 -
ipv6 mld snooping vlan ..... - 204 -
ipv6 mld snooping vlan fastleave ..... - 204 -
ipv6 mld snooping vlan last-member-query-count ..... - 205 -
ipv6 mld snooping vlan last-member-query-interval ..... - 206 -
ipv6 mld snooping vlan query-interval ..... - 207 -
ipv6 mld snooping vlan response-time ..... - 208 -
ipv6 mld snooping vlan router ..... - 209 -
ipv6 mld snooping vlan static-port ..... - 210 -
ipv6 mld snooping vlan forbidden-router-port ..... - 211 -
ipv6 mld snooping vlan static router port ..... - 211 -
ipv6 mld snooping vlan static-group ..... - 212 -
ipv6 mld snooping vlan group ..... - 213 -
ipv6 mld profile ..... - 214 -

profile range ..... - 215 -
ipv6 mld filter ..... - 216 -
ipv6 mld max-groups ..... - 217 -
ipv6 mld max-groups action ..... - 218 -
clear ipv6 mld snooping groups ..... - 219 -
clear ipv6 mld snooping statistics ..... - 219 -
show ipv6 mld snooping groups counters ..... - 220 -
show ipv6 mld snooping groups ..... - 221 -
show ipv6 mld snooping router ..... - 222 -
show ipv6 mld snooping ..... - 223 -
show ipv6 mld snooping vlan ..... - 224 -
show ipv6 mld snooping forward-all ..... - 225 -
show ipv6 mld profile ..... - 226 -
show ipv6 mld filter ..... - 227 -
show ipv6 mld max-group ..... - 228 -
show ipv6 mld max-group action ..... - 229 -

20.MVR ..... - 230 -
mvr ..... - 230 -
mvr vlan ..... - 231 -
mvr group ..... - 232 -
mvr mode ..... - 233 -
mvr query-time ..... - 234 -
mvr port type ..... - 235 -
mvr immediate ..... - 237 -
mvr vlan group ..... - 238 -
show mvr members ..... - 240 -
show mvr interface ..... - 241 -
show mvr ..... - 241 -

21.OSPF ..... - 242 -
area ..... - 242 -
network ..... - 243 -
ospf ..... - 244 -
router-id ..... - 244 -
show ospf ..... - 245 -
show ospf database ..... - 246 -
show ospf neighbor ..... - 247 -

22.POE ..... - 248 -
POE ..... - 248 -
poe reboot ..... - 249 -
poe schedule ..... - 250 -
poe watch-dog ..... - 251 -
show poe ..... - 252 -

23.Port Mirror ..... - 253 -
mirror session source interface ..... - 253 -
mirror session destination interface ..... - 254 -
show mirror ..... - 255 -

24.Port ..... - 256 -
description ..... - 256 -
speed ..... - 257 -
duplex ..... - 259 -
shutdown ..... - 260 -
flowcontrol ..... - 261 -
jumbo-frame ..... - 262 -
protected ..... - 263 -
eee ..... - 264 -
clear interface ..... - 265 -
show interface ..... - 266 -

25.Port Error Disable ..... - 267 -

errdisable recovery cause ..... - 267 -
errdisable recovery cause udld ..... - 269 -
errdisable recovery interval ..... - 269 -
show errdisable recovery ..... - 270 -

26 .Port Security ..... - 271 -
port-security (Global) ..... - 271 -
port-security (Interface) ..... - 272 -
port-security address-limit ..... - 273 -
show port-security ..... - 274 -
show port-security interface ..... - 275 -

27. Protocol VLAN ..... - 276 -
vlan protocol-vlan group (Global) ..... - 276 -
vlan protocol-vlan group (Interface) ..... - 277 -
show vlan protocol-vlan ..... - 278 -
show vlan protocol-vlan interfaces ..... - 279 -

28. QOS ..... - 280 -
qos ..... - 280 -
qos cos ..... - 281 -
qos map ..... - 282 -
qos queue ..... - 285 -
qos remark ..... - 287 -
qos trust ..... - 288 -
qos trust (Interface) ..... - 289 -
show qos ..... - 290 -
show qos interface ..... - 291 -
show qos map ..... - 292 -
show qos queueing ..... - 293 -

29.Rate Limit ..... - 294 -
rate limit egress ..... - 294 -
rate-limit ingress ..... - 295 -
rate limit egress queue ..... - 296 -

30.RIP ..... - 297 -
rip ..... - 297 -
network ..... - 297 -
version ..... - 298 -
show rip ..... - 299 -

31.SNMP ..... - 300 -
snmp ..... - 300 -
snmp view ..... - 301 -
snmp group ..... - 302 -
snmp community ..... - 303 -
snmp user ..... - 304 -
snmp engineid ..... - 306 -
snmp engineid remote ..... - 307 -
snmp trap ..... - 307 -
snmp host ..... - 308 -
show snmp view ..... - 310 -
show snmp group ..... - 311 -
show snmp community ..... - 312 -
show snmp user ..... - 312 -
show snmp engineid ..... - 313 -
show snmp trap ..... - 314 -
show snmp host ..... - 315 -

32. RMON ..... - 315 -
rmon event ..... - 316 -
rmon alarm ..... - 317 -
rmon history ..... - 319 -

clear rmon interfaces statistics ..... - 320 -
show rmon interfaces statistics ..... - 321 -
show rmon event ..... - 323 -
show rmon event log ..... - 324 -
show rmon alarm ..... - 324 -
show rmon history ..... - 325 -
show rmon history statistic ..... - 326 -

33. Spanning Tree ..... - 328 -
instance (MST) ..... - 328 -
name (MST) ..... - 329 -
revision (MST) ..... - 330 -
spanning-tree mst configuration ..... - 331 -
spanning-tree mst cost ..... - 332 -
spanning-tree mst port-priority ..... - 333 -
spanning-tree mst priority ..... - 334 -
spanning-tree ..... - 335 -
spanning-tree mode ..... - 336 -
spanning-tree bpdu ..... - 337 -
spanning-tree bpdu-filter ..... - 338 -
spanning-tree bpdu-guard ..... - 339 -
spanning-tree cost ..... - 340 -
spanning-tree forward-delay ..... - 341 -
spanning-tree hello-time ..... - 342 -
spanning-tree maximum-age ..... - 343 -
spanning-tree edge ..... - 344 -
spanning-tree link-type ..... - 345 -
spanning-tree max-hops ..... - 346 -
spanning-tree mcheck ..... - 346 -
spanning-tree pathcost method ..... - 347 -
spanning-tree port-priority ..... - 348 -
spanning-tree priority ..... - 349 -
spanning-tree tx-hold-count ..... - 350 -
show spanning-tree ..... - 351 -
show spanning-tree interface ..... - 352 -
show spanning-tree mst ..... - 353 -
show spanning-tree mst interface ..... - 354 -
show spanning-tree mst configuration ..... - 356 -

34. Static Routing ..... - 356 -
interface vlan (IPv4) ..... - 357 -
ip route ..... - 358 -
arp ..... - 359 -
interface vlan (IPv6) ..... - 360 -
ipv6 address ..... - 361 -
ipv6 route ..... - 362 -
ipv6 neighbors ..... - 363 -
show ip interface vlan ..... - 364 -
show ipv6 interface vlan ..... - 365 -
show ip route ..... - 366 -
show ipv6 route ..... - 367 -
show arp ..... - 367 -
show ipv6 neighbors ..... - 368 -

35. Storm Control ..... - 369 -
storm-control ..... - 369 -
storm-control action ..... - 371 -
storm-control ifg ..... - 372 -
storm-control level ..... - 373 -
storm-control unit ..... - 374 -
show storm-control ..... - 375 -

36. System File ..... - 376 -

copy ..... - 376 -
delete ..... - 378 -
restore-defaults ..... - 379 -
save ..... - 380 -
show config ..... - 381 -
show flash ..... - 382 -
usb install ..... - 383 -
usb remove ..... - 384 -

37. Surveillance VLAN ..... - 384 -
surveillance-vlan (Global) ..... - 384 -
surveillance-vlan (Interface) ..... - 385 -
surveillance-vlan vlan ..... - 387 -
surveillance-vlan oui-table ..... - 388 -
surveillance-vlan cos (Global) ..... - 389 -
surveillance-vlan cos (Interface) ..... - 390 -
surveillance-vlan mode ..... - 391 -
surveillance-vlan aging-time ..... - 393 -
show surveillance-vlan ..... - 394 -

38. Time ..... - 395 -
clock set ..... - 395 -
clock timezone ..... - 396 -
clock source ..... - 397 -
clock summer-time ..... - 398 -
Sntp ..... - 400 -
show clock ..... - 401 -
show sntp ..... - 401 -

39. UDLD ..... - 402 -
udld ..... - 402 -
udld aggressive ..... - 403 -
udld message time ..... - 404 -
udld reset ..... - 405 -
show udld ..... - 406 -

40. VLAN ..... - 407 -
vlan ..... - 407 -
Name (vlan) ..... - 408 -
switchport mode ..... - 409 -
switchport hybrid pvid ..... - 410 -
switchport hybrid ingress-filtering ..... - 411 -
switchport hybrid acceptable-frame-type ..... - 412 -
switchport hybrid allowed vlan ..... - 414 -
switchport access vlan ..... - 415 -
switchport tunnel vlan ..... - 416 -
switchport trunk native vlan ..... - 417 -
switchport trunk allowed vlan ..... - 419 -
switchport default-vlan tagged ..... - 420 -
switchport forbidden default-vlan ..... - 421 -
switchport forbidden vlan ..... - 422 -
switchport vlan tpid ..... - 423 -
management-vlan ..... - 424 -
show vlan ..... - 425 -
show vlan interface membership ..... - 426 -
show interface switchport ..... - 427 -
show management-vlan ..... - 428 -

41. Voice VLAN ..... - 429 -
voice-vlan (Global) ..... - 429 -
voice-vlan (Interface) ..... - 430 -
voice-vlan vlan ..... - 431 -
voice-vlan oui-table ..... - 432 -

voice-vlan cos (Global) ..... - 433 -
voice-vlan cos (Interface) ..... - 435 -
voice-vlan mode ..... - 436 -
voice-vlan aging-time ..... - 438 -
show voice-vlan ..... - 439 -

# 1. AAA

## aaa authentication

### Syntax

**aaa authentication (login | enable) (default** | LISTNAME) METHODLIST [METHODLIST]
[METHODLIST] [METHODLIST]
**no aaa authentication (login | enable)** LISTNAME

### Parameter

| | |
|---|---|
| **login** | Add/Edit login authentication list |
| **enable** | Add/Edit enable authentication list |
| **default** | Edit default authentication list |
| **LISTNAME** | Specify the list name for authentication type |
| **METHODLIST** | Specify the authenticate method, including none, local,<br>enable, tacacs+, radius. |

### Default

Default authentication list name for type login is "default" and default method is "local".
Default authentication list name for type enable is "default" and default method is "enable"

### Mode

Global Configuration

### Usage

Login authentication is used when user try to login into the switch. Such as CLI

login dialog and WEBUI login web page.
Enable authentication is used only on CLI for user trying to switch from User EXEC mode to Privileged EXEC mode.

Both of them support following authenticate methods.
**Local:** Use local user account database to authenticate. (This method is not supported for enable authentication)
**Enable:** Use local enable password database to authenticate.
**Tacacs+:** Use remote Tacas+ server to authenticate.
**Radius:** Use remote Radius server to authenticate.
**None:** Do nothing and just make user to be authenticated.
Each list allows you to combine these methods with different orders. For example, we want to authenticate login user with remote Tacacs+ server, but server may be crashed. Therefore, we need a backup plan, such as another Radius server. So we can configure the list with Tacacs+ server as first authentication method and Radius server as second one.

Use no form to delete the existing list. However, "default" list is not allowed to remove.

**Example**

This example shows how to add a login authentication list to authenticate with order tacacs+, radius, local.
Switch(config)# aaa authentication login test1 tacacs+ radius local

This example shows how to show existing login authentication lists
Switch# **show aaa authentication login lists**
Login List Name | Authentication Method List
----------+----------
Default | local
test1 | tacacs+ radius local

This example shows how to add an enable authentication list to authenticate with order tacacs+, radius, enable.
Switch(config)# **aaa authentication enable test1 tacacs+ radius enable**

This example shows how to show existing enable authentication lists
Switch# **show aaa authentication login lists**
Enable List Name | Authentication Method List
----------+----------
Default | enable

test2 | tacacs+ radius enable

## login authentication

### Syntax

**login authentication LISTNAME**
**no login authentication**

### Parameter

| | |
|---|---|
| *LISTNAME* | Specify the login authentication list name to use. |

### Default

Default login authentication list for each line is "default".

### Mode

Line Configuration

### Usage

Different access methods are allowed to bind different login authentication lists.
Use "**login authentication**" command to bind the list to specific line (console, telnet, ssh).
Use no form to bind the "default" list back.

### Example

This example shows how to create a new login authentication list and bind to telnet line.
**Switch(config)# aaa authentication login test1 tacacs+ radius local**
**Switch(config)# line telnet**
**Switch(config-line)# login authentication test1**
This example shows how to show line binding lists.
Switch# **show line lists**

```
Line Type              |        AAA Type             |     List Name
-------------+--------------------+-----------------
console              |                    login         | default
|          enable       | default
telnet               |                    login       | test1
|          enable       | default
ssh          |                                  login      | default
|          enable                                                |default
http         |             login    | default
https       |                          login     | default
```

## ip http login authentication

### Syntax

**ip** (**http** | **https**) **login authentication** *LISTNAME*
**no ip** (**http** | **https**) **login authentication**

### Parameter

| | |
|---|---|
| **http** | Bind login authentication list to user access WEBUI<br>with http protocol |
| **https** | Bind login authentication list to user access WEBUI<br>with https protocol |
| *LISTNAME* | Specify the login authentication list name to use. |

### Default

Default login authentication list for each line is "default".

### Mode

Global Configuration

### Usage

Different access methods are allowed to bind different login authentication lists.

Use “ip (http | https) login authentication” command to bind the list to WEBUI access from http or https.
Use no form to bind the “default” list back.

**Example**

This example shows how to create two new login authentication lists and bind to http and https.

```
Switch(config)# aaa authentication login test1 tacacs+ radius
local
Switch(config)# aaa authentication login test2
radius local
Switch(config)# ip http login authentication test1
Switch(config)# ip https login authentication test2
```

This example shows how to show line binding lists.

```
Switch# show line lists
Line Type        |          AAA Type       |     List Name
-------------+-----------------+----------------
console |                    login | default
|       enable | default
telnet   |                    login | default
|       enable | default
ssh       |                    login | default
|       enable | default
   http      |     login | test1
https    |                    login | test2
```

## enable authentication

**Syntax**

**enable authentication** *LISTNAME*
**no enable authentication**

**Parameter**

| | |
|---|---|
| *LISTNAME* | Specify the enable authentication list name to use. |

**Default**

Default enable authentication list for each line is “default”.

**Mode**

Line Configuration

**Usage**

Different access methods are allowed to bind different enable authentication lists.
Use “**enable authentication**” command to bind the list to specific line (console, telnet,
ssh).

Use no form to bind the “default” list back.

**Example**

This example shows how to create a new enable authentication list and bind to telnet line.
Switch(config)# **aaa authentication enable test1 tacacs+ radius enable**
Switch(config)# **line telnet**
Switch(config-line)# **enable authentication test1**

This example shows how to show line binding lists.
Switch# **show line lists**

```
Line Type       |       AAA Type      |       List Name
----------------+---------------------+-----------------
console         |       login   | default
|       enable| default
telnet  |       login   | default
|       enable| test1
ssh     |       login   | default
|               enable          | default
http |  login   | default
https | login   | default
```

## show aaa authentication

**Syntax**

**show aaa authentication** (**login** | **enable**) **lists**

**Parameter**

| | |
|---|---|
| **login** | Show login authentication list |
| **enable** | Show enable authentication list |

**Default**

No default value for this command

**Mode**

Privileged EXEC

**Usage**

Use "**show aaa authentication**" command to show login authentication or enable authentication method lists.

**Example**

This example shows how to show existing login authentication lists

Switch# **show aaa authentication login lists**

```
Login List Name          | Authentication Method List
-------------------+------------------------------
default                  | local
test1                    | tacacs+        radius      local
```

This example shows how to show existing enable authentication lists

Switch# **show aaa authentication login lists**

```
Enable List Name | Authentication Method List
-------------------+------------------------------
default                  | enable
test2                   | tacacs+   radius   enable
```

## show line lists

**Syntax**

**show line lists**

**Parameter**

**Default**

No default value for this command

**Mode**

Privileged EXEC

**Usage**

Use "**show line lists**" command to show all lines' binding list of all authentication, authorization, and accounting function.

**Example**

This example shows how to show line binding lists.
Switch# **show line lists**

```
 Line Type    |      AAA Type        |   List Name
-------------+-----------------+-----------------
        console |               login | default
                |              enable | default
         telnet |               login | test1
                |              enable | default
            ssh |               login | default
                |              enable | default
           http |               login | default
          https |               login | default
```

## tacacs default-config

**Syntax**

**tacacs default-config** [**key** *TACACSKEY*] [**timeout** *<1-30>*]

**Parameter**

| | |
|---|---|
| **Key** *TACACSKEY* | Specify default tacacs+ server key string |
| **timeout** *<1-30>* | Specify default tacacs+ server timeout value |

**Default**

Default tacacs+ key is “”.
Default tacacs+ timeout is 5 seconds.

**Mode**

Global Configuration

**Usage**

Use “**tacacs default-config**” command to modify default values of tacacs+ server.
These default values will be used when user try to create a new tacacs+ server and not assigned these values.

**Example**

This example shows how modify default tacacs+ configuration
Switch(config)# **tacacs default-config timeout 20**
Switch(config)# **tacacs default-config key tackey**

This example shows how to show default tacacs+ configurations.
Switch# **show tacacs default-config**

```
Timeout |               Key
--------+---------
10                |      tackey
```

This example shows how to create a new tacacs+ server with above default config and show results.
Switch(config)# **tacacs host 192.168.1.111**
Switch# **show tacacs**

```
Prio | Timeout |       IP Address     |        Port    | Key
------+---------+------------------+--------+-------
1 |      10      |       192.168.1.111 |       49 | tackey
```

## tacacs host

**Syntax**

**tacacs host** *HOSTNAME* [**port** *<0-65535>*] [**key** *TACPLUSKEY*] [**priority***<0-65535>*]
[**timeout** *<1-30>*]
**no tacacs** [**host** *HOSTNAME*]

**Parameter**

| | |
|---|---|
| **Host***HOSTNAME* | Specify tacacs+ server host name, both IP address and domain name are available. |
| **port** *<0-65535>* | Specify tacacs+ server udp port |
| **key** *TACPLUSKEY* | Specify tacacs+ server key string |
| **priority** *<0-65535>* | Specify tacacs+ server priority |
| **timeout** *<1-30>* | Specify tacacs+ server timeout value |

**Default**

Default tacacs+ key is “”.
Default tacacs+ timeout is 5 seconds.

**Usage**

Use “**tacacs host**” command to add or edit tacacs+ server for authentication, authorization or accounting.
Use no form to delete one or all tacacs+ servers from database.

**Example**

This example shows how to create a new tacacs+ server
Switch(config)# **tacacs host 192.168.1.111 port 12345 key tacacs+ priority 100 timeout 10**

This example shows how to show existing tacacs+ server.

```
Switch# show tacacs
Prio | Timeout |                IP Address            |     Port      |
Key
------+---------+-----------------+--------+----------
100 |                  10        |      192.168.1.111 |    12345 |tacacs+
```

## show tacacs default-config

### Syntax

**show tacacs default-config**

### Parameter

### Default

No default value for this command

### Mode

Privileged EXEC

### Usage

Use "**show tacacs default-config**" command to show tacacs+ default configurations.

### Example

This example shows how to show default tacacs+ configurations.

```
Switch# show tacacs default-config
Timeout |          Key
--------+---------
10      |        tackey
```

## show tacacs

### Syntax

**show tacacs**

**Parameter**

**Default**

No default value for this command

**Mode**

Privileged EXEC

**Usage**

Use "**show tacacs**" command to show existing tacacs+ servers.

**Example**

This example shows how to show existing tacacs+ server.
Switch# **show tacacs**

```
Prio        | Timeout |              IP Address              |     Port      | Key
------+---------+------------------+--------+----------
100 |              10        |          192.168.1.111 |          12345 |tacacs+
```

## show default-config

**Syntax**

**tacacs default-config** [**key** *TACACSKEY*] [**timeout** *<1-30>*]

**Parameter**

| | |
|---|---|
| **key** *RADIUSKEY* | Specify default radius server key string |
| **retransmit** *<1-10>* | Specify default radius server retransmit value |
| **timeout** *<1-30>* | Specify default radius server timeout value |

### Default

Default radius key is “”.
Default radius retransmit is
3 times. Default radius
timeout is 3 seconds.

### Mode

Global Configuration

### Usage

Use “radius default-config” command to modify default values of radius server. These default values will be used when user try to create a new radius server and not assigned these values.

### Example

This example shows how modify default radius configuration
Switch(config)# radius default-config timeout 20
Switch(config)# radius default-config key radiuskey
Switch(config)# radius default-config retransmit 5
This example shows how to show default radius configurations.

```
Retries| Timeout|      Key
--------+--------+---------
5       |        20      | radiuskey radius host
```

This example shows how to create a new radius server with
above default config and show results.
Switch(config)# **radius host 192.168.1.111**
Switch# **show radius**

```
Prio |IP Address| Auth-Port| Retries| Timeout| Usage-Type|      Key
------+----------------+----------+--------+--------+-----------+-
---
1   |192.168.1.111 |  1812      |     5       | 20    |       All      | radiuskey
```

## radius host

### Syntax

**radius host** *HOSTNAME* [**auth-port** *<0-65535>*] [**key** *RADIUSKEY*][**priority** *<0-65535>*] [**retransmit** <1-10>] [**timeout** *<1-30>*] [**type** (login|802.1x|all)]
**no radius** [**host** *HOSTNAME*]

**Parameter**

| | |
|---|---|
| **host** *HOSTNAME* | Specify radius server host name, both IP address and domain name are available. |
| **auth-port** *<0-65535>* | Specify radius server udp port |
| **key** *RADIUSKEY* | Specify radius server key string |
| **priority** *<0-65535>* | Specify radius server priority |
| **retransmit** *<1-10>* | Specify radius server retransmit times |
| **timeout** *<1-30>* | Specify radius server timeout value |
| **Type login**<br>**802.1X all** | Usage type of this server<br>Use for login<br>Use for 802.1X authentication<br>Use for both login and 802.1X authentication |

De

fa

**Default**

**radius key is ""**.
**Default radius timeout is 3 seconds.**

**Mode**

Global Configuration

**Usage**

Use "**radius host**" command to add or edit an existing radius server.
Use no form to delete one or all radius servers from database.

**Example**

This example shows how to create a new radius server
Switch(config)# **radius host 192.168.1.111 auth-port 12345 key radiuskey priority 100 retransmit 5 timeout 10 typeall**

This example shows how to show existing radius server.
Switch# **show radius**

```
Prio |   IP Address| Auth-Port| Retries| Timeout| Usage-Type|    Key
-----+---------------+----------+--------+--------+-----------+---
100 |   192.168.1.111 |12345|        5        |        10 |     All      |radiuskey
```

## show radius default-config

**Syntax**

**show radius default-config**

**Parameter**

**Default**

No default value for this command

**Mode**

Privileged EXEC

**Usage**

Use "**show radius default-config**" command to show radius default configurations.

**Example**

This example shows how to show default radius configurations.
Switch# **show radius default-config**

```
Retries| Timeout|                Key
-------+--------+---------
5            |    20      | radiuskey
```

## show radius

**Syntax**

**show radius**

**Parameter**

**Default**

No default value for this command

**Mode**

Privileged EXEC

**Usage**

Use "**show radius**" command to show existing radius servers.

**Example**

This example shows how to show existing radius server.
Switch# **show radius**

```
Prio |IP Address| Auth-Port| Retries| Timeout| Usage-Type|       Key
-----+---------------+----------+--------+--------+-----------+---
--
100 |192.168.1.111              |12345           |       5       |      10|        All
            |radiuskey
```

# 2.ACL

## mac acl

**Syntax**

**mac acl  NAME**

**no mac acl NAME**

### Parameter

| | |
|---|---|
| NAME | Specify the name of MAC ACL |

### Default

No default is defined

### Mode

Global Configuration

### Usage

Use the mac acl command to create a MAC access list and to enter mac-acl configuration mode. The name of ACL must be unique that can not have same name with other ACL or QoS policy. Once an ACL is created, an implicit "deny any" ACE created at the end of the ACL. That is, if there are no matches, the packets are denied.

Use the no form of this command to delete.

### Example

The example shows how to create a mac acl. You can verify settings by the following show acl command

Switch(config)# **mac acl test**
Switch(mac-al)# **show acl**
MAC access list test

## permit (MAC)

### Syntax

**[sequence <1-2147483647>] permit (A:B:C:D:E:F/A:B:C:D:E:F|any)**

**(A:B:C:D:E:F/A:B:C:D:E:F|any) [vlan <1-4094>] [cos <0-7> <0-7>] [ethtype <0x0600-0xFFFF>]**

**no sequence <1-2147483647>**

**Parameter**

| | |
|---|---|
| **<1-2147483647>** | (Optional) Specify sequence index of ACE, the sequence index represent the priority of an ACE in ACL. |
| **(A:B:C:D:E:F/A:B:C:D:E:F\|any)** | Specify the source MAC address and mask of packet or any MAC address. |
| **(A:B:C:D:E:F/A:B:C:D:E:F\|any)** | Specify the destination MAC address and mask of packet or any MAC address |
| **[vlan <1-4094>]** | (Optional) Specify the vlan ID of packet. |
| **[cos <0-7> <0-7>]** | (Optional) Specify the Class of Service value and mask of packet. |
| **[ethtype <0x0600-0xFFFF>]** | (Optional) Specify Ethernet protocol number of packet |

**Default**

No default is defined

**Mode**

MAC ACL Configuration

**Usage**

Use the permit command to add permit conditions for a mac ACE that bypass those packets hit the ACE. The "sequence" also represents hit priority when ACL bind to an interface. An ACE not specifies "sequence" index would assign a sequence index which is the largest existed index plus 20. If packet content can

match more than one ACE, the lowest sequence ACE is hit. An ACE can not be added if has the same conditions as existed ACE.

**Example**

The example shows how to add an ACE that permit packets with source MAC address 22:33:44:55:66:77 、 VLAN 3 and Ethernet type 1999. You can verify settings by the following **show acl** command

Switch(config)# **mac acl test**
Switch(mac-al)# **sequence 999 permit**
**22:33:44:55:66:77/FF:FF:FF:FF:FF:FF any vlan 3 ethtype 0x2800**
Switch(mac-al)# **show acl**
MAC access list test
sequence 999 permit 22:33:44:55:66:77/FF:FF:FF:FF:FF:FF any vlan 3 ethtype 0x2800

## deny (MAC)

**Syntax**

[**sequence** <1-2147483647>] **deny** (A:B:C:D:E:F/A:B:C:D:E:F|any) (A:B:C:D:E:F/A:B:C:D:E:F|any) [**vlan** <1-4094>] [**cos** <0-7> <0-7>] [**ethtype** <0x0600-0xFFFF>]
[**shutdown**] **no sequence** <1-2147483647>

**Parameter**

| | |
|---|---|
| **<1-2147483647>** | (Optional) Specify sequenceindex of ACE, the sequence index represent the priority of an ACE in ACL. |
| **(A:B:C:D:E:F/A:B:C:D:E:F\|any)** | Specify the source MAC address and mask of packet or any MAC address. |
| **[vlan <1-4094>]** | (Optional) Specify the vlan ID of packet. |
| **[cos <0-7> <0-7>]** | (Optional) Specify the Class of Service value and mask of packet. |

| | |
|---|---|
| **[ethtype <0x0600-0xFFFF>]** | (Optional) Specify Ethernet protocol number of packet |
| **[shutdown]** | (Optional) Shutdown interface while ACE hit |

**Default**

No default is defined.

**Mode**

MAC ACL Configuration

**Usage**

Use the deny command to add deny conditions for a mac ACE that drop those packets hit the ACE. The "**sequence**" also represents hit priority when ACL bind to an interface. An ACE not specifies "**sequence**" index would assign a sequence index which is the largest existed index plus 20. If packet content can match more than one ACE, the lowest sequence ACE is hit. An ACE cannot be added if has the same conditions as existed ACE. Use "**shutdown**" to shutdown interface while ACE hit.

**Example**

The example shows how to add an ACE that denies packets with destination MAC address aa:bb:cc:xx:xx:xx and VLAN 9. You can verify settings by the following **show acl** command

Switch(config)# **mac acl test**
Switch(mac-al)# **sequence 30 permit any any**
Switch(mac-al)# **deny any aa:bb:cc:00:0:00/FF:FF:FF:00:00:00 vlan 9 shutdown**
Switch(mac-al)# **show acl**
MAC access list test
sequence 30 permit any any
sequence 50 deny any AA:BB:CC:00:00:00/FF:FF:FF:00:00:00 vlan 9 shutdown

## ip acl

### Syntax

**ip acl NAME**

**no ip acl NAME**

### Parameter

| | |
|---|---|
| NAME | Specify the name of IPv4 ACL |

### Default

No default is defined

### Mode

Global Configuration

### Usage

Use the **ip acl** command to create an IPv4 access list and to enter ip-acl configuration mode. The name of ACL must be unique that can not have same name with other ACL or QoS policy. Once an ACL is created, an implicit "deny any" ACE created at the end of the ACL. That is, if there are no matches, the packets are denied. Use the no form of this command to delete.

### Example

The example shows how to create an IP ACL. You can verify settings by the following **show acl** command

```
Switch(config)#ip acl iptest
Switch(ip-al)# show acl
   IP access list iptest
```

## permit (IP)

### Syntax

[**sequence** *<1-2147483647>*] **permit** (*<0- 255>* | **ipinip** | **egp** | **igp** | **hmp** | **rdp** | **ipv6** | **ipv6:rout** | **ipv6:frag** | **rsvp** | **ipv6:icmp** | **ospf** | **pim** | **l2tp** | **ip**) (*A.B.C.D /A.B.C.D* | **any**) (*A.B.C.D / A.B.C.D* | **any**) [(**dscp**|**precedence**) *VALUE*]]
[**sequence** *<1-2147483647>*] **permit icmp** (*A.B.C.D / A.B.C.D* | **any**) (*A.B.C.D /A.B.C.D* | **any**) (*<0-255>* | **echo-reply** | **destination-unreachable**|**source-quench** | **echo- request**|**router-advertisement**|**router-solicitation**|**time-exceeded**|**timestamp** | **timestamp-reply** | **traceroute**|**any**) (*<0- 255>* | **any**) [(**dscp** | **precedence**) *VALUE*]
[**sequence** *<1-2147483647>*] **permit tcp** (*A.B.C.D / A.B.C.D* | **any**) (*<0-65535>* | **echo** | **discard** | **daytime** | **ftp- data** | **ftp** | **telnet** | **smtp** | **time** | **hostname** | **whois** | **tacacs-ds** | **domain** | **www** | **pop2** | **pop3** | **syslog** | **talk** | **klogin** | **kshell** | **sunrpc** | **drip** | *PORT_RANGE* | **any**) (*A.B.C.D / A.B.C.D* | **any**) (*<0-65535>* | **echo** | **discard** | **daytime** | **ftp- data** | **ftp** | **telnet** | **smtp** | **time** | **hostname** | **whois** | **tacacs-ds**|**domain** | **www** | **pop2** | **pop3** | **syslog** | **talk** | **klogin** | **kshell** | **sunrpc** | **drip** | *PORT_RANGE* | **any**)[**match-all** *TCP_FLAG*] [(**dscp** | **precedence**) *VALUE*]
[**sequence** *<1-2147483647>*] **permit udp** (*A.B.C.D / A.B.C.D* | **any**) (*<0-65535>* | **echo** | **discard** | **time** | **nameserver** | **tacacs- ds**|**domain** | **bootps** | **bootpc** | **tftp** | **sunrpc**|**ntp** | **netbios-ns** | **snmp** | **snmptrap** | **who** | **syslog** | **talk** | **rip** | *PORT_RANGE* | **any**) (*A.B.C.D / A.B.C.D* | **any**) (*<0-65535>* | **echo** | **discard** | **time** | **nameserver** | **tacacs- ds** | **domain** | **bootps** | **bootpc** | **tftp** | **sunrpc** | **ntp** | **netbios-ns** | **snmp** | **snmptrap** | **who** | **syslog** | *PORT_RANGE* | **any**) [(**dscp** | **precedence**) *VALUE*]
**no sequence** *<1-2147483647>*

## Parameter

| | |
|---|---|
| **<1-2147483647>** | (Optional) Specify sequence index of ACE, the sequence index represent the priority of an ACE in ACL. |
| **(A.B.C.D/A.B.C.D\|any)** | Specify the source IPv4 address and mask of packet or any IPv4 address. |
| **(A.B.C.D/A.B.C.D\|any)** | Specify the destination IPv4 address and mask of packet or any IPv4 address. |
| **[dscp VALUE]** | (Optional) Specify the DSCP of packet. |
| **[precedence VLAUE]** | (Optional) Specify the IP precedence of packet. |
| **icmp-type** | Specify ICMP message type for filtering ICMP packet. Enter a type name of list or a number of ICMP message type. |
| **icmp-code** | Specify ICMP message code for filtering ICMP packet. |

| | |
|---|---|
| **l4-source-port** | Specify TCP/UDP destination port of for filtering TCP/UDP packet. Enter a port name of list or a number of TCP/UDP port. |
| **l4-destination-port** | Specify TCP/UDP destination port of for filtering TCP/UDP packet. Enter a port name of list or a number of TCP/UDP port. |
| **match-all** | Specify tcp flag for TCP packet. If a flag should be set it is prefixed by\"+\".If a flag should be unset it is prefixed by \"-\". Available options are +urg, +ack, +psh, +rst, +syn, +fin,-urg, -ack, -psh, -rst, -syn and -fin.To define more than 1 flag - enter additional flags one after another without a space (example +syn-ack). |

**Default**

No default is defined.

**Mode**

IP ACL Configuration

**Usage**

Use the permit command to add permit conditions for an IP ACE that bypasses those packets hit the ACE. The "**sequence**" also represents hit priority when ACL bind to an interface. An ACE not specifies "**sequence**" index would assign a sequence index which is the largest existed index plus
20. If packet content can match more than one ACE, the lowest sequence ACE is hit. An ACE can not be added if has the same conditions as existed ACE.

**Example**

The example shows how to add a set of ACEs. You can verify settings by the following **show acl** command.

This command shows how to permit a source IP address subnet.
Switch334455(ip-al)# **permit ip 192.168.1.0/255.255.255.0**

This command shows how to permit ICMP echo-request packet with any IP address.
Switch334455(ip-al)# **permit icmp any any echo-request any**

This command shows how to permit any IP address HTTP packets with DSCP 5.
Switch334455(ip-al)# **permit tcp any any any www dscp 5**

This command shows how to permit any source IP address SNMP packet connect to destination IP address 192.168.1.1.
Switch334455(ip-al)# **permit udp any any 192.168.1.1/255.255.255.255 snmp**

Switch334455(ip-al)# **show acl**
IP access list iptest
sequence 1 permit ip 192.168.1.0/255.255.255.0 any
sequence 21 permit icmp any any echo-request any
sequence 41 permit tcp any any any www dscp 5
sequence 61 permit udp any any 192.168.1.1/255.255.255.255 snmp

## deny (IP)

### Syntax

[**sequence** *<1-2147483647>*] **deny** (*<0- 255>* | **ipinip** | **egp** | **igp** | **hmp** | **rdp** | **ipv6** | **ipv6:rout** | **ipv6:frag** | **rsvp** | **ipv6:icmp** | **ospf** | **pim** | **l2tp** | **ip**) (*A.B.C.D / A.B.C.D* | **any**) (*A.B.C.D / A.B.C.D* | **any**) [(**dscp**|**precedence**) *VALUE*]]
[**sequence** *<1-2147483647>*] **deny icmp** (*A.B.C.D / A.B.C.D* | **any**) (*A.B.C.D / A.B.C.D* | **any**) (*<0-255>* | **echo-reply** | **destination-unreachable** | **source-quench** | **echo-request** | **router-advertisement** | **router-solicitation** | **time- exceeded** | **timestamp** |**timestamp-reply** | **traceroute** | **any**) (*<0- 255>* | **any**) [(**dscp** | **precedence**) *VALUE*]
[**sequence** *<1-2147483647>*] **deny tcp** (*A.B.C.D / A.B.C.D* | **any**) (*<0-65535>* | **echo** | **discard** | **daytime** | **ftp-data** | **ftp** | **telnet** | **smtp** | **time** | **hostname** | **whois** | **tacacs-ds** | **domain** | **www** | **pop2** | **pop3** | **syslog** | **talk** | **klogin** | **kshell** | **sunrpc** | **drip** | *PORT_RANGE* | **any**) (*A.B.C.D / A.B.C.D* | **any**) (*<0-65535>* | **echo** | **discard** | **daytime** | **ftp-data** | **ftp** | **telnet** | **smtp** | **time** | **hostname** | **whois** | **tacacs-ds** | **domain** | **www** | **pop2** | **pop3** | **syslog** | **talk** | **klogin** | **kshell** | **sunrpc** | **drip** | *PORT_RANGE* | **any**)[**match-all** *TCP_FLAG*] [(**dscp**|**precedence**) *VALUE*]

[**sequence** *<1-2147483647>*] **deny udp** (*A.B.C.D / A.B.C.D* | **any**) (*<0-65535>* | **echo** | **discard** | **time** | **nameserver** | **tacacs-ds** | **domain** | **bootps** | **bootpc** | **tftp** | **sunrpc** | **ntp** | **netbios-ns** | **snmp** | **snmptrap** | **who** | **syslog** | **talk** | **rip** | *PORT_RANGE* | **any**) (*A.B.C.D / A.B.C.D* | **any**) (*<0-65535>* | **echo** | **discard** | **time** | **nameserver** | **tacacs-ds** | **domain** | **bootps** | **bootpc** | **tftp** | **sunrpc** | **ntp** | **netbios-ns** | **snmp** | **snmptrap** | **who** | **syslog** | *PORT_RANGE* | **any**) [(**dscp**|**precedence**) *VALUE*]
**no sequence** *<1-2147483647>*

## Parameter

| | |
|---|---|
| **<1-2147483647>** | (Optional) Specify sequence index of ACE, the sequence index represent the priority of an ACE in ACL. |
| **(A.B.C.D/A.B.C.D\|any)** | Specify the source IPv4 address and mask of packet or any IPv4 address. |
| **(A.B.C.D/A.B.C.D\|any)** | Specify the destination IPv4 address and mask of packet or any IPv4 address. |
| **[dscp VALUE]** | (Optional) Specify the DSCP of packet. |
| **[precedence VLAUE]** | (Optional) Specify the IP precedence of packet. |
| **icmp-type** | Specify ICMP message type for filtering ICMP packet. Enter a type name of list or a number of ICMP message type. |
| **icmp-code** | Specify ICMP message code for filtering ICMP packet. |
| **l4-source-port** | Specify TCP/UDP destination port of for filtering TCP/UDP packet. Enter a port name of list or a number of TCP/UDP port. |
| **l4-destination-port** | Specify TCP/UDP destination port of for filtering TCP/UDP packet. Enter a port name of list or a number of TCP/UDP port. |
| **match-all** | Specify tcp flag for TCP packet. If a flag should be set it is prefixed by\"+\".If a flag should be unset it is prefixed by \"-\". Available options |

| | |
|---|---|
| | are +urg, +ack, +psh, +rst, +syn, +fin,-urg, -ack, -psh, -rst, -syn and -fin.To define more than 1 flag - enter additional flags one after another without a space (example +syn-ack). |
| **[shutdown]** | (Optional) Shutdown interface while ACE hit |

**Default**

No default is defined.

**Mode**

IP ACL Configuration

**Usage**

Use the deny command to add deny conditions for an IP ACE that drop those packets hit the ACE. The "**sequence**" also represents hit priority when ACL bind to an interface. An ACE not specifies "**sequence**" index would assign a sequence index which is the largest existed index plus 20. If packet content can match more than one ACE, the lowest sequence ACE is hit. An ACE can not be added if has the same conditions as existed ACE. Use "**shutdown**" to shutdown interface while ACE hit.

**Example**

The example shows how to add an ACE that denies packets with source IP address 192.168.1.80. You can verify settings by the following **show acl** command

Switch334455(config)# **ip acl iptest**
Switch334455(ip-al)# **deny ip 192.168.1.80/255.255.255.255 any**
Switch334455(ip-al)# **show acl**

IP access list iptest
sequence 1 deny ip 192.168.1.80/255.255.255.255 any

## ipv6 acl

### Syntax

**ipv6 acl** NAME
**no ipv6 acl** NAME

### Parameter

| | |
|---|---|
| NAME | Specify the name of IPv6 ACL |

### Default

No default is defined

### Mode

Global Configuration

### Usage

Use the ipv6 acl command to create an IPv6 access list and to enter ipv6-acl configuration mode. The name of ACL must be unique that can not have same name with other ACL or QoS policy. Once an ACL is created, an implicit "deny any" ACE created at the end of the ACL. That is, if there are no matches, the packets are denied. Use the no form of this command to delete.

### Example

The example shows how to create an IPv6 ACL. You can verify settings by the following **show acl** command

Switch(config)#**ipv6 acl ipv6test**
Switch(ipv6-al)# **show acl**
IPv6 access list iptes

## Permil(IPv6)

### Syntax

[**sequence** *<1-2147483647>*] **permit** (*<0-255>* | **ipv6**) (*X:X::X:X / <0-128>* | **any**) (*X:X::X:X / <0-128>* | **any**)[(**dscp** | **precedence**) *VALUE*]
[**sequence** *<1-2147483647>*] **permit icmp** (*X:X::X:X / <0-128>* | **any**)( *X:X::X:X / <0-128>* | **any**) (*<0-255>* | **destination-unreachable|packet-too-big|time-exceeded** | **parameter-problem|echo-request|echo-reply** | **mld-query** | **mld-report** | **mldv2-report|mld-done** | **router-solicitation** | **router-advertisement** | **nd-ns** | **nd-na** | **any**) (*<0-255>* | **any**)[( **dscp** | **precedence**) *VALUE*]
[**sequence** *<1-2147483647>*] **permit tcp** (*X:X::X:X / <0-128>* | **any**) (*<0-65535>* | **echo** | **discard** | **daytime** | **ftp-data** | **ftp** | **telnet** | **smtp** | **time** | **hostname** | **whois** | **tacacs-ds** | **domain** | **www** | **pop2** | **pop3** | **syslog** | **talk** | **klogin** | **kshell** | **sunrpc** | **drip** | *PORT_RANGE* | **any**) (*X:X::X:X / <0-128>* | **any**) (*<0-65535>* | **echo** | **discard** | **daytime** | **ftp-data** | **ftp** | **telnet** | **smtp** | **time** | **hostname** | **whois** | **tacacs-ds** | **domain** | **www** | **pop2** | **pop3** | **syslog** | **talk** | **klogin** | **kshell** | **sunrpc** | **drip** | *PORT_RANGE* | **any**) [**match-all** *TCP_FLAG*] [(**dscp** | **precedence**) *VALUE*]
[**sequence** *<1-2147483647>*] **permit udp** (*X:X::X:X / <0-128>* | **any**)(*<0-65535>* | **echo** | **discard** | **time** | **nameserver** | **tacacs-ds** | **domain** | **bootps** | **bootpc** | **tftp** | **sunrpc** | **ntp** | **netbios-ns** | **snmp** | **snmptrap** | **who** | **syslog** | **talk** | **rip** | *PORT_RANGE* | **any**) (*X:X::X:X / <0-128>* | **any**) (*<0-65535>* | **echo** | **discard** | **time** | **nameserver** | **tacacs-ds** | **domain** | **bootps** | **bootpc** | **tftp** | **sunrpc** | **ntp** | **netbios-ns** | **snmp** | **snmptrap** | **who** | **syslog** | *PORT_RANGE* | **any**) [(**dscp** | **precedence**) *VALUE*]
**no sequence** *<1-2147483647>*

## Parameter

| | |
|---|---|
| **<1-2147483647>** | (Optional) Specify sequence index of ACE, the sequence index represent the priority of an ACE in ACL. |
| **(X:X::X:X/<0-128>\|any)** | Specify the source IPv6 address and mask of packet or any IPv6 address. |
| **(X:X::X:X/<0-128>\|any)** | Specify the destination IPv6 address and prefix of packet or any IPv6 address. |
| **[dscp VALUE]** | (Optional) Specify the DSCP of packet. |
| **[precedence VLAUE]** | (Optional) Specify the IP precedence of packet. |
| **icmp-type** | Specify ICMP message type for filtering ICMP packet. Enter a type name of list or a number of ICMP message type. |
| **icmp-code** | Specify ICMP message code for filtering ICMP packet. |
| **l4-source-port** | Specify TCP/UDP destination port of for filtering TCP/UDP packet. |

| | |
|---|---|
| | Enter a port name of list or a number of TCP/UDP port. |
| **l4-destination-port** | Specify TCP/UDP destination port of for filtering TCP/UDP packet. Enter a port name of list or a number of TCP/UDP port. |
| **match-all** | Specify tcp flag for TCP packet. If a flag should be set it is prefixed by\"+\".If a flag should be unset it is prefixed by \"-\". Available options are +urg, +ack, +psh, +rst, +syn, +fin,-urg, -ack, -psh, -rst, -syn and -fin.To define more than 1 flag - enter additional flags one after another without a space (example +syn-ack). |

**Default**

No default is defined.

**Mode**

IPv6 ACL Configuration

**Usage**

Use the permit command to add permit conditions for an IPv6 ACE that bypasses those packets hit the ACE. The "**sequence**" also represents hit priority when ACL bind to an interface. An ACE not specifies "**sequence**" index would assign a sequence index which is the largest existed index plus
20. If packet content can match more than one ACE, the lowest sequence ACE is hit. An ACE can not be added if has the same conditions as existed ACE.

**Example**

The example shows how to add a set of ACEs. You can verify settings by the following **show acl** command.

This command shows how to permit a source IP address subnet.
Switch334455(ipv6-al)# **permit permit ipv6 fe80:1122:3344:5566::1/64 any**

Switch334455(ipv6-al)# **show acl**
IPv6 access list ipv6test
sequence 1 permit ipv6 fe80:1122:3344:5566::1/64 any

## deny (IPv6)

### Syntax

[sequence <1-2147483647>] deny (<0-255> | ipv6) (X:X::X:X / <0-128> | any) (X:X::X:X / <0-128> | any)[( dscp | precedence) VALUE]
[sequence <1-2147483647>] deny icmp (X:X::X:X / <0-128> | any)( X:X::X:X / <0-128> | any) (<0-255> | destination-unreachable|packet-too-big|time-exceeded | parameter-problem|echo-request|echo-reply | mld-query | mld-report | mldv2-report|mld-done | router-solicitation | router-advertisement | nd-ns | nd-na | any) (<0-255> | any)[( dscp | precedence) VALUE]
[sequence <1-2147483647>] deny tcp (X:X::X:X / <0-128> | any) (<0-65535> | echo | discard | daytime | ftp-data | ftp | telnet | smtp | time | hostname | whois | tacacs-ds | domain | www | pop2 | pop3 | syslog | talk | klogin | kshell | sunrpc | drip | PORT_RANGE | any) (X:X::X:X / <0-128> | any) (<0-65535> | echo | discard | daytime | ftp-data | ftp | telnet | smtp | time | hostname | whois | tacacs-ds | domain | www | pop2 | pop3 | syslog | talk | klogin | kshell | sunrpc | drip | PORT_RANGE | any) [match-all TCP_FLAG] [(dscp | precedence) VALUE]
[sequence <1-2147483647>] deny udp (X:X::X:X / <0-128> | any)(<0-65535> | echo | discard | time | nameserver | tacacs-ds | domain | bootps | bootpc | tftp | sunrpc | ntp | netbios-ns | snmp | snmptrap | who | syslog | talk | rip | PORT_RANGE | any) (X:X::X:X / <0-128> | any) (<0-65535> | echo | discard | time | nameserver | tacacs-ds | domain | bootps | bootpc | tftp | sunrpc | ntp | netbios-ns | snmp | snmptrap | who | syslog | PORT_RANGE | any) [(dscp | precedence) VALUE] [shutdown]
no sequence <1-2147483647>

### Parameter

| | |
|---|---|
| **<1-2147483647>** | (Optional) Specify sequence index of ACE, the sequence index represent the priority of an ACE in ACL. |
| **(A.B.C.D/A.B.C.D\|any)** | Specify the source IPv4 address and mask of packet or any IPv4 address. |
| **(A.B.C.D/A.B.C.D\|any)** | Specify the destination IPv4 address and mask of packet or any IPv4 address |
| **[dscp VALUE]** | (Optional) Specify the DSCP of packet. |
| **[precedence VLAUE]** | (Optional) Specify the IP precedence of packet. |
| **icmp-type** | Specify ICMP message type for filtering ICMP packet. |

| | |
|---|---|
| | Enter a type name of list or a number of ICMP message type. |
| **icmp-code** | Specify ICMP message code for filtering ICMP packet. |
| **l4-source-port** | Specify TCP/UDP source port of for filtering TCP/UDP packet. Enter a port name of list or a number of TCP/UDP port. |
| **l4-destination-port** | Specify TCP/UDP destination port of for filtering TCP/UDP packet. Enter a port name of list or a number of TCP/UDP port. |
| **match-all** | Specify tcp flag for TCP packet. If a flag should be set it is prefixed by \"+\".If a flag should be unset it is prefixed by \"-\". Available options are +urg, +ack, +psh, +rst, +syn, +fin,-urg, -ack, -psh, -rst, -syn and -fin.To define more than 1 flag - enter additional flags one after another without a space (example +syn-ack). |
| **[shutdown]** | (Optional) Shutdown interface while ACE hit |

**Default**

No default is defined.

**Mode**

IP ACL Configuration

**Usage**

Use the deny command to add deny conditions for an IPv6 ACE that drop those packets hit the ACE. The "**sequence**" also represents hit priority when ACL bind to an interface. An ACE not specifies "**sequence**" index would assign a sequence index which is the largest existed index plus 20. If packet content can match more than one ACE, the lowest sequence ACE is hit. An ACE can not be added if has the same conditions as existed ACE. Use "**shutdown**" to shutdown interface while ACE hit.

**Example**

The example shows how to add an ACE that denies packets with destination IP address fe80::abcd. You can verify settings by the following **show acl** command

Switch334455(config)# **ipv6 acl ipv6test**
Switch334455(ip-al)# **deny ipv6 any**
**fe80::abcd/128**
Switch334455(ip-al)# **show acl**

IPv6 access list ipv6test
sequence 1 deny ipv6 any fe80::abcd/128

## bind acl

**Syntax**

**(mac|ip|ipv6) acl NAME**

**[no] (mac|ip|ipv6) acl NAME**

**Parameter**

| | |
|---|---|
| (mac\|ip\|ipv6) | Specify a type of ACL to binding to interface |
| NAME | Specify the name of ACL |

**Default**

No default is defined

**Mode**

Interface Configuration

**Usage**

Use the (mac|ip|ipv6) acl NAME command to bind an ACL to interfaces. An interface can bind only one ACL or QoS policy. Use the no form of this command to return to unbind an ACL from interface.

**Example**

The example shows how to bind an existed ACL to interface.

switch(config)# **interface fa1**
switch(config-if)# **mac acl test**
switch(config-if)# **do show running-config interfaces fa1**
interface fa1 mac acl test

## show acl

**Syntax**

**show acl**
**show (mac|ip|ipv6) acl**
**show (mac|ip|ipv6) acl NAME**

**Parameter**

| | |
|---|---|
| (mac\|ip\|ipv6) | Specify a type of ACL to show |
| NAME | Specify the name of ACL |

**Default**

No default is defined

**Mode**

Global Configuration

Context Configuration

**Usage**

Use the **show acl** command to show created ACLs. You can specify mac、ip or ipv6 to show specific type ACL or specify unique name string to show ACL with the name.

**Example**

The example shows how to show all IP ACL.
Switch(config)# **show ip acl**
IP access list iptest
sequence 1 deny ip 192.168.1.80/255.255.255.255 any

## show acl utilization

**Syntax**

**show acl utilization**

**Parameter**

None

**Default**

No default is defined

**Mode**

Global Configuration

**Usage**

Use the show acl utilization command to show the usage of PIE of ASIC. When an ACL bind to interface, it needs ASIC resource to help to filter packet. An ASIC has limited resource. This command help user to know the PIE usage of AISC.

**Example**

The example shows how to show utilization
Switch(config-if)# do show acl utilization
Type: sys usage: 128
Type: mac ACL usage: 128
Type: IPv4 ACL usage: 128
Type: IPv6 ACL usage: 128

# 3.Administration

## configure

**Syntax**

**configure**

**Parameter**

**Default**

No default value for this command.

**Mode**

Privileged EXEC

**Usage**

Use "**configure**" command to enter global configuration mode. In global configuration mode, the prompt will show as "**Switch(config)#**".

**Example**

This example shows how to enter global configuration mode.
Switch# **configure**
Switch(config)#

## clear arp

**Syntax**

**clear arp** [*A.B.C.D*]

**Parameter**

| | |
|---|---|
| *A.B.C.D* | Specify specific arp entry to clear. |

**Default**

No default value for this command.

**Mode**

User EXEC
Privileged EXEC

**Usage**

Use "**clear arp**" command to clear all or specific one arp entry.

**Example**

This example shows how to clear all arp entries.
Switch(config)# **clear arp**

## clear line

### Syntax

**clear line** (**telnet** | **ssh**)

### Parameter

| | |
|---|---|
| **telnet** | Clear all telnet sessions. |
| **ssh** | Clear all ssh sessions. |

### Default

No default value for this command.

### Mode

Privileged EXEC

### Usage

Use "**clear line service**" command to kill all existing sessions for the select service.

### Example

This example shows how to enable telnet service and show current telnet service status.
Switch# **clear line telnet**

## enable

### Syntax

**enable** [*<1-15>*]

**disable** [*<1-14>*]

**Parameter**

| | |
|---|---|
| *<1-15>* | Specify privileged level to enable |
| *<1-14>* | Specify privileged level to disable |

**Default**

Default privilege level is 15 if no privilege level is specified on enable command.
Default privilege level is 1 if no privilege level is specified on disable command.

**Mode**

User EXEC

**Usage**

In User EXEC mode, user only allows to do a few actions. Most of commands are only available in privileged EXEC mode. Use "**enable**" command to enter the privileged mode to do more actions on switch.

In privileged EXEC mode, use "**exit**" command is able to go back to user EXEC mode with original user privilege level. If you need to go back to user EXEC mode with different privilege level, use "**disable**" command to specify the privilege level you need.

In privileged EXEC mode, the prompt will show "**Switch#**"

**Example**

This example shows how to enter privileged EXEC mode and show current privilege level.

Switch> **enable**
Switch# **show privilege**
Current CLI Username:

admin
Current CLI Privilege:
15

This example show how to enter user EXEC mode with privilege 3.

Switch# **disable 3**
Switch> **show**
**privilege**
Current CLI Username:
admin
Current CLI Privilege: 3

## end

### Syntax

end

### Parameter

### Default

No default value for this command.

### Mode

Privileged EXEC
Global
Configuration
Interface
Configuration
Line
Configuration

### Usage

Use “**end**” command to return to privileged EXEC mode directly. Every mode except User EXEC mode has the “end” command.

### Example

This example shows how to enter Interface Configuration mode and use end

command to go back to privileged EXEC mode

```
Switch# configure
Switch(config)# interface gi1
Switch(config-if)# end
Switch#
```

## exit

### Syntax

**exit**

### Parameter

### Default

No default value for this command.

### Mode

User EXEC
Privileged EXEC
Global
Configuration
Interface
Configuration
Line
Configuration

### Usage

In User EXEC mode, "**exit**" command will close current CLI session. In other modes, "**exit**" command will go to the parent mode. And every mode has the "exit" command.

### Example

This example shows how to enter privileged EXEC mode and use exit command to go back to user EXEC mode.

```
Switch> enable
```

Switch# **exit**
Switch>

## history

### Syntax

**history** *<1-256>*
**no history**

### Parameter

| | |
|---|---|
| *<1-256>* | Specify maximum CLI history entry number. |

### Default

Default maximum history entry number is 128.

### Mode

Line Configuration

### Usage

Use "**history**" command to specify the maximum commands history number for CLI running on console, telnet or ssh service. Every command input by user will record in history buffer. If all history commands exceed configured history number, older ones will be deleted from buffer.
Use "**no history**" to disable the history feature. And use "**show history**" to show all history commands.

### Example

This example shows how to change console history number to 100, telnet history number to 150 and ssh history number to 200.
Switch(config)# **line console**
Switch(config-line)# **history 100**
Switch(config-line)# **exit**

```
Switch(config)# line telnet
Switch(config-line)# history 150
Switch(config-line)# exit
Switch(config)# line ssh
Switch(config-line)# history 200
Switch(config-line)# exit
```

This example shows how show line information.

```
Switch# show line
Console ==============================
Session Timeout : 10 (minutes)
History Count   : 100 Password Retry     : 3
Silent Time     : 0 (seconds)
Telnet
================================
Telnet Server    : disabled Session Timeout : 10 (minutes) History Count : 150
Password Retry : 3
Silent Time     : 0 (seconds)
SSH
================================
SSH Server       : disabled Session Timeout : 10 (minutes) History Count : 200
Password Retry : 3
Silent Time     : 0 (seconds)
```

This example shows how show history commands.

```
Switch# show history
Maximun History Count: 100
-------------------------------------------------
1.        enable
2.        configure
3.        line console
4.        exit
5.        show history
6.        line
7.        exit
8.        show history
9.        configure
10.         line
11.         line console
12.         exit
13.         line console
14.         history 100
15.         exit
16.         show history
17.         exit
18. show history
```

## hostname

### Syntax

**hostname** *WORD*

**Parameter**

| | |
|---|---|
| *WORD* | Specify the hostname of the switch. |

**Default**

Default name string is "Switch".

**Mode**

Global Configuration

**Usage**

Use "**hostname**" command to modify hostname of the switch. The system name is also used to be CLI prompt.

**Example**

This example shows how to modify contact information

Switch(config)# **hostname myname**

myname(config)#

## interface

**Syntax**

**interface** *IF_PORTS*
**interface range** *IF_PORTS*

**Parameter**

| | |
|---|---|
| *IF_PORTS* | Specify the port to select. This parameter allows partial port name and ignore case. For Example: fa1 |

| | |
|---|---|
| | FastEthernet3<br>Gigabit4<br>.....<br><br>If port range is specified, the list format is also available. For Example:<br>fa1,3,5<br>fa2,gi1-3<br>..... |

**Default**

No default value for this command.

**Mode**

Global Configuration

**Usage**

Some configurations are port based. In order to configure these configurations, we need to enter Interface Configuration mode to configure them.
Use "**interface**" command to enter the Interface Configuration mode and select the port to be configured.
In Interface Configuration mode, the prompt will show as "**Switch(config- if)#**"

**Example**

This example shows how to enter Interface Configuration mode
Switch# **configure**
Switch(config)# **interface fa1**
Switch(config-if)#

## ip address

**Syntax**

**ip address** *A.B.C.D* [**mask** *A.B.C.D*]

**Parameter**

| | |
|---|---|
| **address** *A.B.C.D* | Specify IPv4 address for switch |
| **mask** *A.B.C.D* | Specify net mask address for switch |

**Default**

Default IP address is 192.168.1.1 and default net mask is 255.255.255.0.

**Mode**

Global Configuration

**Usage**

Use "**ip address**" command to modify administration ipv4 address. This address is very important. When we try to use telnet, ssh, http, https, snmp… to connect to the switch, we need to use this ip address to access it.

**Example**

This example shows how to modify the ipv4 address of the switch.

Switch(config)# **ip address 192.168.1.200 mask 255.255.255.0**

This example shows how to show current ipv4 address of the switch.

Switch# **show ip**
IP Address: 192.168.1.200
Subnet Netmask: 255.255.255.0
Default Gateway: 192.168.1.254

## ip default-gateway

**Syntax**

**ip default-gateway** *A.B.C.D*
**no ip default-gateway**

**Parameter**

| | |
|---|---|
| *A.B.C.D* | Specify default gateway IPv4 address for switch |

**Default**

Default IP address of default gateway is 192.168.1.254.

**Mode**

Global Configuration

**Usage**

Use "**ip default-gateway**" command to modify default gateway address. And use "**no ip default-gateway**" to restore default gateway address to factory default.

**Example**

This example shows how to modify the ipv4 address of the switch.
Switch(config)# **ip default-gateway 192.168.1.100**

This example shows how to show current ipv4 default gateway of the switch.
Switch# **show ip**
IP Address: 192.168.1.1
Subnet Netmask: 255.255.255.0
Default Gateway: 192.168.1.100

## ip dhcp

**Syntax**

**ip dhcp**
**no ip dhcp**

**Parameter**

**Default**

Default DHCP client is disabled.

**Mode**

Global Configuration

**Usage**

Use "**ip dhcp**" command to enabled dhcp client to get IP address from remote DHCP server.
Use "**no ip dhcp**" command to disabled dhcp client and use static ip address.

**Example**

This example shows how to enable dhcp client.
Switch(config)# **ip dhcp**

This example shows how to show current dhcp client state of the switch.
Switch# **show ip dhcp**
DHCP Status : enabled

## ip domain lookup

**Syntax**

**ip domain lookup**
**no ip domain lookup**

**Parameter**

**Default**

Default DNS lookup is enabled

**Mode**

Global Configuration

**Usage**

Use "**ip domain lookup**" command to enable the Domain Name to IP address service.

**Example**

This example enables the DNS service on the system.
Switch(config)# **ip domain lookup**

## ipv6 autoconfig

**Syntax**

**ipv6 autoconfig**
**no ipv6 autoconfig**

**Parameter**

**Default**

Default IPv6 auto config is enabled.

**Mode**

Global Configuration

**Usage**

Use "**ipv6 autoconfig**" command to enabled IPv6 auto configuration feature.
Use "**no ipv6 autoconfig**" command to disabled IPv6 auto configuration feature.

**Example**

This example shows how to disable IPv6 auto config.
Switch(config)# **no ipv6 autoconfig**

This example shows how to show current IPv6 auto config state.
Switch# **show ipv6**
IPv6 DHCP Configuration : Disabled
IPv6 DHCP DUID :
IPv6 Auto Configuration : Disabled

IPv6 Link Local Address : fe80::dcad:beff:feef:102/64
IPv6 static Address : fe80::20e:2eff:fef1:4b3c/128
IPv6 static Gateway Address : ::
IPv6 in use Address : fe80::dcad:beff:feef:102/64
IPv6 in use Gateway Address : ::

## ipv6 address

### Syntax

**ipv6 address** *X:X::X:X* **prefix** *<0-128>*

### Parameter

| | |
|---|---|
| **address** *X:X::X:X* | Specify IPv6 address for switch |
| **prefix** *<0-128>* | Specify IPv6 prefix length for switch |

### Default

No default ipv6 address on the switch.

### Mode

Global Configuration

### Usage

Use "**ipv6 address**" command to specify static IPv6 address.

### Example

This example shows how to add static ipv6 address of the switch.
Switch(config)# **ipv6 address fe80::20e:2eff:fef1:4b3c prefix 128**

This example shows how to show current ipv6 address of the switch.
Switch# **show ipv6**
IPv6 DHCP Configuration : Disabled
IPv6 DHCP DUID :
IPv6 Auto Configuration : Enabled

IPv6 Link Local Address : fe80::dcad:beff:feef:102/64
IPv6 static Address : fe80::20e:2eff:fef1:4b3c/128
IPv6 static Gateway Address : ::
IPv6 in use Address : fe80::dcad:beff:feef:102/64
IPv6 in use Gateway Address : ::

## ipv6 default-gateway

### Syntax

**ipv6 default-gateway** *X:X::X:X*

### Parameter

| | |
|---|---|
| *X:X::X:X* | Specify default gateway IPv6 address for switch |

### Default

No default ipv6 default gateway address on the switch.

### Mode

Global Configuration

### Usage

Use "**ipv6 default-gateway**" command to modify default gateway IPv6 address.

### Example

This example shows how to modify the ipv6 default gateway address of the switch.

Switch(config)# **ipv6 default-gateway fe80::dcad:beff:feef:103**

Switch# **show ipv6**
IPv6 DHCP Configuration : Disabled
IPv6 DHCP DUID :
IPv6 Auto Configuration : Enabled
IPv6 Link Local Address : fe80::dcad:beff:feef:102/64
IPv6 static Address : fe80::20e:2eff:fef1:4b3c/128

IPv6 static Gateway Address : ::
IPv6 in use Address : fe80::dcad:beff:feef:102/64
IPv6 in use Gateway Address : ::

## ipv6 dhcp

### Syntax

**ipv6 dhcp**
**no ipv6 dhc**

### Parameter

### Default

Default DHCPv6 client is disabled.

### Mode

Global Configuration

### Usage

Use "**ipv6 dhcp**" command to enabled dhcpv6 client to get IP address from remote DHCPv6 server.
Use "**no ipv6 dhcp**" command to disabled dhcpv6 client and use static ipv6 address or ipv6 auto config address.

### Example

This example shows how to enable dhcp client.
Switch(config)# **ipv6 dhcp**

This example shows how to show current dhcpv6 client state of the switch.
Switch# **show ipv6 dhcp**
DHCPv6 Status : enabled

## ip name-server

### Syntax

**ip name-server** *A.B.C.D [A.B.C.D]*
**no ip name-server** *A.B.C.D [A.B.C.D]*

**Parameter**

| | |
|---|---|
| *A.B.C.D* | Specify the IP address of the DNS server |

**Default**

**Mode**

Global Configuration

**Usage**

Use the command "IP name server" to specify the IP address of the DNS server.

**Example**

This example shows how to Configure DNS

Switch(config)# ip name-server 111.111.111.111 222.222.222.222

## ip service

**Syntax**

**ip** (**telnet** | **ssh** | **http** | **https**)
**no ip** (**telnet** | **ssh** | **http** | **https**)

**Parameter**

| | |
|---|---|
| **telnet** | Enable/Disable telnet service |
| **ssh** | Enable/Disable ssh service |
| **http** | Enable/Disable http service |
| **https** | Enable/Disable https service |

## Default

Default telnet service is disabled.
Default ssh service is disabled.
Default http service is enabled.
Default https service is disabled.

## Mode

Global Configuration

## Usage

Use "**ip service**" command to enable all kinds of ip services. Such as telnet, ssh, http and https.
Use no form to disable service.

## Example

This example shows how to enable telnet service and show current telnet service status.

```
Switch(config)# ip telnet
Telnetd daemon enabled.
Switch(config)# exit Switch# show line
telnet
Telnet ================================
Telnet Server                  : enabled
Session Timeout : 10 (minutes)
History Count                  : 128
Password Retry                 : 3
Silent Time                    : 0 (seconds)
```

This example shows how to enable https service and show current https service status.

```
Switch(config)# ip https
Switch(config)# exit
Switch# show ip https
HTTPS daemon : enabled
Session Timeout : 10 (minutes)
```

# ip session-timeout

### Syntax

**ip** (**http** | **https**) **session-timeout** *<0-86400>*

### Parameter

| | |
|---|---|
| **http** | Specify session timeout for http service. |
| **https** | Specify session timeout for https service. |
| *<0-86400>* | Specify session timeout minutes. 0 means never timeout. |

### Default

Default session timeout for http and https is 10 minutes.

### Mode

Global Configuration

### Usage

Use "ip session-timeout" command to specify the session timeout value for http or https service. When user login into WEBUI and do not do any action after session timeout will be logged out.

### Example

This example shows how to change http session timeout to 15min and https session timeout to 20min

Switch(config)# **ip http session-timeout 15**
Switch(config)# **ip https session-timeout 20**

This example shows how to enable https service and show current https service status.

Switch# **show ip http**
HTTPS daemon : enabled
Session Timeout : 15 (minutes)

Switch# **show ip https**
HTTPS daemon : disabled
Session Timeout : 20 (minutes)

## ip ssh

### Syntax

**ip ssh (v1|v2|all)**
**no ip ssh (v1|v2|all)**

### Parameter

| | |
|---|---|
| v1 | Generate/Delete version 1 key files |
| v2 | Generate/Delete version 2 key files |
| all | Generate/Delete version 1 and 2 key files |

### Default

Version 2 key files will be generated by default

### Mode

Global Configuration

### Usage

Use "**ip ssh**" command to generate the key files for ssh connection.
Use no form to delete key files. SSH connection may not connect if
no any v1 or v2 ssh key files exist.

### Example

This example shows how to delete and re-generate ssh version 2 key files.
Switch(config)# **no ip ssh v2**
**Switch(config)# do show flash**
**File Name File Size Modified**
**---------- ---------- ----------**
**startup-config 1913 2000-01-01 08:29:10**

```
rsa1                           976          2000-01-05 23:28:38
ssl_cert                       875          2000-01-05 23:03:20
image0 (active)                4856825      2014-04-02 15:17:34
```

Switch(config)# **ip ssh v2**

Generating a SSHv2 default RSA Key.
This may take a few minutes, depending on the key size.

Generating a SSHv2 default DSA Key.
This may take a few minutes, depending on the key size.

```
Switch(config)# do show flash
File Name                      File Size          Modified
-------------- ---------------- -------------
startup-config                 1913         2000-01-01 08:29:10
rsa1                           976          2000-01-05 23:28:38
rsa2                           1675         2000-01-05 23:34:43
dsa2                           668          2000-01-05 23:34:58
ssl_cert                       875          2000-01-05 23:03:20
image0 (active)    4856825     2014-04-02 15:17:34
```

## line

### Syntax

**line** ( **console** | **telnet** | **ssh** )

### Parameter

| | |
|---|---|
| console | Select console line to configure. |
| telnet | Select telnet line to configure. |
| ssh | Select ssh line to configure. |

### Default

No default value for this command.

### Mode

Global Configuration

### Usage

Some configurations are line based. In order to configure these configurations, we need to enter Line Configuration mode to configure them. Use "**line**" command to enter the Line Configuration mode and select the line to be configured.

In Line Configuration mode, the prompt will show as "**Switch(config-line)#**"

**Example**

This example shows how to enter Interface Configuration mode
Switch# **configure**
Switch(config)# **line console**
Switch(config-line)#

## reboot

**Syntax**

**reboot**

**Parameter**

**Default**

No default value for this command.

**Mode**

Privileged EXEC

**Usage**

Use "**reboot**" command to make system hot restart.

**Example**

This example shows how to restart the system
Switch# **reboot**

## enable password

### Syntax

**enable [privilege <1-15>] (password** *UNENCRYPY-PASSWORD* | **secrect***UNENCRYPY-PASSWORD* **| secret encrypted** *ENCRYPT-PASSWORD*)
**no enable** [**privilege** *<0-15>*]

### Parameter

| | |
|---|---|
| **privilege** *<0-15>* | Specify the privilege level to configure. If no privilege level is specified, default is 15. |
| **password** *UNENCRYPY-PASSWORD* | Specify password string and make it not encrypted. |
| **secret** *UNENCRYPY-PASSWORD* | Specify password string and make it encrypted. |
| **secret encrypted** *ENCRYPT-PASSWORD* | Enter an encrypted password. Use this keyword to enter a password that is already encrypted (for instance, a password that you copied from another the configuration file of another device). |

### Default

Default enable password for all privilege levels are "".

### Mode

Global Configuration

### Usage

Use "**enable password**" command to edit password for each privilege level for enable authentication. And use "**no enable**" command to restore enable password to default empty value.

The only way to show this configuration is using "**show running-config**" command.

### Example

This example shows how to edit enable password for privilege level 15
Switch(config)# **enable secret enblpasswd**

## exec-timeout

### Syntax

**exec-timeout** *<0-65535>*

### Parameter

| | |
|---|---|
| *<0-65535>* | Specify session timeout minutes. 0 means never timeout |

### Default

Default session timeout for all lines are 10 minutes.

### Mode

Line Configuration

### Usage

Use "exec-timeout" command to specify the session timeout value for CLI running on console, telnet or ssh service. When user login into CLI and do not do any action after session timeout will be logged out from the CLI session.

### Example

This example shows how to change console session timeout to 15min ,telnet session timeout to 20min and ssh session timeout to 25min.
Switch(config)# line console
Switch(config-line)# exec-timeout **15**
Switch(config-line)# **exit**
Switch(config)# **line telnet**
Switch(config-line)# **exec-timeout 20**
Switch(config-line)# **exit**
Switch(config)# **line ssh**
Switch(config-line)# **exec-timeout 25**

Switch(config-line)# **exit**

This example shows how show line information.

Switch# **show line**

```
Console
==============================================
Session Timeout : 15 (minutes)
History Count     : 128
Password Retry    : 3
Silent Time       : 0 (seconds)

Telnet
================================
================
Telnet Server     : disabled
Session Timeout : 20 (minutes)
History Count     : 128
Password Retry    : 3
Silent Time       : 0 (seconds)


SSH
================================================
SSH Server          : disabled
Session Timeout : 25 (minutes)
History Count     : 128
Password Retry    : 3
Silent Time       : 0 (seconds)
```

## password-thresh

### Syntax

**password-thresh** *<0-120>*

### Parameter

| | |
|---|---|
| *<0-120>* | Specify password fail retry number. 0 means no limit. |

### Default

Default password fail retry number is 3.

## Mode

Line Configuration

## Usage

Use "**password-thresh**" command to specify the password fail retry number for CLI running on console, telnet or ssh service. When user input password to login and authenticate failed, the fail retry number will increase one. After fail retry number exceed configured one, the CLI will block login for the period of silent time which configured by the command "**silent-time**".

## Example

This example shows how to change console fail retry number to 4, telnet fail retry number to 5 and ssh fail retry number to 6.

```
Switch(config)# line console
Switch(config-line)# password-thresh 4
Switch(config-line)# exit
Switch(config)# line telnet
Switch(config-line)# password-thresh 5
Switch(config-line)# exit
Switch(config)# line ssh
Switch(config-line)# password-thresh 6
Switch(config-line)# exit
```

This example shows how show line information.

```
Switch# show line
Console
=====================================
Session Timeout : 10 (minutes)
History Count                 : 128
Password Retry                : 4
Silent Time                   : 0 (seconds)


Telnet
==============================
========
Telnet Server                 :
disabled
Session Timeout : 10 (minutes)
History Count                 : 128
Password Retry                : 5
Silent Time                   : 0 (seconds)
```

SSH
==========
SSH Server : disabled
Session Timeout : 10 (minutes)
History Count : 128
Password Retry : 6
Silent Time : 0 (seconds)

## ping

### Syntax

**ping** *HOSTNAME* **[count** *<1-999999999>***]**

### Parameter

| | |
|---|---|
| *HOSTNAME* | Specify IPv4/IPv6 address or domain name to ping. |
| **count** *<1-999999999>* | Specify how many times to ping. |

### Default

No default value for this command.

### Mode

User EXEC
Privileged EXEC

### Usage

Use "**ping**" command to do network ping diagnostic.

### Example

This example shows how to ping remote host 192.168.1.111.
Switch# **ping 192.168.1.111**
PING 192.168.1.111 (192.168.1.111): 56 data bytes

64 bytes from 192.168.1.111: icmp_seq=0 ttl=128 time=10.0 ms
64 bytes from 192.168.1.111: icmp_seq=1 ttl=128 time=0.0ms
64 bytes from 192.168.1.111: icmp_seq=2 ttl=128 time=0.0ms
64 bytes from 192.168.1.111: icmp_seq=3 ttl=128 time=0.0ms

--- 192.168.1.111 ping statistics ---
4 packets transmitted, 4 packets received, 0% packet loss
round-trip min/avg/max = 0.0/2.5/10.0ms

## traceroute

### Syntax

**traceroute** *A.B.C.D* **[max_hop** *<2-255>***]**

### Parameter

| | |
|---|---|
| *A.B.C.D* | Specify IPv4 to trace. |
| **max_hop** *<2-255>* | Specify maximum hop to trace. |

### Default

No default value for this command.

### Mode

User EXEC
Privileged EXEC

### Usage

Use "**traceroute**" command to do network trace route diagnostic.

### Example

This example shows how to trace route host 192.168.1.111.
Switch# **traceroute 192.168.1.111**
traceroute to 192.168.1.111 (192.168.1.111), 30 hops max, 40 byte packets
1 192.168.1.111 (192.168.1.111) 0 ms 10 ms 0 ms

## silent-time

### Syntax

**silent-time** *<0-65535>*

### Parameter

| | |
|---|---|
| *<0-65535>* | Specify silent time with unit seconds. 0 means do not silent. |

### Default

Default silent time is 0.

### Mode

Line Configuration

### Usage

Use "**silent time**" command to specify the silent time for CLI running on console, telnet or ssh service. When user input password to login and authenticate failed, the fail retry number will increase one. After fail retry number exceed configured one, the CLI will block login for the period of silent time which configured by the command "**silent-time**"..

### Example

This example shows how to change silent time.

```
Switch(config)# line console
Switch(config-line)# silent-time 10
```

This example shows how show line information.

```
Console
==============================
Session Timeout : 10 (minutes)
History Count    : 128
Password Retry   : 3
```

Silent Time : 10 (seconds)

## system name

### Syntax

**system name** *NAME*

### Parameter

| | |
|---|---|
| *NAME* | Specify system name string. |

### Default

Default name string is "Switch".

### Mode

Global Configuration

### Usage

Use "**system name**" command to modify system name information of the switch. The system name is also used to be CLI prompt.

### Example

This example shows how to modify contact information

```
Switch(config)# system name myname
myname(config)#
```

This example shows how to show system name information

```
Switch# show info
System Name          : myname
System Location      : Default Location
System Contact       : Default Contact
MAC Address          : DE:AD:BE:EF:01:02
IP Address           : 192.168.1.1
Subnet Mask          : 255.255.255.0
Loader Version       : 1.3.0.26225
Loader Date          : Thu May 17 15:19:42 CST 2012
```

Firmware Version : 2.5.0-beta.32811
Firmware Date : Mon Sep 24 19:33:42 CST 2012
System Object ID : 1.3.6.1.4.1.27282.3.2.10
System Up Time : 0 days, 0 hours, 2 mins, 37 secs

## system contact

### Syntax

**system contact** *CONTACT*

### Parameter

| | |
|---|---|
| *CONTACT* | Specify contact string. |

### Default

Default contact string is "Default Contact".

### Mode

Global Configuration

### Usage

Use "**system contact**" command to modify contact information of the switch.

### Example

This example shows how to modify contact information
Switch(config)# **system contact callme**

This example shows how to show system contact information
Switch# **show info**
System Name : Switch
System Location : Default Location
System Contact : callme
MAC Address : DE:AD:BE:EF:01:02
IP Address : 192.168.1.1
Subnet Mask : 255.255.255.0

Loader Version : 1.3.0.26225
Loader Date : Thu May 17 15:19:42 CST 2012
Firmware Version : 2.5.0-beta.32811
Firmware Date : Mon Sep 24 19:33:42 CST 2012
System Object ID : 1.3.6.1.4.1.27282.3.2.10
System Up Time : 0 days, 0 hours, 2 mins, 37 secs

## system location

### Syntax

**system location** *LOCATION*

### Parameter

| | |
|---|---|
| *CONTACT* | Specify location string. |

### Default

Default location string is "Default Location".

### Mode

Global Configuration

### Usage

Use "**system location**" command to modify location information of the switch.

### Example

This example shows how to modify contact information
Switch(config)# **system location home**

This example shows how to show system location information
Switch# **show info**
System Name : SwitchEF0102
System Location : home
System Contact : Default Contact
MAC Address : DE:AD:BE:EF:01:02

IP Address : 192.168.1.1
Subnet Mask : 255.255.255.0
Loader Version : 1.3.0.26225
Loader Date : Thu May 17 15:19:42 CST 2012
Firmware Version : 2.5.0-beta.32811
Firmware Date : Mon Sep 24 19:33:42 CST 2012
System Object ID : 1.3.6.1.4.1.27282.3.2.10
System Up Time : 0 days, 0 hours, 2 mins, 37 secs

## terminal length

### Syntax

**terminal length** *<0-24>*

### Parameter

| | |
|---|---|
| *<0-24>* | Specify terminal length value. 0 means no limit. |

### Default

Default terminal length is 24.

### Mode

User EXEC
Privileged EXEC

### Usage

Use "**terminal length**" command to specify the maximum line number the terminal is able to print.

### Example

This example shows how to change terminal length.
Switch# **terminal length 3** Switch# **show**
**running-config SYSTEM CONFIG FILE ::=**
**BEGIN**
**! System Description: RTK RTL8380-24FE-4GEC Switch**

! System Version: v3.0.4.46766
--More--

## username

### Syntax

**username** *WORD<0-32>* [**privilege** (**admin|user|** *<0-15>*)] **(nopassword | password** *UNENCRYPY-PASSWORD* | **secrect** *UNENCRYPY-PASSWORD* **| secret encrypted** *ENCRYPT-PASSWORD*)

**no username** *WORD<0-32>*

### Parameter

| | |
|---|---|
| **username** *WORD<0-32>* | Specify user name to add/delete/edit. |
| **privilege admin** | Specify privilege level to be admin (privilege 15) |
| **privilege user** | Specify privilege level to be user (privilege 1) |
| **privilege** *<0-15>* | Specify custom privilege level |
| **nopassword** | Specify do not use password |
| **password** *UNENCRYPY-PASSWORD* | Specify password string and make it not encrypted. |
| **secret** *UNENCRYPY-PASSWORD* | Specify password string and make it encrypted. |
| **secret encrypted** *ENCRYPT-PASSWORD* | Enter an encrypted password. Use this keyword to enter a password that is already encrypted (for instance, a password that you copied from another the configuration file of another device). |

### Default

Default username "admin" has password "admin" with privilege 15.

### Mode

Global Configuration

### Usage

Use "**username**" command to add a new user account or edit an existing user account. And use "**no username**" to delete an existing user account. The user account is a local database for login authentication.

### Example

This example shows how to add a new user account.

```
Switch(config)# username test secret passwd
```

This example shows how to show existing user accounts.

```
Switch# show username
Priv | Type          |           User Name        |
           Password
------+---------+--------------------+--
---------
01       | secret |                   | dnXencJRwfIV6
15       | secret |       admin | FzjrGO6vfbERY
15           | secret |                test |
7p57T9yMkViSUS
```

## show arp

### Syntax

### show arp

### Parameter

### Default

No default value for this command.

### Mode

User EXEC
Privileged EXEC

**Usage**

Use "**show arp**" command to show all arp entries.

**Example**

This example shows how to show arp entries.

```
Switch# show arp
Address         HWtype HWaddress           Flags Mask         Iface
192.168.1.111 ether       00:0E:2E:F1:4B:3C              C             eth0
```

## show cpu utilization

**Syntax**

**show cpu utilization**

**Parameter**

**Default**

No default value for this command.

**Mode**

Privileged EXEC

**Usage**

Use "**show cpu utilization**" command to show current CPU utilization.

**Example**

This example shows how to show current CPU utilization.

```
Switch# show cpu utilization
CPU utilization
---------------
```

Current: 30%

## show history

### Syntax

### show history

### Parameter

### Default

No default value for this command.

### Mode

User EXEC
Privileged
EXEC
Global
Configuratio
n

### Usage

Use "**show history**" to show commands we input before.

### Example

This example shows how show history commands.

```
Switch# show history
Maximun History Count: 100
-------------------------------------------------
1.   enable
2.   configure
4.        line consoleexit
5.        show history
6.        line
7.        exit
8.        show history
9.        configure
10.         line
11.         line console
12.         exit
```

```
13.         line console
14.         history 100
15.         exit
16.         show history
17.         exit
18.     show history
```

## show info

### Syntax

### show info

### Parameter

### Default

No default value for this command.

### Mode

User EXEC
Privileged EXEC

### Usage

Use "**show info**" command to show system summary information.

### Example

This example shows how to show system version.

```
Switch# show info
System Name             : Switch
System Location         : Default Location
System Contact          : Default Contact
MAC Address             : DE:AD:BE:EF:01:02
IP Address              : 192.168.1.1
Subnet Mask             : 255.255.255.0
Loader Version          : 1.3.0.26225
Loader Date             : Thu May 17 15:19:42 CST 2012
Firmware Version : 2.5.0-beta.32811
Firmware Date           : Mon Sep 24 19:33:42 CST 2012
System Object ID : 1.3.6.1.4.1.27282.3.2.10
System Up Time : 0 days, 1 hours, 49 mins, 29 secs
```

## show ip

### Syntax

**show ip**

### Parameter

### Default

No default value for this command.

### Mode

User EXEC
Privileged EXEC

### Usage

Use "**show ip**" command to show system IPv4 address, net mask and default gateway.

### Example

This example shows how to show current ipv4 address of the switch.
Switch# **show ip**
IP Address: 192.168.1.200
Subnet Netmask: 255.255.255.0
Default Gateway: 192.168.1.254

## show ip dhcp

### Syntax

**show ip dhcp**

### Parameter

### Default

No default value for this command.

**Mode**

User EXEC
Privileged EXEC

**Usage**

Use "**show ip dhcp**" command to show IPv4 dhcp client enable state.

**Example**

This example shows how to show current dhcp client state of the switch.
Switch# **show ip dhcp**
DHCP Status : enabled

## show ip http

**Syntax**

**show ip** (**http**|**https**)

**Parameter**

**Default**

No default value for this command.

**Mode**

Privileged EXEC

**Usage**

Use "**show ip http**" command to show HTTP/HTTPS information.

**Example**

This example shows how to show current ipv4 address of the switch.
Switch# **show ip http**
HTTP daemon : enabled
Session Timeout : 10 (minutes)

Switch# **show ip https**
HTTPS daemon : enabled
Session Timeout : 10 (minutes)

## show ipv6

### Syntax

**show ipv6**

### Parameter

### Default

No default value for this command.

### Mode

User EXEC
Privileged EXEC

### Usage

Use "**show ipv6**" command to show system IPv6 address, net mask, default gateway and auto config state.

### Example

This example shows how to show current ipv6 address of the switch.
Switch# **show ipv6**
###### Config ######

State: enabled

Auto Config: enabled

DHCPv6: disabled

Gateway: ::

###### Status ######

IP Address: fe80::7a76:d9ff:fe0c:1af/64

Default Gateway: ::

## show line

### Syntax

**show line** [(**console** | **telnet** | **ssh**)]

### Parameter

| | |
|---|---|
| **console** | Select console line to show. |
| **telnet** | Select telnet line to show. |
| **ssh** | Select ssh line to show. |

### Default

No default value for this command.

### Mode

Privileged EXEC

### Usage

Use "**show line**" command to show all line configurations including session timeout, history count, password retry number and silent time. For telnet and ssh, it also shows the service enable/disable state.

### Example

This example shows how show all lines' information.

Switch# **show line**
Console ==========
Session Timeout : 15 (minutes)
History Count : 128
Password Retry : 3
Silent Time : 0 (seconds)

```
Telnet ================================
Telnet Server                  : disabled
Session Timeout : 20 (minutes)
History Count                  : 128
Password Retry                 : 3
Silent Time                    : 0 (seconds)

SSH ===================================
SSH Server                     : disabled
Session Timeout : 25 (minutes)
History Count                  : 128
Password Retry                 : 3
Silent Time         : 0 (seconds)
```

## show memory statistics

### Syntax

### show memory statistics

### Parameter

### Default

No default value for this command.

### Mode

Privileged EXEC

### Usage

Use "**show memory statistics**" command to show current memory utilization.

### Example

This example show how to show current system memory statistics.

```
                 total(KB)       used(KB)       free(KB)     shared(KB)     buffer(KB)      cache(KB)
-------------------+------------+------------+------------+------------+------------+--------
----
Mem:             126184          80368          45816              0              0
0
```

-/+ buffers/cache: 80368 45816

Swap: 0 0 0

## show privilege

### Syntax

**show privilege**

### Parameter

### Default

No default value for this command.

### Mode

User EXEC
Privileged EXEC

### Usage

Use "**show privilege**" command to show the privilege level of the current user.

### Example

This example shows how to show privilege.

Switch# **show privilege**
Current CLI Username: admin
Current CLI Privilege: 15

## show username

### Syntax

**show username**

### Parameter

### Default

No default value for this command

### Mode

Privileged EXEC

### Usage

Use “**show username**” command show all user accounts in local database.

### Example

This example shows how to show existing user accounts.

```
Switch# show username
Priv | Type          |       User Name          |                 Password
------+--------+--------------------+----------------------
01      | secret |                                                | dnXencJRwflV6
15      | secret |                                    admin | FzjrGO6vfbERY
15          | secret |                        test | 7p57T9yMkViSUS
```

## show users

### Syntax

### show users

### Parameter

### Default

No default value for this command

### Mode

Privileged EXEC

### Usage

Use "**show users**" command show information of all active users.

**Example**

This example shows how to show existing user accounts.

```
Switch# show users
Username      Protocol                       Location
---------- ------------ ----------------------
admin                      console             0.0.0.0
admin                       telnet                  192.168.1.111
admin           ssh          192.168.1.111
```

## show version

**Syntax**

**show version**

**Parameter**

**Default**

No default value for this command.

**Mode**

User EXEC
Privileged EXEC

**Usage**

Use "**show version**" command to show loader and firmware version and build date.

**Example**

This example shows how to show system version.

```
Switch# show version
Loader Version              : 1.3.0.26225
Loader Date                 : Thu May 17 15:19:42 CST 2012
Firmware Version : 2.5.0-beta.32811
Firmware Date    : Mon Sep 24 19:33:42 CST 2012
```

# 4.Authentication Manager

## authentication

### Syntax

**authentication** (**dot1x**|**mac**|**web**)

**no authentication** (**dot1x**|**mac**|**web**)

### Parameter

### Default

Default is disabled for all type

### Mode

Global Configuration

### Usage

Use "**authentication**" command to enable the global setting of 802.1x/MAC/WEB authentication network access control.

### Example

The following example shows how to enable 802.1x/MAC/WEB authentication.

Switch(config)# authentication dot1x

Switch(config)# **authentication mac**

Switch(config)# **authentication web**

**This example shows how to show authentication**

Autentication dot1x state : enabled
Autentication mac state : enabled
Autentication web state : enabled

Guest VLAN : enabled (3)

Mac-auth Radius User ID Format: XXXXXXXXXXXX

……

## authentication(Interface)

### Syntax

**authentication** (**dot1x**|**mac**|**web**)

**no authentication** (**dot1x**|**mac**|**web**)

### Parameter

### Default

Default is disabled for all type

### Mode

Interface Configuration

### Usage

Use "**authentication**" interface command to enable the port setting of 802.1x/MAC/WEB authentication network access control.

### Example

The following example shows how to enable 802.1x/MAC/WEB authentication.

Switch(config)# **interface fa1**
Switch(config-if)# **authentication dot1x**
Switch(config-if)# **authentication mac**
Switch(config-if)# **authentication web**

The following example shows how to show authentication interface

Switch# **show authentication interface fa1**
Interface FastEthernet1
Admin Control : disable
Host Mode : multi-auth
Type dot1x State : enabled
Type mac State : enabled
Type web State : enabled

## authentication mac radius

### Syntax

**authentication mac radius** [**mac-case** (**lower**|**upper**)] [**mac-delimiter**(**colon**|**dot**|**hyphen**|**none**) [**gap** (2|4|6)]]

### Parameter

| | |
|---|---|
| **mac-case** (**lower**\|**upper**) | Select radius user id to be upper case or lower case. |
| **mac-delimiter** (**colon**\|**dot**\|**hyphen**\|**none**) | Select radius user id delimiter<br>colon: XX:XX:XX:XX:XX:XX<br>dot: XX.XX.XX.XX.XX.XX<br>hyphen: XX-XX-XX-XX-XX-XX<br>none: XXXXXXXXXXXX |
| **gap** (2\|4\|6) | Select delimiter gap<br>2: XX-XX-XX-XX-XX-XX<br>4: XXXX-XXXX-XXXX<br>6: XXXXXX-XXXXXX |

### Default

Default radius id format is upper case with none delimiter.

### Mode

Global Configuration

### Usage

Use "**authentication mac radius**" command to configure the radius user id format used by MAC authentication Radius method.

### Example

The following example shows how to configure MAC authentication radius id

format to be upper case with colon delimiter every 2 chars
Switch(config)# **authentication mac radius mac-case upper**
Switch(config)# **authentication mac radius mac-delimiter colon gap 2**
Switch# **show authentication**
Autentication dot1x state : enabled
Autentication mac state : disabled
Autentication web state : disabled
Guest VLAN : disabled
Mac-auth Radius User ID Format: XX:XX:XX:XX:XX:XX
……

## authentication mac local

### Syntax

**authentication mac local** *mac-addr* **control auth** [**vlan** *<1-4094>*] [**reauth-period** *<300-4294967294>*] [**inactive-timeout** *<60-65535>*]
**authentication mac local** *mac-addr* **control unauth no authentication mac local** *mac-addr*

### Parameter

| | |
|---|---|
| ***mac-addr*** | MAC Authentication local MAC address |
| **control auth** | Host with this MAC address will be authorized |
| **control unauth** | Host with this MAC address will be force unauthorized |
| **vlan** *<1-4094>* | MAC Authentication host assigned VLAN |
| **reauth-period** *<300-4294967294>* | MAC Authentication host reauthentication period |
| **inactive-timeout** *<60-65535>* | MAC authentication host inactive timeout |

### Default

Default is no local MAC Authentication entry.

### Mode

Global Configuration

### Usage

Use "**authentication mac local**" command to add local MAC authentication hosts in database. This local host database is used when MAC authentication method is configured as "local". The MAC authentication module will find host in this local database and authenticated it.

### Example

The following example shows how to add a new local mac authentication host.

Switch(config)# **authentication mac local 00:11:22:33:00:01 control auth vlan 3 reauth-period 500 inactive-timeout 300**

The following example shows how to show authentication

Switch# **show authentication**

.....

Mac-auth Local Entry :

| Reauth | | Inactive Timeout | MAC Address | Control | VLAN | Period |
|---|---|---|---|---|---|---|
| 00:11:22:33:00:01 | Authorized | 3 | 500 | 300 | | |

.....

## authentication guest-vlan

### Syntax

**authentication guest-vlan** *<1-4094>*

**no authentication guest-vlan**

### Parameter

| | |
|---|---|
| *<1-4094>* | Guest VLAN ID |

### Default

Default guest VLAN is disabled

**Mode**

Global Configuration

**Usage**

Use "**authentication guest-vlan**" command to enable the global setting of guest VLAN and specify guest VLAN ID.

**Example**

The following example shows how to create guest VLAN.
Switch(config)# **vlan 3**

## authentication guest-vlan (Interface)

**Syntax**

**authentication guest-vlan**

**no authentication guest-vlan**

**Parameter**

**Default**

Default guest VLAN is disabled

**Mode**

Interface Configuration

**Usage**

Use "**authentication guest-vlan**" command to enable the port setting of guest VLAN.

**Example**

The following example shows how to enable guest VLAN.

Switch(config)# **interface gi1**
Switch(config-if)# **authentication guest-vlan**

## authentication host-mode

### Syntax

**authentication host-mode (multi-auth|multi-host|single-host)**
**no authentication host-mode**

### Parameter

| | |
|---|---|
| **multi-auth** | Multiple Authentication Mode. In this mode, every client need to pass authenticate procedure individually. |
| **multi-host** | Multiple Host Mode. In this mode, only one client need to be authenticated and other clients will get the same access accessibility. |
| **single-host** | Single Host Mode. In this mode, only one host is allowed to be authenticated. It is the same as multi-auth mode with max hosts number configure to be 1. |

### Default

Default is multi-auth mode.

### Mode

Interface Configuration

### Usage

Use "**authentication host-mode**" command to configure the port authentication host mode.
Use the **no** form of this command to restore default value.

### Example

The following example shows how to modify port host mode to multi-host.

```
Switch(config)# interface fa1
Switch(config-if)# authentication host-mode multi-host
Switch# show authentication interface fa1
Interface FastEthernet1
Admin Control                   : auto
Host Mode                       : multi-host
Type dot1x State                : disabled
Type mac State                  : disabled
Type web State                  : disabled
```

## authentication max-hosts

### Syntax

**authentication max-hosts <1-256>**
**no authentication max-hosts**

### Parameter

| | |
|---|---|
| *<1-256>* | Available max host number in multi-auth mode. |

### Default

Default max host number is 256

### Mode

Interface Configuration

### Usage

Use "**authentication max-hosts**" command to configure the port max hosts number for multi-auth mode. The host exceed the max host number is not allowed to create authentication session and do authenticating.
Use **no** form of this command to restore default value.

### Example

The following example shows how to change port max hosts number.

```
Switch(config)# interface fa1
Switch(config-if)# authentication max-hosts 100
Switch# show mac-auth interface fa1
Interface FastEthernet1
Admin Control                   : disable
Host Mode                       : multi-auth
Type dot1x State                : disabled
Type mac State                  : disabled
Type web State                  : disabled
Type Order                      : dot1x MAC/WEB
Method Order                    : radius Guest
VLAN                            : disabled
Reauthentication                : disabled
Max Hosts                       : 100
```

## authentication port-control

### Syntax

**authentication port-control** (**auto**|**force-auth**|**force-unauth**)

**no authentication port-control**

### Parameter

| | |
|---|---|
| **auto** | Need passing authentication procedure to get network accessibility. |
| **force-auth** | Port is force authorized and all clients have network accessibility. |
| **force-unauth** | Port is force unauthorized and all clients have no network accessibility. |

### Default

Default is disabled.

### Mode

Interface Configuration

### Usage

Use "**authentication port-control**" command to enable the port authentication control mode.
Use the **no** form of this command to disable authentication port control.

### Example

The following example shows how to configure port control to auto mode.

```
Switch(config)# interface fa1
Switch(config-if)# authentication port-control auto
Switch# show authentication interface fa1
Interface FastEthernet1
Admin Control                   : auto
Host Mode                       : multi-auth
Type dot1x State                : disabled
Type mac State                  : disabled
Type web State                  : disabled
```

## clear authentication sessions

### Syntax

**clear authentication sessions**
**clear authentication sessions interfaces** *IF_PORTS*
**clear authentication sessions mac** *mac-addr*
**clear authentication sessions session-id** *WORD*
**clear authentication sessions type** (**dot1x**|**mac**|**web**)

### Parameter

| | |
|---|---|
| **interfaces** *IF_PORTS* | Clear sessions on specific interface |
| **mac** *mac-addr* | Clear session with specific MAC address |
| **session-id** *WORD* | Clear session with specific session ID |
| **type** (**dot1x**\|**mac**\|**web**) | Clear session with specific authentication type |

### Default

Default is no local authentication entry.

**Mode**

Privileged EXEC

**Usage**

Use "**clear authentication sessions**" command to delete existing authentication sessions. If no parameter is specified, all sessions will be deleted.
After authentication session is deleted, host need to do authentication procedure again.

**Example**

The following example shows how to clear all authentication sessions.
Switch# **clear authentication sessions**
Switch# **show authentication sessions**
No Auth Manager sessions currently exist

## show authentication

**Syntax**

**show authentication**
**show authentication interfaces** *IF_PORTS*

**Parameter**

| | |
|---|---|
| **interfaces** *IF_PORTS* | Specify port list to show port configurations. |

**Default**

No default value for this command.

**Mode**

Privileged EXEC

## Usage

Use "**show authentication**" command to show all authentication manager configurations.
Use "**show authentication interface**" command to show authentication manager configuration of specific port.

## Example

This example shows how to show the mac authentication configurations of port fa1.

```
Switch# show authentication
Autentication dot1x state          : enabled
Autentication mac state: disabled
Autentication web state: disabled
Guest VLAN      : disabled
Mac-auth Radius user ID Format: XXXXXXXXXXXX

Mac-auth Local Entry    :
Reauth            Inactive MAC Address   Control VLAN    Period   Timeout
------------------- -------------- ------ ---------- ---------
00:11:22:33:44:55         Authorized       3         30000   123

Web-auth Local Entry    :
Reauth  Inactive
user Name       VLAN    Period   Timeout
-------------------------------- ------ ---------- ---------
acct1    5         12345   333

Interface Configurations Interface GigabitEthernet1
Admin Control  : disable
Host Mode       : multi-auth
Type dot1x State          : disabled
Type mac State : disabled
Type web State : disabled
Type Order       : dot1x MAC/WEB
Method Order   : radius
Guest VLAN      : disabled
Reauthentication          : disabled
Max Hosts       : 256
VLAN Assign Mode       : static Common Timers
Reauthenticate Period: 3600 Inactive Timeout    : 60
Quiet Period     : 60 802.1x Parameters
EAP Max Request          : 2
EAP TX Period : 30 Supplicant Timeout : 30 Server Timeout : 30
Web-auth Parameters
```

Login Attempt : 3

Switch# **show authentication interface g7**
Interface ConfigurationsInterface GigabitEthernet7
Admin Control : auto
Host Mode : multi-auth
Type dot1x State : enabled
Type mac State : disabled
Type web State : disabled
Type Order : dot1x MAC/WEB
Method Order : radius Guest
VLAN : disabled
Reauthentication : disabled
Max Hosts 256
VLAN Assign Mode : static
Common Timers Reauthenticate Period: 3600
Inactive Timeout 60
Quiet Period 60
802.1x Parameters
EAP Max Request 2
EAP TX Period 30
Supplicant Timeout 30
Server Timeout : 65535
Web-auth Parameters
Login Attempt

## show authentication sessions

### Syntax

**show authentication sessions [detail]**
**show authentication sessions interface IF_PORTS**
**show authentication sessions session-id WORD**
**show authentication session type (dot1x|mac|web)**

### Parameter

| | |
|---|---|
| **detail** | Show session detail information. |
| **interface** *IF_PORTS* | Show session detail information of specific port |
| **session-id** *WORD* | Show session detail information of specific session id |
| **type** (**dot1x**\|**mac**\|**web**) | Show session detail information of specific authentication type |

### Default

No default value for this command.

### Mode

Privileged EXEC

### Usage

Use "**show authentication sessions**" command to show authentication detail session information.

### Example

This example shows how to show current authentication session brief and detail information.

Switch# **show authentication sessions**

| Interface | MAC Address | Type | Status | Session ID |
|---|---|---|---|---|
| Fa7 | 00:01:6C:CB:29:4A | dot1x | Authorized | 0000000010000A028 |

Switch# **show authentication sessions detail**

```
Interface                       : FastEthernet7
MAC Address                     : 00:01:6C:CB:29:4A
Session ID                      : 0000000010000A028
Current Type                    : dot1x
Status                          : Authorized
Authorized Information
VLAN                            : 5 (from RADIUS)
Reauthenticate Period: 301 (from RADIUS)
Inactive Timeout                : 600 (from RADIUS)
Operational Information
VLAN                            : 5
Session Time                    : 1143
Inactive Time                   : 168
Quiet Time      : N/A
```

# 5. Diagnostic

## show cable-diag

### Syntax

**show cable-diag interfaces** *IF_NMLPORTS*

### Parameter

| | |
|---|---|
| **interfaces** *IF_NMLPORTS* | Display the cable diagnostic information of the copper media for an interface ID or a list of interfaces IDs. |

### Default

### Mode

Privileged EXEC

### Usage

To show the estimated copper cable length attached to a specific interface, use the command **show cable-diag** in the Privilegeg EXEC mode. For the proper information of the cable length, the interface must be active and linked up.

### Example

The following example shows the result of cable diagnostic for the interface fa1 and fa2.

```
Switch# show cable-diag interfaces fa1-2
Port          |    Speed | Local pair | Pair length | Pair status
--------+--------+------------+-------------+--------------
fa1           |    auto    |       Pair A       |         0.88         | Open
Pair B   |   0.82    | Open
Pair C   |   0.80    | Open
Pair D   |   0.78    | Open

fa2           |    auto    |       Pair A         |    0.81           | Open
Pair B   |   0.81    | Open
Pair C   |   0.77    | Open
Pair D   |   0.81    | Open
```

## show fiber-transceiver

### Syntax

**show fiber-transceiver interfaces** *IF_NMLPORTS*

**Parameter**

| | |
|---|---|
| **interfaces** *IF_NMLPORTS* | Display the o diagnostic information of the fiber transceiver for an interface ID or a list of interface IDs. |

**Default**

**Mode**

Privileged EXEC

**Usage**

To show the diagnostic information of the fiber transceiver use the command **show fiber-transceiver** in the Privilegeg EXEC mode.

**Example**

The following example shows the diagnostic information for the interface gi1 and gi2, wherer the int fiber media ports with the transceiver inserted.

```
Switch# show fiber-transceiver interfaces gi1-2
Port    | Temperature | Voltage      | Current              | Output power | Input power |
| [C]                                  | [Volt]          | [mA]                 | [mWatt]               |
[mWatt]                              |
================================================================================
================
  gi1          | N/S          | N/S            | N/S            | N/S                  | N/S                  |
Insert       |
gi2        | N/S          | N/S            | N/S                | N/S          | N/S        | Insert   |
```

Temp - Internally measured transceiver temperature
Voltage - Internally measured supply voltage
Current - Measured TX bias current
Output Power - Measured TX output power in milliWatts
Input Power - Measured RX received power in milliWatts
OE-Present - SFP Presetn or Not Present
LOS - Loss of signal
N/A - Not Available, N/S - Not Supported, W - Warning, E – Error

# 6. DHCP Servre

## dhcp-client

### Syntax

**dhcp-client bind**
**dhcp-client** *A:B:C:D:E:F A.B.C.D <1-4094> NAME*
**no dhcp-client bind**
**no dhcp-client** *A:B:C:D:E:F A.B.C.D <1-4094>*

### Parameter

| | |
|---|---|
| *A:B:C:D:E:F* | Client MAC address |
| *A.B.C.D* | IP address manually assigned to the client |
| *<1-4094>* | VLAN ID corresponding to the client |
| *NAME* | Name, character range 1-32 |

### Default

### Mode

Global Configuration

### Usage

Use the command "DHCP client bind" to enable the static allocation function, so that the server can assign a specified IP address to a fixed client port. Note that the address used for static allocation needs to be within the range of IP address pool allocation.

### Example

Enable static allocation function

switch(config)# dhcp-client bind

Configure static client table entries

switch(config-if)# dhcp-client 00:00:00:00:00:FE 172.168.1.200 172 MyPc

Query client list

switch# show dhcp-server clients

dhcp-client table info:

| MAC Address | ipAddress | VlanId | Hostname |
|---|---|---|---|
| 00:00:00:00:00:FD | 172.168.1.4 | 172 | rbwww |
| 00:00:00:00:00:FE | 172.168.1.200 | 172 | rbwww |

## dhcp-relay

### Syntax

**dhcp-relay**
**no dhcp-relay**

### Parameter

### Default

### Mode

Interface Configuration

### Usage

Use the command "dhcp-relay" to enable port-level functionality of the DHCP server under the interface, noting that either the DHCP server functionality or the DHCP Relay function port group switch needs to be enabled.

### Example

Enable DHCP Server Functions under Interface.

switch(config)# **interface GigabitEthernet 1**

switch(config-if)# **dhcp-relay**

## dhcp-server

### Syntax

**dhcp-server**
**no dhcp-server**

### Parameter

### Default

### Mode

Global Configuration

### Usage

Use the command "dhcp-server" to enable DHCP server global functionality.

### Example

Enabling DHCP server functionality

switch(config)# **dhcp-server**

## dhcp-server group (Global)

### Syntax

**dhcp-server group** *<1-256>* **ip** *A.B.C.D*
**no dhcp-server group** *<1-256>* **ip**

### Parameter

| | |
|---|---|
| *group* | Number of DHCP Server Group |
| *ip* | IP Address of Server Group |

**Default**

**Mode**

Global Configuration

**Usage**

Configure server groups using the command "dhcp-server group"

**Example**

Configure Server Groups

switch(config)# **dhcp-server group 1 ip 172.168.1.1**

## dhcp-server group (Interface)

**Syntax**

**dhcp-server group** *<1-256>*
**no dhcp-server group** *<1-256>*

**Parameter**

| | |
|---|---|
| *group* | Number of DHCP Server Group |

**Default**

**Mode**

VLAN Interface Configuration Mode

**Usage**

Use the command "DHCP server group" to establish the server group and interface relationship under the VLAN interface.

**Example**

Configure server group and VLAN interface relationships.

switch(config)# **interface vlan 172**
switch(config)# **dhcp-server group 1**

## ip pool

**Syntax**

**ip pool** *WORD*
**gateway** *A.B.C.D/M*
**lease** *DD:HH:MM*
**section** *<1-8> A.B.C.D A.B.C.D*
**no ip pool** *WORD*
**no gateway**
**no lease**
**no section**

**Parameter**

| | |
|---|---|
| *WORD* | Address pool name of the DHCP server |
| *A.B.C.D/M* | Gateway IP address and mask |
| *DD:HH:MM* | Lease term assigned to client address |
| *<1-8>* | IP address segment for dynamic allocation |
| *A.B.C.D* | Start IP and end IP for dynamic allocation |

**Default**

**Mode**

Global Configuration

**Usage**

Use the command "IP pool" to configure the DHCP server address pool, including the assigned IP address segment, gateway, and lease term.

**Example**

Configure DHCP address pool ABC

```
switch(config)# ip pool abc
switch(config-ip-pool-abc)# gateway 172.168.1.1/24
switch(config-ip-pool-abc)# lease 0:12:0
switch(config-ip-pool-abc)# section 1 172.168.1.2 172.168.1.200
```

## show dhcp-server clients

**Syntax**

**show dhcp-server clients**

**Parameter**

**Default**

**Mode**

Privileged EXEC

**Usage**

Use the command "show DHCP server clients" to query the list of DHCP clients.

**Example**

Query DHCP client list

```
switch# show dhcp-server clients
dhcp-client table info:
MAC Address              ipAddress            VlanId Hostname
------------------- ---------------- ------ ----
00:00:00:00:00:FD    172.168.1.2          172      rbwww
```

# 7. DHCP Snooping

## ip dhcp snooping

**Syntax**

**ip dhcp snooping**
**no ip dhcp snooping**

**Parameter**

**Default**

**Mode**

DHCP snooping is disabled

**Usage**

Use the ip dhcp snooping command to enable DHCP Snooping function.

**Example**

The example shows how to enable DHCP Snooping on VLAN 1. You can verify settings by the following show ip dhcp snooping command.

```
switch(config)# ip dhcp snooping
switch(config)# ip dhcp snooping vlan 1
switch(config)# show ip dhcp snooping
DHCP Snooping        : enabled
Enable on following Vlans   1
circuit-id default format       : vlan-port
remote-id : 00:11:22:33:44:55 (Switch Mac in Byte Order)
```

## ip dhcp snooping vlan

### Syntax

ip dhcp snooping vlan VLAN-LIST

### Parameter

| | |
|---|---|
| **VLAN-LIST** | Specify VLAN ID or a range of VLANs to enable or<br>disable dynamic Arp inspection |

### Default

Default is disabled on all VLANs

### Mode

Global Configuration

### Usage

Use the **ip dhcp snooping vlan** command to enable VLANs on DHCP Snooping function. Use the **no** form of this command to disable VLANs on DHCP Snooping function.

### Example

The example shows how to enable VLAN 1-100 on DHCP Snooping, and then disable VLAN 30-40 on DHCP Snooping. You can verify settings by the following **show ip dhcp snooping** command.

switch(config)# **exit**
switch(config)# **ip dhcp snooping**
switch(config)# **ip dhcp snooping vlan 1-100**
switch(config)# **show ip dhcp snooping**
DHCP Snooping : enabled
Enable on following Vlans : 1-100
circuit-id default format : vlan-port
remote-id: 00:11:22:33:44:55 (Switch Mac in Byte Order)

switch(config)# **no ip dhcp snooping vlan 30-40**

```
switch(config)# show ip dhcp snooping
DHCP Snooping                  : enabled
Enable on following Vlans      : 1-29,41-
100
circuit-id default format : vlan-port
remote-id : 00:11:22:33:44:55 (Switch Mac in Byte Order)
```

## ip dhcp snooping trust

### Syntax

**ip dhcp snooping trust**
**no ip dhcp snooping trust**

### Parameter

### Default

DHCP snooping trust is disabled

### Mode

Interface Configuration

### Usage

Use the **ip dhcp snooping trust** command to set trusted interface. The switch does not check DHCP packets that are received on the trusted interface; it simply forwards it.

### Example

The example shows how to set interface gi1 to trust. You can verify settings by the following **show ip dhcp snooping interface** command.

```
switch(config)# interface gi1
switch(config-if)# ip dhcp snooping trust
switch(config-if)# do show ip dhcp snooping interface gi1
Interfaces | Trust State | Rate (pps) | hwaddr Check | Insert Option82 |
-----------+--------------+-----------+-----------------+-----------------+
```

gi1 | Trusted | None | disabled | disabled|

## ip dhcp snooping verify

### Syntax

**ip dhcp snooping verify mac-address**
**[no] ip dhcp snooping verify mac-address**

### Parameter

### Default

DHCP snooping verify mac-address is disabled

### Mode

Interface Configuration

### Usage

Use the **ip dhcp snooping verify** command to verify MAC address function on interface.
The "**mac-address**" drop DHCP packets that chaddr and ethernet-source-mac is not match.

### Example

The example shows how to set interface gi1 to validate "**mac- address"**. You can verify settings by the following **show ip dhcp snooping interface** command.
switch(config)# **interface gi1**
switch(config-if)# **ip dhcp snooping verify mac-address**
switch(config-if)# **do show ip dhcp snooping interface gi1**

```
Interfaces | Trust State | Rate (pps) | hwaddr Check | Insert Option82 |
-----------+--------------+-----------+-----------------+-----------------+
gi1        | Unrusted  | None         | disabled         | disabled         |
```

## ip dhcp snooping rate-limit

### Syntax

**ip dhcp snooping rate-limit <1-300>**
**[no] ip dhcp snooping rate-limit**

**Parameter**

| | |
|---|---|
| <1-300> | Set 1 to 300 PPS of DHCP packet rate limitation |

**Default**

Default is un-limited of DHCP packet

**Mode**

Interface Configuration

**Usage**

Use the **ip dhcp snooping rate-limit** command to set rate limitation on interface. The switch drop DHCP packets after receives more than configured rate of packets per second.

**Example**

The example shows how to set rate limit to 30 pps on interface gi1. You can verify settings by the following **show ip dhcp snooping interface** command.

```
switch(config)# interface gi1
switch(config-if)# ip dhcp snooping rate-limit 30
switch(config-if)# do show ip dhcp snooping interfaces gi1
Interfaces|Trust State|Rate (pps)|hwaddr Check|Insert Option82|
----------+-----------+----------+-----------+---------------+
gi1       | Untrusted | 30       | disabled            | disabled            |
```

## clear ip dhcp snooping statistics

**Syntax**

**clear ip dhcp snooping interfaces IF_PORTS statistics**

### Parameter

| | |
|---|---|
| IF_PORTS | specifies ports to clear statistics |

### Default

No default is defined

### Mode

Privileged EXEC

### Usage

Use the **clear ip dhcp snooping interfaces statistics** command to clear statistics that are recorded on interface.

### Example

The example shows how to clear statistics on interface gi1. You can verify settings by the following **show ip dhcp snooping interface statistics** command.

switch# **clear ip dhcp snooping interfaces gi1 statistics**

switch# **show ip dhcp snooping interfaces gi1 statistics**

```
Interfaces | Forwarded | Chaddr Check Dropped | Untrust Port
Dropped | Untrust Port With Option82 Dropped | Invalid Drop
-------+-----------+-----------------+---------------------+------------------------+---
-----
gi1       | 0           | 0               | 0           | 0             | 0
```

## show ip dhcp snooping

### Syntax

**show ip dhcp snooping**

### Parameter

**Default**

No default is defined

**Mode**

Privileged EXEC

**Usage**

Use the **show ip dhcp snooping** command to show settings of DHCP Snooping.

**Example**

The example shows how to show settings of DHCP Snooping

switch(config)# **show ip dhcp snooping**
DHCP Snooping : enabled
Enable on following Vlans : 1
circuit-id default format: vlan-port
remote-id: : 00:11:22:33:44:55 (Switch Mac in Byte Order)

# 8. DOS

## dos

**Syntax**

**dos (daeqsa-deny|icmp-frag-pkts-deny|icmpv4-ping-max- check|icmpv6-ping-max-check|ipv6-min-frag-size-check|land- deny|nullscan-deny|pod-deny|smurf-deny|syn-sportl1024-deny|synfin-deny|synrst-deny|tcp-frag-off-min-check|tcpblat-deny|tcphdr-min-check|udpblat-deny|xmas-deny)**
**dos icmp-ping-max-length** *MAX_LEN*
**dos ipv6-min-frag-size-length** *MIN_LEN*
**dos smurf-netmask** *MASK*
**dos tcphdr-min-length** *HDR_MIN_LEN*
**no dos (tcp-frag-off-min-check|synrst-deny|synfin-deny|xma- deny|nullscan-deny|syn-sportl1024-deny|tcphdr-min-check|smurf- deny|icmpv6-ping-max-check|icmpv4-ping-max-check|icmp-frag- pkts-deny|ipv6-min-frag-size-check|pod-**

deny|tcpblat- deny|udpblat-deny|land-deny|daeqsa-deny)

## Parameter

| | |
|---|---|
| **daeqsa-deny** | Drops the packets if the destination MAC address is<br>equal to the source MAC address. |
| **icmp-frag-pkts-deny** | Drops the fragmented ICMP packets. |
| **icmpv4-ping-max- check** | Checks the maximum size of ICMP ping packets, and drops the packets larger than the maximum packet size defined by the command **dos icmp-ping-max-length** *MAX_LEN*. |
| **icmpv6-ping-max- check** | Checks the maximum size of ICMPv6 ping packets, and drops the packets larger than the maximum packet<br>size defined by the command **dos icmp-ping-max- length** *MAX_LEN*. |
| **ipv6-min-frag- size-check** | Checks the minimum size of IPv6 fragments, and drops the packets smaller than the minimum size defined by the command **dos ipv6-min-frag-size-length**<br>*MIN_LEN*. |
| **land-deny** | Drops the packets if the source IP address is equal to<br>the destination IP address. |
| **nullscan-deny** | Drops the packets with NULL scan. |
| **pod-deny** | Avoids ping of death attack. |
| **smurf-deny** | Avoids smurf attack. |
| **syn-sportl1024-deny** | Drops SYN packets with sport less than 1024. |
| **synfin-deny** | Drops the packets with SYN and FIN bits set. |
| **synrst-deny** | Drops the packets with SYN and RST bits set. |
| **tcp-frag-off-min- check** | Drops the TCP fragment packets with offset equals to |

| | |
|---|---|
| | one. |
| **tcpblat-deny** | Drops the packages if the TCP source port is equal to<br>the TCP destination port. |
| **tcphdr-min-check** | Checks the minimum TCP header and drops the TCP packets with the header smaller than the minimum size defined by the command **dos tcphdr-min-length** *HDR_MIN_LEN*. |
| **udpblat-deny** | Drops the packets if the UDP source port equals to the<br>UDP destination port. |
| **xmas-deny** | Drops the packets if the sequence number is zero, and<br>the FIN, URG and PSH bits are set. |
| **icmp-ping-max- length** *MAX_LEN* | Specify the maximum size of the ICMPv4/ICMPv6 ping packets. The valid range is from 0 to 65535 bytes, and the default value is 512 bytes. |
| **ipv6-min-frag- size-length** *MIN_LEN* | Specify the minimum size of IPv6 fragments. The valid range is from 0 to 65535 bytes, and default value is<br>1240 bytes. |
| **smurf-netmask** *MASK* | Specify the netmask of smurf attack. The length range<br>is from 0 to 323 bytes, and default length is 0 bytes. |
| **tcphdr-min-length** *HDR_MIN_LEN* | Specify the minimum TCP header length. The length range is from 0 to 31 bytes, and default length is 20 bytes. |

**Default**

All of DoS protections are enabled by default. The default parameter are:

- The maximum size of ICMP ping packages is 512 bytes
- The minimum size of IPv6 fragments is 1240 bytes.

- The Smurf netmask length is 0 bytes.
- The minimum TCP header length is 20 bytes.

**Mode**

Global Configuration

**Usage**

To enable the specific Deniel of Service (DoS) protection, use the command **dos** in the Global Configuration mode. Otherwise.

**Example**

The following example sets the minimum fragment size to 1024 bytes, and enables the minimum size of IPv6 fragments validation.

```
Switch(config)# dos ipv6-min-frag-size-length 1024
Switch(config)# dos ipv6-min-frag-size-check
```

## dos(interface)

**Syntax**

**dos**
**no dos**

**Parameter**

**Default**

DoS protection is disabled on each interface.

**Mode**

Interface Configuration

**Usage**

To enable the DoS on the specific interface, use the command **dos** in the

Interface Configuration mode. Otherwise.

### Example

The following example enables the DoS on the interface fa1.

```
Switch(config)# interface fa1
Switch(config-if)# dos
```

## show dos

### Syntax

**show dos**
**show dos interface** IF_PORTS

### Parameter

| | |
|---|---|
| **interface** *IF_PORTS* | An interface ID or the list of interface IDs. |

### Default

### Mode

Privileged EXEC

### Usage

To show the DoS protection configuration, use the command **show dos** in the Privileged EXEC mode. For the status of DoS protection on each interface, use the command **show dos interface** in the Priveleged EXEC mode.

### Example

The following example shows the global DoS protection configuration.

```
Switch# show dos
Type                                | State (Length)
------------------------------------+-------------------------------
DMAC equal to SMAC                  | enabled
```

```
Land (DIP = SIP)            | enabled
UDP Blat (DPORT = SPORT) | enabled
TCP Blat (DPORT = SPORT) | enabled
POD (Ping of Death)         | enabled
IPv6 Min Fragment Size                  | enabled      (1024 Bytes)
ICMP Fragment Packets                   | enabled
IPv4 Ping Max Packet Size | enabled                    (512 Bytes)
IPv6 Ping Max Packet Size | enabled                    (512 Bytes)
Smurf Attack                            | enabled      (Netmask Length: 0)
TCP Min Header Length                   | enabled      (20 Bytes)
TCP Syn (SPORT < 1024)                  | enabled
Null Scan Attack                        | enabled
X-Mas Scan Attack                       | enabled
TCP SYN-FIN Attack                      | enabled
TCP SYN-RST Attack                      | enabled
TCP Fragment (Offset = 1) | enabled
```

```
Switch# show dos
```

The following example shows the status of DoS protection on the interface fa1.

```
Switch# show dos interfaces fa1
Port              | DoS Protection
----------+----------------
fa1       |          disabled
```

# 9. Dynamic ARP Inspection

## ip arp inspection

### Syntax

**ip arp inspection**
**no ip arp inspection**

### Parameter

### Default

Dynamic Arp inspection is disabled

### Mode

Global Configuration

### Usage

Use the ip arp inspection command to enable Dynamic Arp Inspection function.

### Example

The example shows how to enable Dynamic Arp Inspection on VLAN 1. You can verify settings by the following **show ip arp inspection** command.

```
switch(config)# ip arp inspection
switch(config)# ip arp inspection vlan 1
switch(config)# show ip arp inspection
Dynamic ARP Inspection              : enabled
Enable on Vlans  1
```

## ip arp inspection vlan

### Syntax

**ip arp inspection vlan** *VLAN-LIST*
**no ip arp inspection vlan** *VLAN-LIST*

### Parameter

| | |
|---|---|
| *VLAN-LIST* | Specify VLAN ID or a range of VLANs to enable or disable dynamic Arp inspection |

### Default

Default is disabled on all VLANs

### Mode

Global Configuration

### Usage

Use the ip arp inspection vlan command to enable VLANs on Dynamic Arp Inspection function.

### Example

The example shows how to enable VLAN 1-100 on Dynamic Arp Inspection, You can verify settings by the following **show ip arp inspection** command.

```
switch(config)# vlan 1-100
switch(config)# exit
switch(config)# ip arp inspection
switch(config)# ip arp inspection vlan 1-100
switch(config)# show ip arp inspection
Dynamic ARP Inspection      : enabled
Enable on Vlans             : 1-100
```

## ip arp inspection trust

### Syntax

**ip arp inspection trust**
**no ip arp inspection trust**

### Parameter

### Default

Dynamic Arp inspection trust is disabled

### Mode

Interface Configuration

### Usage

Use the **ip arp inspection trust** command to set trusted interface. The switch does not check ARP packets that are received on the trusted interface; it simply forwards it.

### Example

The example shows how to set interface gi1 to trust. You can verify settings by the following show ip arp inspection interface command.

```
switch(config)# interface gi1
switch(config)# ip arp inspection trust
switch(config)# do show ip arp inspection interface gi1
Interfaces | Trust State | Rate (pps) | SMAC Check | DMAC Check | IP Check/Allow Zero
|
------------+--------------+--------------+----------------|-----------------+-------------
------------+
gi1        | Trusted      | None     | disabled      | disabled            | disabled/disabled
```

## ip arp inspection validate

### Syntax

**ip arp inspection validate src-mac**
**ip arp inspection validate dst-mac**
**ip arp inspection validate ip [allow-zeros]**
**no ip arp inspection validate src-mac**
**no ip arp inspection validate dst-mac**
**no ip arp inspection validate ip [allow-zeros]**

### Parameter

### Default

Default is disabled of all validation

### Mode

Interface Configuration

### Usage

Use the **ip arp inspection** validate command to enable validate function on interface. The "**src-mac**" drop ARP requests and reply packets that arp-sender-mac and ethernet- source-mac is not match. The "**dst-mac**" drops ARP reply packets that arp-target-mac and ethernet-dst-mac is not match. The "**ip**" drop ARP request and reply packets that sender-ip is invalid such as broadcast 、

multicast 、 all zero IP address and drop ARP reply packets that target-ip is invalid. The "**allow-zeros**" means won't drop all zero IP address.

**Example**

The example shows how to set interface gi1 to validate "**src-mac**" 、 "**dst-mac**" and "**ip allow zeros**". You can verify settings by the following **show ip arp inspection interface** command.

```
switch(config)# interface gi1
switch(config-if)# ip arp inspection validate src-mac
switch(config-if)# ip arp inspection validate dst-ma
switch(config-if)# ip arp inspection validate ip allow-zeros
switch(config)# do show ip arp inspection interface gi1
Interfaces | Trust State | Rate (pps) | SMAC Check | DMAC Check | IP Check/Allow Zero
|
------------+--------------+--------------+----------------|-----------------+------------
------------+
gi1        | Untrusted  | None            | enabled| enabled| enabled/ enabled
```

## ip arp inspection rate-limit

**Syntax**

**ip arp inspection rate-limit <1-50>**
**[no] ip arp inspection rate-limit**

**Parameter**

| | |
|---|---|
| *<1-50>* | ***Set 1 to 50 PPS of DHCP packet rate limitation*** |

**Default**

Default is un-limited of ARP packet

**Mode**

Interface Configuration

**Usage**

Use the **ip arp inspection rate-limit** command to set rate limitation on interface. The switch drop ARP packets after receives more than configured rate of packets per second.

**Example**

The example shows how to set rate limit to 30 pps on interface gi1. You can verify settings by the following **show ip arp inspection** interface command.

```
switch(config)# interface gi1
switch(config)# ip arp inspection rate-limit 30
switch(config)# do show ip arp inspection interface gi1
Interfaces | Trust State | Rate (pps) | SMAC Check | DMAC Check | IP Check/Allow Zero
|
------------+--------------+--------------+----------------|-----------------+-------------
------------+
gi1        | Untrusted  | 30    | disabled            | disabled            | disabled/disabled
```

## clear ip arp inspection statistics

**Syntax**

**clear ip arp inspection interfaces** IF_PORTS **statistics**

**Parameter**

| | |
|---|---|
| *IF_PORTS* | ***specifies ports to clear statistics*** |

**Default**

No default is defined

**Mode**

Privileged EXEC

**Usage**

Use the clear ip arp inspection interfaces statistics command to clear statistics that are recorded on interface.

### Example

The example shows how to clear statistics on interface gi1. You can verify settings by the following **show ip arp inspection interface statistics** command.

```
switch# clear ip arp inspection interfaces gi1 statistics
switch# show ip arp inspection interfaces gi1 statistics Port| Forward
|Source MAC Failures|Dest MAC Failures|
SIP Validation Failures|DIP Validation Failures|IP-MAC Mismatch Failures
----+---------+------------+-------------+------------+--------------+------------------
gi1|       0 |         0 |         0 |         0 |         0 |         0
```

## show ip arp inspection

### Syntax

### show ip dhcp snooping

### Parameter

### Default

No default is defined

### Mode

Privileged EXEC

### Usage

Use the show ip arp inspection command to show settings of Dynamic Arp Inspection

### Example

The example shows how to show settings of Dynamic Arp Inspection

```
switch(config)# show ip arp inspection

Dynamic ARP Inspection                  : enabled

Enable on Vlans    1
```

## show ip arp inspeciton interface

### Syntax

**show ip arp inspection interfaces** IF_PORTS
**show ip arp inspection interfaces** IF_PORTS **statistics**

### Parameter

| | |
|---|---|
| IF_PORTS | specifies ports to show statistics |

### Default

No default is defined

### Mode

Privileged EXEC

### Usage

Use the **show ip arp inspection interfaces** command to show settings or statistics of interface.

### Example

The example shows how to show settings of interface gi1.

```
switch# show ip arp inspection interface gi1
Interfaces | Trust State | Rate (pps) | SMAC Check | DMAC Check | IP Check/Allow Zero
|
------------+--------------+--------------+----------------|-----------------+-------------
------------+
gi1        | Trusted     | None       | disabled     | disabled      | disabled/disabled
```

The example shows how to show statistics of interface gi1.

```
switch# show ip arp inspection interfaces gi1 statistics
Port| Forward |Source MAC Failures|Dest MAC Failures|
SIP Validation Failures|DIP Validation Failures|IP-MAC Mismatch Failures
----+---------+------------+-------------+------------+--------------+------------------
gi1|       0 |         0 |         0 |         0 |         0 |         0
```

# 10. GVRP

## gvrp (Global)

### Syntax

**gvrp**
**no gvrp**

### Parameter

### Default

GVRP is disabled

### Mode

Global Configuration

### Usage

Disable gvrp will clear all learned dynamic vlan entry and do not learn dynamic vlan anymore.
Use ‘show gvrp’ to show configuration.

### Example

The following example specifies that set global gvrp test.
Switch(config)# **gvrp**
Switch# **show gvrp**

```
GVRP       Status
                    --------------------

                GVRP                              : Enabled
                Join time                       : 200 ms
                Leave time                       : 600 ms
                LeaveAll time                  : 10000 ms
```

## gvrp (Interface)

### Syntax

**gvrp**
**no gvrp**

**Parameter**

**Default**

GVRP is disabled on interface

**Mode**

Interface mode

**Usage**

'no gvrp' will remove dynamic port from vlan.
'gvrp' must work at port mode is trunk.

**Example**

The following example specifies that set port gvrp test. The port gvrp enable must set port mode is trunk firstly.

```
Switch(config)#interface gi1
Switch(config-if)# switchport mode trunk
Switch(config)#gvrp
Switch# show gvrp configuration interfaces gi1
Port | GVRP-Status | Registration | Dynamic VLAN Creation
--------+---------------+---------------+----------------------
gi1     Enabled        Normal         Disabled
```

## gvrp registration-mode

**Syntax**

**gvrp registration-mode (normal | fixed | forbidden)**

**Parameter**

| | |
|---|---|
| normal | register dynamic vlan, and transmit all |

| | |
|---|---|
| | vlan attribute. |
| fixed | do not register dynamic vlan, and only transmit static vlan attribute. |
| forbidden | do not register dynamic vlan, and only transmit default vlan attribute. |

**Default**

Default is Normal

**Mode**

Interface mode

**Usage**

When set registration-mode is fixed or forbidden, will remove the port from vlan witch is dynamic port. And do not learning vlan.

**Example**

The following example specifies that set gvrp registration mode test.
Switch(config)# **interface gi1**
Switch(config-if)# **gvrp registration-mode fixed**
Switch# **show gvrp configuration interfaces gi1**
Port | GVRP-Status | Registration | Dynamic VLAN Creation
--------+---------------+---------------+----------------------
gi1 Enabled Fixed Disabled

## gvrp vlan-create-forbid

**Syntax**

**gvrp vlan-creation-forbid**
**no gvrp vlan-creation-forbid**

**Parameter**

**Default**

Default is disabled.

**Mode**

Interface mode

**Usage**

'gvrp vlan-creation-forbid' will not remove dynamic port from vlan immediate.

**Example**

The following example specifies that set port gvrp vlan-creation-forbid test.

```
Switch(config)#interface gi1
Switch(config-if)# gvrp vlan-creation-forbid
Switch(config-if)#exit
Switch# show gvrp configuration interfaces gi1
Port | GVRP-Status | Registration | Dynamic VLAN Creation
--------+---------------+--------------+---------------------
gi1          Enabled        Normal              Enabled
```

## clear gvrp statistics

**Syntax**

**clear gvrp (error-statistics | statistics) [interfaces IF_PORTS]**

**Parameter**

| | |
|---|---|
| error-statistics | Error-statistics: error gvrp packet statistics |
| statistics | Statistics: gvrp event message |
| **interfaces IF_PORTS** | statistics Specifies posts to clear statistics |

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will clear the ports error statistics or statistics info.

**Example**

The following example specifies that clear gvrp error statistics and statistics test.
Switch# **clear gvrp statistics**
Switch# **clear gvrp error-statistics**

## show gvrp statistics

**Syntax**

**show gvrp (statistics | error-statistics) [interfaces IF_PORTS]**

**Parameter**

| | |
|---|---|
| **none** | Display all ports |
| (statistics\| error- statistics) | statistics – GVRP statistics<br>error-statistics GVRP error |
| **[interfaces IF_PORTS]** | statistics Specifies posts |

**Default**

Display all ports statistics info

**Mode**

Privileged EXEC

**Usage**

This command will display the ports error statistics or statistics info.

**Example**

The following example specifies that display gvrp error statistics and statistics test.

Switch# **show gvrp statistics**

```
Port id          : fa1
Total RX         :   0
JoinEmpty RX :   0
JoinIn RX        :   0
Empty RX         :   0
LeaveIn RX       : 0
LeaveEmpty RX    :   0
LeaveAll RX      :0
Total TX         :   0
JoinEmpty TX   :0
JoinIn TX        :   0
Empty TX         :   0
LeaveIn TX       :0
LeaveEmpty TX    :   0
LeaveAll TX      :   0


Port id          : fa2
Total RX         :   0
JoinEmpty RX :   0
JoinIn RX        :   0
Empty RX         :   0
LeaveIn RX       : 0
  LeaveEmpty RX     :
                    0
LeaveAll RX      :0
Total TX         :   0
...
```

Switch# **show gvrp error-statistics**

```
INVPROT : Invalid protocoal Id
```

INVATYP : Invalid Attribute Type
INVALEN : Invalid Attribute Length
INVAVAL : Invalid Attribute Value
INVEVENT: Invalid Event

| Port | INVPROT | INVATYP | INVALEN | INVAVAL | INVEVENT |
|---|---|---|---|---|---|
| gi1 | 0 | 0 | 0 | 0 | 0 |
| gi2 | 0 | 0 | 0 | 0 | 0 |
| gi3 | 0 | 0 | 0 | 0 | 0 |
| gi4 | 0 | 0 | 0 | 0 | 0 |
| gi5 | 0 | 0 | 0 | 0 | 0 |
| gi6 | 0 | 0 | 0 | 0 | 0 |

## show gvrp

### Syntax

**show gvrp**

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

This command will display the gvrp global info.

### Example

The following example specifies that display gvrp test.

```
Switch# show gvrp
GVRP    Status
----------------------------

GVRP                    : Disabled
Join time               : 200 ms
```

Leave time : 600 ms
LeaveAll time : 10000 ms

## show gvrp configuration

### Syntax

**show gvrp configuration [interface IF_PORTS]**

### Parameter

| | |
|---|---|
| none | Display all ports configuration |
| [interface IF_PORTS] | Display Specifies posts configuration |

### Default

Display all ports configuration info

### Mode

Privileged EXEC

### Usage

This command will display the ports configuration info.

### Example

The following example specifies that display gvrp port configuration test.

```
Switch# show gvrp configuration
Port | GVRP-Status | Registration | Dynamic VLAN Creation
--------+---------------+---------------+----------------------
gi1      Disabled        Normal                Enabled
gi 2     Disabled        Normal          Enabled
```

# 11. IGMP Snooping

## ip igmp snooping

### Syntax

**ip igmp snooping**
**no ip igmp snooping**

### Parameter

### Default

Default is enabled

### Mode

Global Configuration

### Usage

Use the **ip igmp snooping** command to enable IGMP snooping function.
Use the **no** form of this command to disable.
You can verify settings by the **show ip igmp snooping** command.

### Example

The following example specifies that set ip igmp snooping test.

Switch(config)# **no ip igmp snooping**

## ip igmp snooping version

### Syntax

**ip igmp snooping version (2|3)**

### Parameter

| | |
|---|---|
| (2\|3) | IGMP version 2 or IGMP version 3 basic |

| | |
|---|---|
| | mode |

**Default**

Default is version 2

**Mode**

Global Configuration

**Usage**

Use the **ip igmp snooping version** command to change IGMP support version. Only basic mode is supported in v3. When change version from v3 to v2, all querier version will update to version 2.
You can verify settings by the **show ip igmp snooping** command.

**Example**

The following example specifies that set ip igmp snooping version 3.

Switch(config)# **ip igmp snooping version 3**

## ip igmp snooping querier

**Syntax**

**ip igmp snooping vlan <VLAN-LIST> querier [version (2|3)]**
**no ip igmp snooping [vlan <VLAN-LIST>] querier**

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| (2\|3) | Query version 2 or 3 |

**Default**

No ip igmp snooping querier by default

**Mode**

Global Configuration

**Usage**

When enable ip igmp vlan querier, there will process router select, the select successful will send general and specific query.
Use the **ip igmp snooping querier** command to add querier.

**Example**

The following example specifies that set ip igmp snooping querier test.

Switch(config)# **ip igmp snooping vlan 2 querier version 3**

## ip igmp snooping vlan

**Syntax**

**ip igmp snooping vlan** VLAN-LIST
**no ip igmp snooping vlan** VLAN-LIST

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |

**Default**

Default is disabled for all VLANs

**Mode**

Global Configuration

**Usage**

Disable will clear all ip igmp snooping dynamic group and dynamic router port and make all static ip igmp group invalid of this vlan. Will not learn dynamic group and router port by igmp message any more.
Use the **ip igmp snooping vlan** command to enable IGMP on VLAN.

**Example**

The following example specifies that set ip igmp snooping vlan test.

Switch(config)# **ip igmp snooping**
Switch(config)# **ip igmp snooping vlan 2**

## ip igmp snooping vlan fastleave

**Syntax**

**ip igmp snooping vlan** <VLAN-LIST> **fastleave**

**no ip igmp snooping vlan** <VLAN-LIST> **fastleave**

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |

**Default**

Default is disabled

**Mode**

Global Configuration

**Usage**

Use the **ip igmp snooping vlan fastleave** command to enable fastleave function. Group will remove port immediately when receive leave packet.

**Example**

The following example specifies that set ip igmp snooping vlan fastleave test.
Switch(config)# **ip igmp snooping vlan 1 fastleave**

## ip igmp snooping vlan query-interval

**Syntax**

**ip igmp snooping vlan <VLAN-LIST> query-interval <30-18000>**
**no ip igmp snooping vlan <VLAN-LIST> query-interval**

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| query-interval <30-18000> | specifies query interval to set |

**Default**

Default is 125

**Mode**

Global Configuration

**Usage**

Use the **ip igmp snooping vlan query-interval** command to set interval between each query.

**Example**

The following example specifies that set **ip igmp snooping vlan query- interval** test.
Switch(config)# **ip igmp snooping vlan 1 query-interval 100**

## ip igmp snooping vlan response-time

**Syntax**

**ip igmp snooping vlan** <VLAN-LIST> **response-time** <5-20>
**no ip igmp snooping vlan** <VLAN-LIST> **response-time**

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| response-time <5-20> | specifies a response time to set |

**Default**

Default is 10

**Mode**

Global Configuration

**Usage**

Use the **ip igmp snooping vlan response-time** command to set response time.

**Example**

The following example specifies that set **ip igmp snooping vlan response-time** test.
Switch(config)# ip igmp snooping vlan 1 response-time 12

## ip igmp snooping vlan router

**Syntax**

**ip igmp snooping vlan** VLAN-LIST **router learn pim-dvmrp**
**no ip igmp snooping vlan** VLAN-LIST **router learn pim-dvmrp**

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |

**Default**

Default is enabled

**Mode**

Global Configuration

**Usage**

Use the **ip igmp snooping vlan router** command to enable learning router port by routing protocol packets such as PIM/PIMv2, DVMRP, MOSPF.

**Example**

The following example specifies that set **ip igmp snooping vlan router** test.

Switch(config)# **ip igmp snooping vlan 99 router**

## ip igmp snooping vlan forbidden-port

**Syntax**

**ip igmp snooping vlan** <VLAN-LIST> **forbidden-port** IF_PORTS
**no ip igmp snooping vlan** <VLAN-LIST> **forbidden-port** IF_PORTS

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| IF_PORTS | specifies a port list to set or remove |

**Default**

No forbidden ports by default

**Mode**

Global Configuration

**Usage**

'ip igmp snooping vlan 1 static-port gi1-2' will add static port gi1-2 for vlan 1.the all known vlan 1 ipv4 group will add the static ports.
'ip igmp snooping vlan 1 forbidden-port gi3-4' will add forbidden port gi3-4 for vlan 1.the all known vlan 1 ipv4 group will remove the forbidden ports.
The configure can use 'show ip igmp snooping forward-all'.

Use the **ip igmp snooping vlan forbidden-port** command to add static non-forwarding port, all known vlan 1 ipv4 group will remove the forbidden ports.

**Example**

The following example specifies that set ip igmp snooping static/forbidden port test.
Switch(config)# **ip igmp snooping vlan 1 forbidden -port gi3-4**

## ip igmp snooping vlan static-port

**Syntax**

**ip igmp snooping vlan** <VLAN-LIST> **static-port** IF_PORTS
**no ip igmp snooping vlan** <VLAN-LIST> **static-port** IF_PORTS

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| IF_PORTS | specifies a port list to set or remove |

**Default**

No static port by default

**Mode**

Global Configuration

### Usage

Use the **ip igmp snooping vlan static-port** command to add static forwarding port, all known vlan 1 ipv4 group will add the static ports.

### Example

The following example specifies that set ip igmp snooping static port test.

Switch(config)# **ip igmp snooping vlan 1 static -port gi1-2**

## ip igmp snooping vlan static-router-port

### Syntax

**ip igmp snooping vlan** <VLAN-LIST> **static-router-port** IF_PORTS
**no ip igmp snooping vlan** <VLAN-LIST> **static-router-port** IF_PORTS

### Parameter

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| IF_PORTS | specifies a port list to set or remove |

### Default

No forbidden router ports by default

### Mode

Global Configuration

### Usage

Use the **ip igmp snooping vlan static-router-port** command to add static router port. All query packets will forward to this port.

### Example

The following example specifies that set ip igmp snooping static test.

Switch(config)# **ip igmp snooping vlan 1 static-router-port gi1-2**

## ip igmp snooping vlan static-group

### Syntax

**ip igmp snooping vlan <VLAN-LIST> static-group [<ip-addr>] interfaces IF_PORTS**
**no ip igmp snooping vlan <VLAN-LIST> static-group <ip-addr> interfaces IF_PORTS**

### Parameter

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| ip-addr | specifies multicast group ipv4 address |
| IF_PORTS | specifies port list to set or remove |

### Default

No static group by default

### Mode

Global Configuration

### Usage

Use the **ip igmp snooping vlan static-group** command to add a static group. The static group will not learn other dynamic ports. If the dynamic group exists, then the static group will overlap the dynamic group. The static group set to valid unless igmp snooping global and vlan enable.

### Example

The following example specifies that set ip igmp snooping static group test.

Switch(config)# **ip igmp snooping vlan 1 static-group 224.1.1.1 interfaces gi1-2**

## ip igmp snooping vlan group

### Syntax

**no ip igmp snooping vlan <VLAN-LIST> group <ip-addr>**

### Parameter

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| ip-addr | specifies multicast group ipv4 address |

### Default

### Mode

Global Configuration

### Usage

Use the **no ip igmp snooping vlan group** command to delete a group which could be static or dynamic.

### Example

The following example specifies that set ip igmp snooping static group test.

Switch(config)# **no ip igmp snooping vlan 1 group 224.1.1.1**

## ip igmp profile

### Syntax

**ip igmp profile <1-128>**

**no ip igmp profile <1-128>**

**Parameter**

| | |
|---|---|
| <1-128> | specifies profile ID |

**Default**

No profie exist by default

**Mode**

Global Configuration

**Usage**

Use the **ip igmp profile** command to enter profile configuration

**Example**

The following example specifies that set ip igmp profile test.
Switch(config)# **ip igmp profile 1**

## profile range

**Syntax**

**profile range ip <ip-addr> [ip-addr] action (permit | deny)**

**Parameter**

| | |
|---|---|
| <ip-addr> | Start ipv4 multicast address |
| [ip-addr] | End ipv4 multicast address |
| (permit \| deny) | Permit: allow Multicast address range ip address learning<br>deny: do not allow Multicast address |

| | |
|---|---|
| | range ip address learning |

**Default**

**Mode**

igmp profile configuration mode

**Usage**

Use the **profile** command to generate IGMP profile.

**Example**

The following example specifies that set ip igmp profile test.
Switch(config)# **ip igmp profile 1**
Switch(config-igmp-profile)# **profile range ip 224.1.1.1 224.1.1.8 action permit**

## ip igmp filter

**Syntax**

**ip igmp filter <1-128>**
**[no] ip igmp filter**

**Parameter**

| | |
|---|---|
| <1-128> | specifies profile ID |

**Default**

**Mode**

Port Configuration

### Usage

Use the **ip igmp filter** command to bind a profile for port. When the port bind a profile. Then the port learning group will update, if the group is not match the profile rule it will remove the port from the group. Static group is excluded.

### Example

The following example specifies that set ip igmp filter test.
Switch(config)# **interface gi1**
Switch(config-if)#**ip igmp filter 1**

## ip igmp max-groups

### Syntax

**ip igmp max-groups <0-1024>**
**no ip igmp max-groups**

### Parameter

| | |
|---|---|
| <0-1024> | The maximum number of IGMP groups that an interface can join. |

### Default

Default is 1024

### Mode

Port Configuration

### Usage

Use the **ip igmp max-groups** command to limit port learning max group number. When the port has reach limitation, new group will not add this port. Static group is excluded.

### Example

The following example specifies that set ip igmp max-groups test.
Switch(config-if)#**ip igmp max-groups 10**

## ip igmp max-groups action

### Syntax

**ip igmp max-groups action (deny | replace)**

### Parameter

| | |
|---|---|
| (deny \| replace) | Deny: current port igmp group arrived max-groups,don't add group.<br>Replace: current port igmp group arrived max-groups,remove port for rand group, and add port to new group. |

### Default

Default action is deny

### Mode

Port Configuration

### Usage

Use the **ip igmp max-groups action** command to set the action when the numbers of groups reach the limitation.

### Example

The following example specifies that set action replace test.
Switch(config-if)#**ip igmp max-groups action replace**

## clear ip igmp snooping groups

### Syntax

**clear ip igmp snooping groups [(dynamic | static)]**

### Parameter

| | |
|---|---|
| none | Clear ip igmp groups include dynamic and static |
| (dynamic \| static) | Ip igmp group type is dynamic or static |

### Default

### Mode

Privileged EXEC

### Usage

This command will clear the ip igmp groups for dynamic or static or all of type. You can verify settings by the **show ip igmp snooping groups** command.

### Example

The following example specifies that clear ip igmp snooping groups test.
Switch# **clear ip igmp snooping groups**
Switch# **show ip igmp snooping groups**
VLAN | Group IP Address | Type | Life(Sec) | Port
------+-----------------+--------+-----------+-----------------
Total Number of Entry = 0

## clear ip igmp snooping statistics

### Syntax

**clear ip igmp snooping statistics**

**Parameter**

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will clear the igmp statistics.
You can verify settings by the **show ip igmp snooping** command.

**Example**

The following example specifies that clear ip igmp snooping statistics test.
Switch# **clear ip igmp snooping statistics**
Switch# **show ip igmp snooping**
IGMP Snooping Status
---

Snooping : Enabled Report
Suppression : Enabled
Operation Version : v2
Forward Method : mac Unknown
IP Multicast Action : Flood

Packet Statistics
Total RX : 0
Valid RX : 0
Invalid RX : 0
Other RX : 0
Leave RX : 0
Report RX : 0
General Query RX : 0
Specail Group Query RX : 0
Specail Group & Source Query RX : 0
Leave TX : 0
Report TX : 0

General Query TX : 0
Specail Group Query TX : 0
Specail Group & Source Query TX : 0

## show ip igmp snooping groups counters

**Syntax**

**show ip igmp snooping groups**

**Parameter**

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will display the ip igmp group counter include static group.

**Example**

The following example specifies that display ip igmp snooping group counter test.
Switch# **show ip igmp snooping group counters**
Total ip igmp snooping group number: 2
Total ip igmp snooping static mac number: 0

## show ip igmp snooping groups

**Syntax**

**show ip igmp snooping groups [(dynamic | static)]**

**Parameter**

| | |
|---|---|
| none | Show ip igmp groups include dynamic and static |
| (dynamic \| static) | Display Ip igmp group type is dynamic or static |

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will display the ip igmp groups for dynamic or static or all of type.

**Example**

The following example specifies that show ip igmp snooping groups.
Switch# **show ip igmp snooping groups**
VLAN | Group IP Address | Type | Life(Sec) | Port
------+-----------------+--------+-----------+-----------------
1 | 224.1.2.3 | Static| -- | fa9
1 | 224.1.2.4 | Static| -- | fa10

Total Number of Entry = 2

## show ip igmp snooping router

**Syntax**

**show ip igmp snooping router [(dynamic | forbidden |static )]**

**Parameter**

| | |
|---|---|
| none | Show ip igmp router include dynamic and static and forbidden |
| (dynamic \|forbidden \| | Display Ip igmp router info for different |

| | |
|---|---|
| static) | type |

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will display the ip igmp router info.

**Example**

The following example specifies that show ip igmp snooping router.

```
Switch# show ip igmp snooping router
Dynamic Router Table
VID | Port | Expiry Time(Sec)
------+---------+-----------------

Total Entry 0

Static Router Table
VID | Port Mask
------+------------------------
1 | fa4

Total Entry 1

Forbidden Router Table
VID | Port Mask
------+------------------------
1 | fa8

Total Entry 1
```

## show ip igmp snooping querier

### Syntax

**show ip igmp snooping querier**

### Parameter

| | |
|---|---|
| none | Show all vlan ip igmp querier info. |

### Default

### Mode

Privileged EXEC

### Usage

This command will display all of the static vlan ip igmp querier info.

### Example

The following example specifies that show ip igmp snooping querier test.

```
Switch# show ip igmp snooping querier
VID |    State    |    Status | Version | Querier IP
-------+-------------+-------------+-----------+-----------------
--
1 |    Disabled      | Non-Querier |      No|    ------

Total Entry 1
```

## show ip igmp snooping

### Syntax

**show ip igmp snooping**

### Parameter

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will display ip igmp snooping global info.

**Example**

The following example specifies that show ip igmp snooping test.
Switch# **show ip igmp snooping**
IGMP Snooping Status
---

Snooping : Enabled
Report Suppression : Enabled
Operation Version : v2
Forward Method : mac
Unknown Multicast Action : Flood

Packet Statistics
Total RX : 0
Valid RX : 0
Invalid RX : 0
Other RX : 0
Leave RX : 0
Report RX : 0
General Query RX : 0
Specail Group Query RX : 0
Specail Group & Source Query RX : 0
Leave TX : 0
Report TX : 0
General Query TX : 0
Specail Group Query TX : 0
Specail Group & Source Query TX : 0

## show ip igmp snooping vlan

### Syntax

**show ip igmp snooping vlan [VLAN-LIST]**

### Parameter

| | |
|---|---|
| none | Show all ip igmp snooping vlan info |
| [VLAN-LIST] | Show specifies vlan ip igmp snooping info |

### Default

### Mode

Privileged EXEC

### Usage

This command will display ip igmp snooping vlan info.

### Example

The following example specifies that show ip igmp snooping vlan test.
Switch# **show ip igmp snooping vlan 1**
IGMP Snooping is globaly enabled
IGMP Snooping VLAN 1 admin : disabled
IGMP Snooping operation mode : disabled
IGMP Snooping robustness: admin 2 oper 2
IGMP Snooping query interval: admin 125 sec oper 125 sec
IGMP Snooping query max response : admin 10 sec oper 10 sec
IGMP Snooping last member query counter: admin 2 oper 2
IGMP Snooping last member query interval: admin 1 sec oper 1 sec
IGMP Snooping last immediate leave: disabled
IGMP Snooping automatic learning of multicast router ports: enabled

## show ip igmp snooping forward-all

### Syntax

**show ip igmp snooping forward-all [vlan VLAN-LIST]**

**Parameter**

| | |
|---|---|
| none | Show all ip igmp snooping vlan forward-all info |
| [vlan VLAN-LIST] | Show specifies vlan of ip igmp forward info. |

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will display ip igmp snooping forward all info.

**Example**

The following example specifies that show ip igmp snooping forward-all test.
Switch# **show ip igmp snooping forward-all 1**
IGMP Snooping VLAN 1
IGMP Snooping static port : None
IGMP Snooping forbidden port : None

## show ip igmp profile

**Syntax**

**show ip igmp profile [<1-128>]**

**Parameter**

| | |
|---|---|
| none | Show all ip igmp snooping profile info |

| | |
|---|---|
| [<1-128>] | Show specifies index profile info |

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will display ip igmp profile info.

**Example**

The following example specifies that show ip igmp profile test.
Switch# **show ip igmp profile**
IP igmp profile index: 1
IP igmp profile action: permit
Range low ip: 224.1.1.1
Range high ip: 224.1.1.8

IP igmp profile index: 2
IP igmp profile action: deny
Range low ip: 225.1.1.0
Range high ip: 225.1.2.1

## show ip igmp filter

**Syntax**

**show ip igmp filter [interfaces IF_PORTS]**

**Parameter**

| | |
|---|---|
| none | Show all port filter |
| [interfaces IF_PORTS] | Show specifies ports filter |

### Default

### Mode

Privileged EXEC

### Usage

This command will display ip igmp port filter info.

### Example

The following example specifies that show ip igmp filter test.
Switch# **show ip igmp filter**
Port ID | Profile ID
---------+--------------
gi1 : 1
gi2 : None
gi3 : None
gi4 : None
gi5 : None
--More--

## show ip igmp max-group

### Syntax

**show ip igmp max-group [interfaces IF_PORTS]**

### Parameter

| | |
|---|---|
| none | Show all port max-group |
| [interfaces IF_PORTS] | Show specifies ports max-group |

### Default

### Mode

Privileged EXEC

**Usage**

This command will display ip igmp port max-group.

**Example**

The following example specifies that show ip igmp max-group test.
Switch(config-if)#**ip igmp max-groups 50**
Switch# **show ip igmp max-group**

Port ID | Max Group
---------+--------------
gi1 : 50
gi2 : 256
gi3 : 256
gi4 : 256
gi5 : 256
--More--

## show ip igmp max-group action

**Syntax**

**show ip igmp max-group action [interfaces IF_PORTS]**

**Parameter**

| | |
|---|---|
| none | Show all port max-group action |
| [interfaces IF_PORTS] | Show specifies ports max-group action |

**Default**

**Mode**

Privileged EXEC

### Usage

This command will display ip igmp port max-group action.

### Example

The following example specifies that show ip igmp max-group action test.
Switch(config)#**interface gi1**
Switch(config-if)#**ip igmp max-groups action replace**
Switch# **show ip igmp max-group action**
Port ID | Max-groups Action
---------+--------------------
gi1 : replace
gi2 : deny
gi3 : deny
gi4 : deny
gi5 : deny
--More--

# 12. IP Source Guard

## ip source verify

### Syntax

**ip source verify [mac-and-ip]**
**no ip source verify**

### Parameter

| | |
|---|---|
| mac-and-ip | Verify by mac and ip address boundle |

### Default

IP Source Guard is disabled on interface. Default is that verifying ip address only

### Mode

Port Configuration

### Usage

Use the **ip source verify** command to enable IP Source Guard function. Default IP Source Guard filter source IP address. The "**mac-and-ip**" filters not only source IP address but also source MAC address.

### Example

The example shows how to enable IP Source Guard with source IP address filtering on interface gi1.
Switch(config)# **interface gi1**
switch(config-if)# **ip source verify**

The example shows how to enable IP Source Guard with source IP and MAC address filtering on interface gi2.

Switch(config)# **interface gi2**
switch(config-if)# **ip source verify mac-and-ip**
switch(config-if)# **do show ip source interfaces gi1-2**
Port | Status | Max Entry | Current Entry
----------+----------+----------+----------
gi1 | Verify MAC+IP | No Limit | 0
gi2 | disabled | No Limit | 0

## ip source binding

### Syntax

**ip source binding A:B:C:D:E:F vlan <1-4094> A.B.C.D interface IF_PORT**
**no ip source binding A:B:C:D:E:F vlan <1-4094> A.B.C.D interface IF_PORT**

### Parameter

| | |
|---|---|
| A:B:C:D:E:F | Specify a MAC address of a binding entry |

| | |
|---|---|
| VLAN <1-4094> | Specify a VLAN ID of a binding entry |
| A.B.C.D | Specify IP address and MASK of a binding entry. |
| IF_PORT | Specify interface of a binding entry. |

**Default**

Default is no binding entry.

**Mode**

Global Configuration

**Usage**

Use the **ip source binding** command to create a static IP source binding entry has an IP address, its associated MAC address、VLAN ID、interface.
Use the **no** form of this command to delete static entry.
You can verify settings by the **show ip source binding** command.

**Example**

The example shows how to add a static IP source binding entry.
Switch(config)# **ip source binding 00:11:22:33:44:55 vlan 1 192.168.1.55 interface fa1**
switch(config)# **do show ip source binding**
Bind Table: Maximun Binding Entry Number 192
Port | VID | MAC Address | IP | Type | Lease Time
----+------+------------------+-----------------------------------+--------
----+-----------
fa1 |1 | 00:11:22:33:44:55 |192.168.1.55(255.255.255.255)| Static | NA

## show ip source interface

**Syntax**

**show ip source interfaces IF_PORTS**

**Parameter**

| | |
|---|---|
| **IF_PORTS** | specifies ports to show |

**Default**

No default is defined

**Mode**

Privileged EXEC

**Usage**

Use the **show ip source interface** command to show settings of IP Source Guard of interface

**Example**

The example shows how to show settings of IP Source Guard of interface gi1

```
switch# show ip source interfaces gi1
Port    |  Status          | Max Entry | Current Entry
----------+------------------------+--------------+--------------
gi1 | Verify MAC+IP | No Limit |  0
```

## show ip source binding

**Syntax**

**show ip source binding [(dynamic|static)]**

**Parameter**

| | |
|---|---|
| **dynamic** | Show entries that added by DHCP snooping learn |
| **static** | Show entries that added by user |

**Default**

No default is defined

**Mode**

Privileged EXEC

**Usage**

Use the **show ip source binding** command to show binding entries of IP Source Guard.

**Example**

The example shows how to show static binding entries of IP Source Guard.

switch# **show ip source binding**
Bind Table: Maximun Binding Entry Number 192
Port | VID | MAC Address | IP | Type | Lease Time
----+------+-------------------+-------------------------------------+--------
----+-----------
fa1 |1 | 00:11:22:33:44:55 |192.168.1.55(255.255.255.255)| Static | NA

# 13. Link Aggregation

## lag

**Syntax**

**lag** *<1-8>* **mode** (**static** | **active** | **passive**)
**no lag**

**Parameter**

| | |
|---|---|
| *<1-8>* | Specify the LAG id for the interface |
| **static** | Specify the LAG to be static mode and join the interface into this LAG. |

| | |
|---|---|
| **active** | Specify the LAG to be dynamic mode and join the interface into this LAG with LACP active port. |
| **passive** | Specify the LAG to be dynamic mode and join the interface into this LAG with LACP passive port. |

**Default**

There is no LAG in default.

**Mode**

Interface Configuration

**Usage**

Link aggregation group function allows you to aggregate multiple physical ports into one logic port to increase bandwidth. This command makes normal port join into the specific LAG logic port with static or dynamic mode. And use "**no lag**" to leave the LAG logic port.

**Example**

This example shows how to create a dynamic LAG and join fa1-fa3 to this LAG.

Switch(config)# **interface range fa1-3**
Switch(config-if)# **lag 1 mode active**

This example shows how to show current LAG status.

Switch# **show lag**
Load Balancing: src-dst-mac-ip.

```
Group ID |  Type   |                        Ports
---------+--------+-------------------------------
1        |         LACP |   Inactive: fa1-3
2        | ------ |
3        | ------ |
4        | ------ |
5        | ------ |
6        | ------ |
7        | ------ |
8| ------ |
```

## lag load-balance

### Syntax

**lag load-balance** (**src-dst-mac** | **src-dst-mac-ip**)
**no lag load-balance**

### Parameter

| | |
|---|---|
| **src-dst-mac** | Specify algorithm to balance traffic by using source and destination MAC address for all packets. |
| **src-dst-mac-ip** | Specify algorithm to balance traffic by using source and destination IP address for IP packets and using source and destination MAC address for non-IP packets. |

### Default

Default load balance algorithm is src-dst-mac

### Mode

Global Configuration

### Usage

Link aggregation group port should transmit packets spread to all ports to balance traffic loading. There are two algorithm supported and this command allow you to select the algorithm.

### Example

This example shows how to change load balance algorithm to src-dst-mac-ip.
Switch(config)# **lag load-balance src-dst-mac-ip**

## lacp port-priority

### Syntax

**lacp port-priority** *<1-65535>*
**no lacp port-priority**

### Parameter

| | |
|---|---|
| *<1-65535>* | Specify port priority value |

### Default

Default port priority is 1.

### Mode

Interface Configuration

### Usage

LACP port priority is used for two connected DUT to select aggregation ports. Lower port priority value has higher priority. And the port with higher priority will be selected into LAG first.

### Example

This example shows how to configure interface fa1 lacp port priority to 100.
Switch(config)# **interface fa1**
Switch(config-if)# **lacp port-priority 100**

## lacp system-priority

### Syntax

**lacp system-priority** *<1-65535>*
**no lacp system-priority**

### Parameter

| | |
|---|---|
| *<1-65535>* | Specify system priority value |

**Default**

Default system priority is 32768.

**Mode**

Global Configuration

**Usage**

LACP system priority is used for two connected DUT to select master switch. Lower system priority value has higher priority. And the DUT with higher priority can decide which ports are able to join the LAG.

**Example**

This example shows how to configure lacp system priority to 1000.
Switch(config)# **lacp system-priority 1000**

## show lacp

**Syntax**

**show lacp sys-id**
**show lacp [<1-8>] counters**
**show lacp [<1-8>] (internal | neighbor) [detail]**

**Parameter**

**Default**

No default values for this command.

**Mode**

Privileged EXEC

**Usage**

Use "**show lacp sys-id**" command to displays the system identifier that is being used by LACP. The system identifier is made up of the LAPC system priority and the switch MAC address.
Use "**show lacp counter**" command to display LACP statistic information.
Use "**show lacp internal**" command to display local information.
Use "**show lacp neighbor**" command to display remote information.

**Example**

This example shows how to show system identifier that is being used by LACP

Switch# **show lacp sys-id**
32768, 1c2a.a3c4.0292

This example shows how to show LACP statistics.

Switch# **show lacp counters**

| | LACPDUs | | LACPDUs |
|---|---|---|---|
| Port | Sent | Recv | Pkts Err |

## show lag

**Syntax**

**show lag**

**Parameter**

**Default**

No default values for this command.

**Mode**

Privileged EXEC

**Usage**

Use “**show lag**” command to show current LAG load balance algorithm and members active/inactive status.

**Example**

This example shows how to show current LAG status.

Switch# **show lag**

Load Balancing: src-dst-mac-ip.

```
Group ID |  Type  |                        Ports
---------+--------+----------------------
1                        |    LACP |   Inactive: fa1-3
2                        |------ |
3                        |------ |
4                        |------ |
5                        |------ |
6                        |------ |
7           |------ |
8           |------ |
```

# 14. LLDP

## lldp

**Syntax**

**lldp**
**no lldp**

**Parameter**

**Default**

Default is enabled

**Mode**

Global Configuration

**Usage**

Use "**lldp**" command to enable LLDP RX/TX ability. The LLDP enable status is displayed by "**show lldp**" command.

**Example**

The following example sets LLDP enable/disable.

```
Switch (config)# lldp
Switch# show lldp

State: Enabled Timer: 30
Seconds
Hold multiplier: 4 Reinit delay: 2 Seconds
Tx delay: 2 Seconds
LLDP packet handling: Flooding

Port                |State | Optional TLVs             | Address
-------- + ------ + -------------- + --------
fa1   |               RX,TX |                           |192.168.1.2
fa2 |                 RX,TX |                           |192.168.1.2
fa3 |                 RX,TX |                           |192.168.1.2
fa4 |                 RX,TX |                           |192.168.1.2
fa5   |RX,TX    |                     |192.168.1.2
```

## lldp rx

**Syntax**

**lldp rx**
**no lldp rx**

**Parameter**

**Default**

Default is enabled

**Mode**

Port Configuration

**Usage**

Use "**lldp rx**" command to enable the LLDP PDU RX ability. The configuration

could be shown by "**show lldp**" command.

**Example**

This example sets port gi1 to enable LLDP RX
Switch(config)# **interface gi1**
Switch(config-if)# **lldp rx**

## lldp tx

**Syntax**

**lldp tx**
**no lldp tx**

**Parameter**

**Default**

Default is enabled

**Mode**

Port Configuration

**Usage**

Use "**lldp tx**" command to enable the LLDP PDU TX ability. The configuration could be shown by "**show lldp**" command.

**Example**

This example sets port gi1 to enable LLDP TX
Switch(config)# **interface gi1**
Switch(config-if)# **lldp tx**

## lldp lldpdu

**Syntax**

### lldp lldpdu (filtering|flooding|bridging)

### Parameter

| | |
|---|---|
| **bridging** | When LLDP is globally disabled, LLDP packets are bridging (bridging LLDP PDU to VLAN member ports). |
| **filtering** | When LLDP is globally disabled, LLDP packets are filtered (deleted). |
| **flooding** | When LLDP is globally disabled, LLDP packets are flooded (forwarded to all interfaces). |

### Default

Default LLDP PDU handling behavior when LLDP disabled is flooding

### Mode

Global Configuration

### Usage

Use "**lldp lldpdu**" command to configure the LLDP PDU handling behavior when LLDP is globally disabled. It should be noticed that if LLDP is globally enabled and per port LLDP RX status is configured to disabled, the received LLDP PDU would be dropped instead of taking the global disable behavior.

### Example

This example sets LLDP disable action to bridging.

Switch(config)# **lldp lldpdu bridging**
Switch# **show lldp**

State: Enabled
Timer: 30 Seconds
Hold multiplier: 4
Reinit delay: 2 Seconds

Tx delay: 2 Seconds
LLDP packet handling: Bridging

## lldp tlv-select

### Syntax

**lldp tlv-select** *TLV* [*TLV*] [*TLV*] [*TLV*] [*TLV*] [*TLV*] [*TLV*] [*TLV*]
**no lldp tlv-select**

### Parameter

| | |
|---|---|
| TLV | Specify the selected optional TLV. Available optional TLVs are : sys-name (system name), sys-desc (system description), sys-cap (system capability), mac-phy (802.3 MAC-PHY), lag (802.3 link aggregation), max-frame-size (802.3 max frame size), and management-addr (management address). |

### Default

Default is no selected optional TLV.

### Mode

Port Configuration

### Usage

Use "lldp tlv-select" command to attach selected TLV in PDU.

### Example

This example selects system name, system description, system capability, 802.3 MAC-PHY, 802.3 link aggregation, 802.3 max frame size, and management address TLVs for interface gi1 and gi3.

Switch(config)# **interface range gi 1,3**
Switch(config-if-range)# **lldp tlv-select port-desc sys-name sys-desc sys-cap mac-phy lag max-frame-size management-addr**
Switch(config-if-range)# **end**
Switch# **show lldp interfaces gi1,3**

State: Disabled Timer: 10
Seconds
Hold multiplier: 3 Reinit delay: 2 Seconds
Tx delay: 2 Seconds
LLDP packet handling: Flooding

Port | State | Optional TLVs | Address
-------- + ------ + -------------- + --------
gi1 | RX,TX | PD, SN, SD, SC |192.168.1.254
gi3 | RX,TX | PD, SN, SD, SC |192.168.1.254

Port ID: gi1
802.3 optional TLVs: 802.3-mac-phy, 802.3-lag, 802.3-max- frame-size, management-addr
802.1 optional TLVs
PVID: Enabled

Port ID: gi3
802.3 optional TLVs: 802.3-mac-phy, 802.3-lag, 802.3-max- frame-size, management-addr
802.1 optional TLVs
PVID: Enabled

## lldp tlv-select pvid

### Syntax

**lldp tlv-select pvid (disable|enable)**
**no lldp tlv-select pvid**

### Parameter

| | |
|---|---|
| **disable** | Disable LLDP 802.1 PVID TLV attach state |
| **enable** | Enable LLDP 802.1 PVID TLV attach state |

### Default

Default is enabled

**Mode**

Port Configuration

**Usage**

Use "**lldp tlv-select pvid**" command to configure the 802.1 PVID TLV attach enable status. The configuration could be shown by "**show lldp**" command.

**Example**

This example sets port gi1 PVID TLV attaches status to disable and port gi2 to enable.

```
Switch(config)# interface gi1
Switch(config-if)# lldp tlv-select pvid disable
Switch(config-if)# interface gi2
Switch(config-if)# lldp tlv-select pvid enable

Switch# show lldp interfaces gi1,gi2

State: Disabled Timer: 10
Seconds
Hold multiplier: 3 Reinit delay: 2 Seconds
Tx delay: 2 Seconds
LLDP packet handling: Flooding

Port                    |    State | Optional TLVs              | Address
-------- + ------ + -------------- + --------   gi1 |RX,TX |
                                |192.168.1.254
gi2 |                         RX,TX |                            |192.168.1.254

Port ID: gi1
802.3 optional TLVs:
802.1 optional TLVs PVID:
Disabled

Port ID: gi2
802.3 optional TLVs:
802.1 optional TLVs
PVID: Enabled
```

## lldp tlv-select vlan-name

**Syntax**

**lldp tlv-select vlan-name (add|remove)** *VLAN-LIST*

**Parameter**

| | |
|---|---|
| **add** *VLAN-LIST* | Add VLAN list for LLDP 802.1 VLAN-NAME TLV<br>on the specific interface. The configured ports should be member of all the specified VLANs or the VLAN-LIST is not valid. |
| **remove** *VLAN-LIST* | Remove VLAN list of LLDP 802.1 VLAN-NAME<br>TLV from interface. |

**Default**

Default is no VLAN added.

**Mode**

Port Configuration

**Usage**

Use "**lldp tlv-select vlan-name**" command to add or remove VLAN list for 802.1 VLAN-NAME TLV. The configuration could be shown by "**show lldp**" command.

**Example**

This example add VLAN 100 to VLAN-NAME TLV for port gi10.

Switch(config)# **vlan 100**
Switch(config-vlan)# exit
Switch(config)# **interface gi1**
Switch(config-if)# **switchport trunk allowed vlan add all**
Switch(config-if)# **lldp tlv-select vlan-name add 100**
Switch(config-if)# **end**

Switch# **show lldp interfaces gi1**

State: Enabled Timer: 30
Seconds

```
Hold multiplier: 4
Reinit delay: 2
Seconds Tx delay: 2 Seconds
LLDP packet handling: Flooding

Port            |State | Optional TLVs                  | Address
--------- + ------ + -------------- + --------
gi1          | RX,TX     |                                    |192.168.1.2

Port ID: gi1
802.3 optional TLVs:
802.1 optional TLVs
PVID: Enabled
VLANs: 100
```

## show lldp

### Syntax

**show lldp**
**show lldp interface** *IF_NMLPORTS*

### Parameter

| | |
|---|---|
| *IF_NMLPORTS* | Specify the ports to display information |

### Default

This command has no default value.

### Mode

Privileged EXEC

### Usage

Use "**show lldp**" and "**show lldp interface**" commands to display LLDP global information including LLDP enable status, LLDP PDU TX interval, hold time multiplier, re-initial delay, TX delay, and LLDP packet handling when LLDP is disabled. The per port information displayed includes port LLDP RX/TX enable

status, selected TLV to TX and IP address. The abbreviations in optional TLVs are: port description (PD), system name (SN),system description (SD), and system capability (SC).

### Example

This example displays lldp information of port gi1 and gi2
Switch# **show lldp interfaces gi1,gi2**

State:
Disabled Timer:
30 Seconds
Hold multiplier: 4
Reinit delay: 2 Seconds
Tx delay: 2 Seconds
LLDP packet handling: Flooding

Port| State | Optional TLVs | Address
-------- + ------ + -------------- + --------
gi1 | RX,TX | PD, SN,
SD, SC |192.168.1.254
Gi2 | RX,TX | |192.168.1.254

Port ID: gi1
802.3 optional TLVs: 802.3-mac-phy, 802.3-lag, 802.3-max- frame-size,
management-addr
802.1 optional
TLVs PVID:
Enabled

Port ID: gi2
802.3 optional TLVs:
802.1 optional TLVs
PVID: Enabled

## show lldp local-device

### Syntax

**show lldp local-device**
**show lldp interfaces** IF_NMLPORTS **local-device**

### Parameter

| | |
|---|---|
| *IF_NMLPORTS* | Specify the ports to display information |

### Default

There is no default configuration for this command

### Mode

Privileged EXEC

### Usage

Use "**show lldp local-device**" command to show the local configuration of LLDP PDU. By the commands, a user can view the contents of LLDP/ LLDP-MED TLVs that would be attached in LLDP PDU.

### Example

This example displays the local device information.
Switch# **show lldp local-device**

LLDP Local Device Information:
Chassis Type : Mac Address
Chassis ID : 00:12:12:12:12:12
System Name : Switch121212
System Description :
System Capabilities Support : Bridge
System Capabilities Enable : Bridge
Management Address : 192.168.1.254(IPv4)

## show lldp neighbor

### Syntax

**show lldp neighbor**
**show lldp interfaces** *IF_NMLPORTS* **neighbor**

### Parameter

| | |
|---|---|
| *IF_NMLPORTS* | Specify the ports to display information |

**Default**

There is no default configuration for this command

**Mode**

Privileged EXEC

**Usage**

Use "**show lldp neighbor**" command to display the received neighbor LLDP PDU information.

**Example**

This example displays the neighbor information.
Switch# **show lldp neighbor**

```
Port |Device ID|Port ID                    |SysName|Capabilities       |TTL
---- + --------- + ----- + ------+ ---------- + --
gi3 | 00:12:12:12:12:12 |                                    gi1 |
Switch121212 |                    Bridge |          111
gi11 |                    TREEBASE |00:1A:4D:26:EB:E8 |
TREEBASE |          Station Only |               33
```

# 15.Logging

## logging

**Syntax**

**logging**
**no logging**

**Parameter**

### Default

Logging service is enabled.

### Mode

Global Configuration

### Usage

To enable logging service on the switch, use the command **logging** in the Global Configuration mode.

### Example

The following example disables and enables the logging service on the switch.

```
Switch(config)# no logging
Switch(config)# logging
```

## logging host

### Syntax

**logging host** (*ip-addr*|*hostname*) [**facility** *facility*] [**port** *port*] [**severity** *sev*]

**no logging host** (*ip-addr*|*hostname*)

### Parameter

| | |
|---|---|
| *ipv4-addr* | IPv4 address of the remote logging server. |
| *hostname* | Hostname of the remote logging server. |
| **facility** *facility* | Specify the facility of the logging messages. It can be on of the following value: local0, local1, local2, local3, local4, local5, local6, and local7. The default value of facility is local7. |
| **port** *port* | Specify the port number of the remote logging server.<br>The valid range is from 0 to 65535, and the |

| | |
|---|---|
| | default value is 512. |
| **severity** *sev* | Specify the minimum severity of the logging messages. The valid range is from 0 to 7, and the number 0 to 7 represents emerg, alert, critical, error, warning, notice, info, and debug individually. The default value of minimum severity level is 5 (emerg, alert, crit, error,warning, notice). |

**Default**

No remote logging destination is configured.

**Mode**

Global Configuration

**Usage**

To define the logging server, use the command **logging host** to add the remote logging server in the Global Configuration mode. Otherwise, use the command **no logging host** to remove the remote logging rules.

For the host name configuration, logging service would try translating the host name to IP address directly. Add the logging host would be failed on the failure of host name translating.

**Example**

The following example adds the remote logging rules by IP and Hostname.

```
Switch(config)# logging host 1.2.3.4
Switch(config)# logging host SYSLOG
```

## logging severity

**Syntax**

**logging** (**buffered**|**console**|**file**) [**severity** *sev*]

**no logging** (**buffered**|**console**|**file**)

**Parameter**

| | |
|---|---|
| **buffered** | Log messages to RAM. |
| **console** | Log messages to console buffer. |
| **file** | Log messages to Flash. |
| **severity** *sev* | Specify the minimum severity of the logging messages.<br>The valid range is from 0 to 7, and the number 0 to 7 represents emerg, alert, critical, error, warning, notice, info, and debug individually. The default minimum severity of the **logging severity** configuration is 5 (emerg,alert, crit, error, warning, notice). |

**Default**

Logging to buffered and console is enabled, and the default minimum severity level is 5 (emerg, alert, crit, error, warning, notice).

**Mode**

Global Configuration

**Usage**

To set the minimum severity for the messages that are logged to RAM, console, or Flash, use the command logging severity in the Global Configuration mode. Use the **no** form of the command to remove the mechanism of logging to RAM, console, or Flash individually.

**Example**

The following example sets the minimum severity level of logging to RAM and Flash as debugging.

```
Switch(config)# logging buffered 7
Switch(config)# logging flash 7
```

## show logging

### Syntax

**show logging** [**buffered**|**file**]

### Parameter

| | |
|---|---|
| **buffered** | Display the log messages stored in the RAM. |
| **file** | Display the log messages stored in the Flash. |

### Default

### Mode

Previledged EXEC

### Usage

To display the global logging configuration, and the logging messages stored in the RAM and Flash, use the command **show logging** in the Privileged EXEC mode.

### Example

The following example shows the global logging configuration.

```
Switch# show logging

Logging service is enabled

Aggregation: enabled
Aggregation aging time: 300 sec
```

Console Logging: level notice
Buffer Logging : level notice
File Logging : disabled

Buffer Logging
---
*Mar 20 2020 18:27:26: AAA-5-CONNECT: New console connection for user admin, source async ACCEPTED
*Mar 20 2020 18:27:24: AAA-4-REJECT: New console connection, source async REJECTED
*Mar 20 2020 18:16:08: AAA-5-DISCONNECT: console connection for user admin, source async TERMINATED
*Mar 20 2020 18:12:21: PORT-5-LINK_DOWN: Interface GigabitEthernet19 link down
*Mar 20 2020 17:58:23: PORT-5-LINK_UP: Interface GigabitEthernet19 link up, aggregated (2)
*Mar 20 2020 17:58:22: PORT-5-LINK_DOWN: Interface GigabitEthernet19 link down, aggregated (2)

## clear logging

### Syntax

**clear logging** (**buffered**|**file**)

### Parameter

| | |
|---|---|
| **buffered** | Clear the log messages stored in the RAM. |
| **file** | Clear the log messages stored in the Flash. |

### Default

### Mode

Privileged EXEC

### Usage

To clear the log messages from the internal logging buffer and flash, use the command **clear logging** in the Privileged EXEC mode.

### Example

The following example clear the log messages stored in RAM and Flash.

Switch# **clear logging buffered**
Switch# **clear logging file**

# 16.MAC Address Table

## mac address-table aging-time

### Syntax

**mac accress-table aging-time** *seconds*

### Parameter

| | |
|---|---|
| *seconds* | The time in seconds that an entry remains in the MAC address table. Its valid range is from 10 to 630 seconds,and the default value is 300 seconds. |

### Default

The default aging time is 300 seconds.

### Mode

Global Configuration

### Usage

To set the aging time of the MAC address table, use the command **mac address-table aging-time** in the Global Configuration mode.

### Example

The following example set the agimg time to 500 seconds.

```
Switch(config)# mac address-table aging-time 500
```

## mac address-table static

### Syntax

**mac address-table static** *mac-addr* **vlan** *vlan-id* **interfaces** *IF_PORTS*
**mac address-table static** *mac-addr* **vlan** *vlan-id* **drop**
**no mac address-table static** *mac-addr* **vlan** *vlan-id*

### Parameter

| | |
|---|---|
| *mac-addr* | MAC address. |
| **vlan** *vlan-id* | Specify the VLAN ID for the interface. |
| **Interface** *IF_PORTS* | Specify the interface ID or a list of interface IDs. |
| **drop** | Drop the packets with the specified source or destination unicast MAC address. |

### Default

No static addresses are configured

### Mode

Global Configuration

### Usage

To add a static address to the MAC address table, use the command **mac address-table static** in the Global Configuration mode. For the unicast MAC address filtering, use the command **mac address-table static** with parameter **drop** to drop the packets with the specified source or destination unist MAC address. To delete the static entry from the MAC address table, use the **no** form of the command.

### Example

The following example adds a static address into MAC address table.
Switch# **mac address-table static 00:11:22:33:44:55 vlan 1 interfaces fa5**

The following example adds a rule of unist address filtering into MAC address table.
Switch# **mac address-table static 00:11:22:33:44:55 vlan 1 drop**

## clear mac address-table

### Syntax

**clear mac address-table dynamic [interfaces** *IF_PORTS*|**vlan** *vlan-id*]

### Parameter

| | |
|---|---|
| **interfaces** ***IF_PORTS*** | Delete all dynamic addresses learned on the specific interface. |
| **vlan** *vlan-id* | Delete all source addresses learned on the specific VLAN. |

### Default

### Mode

Privileged EXEC

### Usage

To clear the dynamic (learned) MAC entries from the MAC address table, the specific interface, or the specific VLAN, use the command **clear mac address-table** in the Priveleged EXEC mode.

### Example

The following example clears the learned MAC addresses on the interface gi1.
Switch# clear mac address-table dynamic interfaces gi1

## show mac address-table

### Syntax

**show mac address-table** [**dynamic**|**static**] [**interface** *IF_PORTS*] [**vlan** *vlan-id*]
**show mac address-table** [*mac-addr*] [**vlan** *vlan-id*]

### Parameter

| | |
|---|---|
| **dynamic** | Display only dynamic MAC addresses |
| **static** | Display only static MAC addresses |
| **interface** *IF_PORTS* | Display the MAC addresses entries for a specifc interface. |
| **vlan** *vlan-id* | Display the MAC address entries for a specific VLAN. |
| *mac-addr* | Display entries for a specific MAC address |

### Default

### Mode

Privileged EXEC

### Usage

To show the entry in the MAC address table, use the command **show mac address-table** in the Privilieged EXEC mode.

### Example

The following example displays the entire MAC addrss table.

```
Switch# show mac address-table
VID|MAC Address                |          Type            |      Ports
------+------------------+-----------------+--------------

1 | DE:AD:BE:EF:01:02 |                Management        | CPU
1 | 00:01:02:03:04:05 |                 Static           | All
100 | 00:11:22:33:44:55 |               Static               | gi1
```

1 | 1C:E6:C7:8F:10:02 | Dynamic | fa3
1 | AA:BB:CC:DD:EE:FF | Static | All
1 | DE:AD:BE:EF:01:0C | Dynamic | gi1

## show mac address-table counters

### Syntax

### show mac address-table counters

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

To display the total entries in the MAC addrss table, use the command **show mac address-table counters** in the Privilieged EXEC mode.

### Example

The following example display numbers of addresses in the address table.
Switch# show mac address-table counters
Total number of entries: 5

## show mac address-table aging-time

### Syntax

### show mac address-table aging-time

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

To show MAC address aging time, use the command **show mac address-table aging-time** in the Privilieged EXEC mode.

### Example

The following example displays aging time for the MAC address table.

```
Switch# show mac address-table aging-time
  Mac Address Table aging time:   300 sec
```

# 17.MAC VLAN

## vlan mac-vlan group (Global)

### Syntax

**vlan mac-vlan group** *<1- 2147483647> mac-address* **mask** *<9-48>*
**no vlan mac-vlan group** *mac-address* **mask** *<9-48>*

### Parameter

| | |
|---|---|
| *<1-2147483647>* | Specify the group ID |
| *Mac-address* | Specify the MAC address to be mapped. |
| *<9-48>* | Specify the mask length of MAC address. |

### Default

No MAC Groups are configured.

### Mode

Global Configuration

### Usage

Use the "**vlan mac-vlan group"** command to create MAC address group.
Use the **no** form of this command to delete specify group.

### Example

The following example shows how to create a MAC group with group ID 3.
Switch(config)# **vlan mac-vlan group 333 22:33:44:55:66:77 mask 48**

## vlan mac-vlan group (Interface)

### Syntax

**vlan mac-vlan group <**1- 2147483647**> vlan <**1-4094**>**
**no vlan mac-vlan [group <**1- 2147483647**>]**

### Parameter

| | |
|---|---|
| *<1-2147483647>* | Specify the group ID.(optional in no form) Delete all mapping group if not specify. |
| *<1-4094>* | Specify the VLAN ID to give to match packet. |

### Default

No mappings are configured.

### Mode

Interface Configuration

### Usage

Use the "**vlan mac-vlan group"** to create mapping of group and VLAN ID of

an interface.
Use the **no** form of this command to delete mapping.

**Example**

The following example shows how to mapping group id 333 to VLAN 100 on interface fa1.

```
Switch(config)# interface fa1
Switch(config-if)# vlan mac-vlan group 333 VLAN 100
```

## show vlan mac-vlan groups

**Syntax**

**show vlan mac-vlan groups**

**Parameter**

**Default**

**Mode**

Privileged EXEC

**Usage**

Use the **show vlan mac-vlan groups** command to display mac groups configuration

**Example**

This following example shows how to display mac group.

```
Switch# show vlan mac-vlan groups
Mac Address          Mask                Group Id
-------------------- --------------------        --
------------------
22:33:44:55:66:77    48                  222
44:55:66:77:88:99    48                  333
```

88:99:00:aa:bb:cc 40 444
88:99:00:ab:bb:10 48 111

## show vlan mac-vlan interfaces

### Syntax

**show vlan mac-vlan [interfaces** IF_PORTS]

### Parameter

| | |
|---|---|
| IF_PORTS | (Optional) Specify interfaces mac vlan to display. Display all ports if not specify. |

### Default

### Mode

Privileged EXEC

### Usage

Use the **show vlan mac-vlan interface** command in EXEC mode to display the mac-vlan interfaces setting

### Example

The following example shows how to display the MAC-Based VLAN interfaces setting

Switch# **show vlan mac-vlan interfaces fa1**
Port fa1 :
Mac based VLANs: Group ID
Vlan ID
---
---
333 444
444 1

# 18.Management ACL

## management access-list

### Syntax

**management access-list** NAME
**no management access-list** NAME

### Parameter

| | |
|---|---|
| NAME | The name of management ACL |

### Default

No management ACL is configured.

### Mode

Global Configuration

### Usage

Use the **management access-list** command to create a management access list and to enter management access-list configuration mode. The name of ACL must be unique that cannot have same name with other management ACL. Use the no form of this command to delete

### Example

The following example shows how to add a management ACL with name "test"
Switch(config)# **management access-list test**

## management access-class

### Syntax

**management access-class** NAME
**no management access-class**

### Parameter

| | |
|---|---|
| NAME | The name of management ACL to be used. |

### Default

Default is no management ACL restrictions

### Mode

Global Configuration

### Usage

Use the **management access-class** command to activate a management ACL. Use the no form of this command to delete

### Example

The following example shows how to add a management ACL with name "test"
Switch(config)# **management access-list test**

## deny

### Syntax

**[sequence** <1-65535>**] deny interfaces** IF_PORTS **service(all|http|https|snmp|ssh|telnet)**
**[sequence** <1-65535>**] deny ip** A.B.C.D/A.B.C.D **interfaces** IF_PORTS service (all|http|https|snmp|ssh|telnet)
**[sequence** <1-65535>**] deny ipv6** X:X::X:X/<0-128> **interfaces** IF_PORTS service (all|http|https|snmp|ssh|telnet)

### Parameter

| | |
|---|---|
| <1-65535> | (Optional) Specify sequence index of ACL entry, the sequence index represent the priority of an entry in ACL. If not specified, the switch assigns a number from 1 in ascending order. |
| **interfaces** *IF_PORTS* | Specify the interface ID or a list of interface IDs. |
| **ip** A.B.C.D/A.B.C.D | Specify the source IP address and mask of packet. |
| **ipv6** X:X::X:X/<0-128> | Specify the source IPv6 address and prefix length of packet. |
| **(all\|http\|https\|snmp\|ssh\|telnet)** | Specify the type of services. |

### Default

No rules are configured.

### Mode

Management Access-List Configuration

### Usage

Use the deny command to add deny rules that drop those packets hit the rule.

### Example

The following example shows how to add a deny rule to drop all types of services packets that source ip is 1.1.1.1 from interface gi1.

```
Switch(config)# management access-list test
Switch(config-macl)# sequence 1 deny ip
1.1.1.1/255.255.255.255 interfaces gi1 service all
```

## permit

## Syntax

**[sequence** <1-65535>**] permit interfaces** IF_PORTS **service (all|http|https|snmp|ssh|telnet)**
**[sequence** <1-65535>**] permit ip** A.B.C.D/A.B.C.D **interfaces** IF_PORTS **service (all|http|https|snmp|ssh|telnet)**
**[sequence** <1-65535>**] permit ipv6** X:X::X:X/<0-128> **interfaces** IF_PORTS **service (all|http|https|snmp|ssh|telnet)**

## Parameter

| | |
|---|---|
| <1-65535> | (Optional) Specify sequence index of ACL entry, the sequence index represent the priority of an entry in ACL. If not specified, the switch assigns a number from 1 in ascending order. |
| **interfaces** *IF_PORTS* | Specify the interface ID or a list of interface IDs. |
| **ip** A.B.C.D/A.B.C.D | Specify the source IP address and mask of packet. |
| **ipv6** X:X::X:X/<0-128> | Specify the source IPv6 address and prefix length of packet. |
| **(all\|http\|https\|snmp\|ssh\|telnet)** | Specify the type of services. |

## Default

No rules are configured.

## Mode

Management Access-List Configuration

## Usage

Use the permit command to add permit rules that bypass those packets hit the rule.

## Example

The following example shows how to add a permit rule to bypass http service packets that source ip is 2.2.2.2 from interface gi1.

Switch(config)# **management access-list test**
Switch(config-macl)# **sequence 2 permit ip 2.2.2.2/255.255.255.255 interfaces gi1 service http**

## no sequence

### Syntax

**no sequence** <1-65535>

### Parameter

| | |
|---|---|
| <1-65535> | Specify sequence index of ACL entry to delete. |

### Default

No rules are configured.

### Mode

Management Access-List Configuration

### Usage

Use the **no sequence** command to delete an entry in management ACL.

### Example

The following example shows how to delete an entry.

Switch(config)# **management access-list test**
Switch(config-macl)# **sequence 10 deny interfaces gi1 service all**
Switch(config-macl)# **no sequence 10**

## show management access-list

### Syntax

**show management access-list [**NAME**]**

### Parameter

| | |
|---|---|
| NAME | Specify the name of management ACL to displayed |

### Default

No default is defined

### Mode

Privileged EXEC

### Usage

Use the **show management access-list** command to show management ACL.

### Example

The example shows how to show management access-list

Switch#Switch# show management access-list 1
management access-list is created test
----
sequence 1 deny ip 1.1.1.1/255.255.255.255 interfaces gi1 service all
! (Note: all other access implicitly denied)

## show management access-class

### Syntax

**show management access-class**

### Parameter

**Default**

No default is defined

**Mode**

Privileged EXEC

**Usage**

Use the **show management access-class** command to show the active management access-list.

**Example**

The example shows how to show management access-class

Switch# **show management access-class**
Management access-class is enabled, using access-list test

# 19.MLD Snooping

## ipv6 mld snooping

**Syntax**

**ipv6 mld**
**snooping no ipv6**
**mld snooping**

**Parameter**

**Default**

Default is disabled

**Mode**

Global Configuration

**Usage**

Use the **ipv6 mld snooping** command to enable MLD snooping function. Use the **no** form of this command to disable. Disable will clear all ipv6 mld snooping dynamic group and dynamic router port, and make the static ipv6 mld group invalid. No more dynamic group and router port by mld message will be learned. You can verify settings by the **show ipv6 mld snooping** command.

**Example**

The following example specifies that set **ipv6 mld snooping** test.

Switch(config)# **ipv6 mld snooping**

## ipv6 mld snooping report-suppression

**Syntax**

**ipv6 mld snooping report-suppression**
**no ipv6 mld snooping report-suppression**

**Parameter**

**Default**

Default is enabled

**Mode**

Global Configuration

**Usage**

Use the **ipv6 mld snooping report-suppression** command to enable MLD snooping report-suppression function.

Use the **no** form of this command to disable. Disable report-supression will forward all received reports to the vlan router ports.
You can verify settings by the **show ipv6 mld snooping** command.

**Example**

The following example specifies that disable ipv6 mld snooping report-suppression test.
Switch(config)# **no ipv6 mld snooping report-suppression**

## ipv6 mld snooping version

**Syntax**

**ipv6 mld snooping version (1|2)**

**Parameter**

| | |
|---|---|
| (1\|2) | Ipv6 mld snooping running version 1 or 2 |

**Default**

Default is version 1

**Mode**

Global Configuration

**Usage**

Use the **ipv6 mld snooping version** command to change MLD support version. Version 2 packet won't be processed if choose version 1.
You can verify settings by the **show ip igmp snooping** command.

**Example**

The following example specifies that set ipv6 mld snooping version 2.

Switch(config)# **ipv6 mld snooping version 2**

## ipv6 mld snooping unknown-multicast action

### Syntax

**ipv6 mld snooping unknown-multicast action (drop | flood |router-port)**
**no ipv6 mld snooping unknown-multicast action**

### Parameter

| | |
|---|---|
| (drop \| flood \| router- port) | Drop 、 flood in vlan or forward to router port of<br>unknown multicast packet |

### Default

Default is flood.

### Mode

Global Configuration

### Usage

When igmp and mld snooping disabled, it can't set action router-port.
When disable igmp snooping & mld snooping, it set unknown multicast action flood.
When action is router-port to flood or drop, it will delete the unknown multicast group entry.

Use the **ipv6 mld snooping unknown-multicast action** command to change action.
Use the **no** form of this command to restore to default.
You can verify settings by the **show ipv6 mld snooping** command.

### Example

The following example specifies that set ipv6 mld unknown multicast action router-port test.
Switch(config)# **ipv6 mld snooping unknown-multicast action router-port**

## ipv6 mld snooping vlan

### Syntax

**ipv6 mld snooping vlan VLAN-LIST**
**no ipv6 mld snooping vlan VLAN-LIST**

### Parameter

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |

### Default

Default is disabled for all VLANs

### Mode

Global Configuration

### Usage

Disable will clear all ipv6 mld snooping dynamic group and dynamic router port and make all static ip igmp group invalid of this vlan. Will not learn dynamic group and router port by igmp message any more.
Use the **ipv6 mld snooping vlan** command to enable MLD on VLAN.
Use the **no** form of this command to disable
You can verify settings by the **show ipv6 mld snooping vlan** command.

### Example

The following example specifies that set ipv6 mld snooping vlan test.

Switch(config)# **ipv6 mld snooping vlan 1**

## ipv6 mld snooping vlan fastleave

### Syntax

**ipv6 mld snooping vlan <VLAN-LIST> fastleave**
**no ipv6 mld snooping vlan <VLAN-LIST> fastleave**

### Parameter

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |

### Default

Default is disabled

### Mode

Global Configuration

### Usage

Use the **ipv6 mld snooping vlan fastleave** command to enable fastleave function. Group will remove port immediately when receive leave packet. Use the **no** form of this command to disable.
You can verify settings by the **show ipv6 mld snooping vlan** command

### Example

The following example specifies that set ipv6 mld snooping vlan fastleave test.
Switch(config)# **ipv6 mld snooping vlan 1 fastleave**

## ipv6 mld snooping vlan last-member-query-count

### Syntax

**ipv6 mld snooping vlan <VLAN-LIST> last-member-query-count <1-7>**
**no ipv6 mld snooping vlan <VLAN-LIST> last-member-query-count**

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| last-member-query-count <1-7> | specifies last member query count to set |

**Default**

Default is 2

**Mode**

Global Configuration

**Usage**

Use the **ipv6 mld snooping vlan last-member-query-count** command to change how many query packets will send.
Use the **no** form of this command to restore to default.
You can verify settings by the **show ipv6 mld snooping vlan** command

**Example**

The following example specifies that set **ipv6 mld snooping vlan last-member-query-count** test.
Switch(config)# **ipv6 mld snooping vlan 1 last-member-query-count 5**

## ipv6 mld snooping vlan last-member-query-interval

**Syntax**

**ipv6 mld snooping vlan <VLAN-LIST> last-member-query-interval <1- 60>**
**no ipv6 mld snooping vlan <VLAN-LIST> last-member-query-interval**

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |

| | |
|---|---|
| last-member-query-interval <1-60> | specifies last member query interval to set |

**Default**

Default is 1

**Mode**

Global Configuration

**Usage**

Use the **ipv6 mld snooping vlan last-member-query-interval** command to set interval between each query packet.
Use the **no** form of this command to restore to default

You can verify settings by the **show ipv6 mld snooping vlan** command

**Example**

The following example specifies that set **ipv6 mld snooping vlan last-member-query-interval** test.
Switch(config)# **ipv6 mld snooping vlan 1 last-member-query-interval 3**

## ipv6 mld snooping vlan query-interval

**Syntax**

**ipv6 mld snooping vlan <VLAN-LIST> query-interval <30-18000>**
**no ipv6 mld snooping vlan <VLAN-LIST> query-interval**

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| query-interval <30-18000> | specifies query interval to set |

**Default**

Default is 125

**Mode**

Global Configuration

**Usage**

Use the **ipv6 mld snooping vlan query-interval** command to set interval between each query.
Use the **no** form of this command to restore to default
You can verify settings by the **show ipv6 mld snooping vlan** command

**Example**

The following example specifies that set **ipv6 mld snooping vlan query-interval** test.
Switch(config)# **ipv6 mld snooping vlan 1 query-interval 100**

## ipv6 mld snooping vlan response-time

**Syntax**

**ipv6 mld snooping vlan <VLAN-LIST> response-time <5-20>**
**no ipv6 mld snooping vlan <VLAN-LIST> response-time**

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| response-time <5-20> | specifies a response time to set |

**Default**

Default is 10

### Mode

Global Configuration

### Usage

Use the **ipv6 mld snooping vlan response-time** command to set response time.
Use the **no** form of this command to restore to default.
You can verify settings by the **show ipv6 mld snooping vlan** command

### Example

The following example specifies that set **ipv6 mld snooping vlan response-time** test.
Switch(config)# **ipv6 mld snooping vlan 1 response-time 12**

## ipv6 mld snooping vlan router

### Syntax

**ipv6 mld snooping vlan VLAN-LIST router learn pim-dvmrp**
**no ipv6 mld snooping vlan VLAN-LIST router learn pim-dvmrp**

### Parameter

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |

### Default

Default is enabled

### Mode

Global Configuration

### Usage

Use the **ipv6 mld snooping vlan router** command to enable learning router port by routing protocol packets such as PIM/PIMv2, DVMRP, MOSPF. Use the **no** form of this command to disable.
You can verify settings by the **show ipv6 mld snooping vlan** command

**Example**

The following example specifies that set **ipv6 mld snooping vlan router** test.

Switch(config)# **ipv6 mld snooping vlan 99 router**

## ipv6 mld snooping vlan static-port

**Syntax**

**ipv6 mld snooping vlan <VLAN-LIST> static-port IF_PORTS**
**no ipv6 mld snooping vlan <VLAN-LIST> static-port IF_PORTS**

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| IF_PORTS | specifies a port list to set or remove |

**Default**

No static port by default

**Mode**

Global Configuration

**Usage**

Use the **ipv6 mld snooping vlan static-port** command to add static forwarding port, all known vlan 1 ipv6 group will add the static ports.
Use the **no** form of this command to delete static port.
You can verify settings by the **show ipv6 mld snooping forward-all** command.

**Example**

The following example specifies that set ipv6 mld snooping static port test.

Switch(config)# **ipv6 mld snooping vlan 1 static -port gi1-2**

## ipv6 mld snooping vlan forbidden-router-port

### Syntax

**ipv6 mld snooping vlan <VLAN-LIST> forbidden-router-port IF_PORTS**
**no ipv6 mld snooping vlan <VLAN-LIST> forbidden-router-port IF_PORTS**

### Parameter

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| IF_PORTS | specifies a port list to set or remove |

### Default

No forbidden router ports by default

### Mode

Global Configuration

### Usage

Use the **ipv6 mld snooping vlan forbidden-router-port** command to add static forbidden router port. This will also remove port from static router port. The forbidden router port will not forward received query packet.
Use the **no** form of this command to delete forbidden router port.
You can verify settings by the **show ipv6 mld snooping router** command.

### Example

The following example specifies that set ipv6 mld snooping forbidden test.

Switch(config)# **ipv6 mld snooping vlan 1 forbidden-router-port gi2**

## ipv6 mld snooping vlan static router port

### Syntax

**ipv6 mld snooping vlan <VLAN-LIST> static-router-port IF_PORTS**
**no ipv6 mld snooping vlan <VLAN-LIST> static-router-port IF_PORTS**

### Parameter

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| IF_PORTS | specifies a port list to set or remove |

### Default

None static router ports by default

### Mode

Global Configuration

### Usage

Use the **ipv6 mld snooping vlan static-router-port** command to add static router port. All query packets will forward to this port.
Use the **no** form of this command to delete static router port.
You can verify settings by the **show ipv6 mld snooping router** command.

### Example

The following example specifies that set ipv6 mld snooping static test.

Switch(config)# **ipv6 mld snooping vlan 1 static-router-port gi1-2**

## ipv6 mld snooping vlan static-group

### Syntax

**ipv6 mld snooping vlan <VLAN-LIST> static-group [<ipv6-addr>] interfaces IF_PORTS**
**no ipv6 mld snooping vlan <VLAN-LIST> static-group <ipv6-addr>**

**interfaces IF_PORTS**

**Parameter**

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| ipv6-addr | specifies multicast group ipv4 address |
| IF_PORTS | specifies port list to set or remove |

**Default**

No static group by default

**Mode**

Global Configuration

**Usage**

Use the **ipv6 mld snooping vlan static-group** command to add a static group. The static group will not learn other dynamic ports. If the dynamic group exists, then the static group will overlap the dynamic group. The static group set to valid unless igmp snooping global and vlan enable.

Use the **no** form of this command to delete a port in static group. If remove the last member of static group, the static group will be delete.

You can verify settings by the **show ipv6 mld snooping group** command.

**Example**

The following example specifies that set ipv6 mld snooping static group test.

Switch(config)# **ipv6 mld snooping vlan 1 static-group ff13::1 interfaces gi1-2**

## ipv6 mld snooping vlan group

### Syntax

**no ipv6 mld snooping vlan <VLAN-LIST> group <ipv6-addr>**

### Parameter

| | |
|---|---|
| VLAN-LIST | specifies VLAN ID list to set |
| ipv6-addr | specifies multicast group ipv6 address |

### Default

### Mode

Global Configuration

### Usage

Use the **no ipv6 mld snooping vlan group** command to delete a group which could be static or dynamic.
You can verify settings by the **show ipv6 mld snooping group** command.

### Example

The following example specifies that set ip igmp snooping static group test.

Switch(config)# **no ip igmp snooping vlan 1 group ff13::1**

## ipv6 mld profile

### Syntax

**ipv6 mld profile <1-128>**
**no ipv6 mld profile <1-128>**

### Parameter

| | |
|---|---|
| <1-128> | specifies profile ID |

**Default**

No profie exist by default

**Mode**

Global Configuration

**Usage**

Use the **ipv6 mld profile** command to enter profile configuration Use the **no** form of this command to delete profile
You can verify settings by the **show ipv6 mld profile** command

**Example**

The following example specifies that set ipv6 mld profile test.
Switch(config)# **ipv6 mld profile 1**
Switch(config-mld-profile)# **profile range ipv6 ff13::1 ff13::10 action permit**

## profile range

**Syntax**

**profile range ipv6 <ipv6-addr> [ipv6-addr] action (permit | deny)**

**Parameter**

| | |
|---|---|
| <ipv6-addr> | Start ipv6 multicast address |
| [ipv6-addr] | End ipv6 multicast address |
| (permit \| deny) | Permit: allow Multicast address range ip address learning<br>deny: do not allow Multicast address range ip address learning |

**Default**

**Mode**

mld profile configuration mode

**Usage**

Use the **profile** command to generate MLD profile.
You can verify settings by the **show ipv6 mld profile** command

**Example**

The following example specifies that set ipv6 mld profile test.
Switch(config)# **ipv6 mld profile 1**
Switch(config-mld-profile)# **profile range ipv6 ff13::1 ff13::10 action permit**

## ipv6 mld filter

**Syntax**

**ipv6 mld filter <1-128>**
**no ipv6 mld filter**

**Parameter**

| | |
|---|---|
| <1-128> | specifies profile ID |
| [interfaces IF_PORTS] | specifies interfaces to display |

**Default**

**Mode**

Port Configuration

**Usage**

Use the **ipv6 mld filter** command to bind a profile for port.
When the port bind a profile. Then the port learning group will

update, if the group is not match the profile rule it will remove the port from the group. Static group is excluded.
Use the **no** form of this command to delete profile
You can verify settings by the **show ipv6 mld filter** command

**Example**

The following example specifies that set ipv6 mld filter test.

Switch(config)# **interface gi1**
Switch(config-if)# **ipv6 mld filter 1**

## ipv6 mld max-groups

**Syntax**

**ipv6 mld max-groups <0-1024>**
**no ipv6 mld max-groups**

**Parameter**

| | |
|---|---|
| <0-1024> | specifies profile ID |

**Default**

Default is 1024

**Mode**

Port Configuration

**Usage**

Use the **ipv6 mld max-groups** command to limit port learning max group number. When the port has reach limitation, new group will not add this port. Static group is excluded.

Use the **no** form of this command to restore to default
You can verify settings by the **show ipv6 mld max-groups** command.

### Example

The following example specifies that set ipv6 mld max-groups test.
Switch(config)# **interface gi1**
Switch(config-if)# **ipv6 mld max-groups 10**

## ipv6 mld max-groups action

### Syntax

**ipv6 mld max-groups action (deny | replace)**

### Parameter

| | |
|---|---|
| (deny \| replace) | Deny: current port igmp group arrived max-groups,don't add group.<br>Replace: current port igmp group arrived max-groups,remove port for rand group, and add port to new group. |

### Default

Default action is deny

### Mode

Interface mode

### Usage

Use the **ipv6 mld max-groups action** command to set the
action when the numbers of groups reach the limitation.
Use the **no** form of this command to restore to default
You can verify settings by the **show ipv6 mld max-groups** command.

### Example

The following example specifies that set action replace test.

Switch(config-if)#**ipv6 mld max-groups action replace**

## clear ipv6 mld snooping groups

### Syntax

**clear ipv6 mld snooping groups [(dynamic | static)]**

### Parameter

| | |
|---|---|
| None | Clear ipv6 mld groups include dynamic and static |
| (dynamic \| static) | ipv6 mld group type is dynamic or static |

### Default

### Mode

Privileged EXEC

### Usage

This command will clear the ipv6 mld groups for dynamic or static or all of type. You can verify settings by the **show ipv6 mld snooping groups** command..

### Example

The following example specifies that clear ipv6 mld snooping groups test.

Switch# **clear ipv6 mld snooping groups**

## clear ipv6 mld snooping statistics

### Syntax

**clear ipv6 mld snooping statistics**

**Parameter**

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will clear the igmp statistics.
You can verify settings by the **show ipv6 mld snooping** command.

**Example**

The following example specifies that clear ipv6 mld snooping statistics test.
Switch# **clear ipv6 mld snooping statistics**

## show ipv6 mld snooping groups counters

**Syntax**

**show ipv6 mld snooping groups counters**

**Parameter**

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will display the ipv6 mld group counter include static group.

**Example**

The following example specifies that display ipv6 mld snooping group counter test.
Switch# **show ipv6 mld snooping group counters**
Total ipv6 mld snooping group number: 2

## show ipv6 mld snooping groups

### Syntax

**show ipv6 mld snooping groups [(dynamic | static)]**

### Parameter

| | |
|---|---|
| none | Show ipv6 mld groups include dynamic and static |
| (dynamic \| static) | Display ipv6 mld group type is dynamic or static |

### Default

display all ipv6 mld groups

### Mode

Privileged EXEC

### Usage

This command will display the ipv6 mld groups for dynamic or static or all of type.

### Example

The following example specifies that show ipv6 mld snooping groups test.
Switch# **show ipv6 mld snooping groups**

```
VLAN |        Group IP Address                | Type | Life(Sec) | Port
------+---------------------------------------+--------+-----------
+-----------------
```

1 |  ff13::1 | Static|  --  | fa1
1 |  ff13::2 | Static|  --  | fa2

Total Number of Entry = 2

## show ipv6 mld snooping router

### Syntax

**show ipv6 mld snooping router [(dynamic | forbidden |static )]**

### Parameter

| | |
|---|---|
| none | Show ipv6 mld router include dynamic and static and forbidden |
| (dynamic \| forbidden \| static) | Display ipv6 mld router info for different type |

### Default

### Mode

Privileged EXEC

### Usage

This command will display the ipv6 mld router info.

### Example

The following example specifies that show ipv6 mld snooping router test.
Switch# **show ipv6 mld snooping router**
Dynamic Router Table
VID | Port | Expiry Time(Sec)
------+---------+-----------------

Total Entry 0

Static Router Table VID |
Port Mask
------+------------------------
1 | fa5

Total Entry 1

Forbidden Router Table VID
| Port Mask
------+------------------------

Total Entry 0

## show ipv6 mld snooping

**Syntax**

**show ipv6 mld snooping**

**Parameter**

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will display ipv6 mld snooping global info.

**Example**

The following example specifies that show ipv6 mld snooping test.
Switch# **show ipv6 mld snooping**
MLD Snooping Status
--------------------

Snooping : Disabled

Report Suppression : Enabled
Operation Version : v1
Forward Method : mac
Unknown Multicast Action : Flood

Packet Statistics
Total RX : 0
Valid RX : 0
Invalid RX : 0
Other RX : 0
Leave RX : 0
Report RX : 0
General Query RX : 0
Specail Group Query RX : 0
Specail Group & Source Query RX : 0
Leave TX : 0
Report TX : 0
General Query TX : 0
Specail Group Query TX : 0
Specail Group & Source Query TX : 0

## show ipv6 mld snooping vlan

### Syntax

**show ipv6 mld snooping vlan [VLAN-LIST]**

### Parameter

| | |
|---|---|
| none | Show all ipv6 mld snooping vlan info |
| [VLAN-LIST] | Show specifies vlan ipv6 mld snooping info |

### Default

Show all ipv6 mld snooping vlan info

### Mode

Privileged EXEC

**Usage**

This command will display ipv6 mld snooping vlan info.

**Example**

The following example specifies that show ipv6 mld snooping vlan test.
Switch# **show ipv6 mld snooping vlan 1**
MLD Snooping is globaly disabled
MLD Snooping VLAN 1 admin : disabled
MLD Snooping oper mode : disabled
MLD Snooping robustness: admin 2 oper 2
MLD Snooping query interval: admin 125 sec oper 125 sec
MLD Snooping query max response : admin 10 sec oper 10 sec
MLD Snooping last member query counter: admin 2 oper 2
MLD Snooping last member query interval: admin 1 sec oper 1 sec
MLD Snooping last immediate leave: disabled
MLD Snooping automatic learning of multicast router ports: enabled

## show ipv6 mld snooping forward-all

**Syntax**

**show ipv6 mld snooping forward-all [vlan VLAN-LIST]**

**Parameter**

| | |
|---|---|
| none | Show all ipv6 mld snooping vlan forward-all info |
| [vlan VLAN-LIST] | Show specifies vlan of ipv6 mld forward info. |

**Default**

Show all vlan ipv6 mld forward all info

**Mode**

Privileged EXEC

**Usage**

This command will display ipv6 mld snooping forward all info.

**Example**

The following example specifies that show ipv6 mld snooping forward-all test.
Switch# **show ipv6 mld snooping forward-all**
MLD Snooping VLAN 1
MLD Snooping static port : None
MLD Snooping forbidden port : None

## show ipv6 mld profile

**Syntax**

**show ipv6 mld profile [<1-128>]**

**Parameter**

| | |
|---|---|
| none | Show all ipv6 mld snooping profile info |
| [<1-128>] | Show specifies index profile info |

**Default**

Show all ipv6 mld profile info

**Mode**

Privileged EXEC

**Usage**

This command will display ipv6 mld profile info.

**Example**

The following example specifies that show ipv6 mld profile test.
Switch# **show ipv6 mld profile**
IPv6 mld profile index: 1
IPv6 mld profile action: permit
Range low ip: ff13::1
Range high ip: ff13::10

## show ipv6 mld filter

**Syntax**

**show ipv6 mld filter [interfaces IF_PORTS]**

**Parameter**

| | |
|---|---|
| none | Show all port filter |
| [interfaces IF_PORTS] | Show specifies ports filter |

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will display ipv6 mld port filter info.

**Example**

The following example specifies that show ipv6 mld filter test.
Switch# **show ipv6 mld filter**
Port ID | Profile ID

---------+--------------
gi1 : 1
gi2 : None
gi3 : None
gi4 : None
gi5 : None
 --More--

## show ipv6 mld max-group

### Syntax

**show ipv6 mld max-group [interfaces IF_PORTS]**

### Parameter

| | |
|---|---|
| none | Show all port max-group |
| [interfaces IF_PORTS] | Show specifies ports max-group |

### Default

### Mode

Privileged EXEC

### Usage

This command will display ipv6 mld port max-group.

### Example

The following example specifies that show ipv6 mld max-group test.
Switch(config-if)# **ipv6 mld max-groups 50**
Switch# **show ipv6 mld max-group**
Port ID | Max Group
---------+--------------
gi1 : 50

gi2 : 256
gi3 : 256
gi4 : 256
gi5 : 256
--More--

## show ipv6 mld max-group action

### Syntax

**show ipv6 mld max-group action [interfaces IF_PORTS]**

### Parameter

| | |
|---|---|
| none | Show all port max-group action |
| [interfaces IF_PORTS] | Show specifies ports max-group action |

### Default

Show all ports ipv6 mld max-group action

### Mode

Privileged EXEC

### Usage

This command will display ipv6 mld port max-group action.

### Example

The following example specifies that show ipv6 mld max-group action test.
Switch(config-if)# **ipv6 mld max-groups action replace**
Switch# **show ipv6 mld max-group action**
Port ID | Max-groups Action
---------+--------------------
gi1 : replace
gi2 : deny

gi3 : deny
gi4 : deny
gi5 : deny
--More--

# 20.MVR

## mvr

### Syntax

**mvr**
**no mvr**

### Parameter

### Default

Default is disabled

### Mode

Global Configuration

### Usage

Use the **mvr** command to enable MVR function. The command will clear all mvr VLAN ID multicast snooping group.
Use the **no** form of this command to disable. Disable will clear all mvr group.
You can verify settings by the **show mvr** command.

### Example

The following example specifies that set **mvr** test.
Switch(config)# **mvr**
Switch(config)# **no mvr**

Switch# **show mvr**
**MVR Running : Disabled**
MVR Multicast VLAN : 1
MVR Group Range : None
MVR Max Multicast Groups : 128
MVR Current Multicast Groups : 0
MVR Global query response time : 1 sec
MVR Mode : compatible

## mvr vlan

### Syntax

**mvr vlan <VLAN-ID>**

### Parameter

| | |
|---|---|
| <VLAN-ID> | The exist static vlan id |

### Default

Default mvr vlan id is 1

### Mode

Global Configuration

### Usage

Use the **mvr vlan** command to modify mvr vlan id when the mvr status is enabled.
Change mvr vlan id will delete the old mvr vlan and new mvr vlan group. If there have configure source or receiver port, there will check the source must only in the mvr vlan , and receiver port must not in the mvr vlan member.
You can verify settings by the **show mvr** command.

### Example

The following example specifies that configure mvr vlan 2 test.
Switch(config)# **vlan 2**
Switch(config)# **mvr**
**The operation will delete groups of VLAN ID is MVR VLAN include static groups. Continue? [yes/no]:y**
Switch(config)# **mvr vlan 2**
**The operation will delete the old and new MVR VLAN groups include static MVR groups.Continue? [yes/no]:y**

Switch# **show mvr**
MVR Running :
Enabled
**MVR Multicast**
**VLAN : 2**
MVR Group Range :
None
MVR Max Multicast Groups :
128
MVR Current Multicast Groups :
0
MVR Global query response
time : 1 sec
MVR Mode : compatible

## mvr group

### Syntax

**mvr group <ip-address> [<1-128>]**

### Parameter

### Default

| | |
|---|---|
| < ip-address> | Start MVR IP multicast address |
| [<1-128>] | Contiguous series of IP addresses. |

### Mode

Global Configuration

### Usage

Use the **mvr group** command to configure mvr group address range when mvr is enabled. The command will delete all mvr vlan ipv4 group entry You can verify settings by the **show mvr** command

### Example

The following example specifies that set mvr group range is 224.1.1.1 ~ 224.1.1.8 test.
Switch(config)# **mvr**
Switch(config)# **mvr group 224.1.1.1 8**
**The operation will delete the MVR VLAN groups include static MVR groups.Continue? [yes/no]:y**
Switch# **show mvr**
MVR Running : Enabled
MVR Multicast VLAN : 2
**MVR Group Range : 224.1.1.1**
**~ 224.1.1.8**
MVR Max Multicast Groups : 128
MVR Current Multicast Groups : 0
MVR Global query response time : 1 sec
MVR Mode : compatible

## mvr mode

### Syntax

**mvr mode (dynamic | compatible)**

### Parameter

| | |
|---|---|
| (dynamic\|compatible) | dynamic: Allows dynamic MVR membership on source ports<br>compatible: does not support IGMP dynamic joins on source ports. |

**Default**

Default is compatible.

**Mode**

Global Configuration

**Usage**

Use the **mvr mode** command to change mvr mode when mvr is enabled.
You can verify settings by the **show mvr** command.

**Example**

The following example specifies that set mvr mode dynamic test.
Switch(config)#**mvr**
Switch(config)#**mvr mode dynamic**
Switch# **show mvr**
MVR Running : Enabled
MVR Multicast VLAN : 2
MVR Group Range : 224.1.1.1 ~ 224.1.1.8
MVR Max Multicast Groups : 128
MVR Current Multicast Groups : 0
MVR Global query response time : 1 sec
**MVR Mode : dynamic**

## mvr query-time

**Syntax**

**mvr query-time <1-10>**
**no mvr query-time**

**Parameter**

| | |
|---|---|
| <1-10> | specifies query response time is 1~10 sec. |

**Default**

Default is 1 sec

**Mode**

Global Configuration

**Usage**

Use the **mvr query-time** command to configure when mvr is enabled. Use the **no** form of this command to set query-time default value. You can verify settings by the **show mvr** command.

**Example**

The following example specifies that set mvr query-time 10 sec test.

Switch(config)# **mvr**
Switch(config)# **mvr query-time 10**
Switch# **show mvr**
MVR Running :
Enabled
MVR Multicast
VLAN : 2
MVR Group Range : 224.1.1.1 ~ 224.1.1.8
MVR Max Multicast
Groups : 128
MVR Current Multicast
Groups : 0
**MVR Global query response time : 10 sec**
MVR Mode : dynamic

## mvr port type

**Syntax**

**mvr type (source | receiver)**
**no mvr type**

**Parameter**

| | |
|---|---|
| (source \| receiver) | Source: Configure uplink ports that receive and send multicast data as source ports.<br>Subscribers cannot be directly connected to source ports. All source ports on a switch belong to the single multicast VLAN. Receiver: Configure a port as a receiver port if it is a subscriber port and should only receive multicast data. It does not receive data unless it becomes a member of the multicast group, either statically or by using IGMP leave and join messages.<br>Receiver ports cannot belong to themulticast VLAN. |

**Default**

**Mode**

Port Configuration

**Usage**

Use the **mvr type** command to configure mvr port type when mvr is enabled. The source port must only belong to mvr vlan. The receiver port must not belong to mvr vlan, and port mode must be access mode.
Use the **no** form of this command to set mvr type none
You can verify settings by the **show mvr interface** command

**Example**

The following example specifies that set gi1 fa1 is source port , fa2 is receiver port test.
Switch(config)# **vlan 2**
Switch(config-vlan)#**exit**

```
Switch(config)#mvr
Switch(config)#mvr vlan 2
Switch(config)#mvr group 224.1.1.1 8
Switch(config)# interface gi1
Switch(config-if)# switchport trunk allowed vlan 2
Switch(config-if)# mvr
type source
Switch(config-if)#exit
Switch(config)# interface
gi2
Switch(config-if)# switchport
mode access
Switch(config-if)#mvr type
receiver
Switch# show mvr interface
Port | Type | Immediate Leave
--------+---------+----------------
gi1|     Source|       Disabled
  gi2| Receiver|         Disabled
```

## mvr immediate

**Syntax**

**mvr immediate**
**no mvr immediate**

**Parameter**

**Default**

Default is disabled

**Mode**

Port Configuration

**Usage**

Use the **mvr immediate** command to configure mvr support immediate leave

when mvr is enabled.
**Note** This command applies to only receiver ports and should only be enabled on receiver ports to which a single receiver device is connected.
Use the **no** form of this command to disable immediate leave. You can verify settings by the **show mvr interface** command

**Example**

The following example specifies that set gi2 immediate enable test. The configure should configure mvr receiver port firstly.(eg. mvr port type)
Switch(config)# **interface gi2**
Switch(config-if)#**mvr immediate**
Switch(config-if)#**exit**
Switch(config)# **exit**
Switch# **show mvr interface**
Port | Type | Immediate Leave
--------+---------+-----------------
gi1 | Source| Disabled
gi2 | Receiver| **Enabled**

## mvr vlan group

**Syntax**

**mvr vlan <VLAN-ID> group <ip-addr> interfaces IF_PORTS**
**no mvr vlan < VLAN-ID> group <ip-addr> interfaces IF_PORTS**

**Parameter**

| | |
|---|---|
| VLAN-ID | specifies MVR VLAN ID for static group |
| ip-addr | specifies multicast MVR group address |
| IF_PORTS | specifies port list to set or remove |

**Default**

**Mode**

Global Configuration

**Usage**

Use the **mvr vlan group** command to add a static group or configure static group member ports when mvr is enabled.This command applies to only receiver ports.
In compatible mode, this command applies to only receiver ports.
In dynamic mode, it applies to receiver ports and source ports.
When remove static mvr group all ports, the static group will be delete. Or can use **no ip igmp vlan VLAN-ID group** to delete the mvr static group.Static group can't learn dynamic port by igmp memesage.
Use the **no** form of this command to delete a port in static group. If remove the last member of static group, the static group will be delete.

You can verify settings by the **show mvr members** command.

**Example**

The following example specifies that set mvr static group test.
The configure must configure mvr receiver port firstly.(eg. mvr port type)
Switch(config)# **mvr vlan 2 group 224.1.1.1 interfaces gi2**
Switch# **show mvr members**
clear mvr members
Gourp IP Address | Type | Life(Sec) | Port
------------------+--------+-----------+-----------------
224.1.1.1 | Static| -- | gi2

Total Number of Entry = 1

**Syntax**

**clear mvr members [dynamic|static]**

**Parameter**

| | |
|---|---|
| dynamic | specifies MVR dynamic group |
| static | specifies MVR static group |

**Default**

Clear all of mvr group

**Mode**

Privileged EXEC

**Usage**

This command will clear the mvr groups for selected type.

**Example**

The following example specifies that clear all mvr groups test.

Switch# **clear mvr members**

## show mvr members

**Syntax**

**show mvr members**

**Parameter**

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will display the mvr groups for all of type.

**Example**

The following example specifies that show mvr groups test.

Switch# **show mvr members**

## show mvr interface

**Syntax**

**show mvr interface [IF_PORTS]**

**Parameter**

| | |
|---|---|
| IF_PORTS | Show specifies port list configurationt |

**Default**

**Mode**

Privileged EXEC

**Usage**

This command will display mvr port type and port immediate status.

**Example**

The following example specifies that show mvr interface test.

Switch# **show mvr interface**

## show mvr

**Syntax**

**show mvr**

**Parameter**

### Default

### Mode

Privileged EXEC

### Usage

This command will display mvr global information.

### Example

The following example specifies that show mvr test.
Switch# **show mvr**
MVR Running : Enabled
MVR Multicast VLAN : 100
MVR Group Range : 224.1.1.1 ~ 224.1.1.128
MVR Max Multicast Groups : 128
MVR Current Multicast Groups : 0
MVR Global query response time : 1 sec
MVR Mode : compatible

# 21.OSPF

## area

### Syntax

**area [<0-4294967295> | A.B.C.D]**
**no area [<0-4294967295> | A.B.C.D]**

### Parameter

| | |
|---|---|
| *<0-4294967295>* | OSPF area ID is a decimal value |
| *A.B.C.D* | OSPF area ID in IP address format |

### Default

### Mode

OSPF configuration mode

### Usage

Use the command "area" to configure the area of OSPF.

### Example

Configure OSPF area

```
Switch(config)# ospf 1
Switch(config-ospf-1)# area 0
Switch(config-ospf-1-area-0.0.0.0)#
```

## network

### Syntax

**network** *A.B.C.D/M*
**no network** *A.B.C.D/M*

### Parameter

| | |
|---|---|
| ***A.B.C.D/M*** | Ospf network prefix |

### Default

### Mode

OSPF area mode

### Usage

Use the command "network" to publish the IP routing network of OSPF.

**Example**

Publish the IP routing network of OSPF

Switch(config)# **ospf 1**
Switch(config-ospf-1)# **area 0**
Switch(config-ospf-1-area-0.0.0.0)# **network 12.1.1.1/24**

## ospf

**Syntax**

**ospf [1]**
**no ospf [1]**

**Parameter**

| | |
|---|---|
| 1 | Process ID |

**Default**

**Mode**

Global Configuration

**Usage**

Use the command "OSPF" to enable the OSPF dynamic protocol.

**Example**

Enable OSPF

Switch(config)# **ospf 1**
Switch(config-ospf-1)#

## router-id

### Syntax

**router-id** *A.B.C.D*
**no router-id**

### Parameter

| | |
|---|---|
| *A.B.C.D* | OSPF router ID in IP address format |

### Default

### Mode

OSPF configuration mode

### Usage

use Configure OSPF router ID with the command "router ID"

### Example

Configure OSPF router ID
Switch(config)# **ospf 1**
Switch(config-ospf-1)# **router-id 1.1.1.1**

## show ospf

### Syntax

**show ospf**

### Parameter

### Default

### Mode

Privileged EXEC
Global Configuration

### Usage

Use the command "show OSPF" to query OSPF information.

### Example

Querying OSPF information

```
Switch# show ospf
OSPF Process 1, Router ID: 1.1.1.1
Supports only single TOS (TOS0) routes
This implementation conforms to RFC2328
  RFC1583Compatibility flag is disabled
  OpaqueCapability flag is disabled
  Initial SPF scheduling delay 0 millisec(s)
  Minimum hold time between consecutive SPFs 50 millisec(s)
  Maximum hold time between consecutive SPFs 5000 millisec(s)
  Hold time multiplier is currently 1
  SPF algorithm has not been run
  SPF timer is inactive
  LSA minimum interval 0 msecs
  LSA minimum arrival 0 msecs
  Write Multiplier set to 0
  Refresh timer 10 secs
  Number of external LSA 0. Checksum Sum 0x00000000
  Number of opaque AS LSA 0. Checksum Sum 0x00000000
  Number of areas attached to this router: 1
  Area ID: 0.0.0.0 (Backbone)
  Number of interfaces in this area: Total: 0, Active: 0
  Number of fully adjacent neighbors in this area: 0
  Area has no authentication
  SPF algorithm executed 0 times
  Number of LSA 0
  Number of router LSA 0. Checksum Sum 0x00000000
  Number of network LSA 0. Checksum Sum 0x00000000

  Number of ASBR summary LSA 0. Checksum Sum 0x00000000
  Number of NSSA LSA 0. Checksum Sum 0x00000000
  Number of opaque link LSA 0. Checksum Sum 0x00000000
  Number of opaque area LSA 0. Checksum Sum 0x00000000
```

## show ospf database

### Syntax

**show ospf database**

**Parameter**

**Default**

**Mode**

Privileged EXEC
Global Configuration

**Usage**

Use the command "show OSPF database" to query OSPF database summary information.

**Example**

Querying OSPF database summary information

Switch# **show ospf database**

OSPF Process 1 with Router ID :1.1.1.1
Database information:

## show ospf neighbor

**Syntax**

**show ospf neighbor**

**Parameter**

**Default**

**Mode**

Privileged EXEC

Global Configuration

**Usage**

Use the command "show OSPF neighbor" to query OSPF neighbor information.

**Example**

Querying OSPF neighbor information

Switch# **show ospf neighbor**

OSPF Process 1 with Router ID :1.1.1.1
neighbors:

Type: D - Dynamic, S - Static
Type Neighbor ID Pri State Dead Time Address Interface
RXmtL RqstL DBsmL

# 22.POE

## POE

**Syntax**

**poe**
**no poe**

**Parameter**

**Default**

All ports are enabled for poe power supply by default. ( Poe-enabled device)

**Mode**

interface configuration.

**Usage**

Use the **poe** command in interface mode to enable port poe power supply.
Use the **no poe** command in interface mode to disable port poe power supply.
You can check the port poe working status by using the **show poe** Privileged EXEC command.

**Example**

The following example shows how to config poe.
Switch(config)# **interface GigabitEthernet 1**
Switch(config-if)# **poe**
Switch# **show poe**
Get poe power:

```
  Port   |  Enable | State | type | level | actual-     | volatge(V) | current(mA)
         |         |       |      |       | power(mW) |              |
--------+---------+-------+------+-------+-----------+------------
+-------------
  gi1        enable      on     AT      4        676          52
13
  gi2        enable     off     AF      0        N/A          N/A
N/A
  gi3        enable     off     AF      0        N/A          N/A
N/A
  gi4        enable     off     AF      0        N/A          N/A
N/A
  gi5        enable     off     AF      0        N/A          N/A
N/A
  gi6        enable     off     AF      0        N/A          N/A
N/A
  gi7        enable     off     AF      0        N/A          N/A
N/A
  gi8        enable     off     AF      0        N/A          N/A
N/A

  Total used power: 676 (mW)
  Current Temperature: 65 (C)
```

## poe reboot

### Syntax

**poe reboot** *HH:MM:SS* **delay** *HH:MM:SS*
**no poe reboot**

### Parameter

| | |
|---|---|
| ***HH:MM:SS*** | Set the time for POE port restart and delay startup. The minimum granularity is to minutes |

### Default

### Mode

interface configuration.

### Usage

Use the command "Poe reboot" to set the POE port restart, turn off the POE power supply by setting the restart time, and reset the power supply by setting the delay time. Using this function, you need to synchronize the system time first.

Poe function only supports Poe managed switches of the same series, but not non Poe managed switches.

### Example

Set interface Poe watchdog

Switch(config)# **interface GigabitEthernet 1**
Switch(config-if)# **poe reboot 12:05:00 delay 00:05:00**

## poe schedule

### Syntax

**poe schedule week** *days* **hour** *hours*
**no poe schedule week** *days* **hour** *hours*

**Parameter**

| | |
|---|---|
| *days* | Port poe power supply days |
| *hours* | Port poe power supply hours |

**Default**

All ports open POE function all day by default. ( Poe-enabled device)

**Mode**

interface configuration.

**Usage**

Use the **poe schedule** command in interface mode to set port poe power supply time.
Use the **no poe schedule** command in interface mode to clear port poe power supply time..
You can check the port poe work time setting view through the web.

**Example**

The following example shows how to config poe schedule.
Switch(config)# **interface GigabitEthernet 1**
Switch(config-if)# **poe schedule week mon hour 1**

Note: The configured time has a deviation of about 0~10 minutes.

## poe watch-dog

**Syntax**

**poe watch-dog**
**no poe watch-dog**

**Parameter**

### Default

The default Poe watchdog is off.

### Mode

interface configuration.

### Usage

Use the command "Poe watch dog" to set the port Poe watchdog function.
Poe function only supports Poe managed switches of the same series, but not non Poe managed switches.

### Example

Set interface Poe watchdog

Switch(config)# **interface GigabitEthernet 1**
Switch(config-if)# **poe watch-dog**

## show poe

### Syntax

**show poe**

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

Use the command "show Poe" to query the POE function of the system.
Poe function only supports Poe managed switches of the same series, but not

non Poe managed switches.

**Example**

Querying Poe configuration

Switch# **show poe**

Get poe power:

```
  Port    |   Enable | State | type | level | actual-      | volatge(V) | current(mA)
          |          |       |      |       | power(mW) |              |
--------+---------+-------+------+-------+-----------+------------+---------
----
  gi1         enable      on     AT       4        676          52           13
  gi2         enable     off     AF       0        N/A          N/A          N/A
  gi3         enable     off     AF       0        N/A          N/A          N/A
  gi4         enable     off     AF       0        N/A          N/A          N/A
  gi5         enable     off     AF       0        N/A          N/A          N/A
  gi6         enable     off     AF       0        N/A          N/A          N/A
  gi7         enable     off     AF       0        N/A          N/A          N/A
  gi8         enable     off     AF       0        N/A          N/A          N/A

  Total used power: 676 (mW)
  Current Temperature: 65 (C)
```

# 23.Port Mirror

## mirror session source interface

**Syntax**

**mirror session** <1-4> **source interfaces** *IF_PORTS* (**both** | **rx** | **tx**)
**no mirror session** <1-4> **source interfaces** *IF_PORTS* (**both** | **rx** | **tx**)
**no mirror session** (<1-4> | **all**)

**Parameter**

| | |
|---|---|
| *<1-4>* | Specify the mirror session to configure |
| *IF_PORTS* | Specify the source interface, Valid interfaces include physical ports and port channels. |

| | |
|---|---|
| **both** | Mirror tx and rx direction |
| **rx** | Mirror rx direction only |
| **tx** | Mirror tx direction only |

### Default

No monitor sessions are configured.

### Mode

Global Configuration

### Usage

Use the "**mirror session source interface"** command to start a port mirror session.
Use the **no** form of this command to stop a port mirroring session.
Use the "**no mirror session**" command to disable all mirror sessions or specific mirror session.

### Example

The following example shows how to create a local SPAN session 1 to monitor both sent and received traffic on source port fa1.

Switch(config)# **mirror session 1 source interface fa2-5 both**
Switch(config)# **mirror session 1 destination interface fa1**
Switch(config)# **show mirror session 1**
Session 1 Configuration
Source RX Port : fa2-5
Source TX Port : fa2-5
Destination port : fa1
Ingress State: disabled

## mirror session destination interface

### Syntax

**mirror session** <1-4> **destination interface** *IF_NMLPORT* [**allow-ingress**]

**no mirror session** <1-4> **destination interface** *IF_NMLPORT*
**no mirror session** (<1-4> | **all**)

**Parameter**

| | |
|---|---|
| *<1-4>* | Specify the mirror session to configure |
| *IF_NMLPORT* | Specify the SPAN destination. A destination must be a physical port |
| **allow-ingress** | Enable ingress traffic forwarding. |

**Default**

No monitor sessions are configured.

**Mode**

Global Configuration

**Usage**

Use the "**mirror session destination interface"** command to start a destination interface of a port mirror session.
Use the **no** form of this command to stop a destination interface of a port mirroring session.
Use the "**no mirror session**" command to disable all mirror sessions or specific mirror session.

**Example**

The following example shows how to create a local session 1 to monitor both sent and received traffic on source port fa1.

Switch(config)# **mirror session 1 destination interface fa1**
Switch# show mirror session 1
Session 1 Configuration
Source RX Port : fa2-5
Source TX Port : fa2-5
Destination port : fa1
Ingress State: disabled

## show mirror

### Syntax

**show mirror** [**session** *<1-4>*]

### Parameter

| | |
|---|---|
| *<1-4>* | Specify the mirror session to display |

### Default

### Mode

Privileged EXEC

### Usage

Use the **show mirror** command to display mirror session configuration

### Example

This following example shows how to display mirror session configuration
Switch#**show mirror session 1**
Session 1 Configuration Source
RX Port : gi2-5
Source TX Port : gi2-5
Destination port : gi1
Ingress State: disabled

# 24.Port

## description

### Syntax

**description** *WORD<1-32>*

**no description**

**Parameter**

| | |
|---|---|
| *WORD<1-32>* | Specifiy port description string. |

**Default**

Default port description is empty.

**Mode**

Interface Configuration

**Usage**

Use "**description**" command to give the port a name to identify it easily.
If description includes space character, please use double quoted to wrap it. Use **no** form to restore description to empty string.

**Example**

This example shows how to modify port descriptions.

```
Switch(config)# interface gi1
Switch(config-if)# description "uplink port"
```

This example shows how to show current port description on interface fa1

```
Switch# show interfaces gi1 status
Port    Name            Status        Vlan   Duplex   Speed      Type
gi1     uplink port       connected     1    a-full   a-10M      Copper
```

## speed

**Syntax**

**speed** (**10** | **100** | **1000**)
**speed auto** [(**10** | **100** | **1000** | **10/100**)]
**speed nonegtiate**
**no speed nonegtiate**

## Parameter

| | |
|---|---|
| **10** | Specify port speed to force 10Mbits/s or auto with 10Mbits/s ability. |
| **100** | Specify port speed to force 100Mbits/s or auto with 100Mbits/s ability. |
| **1000** | Specify port speed to force 1000Mbits/s or auto with 1000Mbits/s ability. |
| **10/100** | Specify port speed to auto with 10Mbits/s and 100Mbits/s |

## Default

Default port speed is auto with all available abilities.

## Mode

Interface Configuration

## Usage

Use "**speed**" command to change port speed configuration. The speed is only able to configure to the physical maximum speed. For example, in fast Ethernet port, speed 1000 is not available.

You cannot configure the speed on the SFP module ports, but you can configure the speed to not negotiate (nonegotiate) if it is connected to a device that does not support autonegotiation.

## Example

This example shows how to modify port speed configuration.

```
Switch(config)# interface fa1
Switch(config-if)# speed 100
Switch(config-if)# exit
Switch(config)# interface fa2
Switch(config-if)# speed auto 10/100
```

This example shows how to show current speed configuration

```
Switch# show running-config interfaces fa1-2
interface fa1
speed 100
interface fa2
speed auto 10/100
```

This example shows how to show current interface link speed

```
Switch# show interfaces fa1-2 status
Port Name        Status    Vlan Duplex Speed          Type

gi1              notconnect  1      auto     100M       Copper
gi2              notconnect  1      auto     auto       Copper
```

## duplex

### Syntax

**duplex** (**auto** | **full** | **half**)

### Parameter

| | |
|---|---|
| **auto** | Specify port duplex to auto negotiation. |
| **full** | Specify port duplex to force full duplex. |
| **half** | Specify port duplex to force half duplex. |

### Default

Default port duplex is auto.

### Mode

Interface Configuration

### Usage

Use "**duplex**" command to change port duplex configuration.

### Example

This example shows how to modify port duplex configuration.

```
Switch(config)# interface fa1
Switch(config-if)# duplex full
Switch(config-if)# exit
Switch(config)# interface fa2
Switch(config-if)# duplex half
```

This example shows how to show current speed configuration

```
Switch# show running-config interfaces fa1-2
interface fa1
duplex full
interface fa2
duplex half
```

This example shows how to show current interface link speed

```
Switch# show interfaces fa1-2 status
Port Name       Status    Vlan Duplex Speed          Type
fa1             connected 1    full   a-100M Copper
fa2             connected 1    half   a-100M Copper
```

## shutdown

### Syntax

**shutdown**
**no shutdown**

### Parameter

### Default

Default port admin state is no shutdown.

### Mode

Interface Configuration

### Usage

Use "**shutdown**" command to disable port and use "**no shutdown**" to enable port. If port is error disabled by some reason, use "no shutdown" command can also recovery the port manually.

### Example

This example shows how to modify port duplex configuration.
Switch(config)# **interface fa1**
Switch(config-if)# **shutdown**

This example shows how to show current admin state configuration
Switch# **show running-config interfaces fa1**
interface fa1
shutdown

This example shows how to show current link status

| Port | Name | Status | Vlan | Duplex | Speed | Type |
|---|---|---|---|---|---|---|
| fa1 | | **disable** | 1 | full | auto | Copper |

## flowcontrol

### Syntax

**flowcontrol** (**auto** | **off** | **on**)
**no flowcontrol**

### Parameter

| | |
|---|---|
| **auto** | Automatically enables or disables flow control on the interface. |
| **off** | Disable port flow control. |
| **on** | Enable port flow control. |

### Default

Default port flow control is off.

### Mode

Interface Configuration

### Usage

Use “**flowcontrol**” command to change port flow control configuration.
Use **no** form to restore flow control to default (off) configuration.

### Example

This example shows how to modify port duplex configuration.
Switch(config)# **interface fa1**
Switch(config-if)# **flowcontrol on**

This example shows how to show current flow control configuration
Switch# **show interfaces fa1**
Hardware is Fast Ethernet
Full-duplex, Auto-speed, media type is Copper
**flow-control is on**
0 packets input, 0 bytes, 0 throttles Received 0 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 multicast, 0 pause input
0 input packets with dribble condition detected
379 packets output, 31981 bytes, 0 underrun
0 output errors, 0 collisions, 0 interface resets
0 babbles, 0 late collision, 0 deferred
0 PAUSE output

## jumbo-frame

### Syntax

**jumbo-frame** *<1518-9216>*

### Parameter

| | |
|---|---|
| *<1518-9216>* | Specify the maximum frame size. |

### Default

Default maximum frame size is 1522.

### Mode

Global Configuration

**Usage**

Use "**jumbo-frame**" command to modify maximum frame size.
The only way to show this configuration is using "**show running-config**" command.

**Example**

This example shows how to modify maximum frame size on fa1 to 9216 bytes.
Switch(config)# **jumbo-frame 9216**

This example shows how to show current jumbo-frmae size
Switch# **show running-config**
jumbo-frame 9216

## protected

**Syntax**

**protected**
**no protected**

**Parameter**

**Default**

Default protected state is no protected.

**Mode**

Interface Configuration

**Usage**

Use "**protected**" command to make port to be protected. Protected port is only allowed to communicate with unprotected port. In other words, protected port is not allowed to communicate

with another protected port.
Use **no** form to make port unprotected.

**Example**

This example shows how to configure port fa1 and fa2 to be protected port.

```
Switch(config)# interface range fa1-2
Switch(config-if-range)# protected
```

This example shows how to show current protected port state.

```
Switch# show interfaces fa1-2 protected
Port                | Protected State
-------+-----------------
fa1 |enabled

fa2 |enabled
```

## eee

**Syntax**

**eee**
**no eee**

**Parameter**

**Default**

Default eee state is disabled.

**Mode**

Interface Configuration

**Usage**

Use "**eee**" command to make port to enable the energy efficient Ethernet feature.
Use **no** form of this command to disable eee.
The only way to show this configuration is using "**show running-config**" command.

### Example

This example shows how to configure port fa1 and fa2 to be protected port.
Switch(config)# **interface fa1**
Switch(config-if)# **eee**

This example shows how to show current jumbo-frmae size
Switch# **show running-config interface fa1**
interface fa1
eee

## clear interface

### Syntax

**clear interfaces** *IF_PORTS* **counters**

### Parameter

| | |
|---|---|
| *IF_PORTS* | Specify port to clear counters. |

### Default

No default value for this command.

### Mode

Privileged EXEC

### Usage

Use "**clear interface**" command to clear statistic counters on specific ports.

### Example

This example shows how to clear counters on port fa1.
Switch(config)# **clear interfaces fa1 counters**

This example shows how to show current counters

Switch# **show interfaces fa1**
Hardware is Fast Ethernet
Auto-duplex, Auto-speed, media type is Copper
flow-control is off
0 packets input, 0 bytes, 0 throttles Received 0 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 multicast, 0 pause input
0 input packets with dribble condition detected
0 packets output, 0 bytes, 0 underrun
0 output errors, 0 collisions, 0 interface resets
0 babbles, 0 late collision, 0 deferred
0 PAUSE output

## show interface

### Syntax

**show interfaces** *IF_PORTS*
**show interfaces** *IF_PORTS* **status**
**show interfaces** *IF_PORTS* **potected**

### Parameter

| | |
|---|---|
| *IF_PORTS* | Specifiy port to show. |

### Default

No default value for this command.

### Mode

Privileged EXEC

### Usage

Use "**show interface**" command to show detail port counters, parameters and status.
Use "**show interface status**" command to show brief port status.
Use "**show interface protected**" command to show protected status.

### Example

This example shows how to show current counters

Switch# **show interfaces fa1**

Hardware is Fast Ethernet
Auto-duplex, Auto-speed, media type is Copper flow-control is off
0 packets input, 0 bytes, 0 throttles Received 0 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 multicast, 0 pause input
0 input packets with dribble condition detected
0 packets output, 0 bytes, 0 underrun
0 output errors, 0 collisions, 0 interface resets
0 babbles, 0 late collision, 0 deferred
0 PAUSE output

This example shows how to show current protected port state.

Switch# **show interfaces fa1-2 protected**

```
Port          | Protected State
--------------+----------------
fa1 |enabled
fa2 |enabled
```

This example shows how to show current port status

Switch# **show interfaces fa1 status**

| Port Name | Status | Vlan | Duplex | Speed | Type |
|---|---|---|---|---|---|
| fa1 | connected | 1 | full | a-100M | Copper |

# 25.Port Error Disable

## errdisable recovery cause

### Syntax

**errdisable recovery cause** (**all**|**acl**|**arp-inspection**|**bpduguard**|**broadcast-flood**|**dhcp-rate limit**|**psecure-violation**|**selfloop**|**unicast-flood**|**unknown-multicastflood**)
**no errdisable recovery cause** (**all**|**acl**|**arp-inspection**|**bpduguard**|**broadcast-flood**|**dhcp-rate-limit**|**psecure-violation**|**selfloop**|**unicast-flood**|**unknown-multicastflood**)

### Parameter

| | |
|---|---|
| **all** | Enable the auto recovery for port error disabled from all causes. |
| **acl** | Enable the auto recovery for port error disabled from the ACL cause. |
| **arp-inspection** | Enable the auto recovery for port error disabled from the ARP inspection cause. |
| **bpduguard** | Enable the auto recovery for port error disabled from the STP BPDU Guard cause. |
| **broadcast-flood** | Enable the auto recovery for port error disabled from the broadcast flooging cause. |
| **dhcp-rate-limit** | Enable the auto recovery for port error disabled from the DHCP rate limit cause. |
| **psecure-violation** | Enable the auto recovery for port error disabled from the port security cause. |
| **selfloop** | Enable the auto recovery for port error disabled from the STP self-loop cause. |
| **unicast-flood** | Enable the auto recovery for port error disabled from the unicast flooding cause. |
| **unknown-multicastflood** | Enable the auto recovery for port error disabled from the unknown multicast flooding cause. |

**Default**

Error disable recovery is disabled for all cause.

**Mode**

Global Configuration

**Usage**

Ports would be disabled because of the invalid actions detected by protocols. To enable the port error disable recovery from the specific cause, use the command **errdisable recovery cause** in the Global Configuration mode.

**Example**

The following example enables the port error disable recovery for the STP

BPDU Guard and self-loog cause.

Switch(config)# errdisable recovery cause bpduguard
Switch(config)# errdisable recovery cause selfloop

## errdisable recovery cause udld

### Syntax

**errdisable recovery cause udld**
**no errdisable recovery cause udld**

### Parameter

### Default

Default is disabled

### Mode

Global Configuration

### Usage

Use the command "errdisable recovery cause UDLD" to enable automatic recovery of one-way link detection (UDLD).

### Example

Configuring the errdisable function of UDLD

switch(config)# **errdisable recovery cause udld**
switch# **show errdisable recovery**
ErrDisable Reason Timer Status
----------+---------------
bpduguard | disabled
udld | enabled
...

## errdisable recovery interval

### Syntax

**errdisable recovery interval** *seconds*

### Parameter

| | |
|---|---|
| *seconds* | The time in seconds to recover from a specific error- disable state. The vaild range is 0 to 86400 seconds,and the default value is 300 seconds. |

### Default

The default recovery time is 300 seconds.

### Mode

Global Configuration

### Usage

To set the recovery time of the error disabled ports, use the command **errdisable recovert interval** in the Global Configuration mode.

### Example

The following example set the agimg time to 500 seconds.
Switch(config)# errdisable recovery interval 60

## show errdisable recovery

### Syntax

**show errdisable recovery**

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

To show the error disable configuration and the interfaces in the error disabled state, use the command **show errdisable recovery** in the Privileged EXEC mode.

### Example

The following example shows the error disable configuration, and the interfaces in the error disabled state.

```
Switch# show errdisable recovery
ErrDisable Reason                          | Timer Status
---------------------------+---------------
bpduguard | enabled
selfloop | enabled
broadcast-flood | disabled
unknown-multicast-flood | disabled
unicast-flood | disabled
acl | disabled
psecure-violation | disabled
dhcp-rate-limit | disabled
arp-inspection | disabled

Timer Interval : 60 seconds
Interfaces that will be enabled at the next timeout:

Port |Error Disable Reason           | Time Left
-----+---------------------------+------------
```

# 26 .Port Security

## port-security (Global)

### Syntax

**port-security**

**no port-security**

**Parameter**

**Default**

Default is disabled

**Mode**

Global Configuration

**Usage**

The "**port-security**" command enables the port security functionality globally.
Use the **no** form of this command to disable.
You can verify settings by the **show port-security** command.

**Example**

The following example shows how to enable port security
switch(config)# **port-security**
switch# **show port-security**
port-security is: Enabled

## port-security (Interface)

**Syntax**

**port-security**
**no port-security**

**Parameter**

**Default**

Default is disabled

**Mode**

Port Configuration

**Usage**

The "**port-security**" command enables the port security functionality on this port.
Use the **no** form of this command to disable
You can verify settings by the **show port-security interface** command.

**Example**

The following example shows how to enable port security on interface fa1

```
switch(config)# interface fa1
switch(config-if)# port-security
switch(config)# show port-security interfaces gi1
Port   |   Security         | CurrentAddr |  Action
--------+-------------------+---------------+----------------------
gi1    |   Enabled (     1)   |   0        |         Discard
```

## port-security address-limit

**Syntax**

**port-security address-limit** <1-256>
**port-security violation (protect | restrict |shutdown)**
**no port-security address-limit**
**no port-security violation**

**Parameter**

| | |
|---|---|
| *<1-256>* | The learning-limit number. It specifies how many MAC addresses this port can learn. |
| **protect** | Discard new MAC data frame when MAC learning exceeds the limit. |
| **restrict** | When MAC learning exceeds the limit, new MAC data frames are forwarded and counted. |
| **shutdown** | Shutdown this port when receives a |

| | |
|---|---|
| | packet whose SMAC is new to system and exceed the learning limit number. |

**Default**

The address-limit default is 1 and action is "drop".

**Mode**

Port Configuration

**Usage**

Use the "**port-security address-limit**" command to set the learning-limit number and the violation action.
Use the **no** form of this command to restore the default settings.
You can verify settings by the **show port-security interface** command.

**Example**

The following example shows how to enable port security on port 1 and set the learning limit number to 10.
switch(config)# **interface gi1**
switch(config-if)# **port-security address-limit 10 action discard**
switch(config-if)# **port-security**
switch(config)# **show port-security interfaces gi1**

```
Port   Status        MaxAddr   TotalAddr    ConfigAddr   Violation      Action
-----  ------------  --------  -----------  -----------  -------------  ---------
gi1    Up             10         0            0            0             Protect
```

## show port-security

**Syntax**

**show port-security**

**Parameter**

### Default

No default value for this command.

### Mode

Privileged EXEC

### Usage

Use "**show port-security**" command to show port-security global information.

### Example

This example shows how to show port-security configurations.
Switch# **show port-security**
port-security is: Enabled

## show port-security interface

### Syntax

**show port-security interface** *IF_PORTS*

### Parameter

| | |
|---|---|
| *IF_PORTS* | Select port to show port-security configurations. |

### Default

No default value for this command.

### Mode

Privileged EXEC

### Usage

Use "**show port-security interfaces**" command to show port-security information of the specified port.

**Example**

This example shows how to show port-security configurations on interface gi1.

```
Switch# show port-security interfaces gi1
Port   Status          MaxAddr   TotalAddr   ConfigAddr   Violation      Action
-----  ------------ --------  ----------- -----------  ------------ ----------
gi1    Up              10          0             0              0              Protect
```

# 27. Protocol VLAN

## vlan protocol-vlan group (Global)

**Syntax**

**vlan protocol-vlan group** <1-8> **frame-type**(ethernet_ii|llc_other|snap_1042) **protocol-value** VALUE
**no vlan protocol-vlan group** <1-8>

**Parameter**

| | |
|---|---|
| <1-8> | Specify protocol vlan group to configure |
| (ethernet_ii\|llc_other\|snap_1042) | Specify protocol based frame type |
| VALUE | Specify protocol value to configure |

**Default**

no protocol vlan group are configured

**Mode**

Global Configuration

**Usage**

Use the **vlan protocol-vlan group** Global Configuration mode command to add protocol vlan group with spefied proto type and value.
Use the **no** form of this command to remove protocol vlan group setting.
You can verify your setting by entering the **show vlan proto-vlan Privileged EXEC** command

**Example**

The following example show how to configure protocol vlan group:
Switch(config)# **vlan protocol-vlan group 1 frame-type ethernet_ii protocol-value 0x806**
Switch(config)# **vlan protocol-vlan group 2 frame-type llc_other protocol-value 0x800**
Switch# **show vlan protocol-vlan**

```
Group ID    |  Status    | Type    |    value
--------------+------------------+--------------------+----------
--------
1           | Enabled    |  Ethernet    | 0x0806
2           | Enabled    |  LLC other   |   0x0800
3           | Disabled   |    --   |     --
4| Disabled             |    --   |     --
4           | Disabled   |    --   |     --
5           | Disabled   |    --   |     --
6           | Disabled   |    --   |     --
7           | Disabled   |    --   |     --
```

## vlan protocol-vlan group (Interface)

**Syntax**

**vlan protocol-vlan group** <1-8> **vlan** <1-4094>
**no vlan protocol-vlan group** <1-8>

**Parameter**

| | |
|---|---|
| <1-8> | Specify protocol vlan group to binding |

| | |
|---|---|
| <1-4094> | Specifies the Proto VLAN ID to configure. |

**Default**

In default all group are not binding to any interface.

**Mode**

Interface configuration

**Usage**

Use the **vlan protocol-vlan binding** Interface Configuration mode command to binding protocol VLAN Group on specified interfaces,
Use the **no** form of this command to cancel protocol VLAN Group Binding. You can verify your setting by entering the **show vlan protocol-vlan interfaces IF_PORTS Privileged EXEC** command

**Example**

The following example how to configure Protocol VLAN function on specified interfaces..
Switch(config)# **interface gi1**
Switch(config-if)# **vlan protocol-vlan group 1 vlan 2**

## show vlan protocol-vlan

**Syntax**

**show vlan protocol-vlan [group** <1-8>**]**

**Parameter**

| | |
|---|---|
| <1-8> | Specify protocol vlan group to display |

**Default**

### Mode

Privileged EXEC

### Usage

Use the **show vlan proto-vlan** command in EXEC mode to display Proto VLAN group configuration

### Example

The following example how to display Proto VLAN group configuration

```
Switch# show vlan protocol-vlan
Group ID    |   Status  |    Type    |    value
--------------+--------------------+----------------------+------
-----------
1           | Enabled   |  Ethernet  |    0x0806
2           | Enabled   |   LLC other |    0x0800
3           | Disabled  |    --      |     --
4           | Disabled  |    --      |     --
5           | Disabled  |    --      |     --
6           | Disabled  |    --      |     --
7           | Disabled  |    --      |     --
8           | Disabled  |    --      |     --
```

## show vlan protocol-vlan interfaces

### Syntax

**show vlan protocol-vlan interfaces** IF_PORTS

### Parameter

| | |
|---|---|
| IF_PORTS | Specify interfaces protocol vlan to display |

### Default

### Mode

Privileged EXEC

**Usage**

Use the **show vlan protocol-vlan interface** command in EXEC mode to display the Protocol VLAN interfaces setting

**Example**

The following example shows how to display the Protocol VLAN interfaces setting

```
Switch# show vlan protocol-vlan interfaces fa1
Port fa1 :
Group 1
Status        : Enabled
VLAN ID       : 2
Group 2
Status        : Enabled
VLAN ID       : 3
Group 3
Status        : Disabled
Group 4
Status        : Disabled
Group 5
Status        : Disabled
Group 6
Status        : Disabled
Group 7
Status        : Disabled
Group 8
Status : Disabled
```

# 28. QOS

## qos

**Syntax**

**qos**
**no qos**

**Parameter**

**Default**

Default qos is disabled.

**Mode**

Global Configuration

**Usage**

Use "**qos**" command to enable quality of service which according to basic trust type to assign queue for packets, and packets with higher priority are able to send first.
Use no form of this command to disable quality of service.

**Example**

This example shows how to change qos to basic mode.
Switch(config)# **qos basic**

This example shows how to check current qos mode.
Switch# **show qos**
QoS Mode: basic
Basic trust: cos

## qos cos

**Syntax**

**qos cos** *<0-7>*

**Parameter**

| | |
|---|---|
| **cos** <0-7> | Specify the CoS value for the interface. |

### Default

Default CoS value for interface is 0.

### Mode

Interface Configuration

### Usage

Sometimes, there is no qos information in the packets, such as CoS, DSCP, IP Precedence. But we still can give the priority for packets by configuring the interface default cos value. If there is no qos information in the packets, the device will use this default cos value and find the cos-queue map to get the final destination queue.

Use "**qos cos**" command to assign port default cos value.

### Example

This example shows how to configure default cos value 7 on interface gi1.

```
Switch(config)# interface GigabitEthernet 1
Switch(config-if)# qos cos 7
Switch(config-if)# end
Switch# show qos interface GigabitEthernet 1
Port | CoS         | Trust State | Remark Cos | Remark DSCP | Remark IP Prec
--------+-------+---------------+------------+-------------+---------
gi1 |     7         |          enabled |          disabled |          disabled | disabled |
```

## qos map

### Syntax

**qos map** (**cos-queue** | **dscp-queue** | **precedence-queue**) *SEQUENCE* **to** *<1-8>*
**qos map** (**queue-cos** | **queue-precedence**) *SEQUENCE* **to** *<0-7>*
**qos map queue-dscp** *SEQUENCE* **to** *<0-63>*

### Parameter

| | |
|---|---|
| **cos-queue** | Configure or show CoS to queue map |
| **dscp-queue** | Configure or show DSCP to queue map |
| **precedence-queue** | Configure or show IP Precedence to queue map. |
| **queue-cos** | Configure or show queue to CoS map |
| **queue-dscp** | Configure or show queue to DSCP map |
| **queue-precedence** | Configure or show queue to IP Precedence map |
| SEQUENCE | Specify the cos, dscp, precedence or queue with one or multiple values. |
| <1-8> | Specify th queue id |
| <0-7> | Specify the cos or precedence values |
| <0-63> | Specify the dscp values |

**Default**

The default values of cos-queue are showing in the following table.

| CoS | Queue ID |
|---|---|
| 0 | 1 |
| 1 | 2 |
| 2 | 3 |
| 3 | 4 |
| 4 | 5 |
| 5 | 6 |
| 6 | 7 |
| 7 | 8 |

The default values of dscp-queue are showing in the following table.

| DSCP | Queue ID |
|---|---|
| 0~7 | 1 |
| 8~15 | 2 |
| 16~23 | 3 |
| 24~31 | 4 |
| 32~39 | 5 |
| 40~47 | 6 |
| 48~55 | 7 |
| 56~63 | 8 |

The default values of ip precedence are showing in the following table.

| IP Precedence | Queue ID |
|---|---|
| 0 | 1 |
| 1 | 2 |

| | |
|---|---|
| 2 | 3 |
| 3 | 4 |
| 4 | 5 |
| 5 | 6 |
| 6 | 7 |
| 7 | 8 |

The default values of queue-cos are showing in the following table.

| Queue ID | CoS |
|---|---|
| 1 | 0 |
| 2 | 1 |
| 3 | 2 |
| 4 | 3 |
| 5 | 4 |
| 6 | 5 |
| 7 | 6 |
| 8 | 7 |

The default values of queue-dscp are showing in the following table.

| Queue ID | DSCP |
|---|---|
| 1 | 0 |
| 2 | 8 |
| 3 | 16 |
| 4 | 24 |
| 5 | 32 |
| 6 | 40 |
| 7 | 48 |
| 8 | 56 |

The default values of queue-precedence are showing in the following table.

| Queue ID | IP Precedence |
|---|---|
| 1 | 0 |
| 2 | 1 |
| 3 | 2 |
| 4 | 3 |
| 5 | 4 |
| 6 | 5 |
| 7 | 6 |
| 8 | 7 |

**Mode**

Global Configuration

**Usage**

According to different trust type, packets will be assigned to different queue based on the specific qos map. For example, if the trust type is trust cos, the device will get the cos value in packet and reference the cos-queue mapping to assign the correct queue.

The queue to cos, dscp or precedence maps are used by remarking function. If the port remarking feature is enabled, the remarking function will reference these 3 tables to remark packets.

### Example

This example shows how to map cos 6 and 7 to queue 1.

```
Switch(config)# qos map cos-queue 6 7 to 1
Switch# show qos map cos-queue
CoS to Queue mappings
COS                0   1   2   3   4   5   6   7
---------------------------------
Queue     2   1   3   4   5   6     1   1
```

This example shows how to map queue 4 and 5 to cos 7. Switch(config)# **qos map queue-cos 4 5 to 7**

```
Switch# show qos map queue-cos
  Queue to CoS mappings

Queue 1   2   3   4   5   6   7   8
------------------------------
CoS      1   0   2   7   7   5   6   7
```

## qos queue

### Syntax

**qos queue strict-priority-num** *<0-8>*
**qos queue weight** *SEQUENCE*

### Parameter

| | |
|---|---|
| **strict-priority- num** <0-8> | Specify the strict priority queue number |
| **Weight** SEQUENCE | Specify the non-strict priority queue weight value. The valid queue weight value is from 1 to 127. |

## Default

Default strict priority queue number is 8, it means all queues are strict priority queue.

The default queue weight for each queue is shown in following table.

| Queue ID | Queue Weight |
|---|---|
| 1 | 1 |
| 2 | 2 |
| 3 | 3 |
| 4 | 4 |
| 5 | 5 |
| 6 | 9 |
| 7 | 13 |
| 8 | 15 |

## Mode

Global Configuration

## Usage

The device support total 8 queues for QoS queueing. It is able to set the queue to be strict priority queue or weighted queue to prevent starvation. The queue with higher id value has higher priority.
First, you need to decide how many strict priority queue you need. The strict priority queue will always occupy the higher priority queue. For example, if you specify the strict priority number to be 2, then the queue 7 and 8 will be the strict priority queues and the others are weighted queues.
After you setup the number of strict priority queue, you need to setup the weight for the weighted queues by using "qos queue weight" command. And the bandwidth will shared by the weight you configured between these weighted queues.

## Example

This example shows how to setup device with 3 strict priority queues and give other weighted queues with weight 5, 10, 15, 20, 25.

```
Switch(config)# qos queue strict-priority-num 3
Switch(config)# qos queue weight 5 10 15 20 25
```

```
Switch# show qos queueing
qid-weights             Ef - Priority
1    -      5           dis- N/A
2    -     10           dis- N/A
3    -     15           dis- N/A
4    -     20           dis- N/A
5    -     25           dis- N/A
6    - N/A              ena- 6
7    - N/A              ena- 7
8    - N/A              ena- 8
```

## qos remark

### Syntax

**qos remark (cos | dscp | precedence)**
**no qos remark (cos | dscp | precedence)**

### Parameter

| | |
|---|---|
| **cos** | Enable/Disable cos remarking. |
| **dscp** | Enable/Disable dscp remarking. |
| **precedence** | Enable/Disable precedence remarking. |

### Default

Default CoS remarking is
disabled.
Default DSCP remarking is
disabled.
Default IP Precedence remarking is disabled.

### Mode

Interface Configuration

### Usage

QoS remarking feature allow you to change priority information in packets based on egress queue. For example, you want all packets egress from interface fa1 queue 1 to remark the cos

value to be 5 for next tier of device, you can enable the cos remarking feature on fa1 and configure the queue-cos map for queue 1 map to cos 5.

Use "**qos remark**" command to enable remarking feature on specific type. And use "**no qow remark**" command to disable it.

**Example**

This example shows how to enable remarking features on interface fa1.

```
Switch(config)# interface GigabitEthernet 1
Switch(config-if)# qos remark cos
Switch(config-if)# qos remark dscp
Switch(config-if)# qos remark precedence
Switch(config-if)# end
Switch# show qos interface GigabitEthernet 1
Port | CoS              | Trust State | Remark Cos | Remark DSCP | Remark IP Prec
--------+-------+---------------+------------+-------------+-------
gi1 |                    0      |         enabled |         enabled |         enabled | enabled |
```

## qos trust

**Syntax**

**qos trust** (**cos** | **cos-dscp** | **dscp** | **precedence**)

**Parameter**

| | |
|---|---|
| **cos** | Specify the device to trust CoS |
| **cos-dscp** | Specify the device to trust DSCP for IP packets, and trust CoS for non-IP packets. |
| **dscp** | Specify the device to trust DSCP |
| **precedence** | Specify the device to trust IP Precedence |

**Default**

Default QoS trust type is cos.

**Mode**

Global Configuration

**Usage**

In QoS basic mode, there are 4 trust types for device to judge the appropriate queue of the packets. This command is able to switch between these trust types.

**CoS:**

IEEE 802.1p defined 3bits priority value in vlan tag. Trust this value in packets and assign queue according to cos-queue map.

**DSCP:**

IETF RFC2474 defined 6bits priority value in IP packet (highest 6bits in ToS field). Trust this value in packets and assign queue according to dscp-queue map.

**IP Precedence:**

The highest 3bits priority value in IP packet ToS field. Trust this value in packets and assign queue according to precedence-queue map.

**CoS-DSCP:**

Trust DSCP for IP packets and assign queue according to dscp-queue map. Trust CoS for non-IP packets and assign queue according to cos-queue map.

**Example**

This example shows how to change qos basic mode trust types.

Switch(config)# **qos trust cos**
Switch(config)# **qos trust cos-dscp**
Switch(config)# **qos trust dscp**
Switch(config)# **qos trust precedence**

This example shows how to check current qos trust type.

Switch# **show qos**
QoS Mode: basic
Basic trust: ip-precedence

## qos trust (Interface)

**Syntax**

**qos trust**
**no qos trust**

**Parameter**

**Default**

Default interface qos trust state is enabled.

**Mode**

Interface Configuration

**Usage**

After QoS function is enabled in basic mode, the device also support per interface enable/disable the qos function. If the trust state on interface is enabled, all ingress packets of this interface will remap according to the trust type and the qos maps. Otherwise, all ingress packets will assign to queue 1.

Use "**qos trust**" to enable trust state on interface and use "**no qos trust**" to disable trust state on interface.

**Example**

This example shows how to disable qos trust state on interface gi1.

```
Switch(config)# interface GigabitEthernet 1
Switch(config-if)# no qos trust
Switch(config-if)# end
Switch# show qos interface GigabitEthernet 1
Port | CoS              | Trust State | Remark Cos | Remark DSCP | Remark IP Prec
--------+-------+---------------+------------+-------------+----------
gi1 |                0          |         disabled |         disabled |         disabled | disabled |
```

## show qos

**Syntax**

**show qos**

**Parameter**

### Default

No default value for this command.

### Mode

Privileged EXEC

### Usage

Use "**show qos**" command to show qos state and trust type.

### Example

This example shows how to check current qos mode.
Switch# **show qos**
QoS Mode: basic
Basic trust: cos

## show qos interface

### Syntax

**show qos interface** *IF_PORTS*

### Parameter

| | |
|---|---|
| *IF_PORTS* | Select port to show qos configurations. |

### Default

No default value for this command.

### Mode

Privileged EXEC

### Usage

Use "**show qos interfaces**" command to show port default cos ,remarking state and remarking type state informations.

**Example**

This example shows how to show qos configurations on interface fa1.

```
Switch# show qos interface GigabitEthernet 1
Port | CoS              | Trust State | Remark Cos | Remark DSCP | Remark IP Prec
--------+-------+---------------+------------+-------------+-------
gi1 |                7  |         enabled |         disabled |         disabled | disabled |
```

## show qos map

**Syntax**

**show qos map** [(**cos-queue** | **dscp-queue** | **precedence-queue** | **queue-cos** |**queue-dscp** | **queue-precedence**)]

**Parameter**

| | |
|---|---|
| **cos-queue** | Show CoS to queue map. |
| **dscp-queue** | Show DSCP to queue map. |
| **precedence-queue** | Show IP Precedence to queue map. |
| **queue-cos** | Show queue to CoS map. |
| **queue-dscp** | Show queue to DSCP map. |
| **queue-precedence** | Show queue to IP Precedence map. |

**Default**

No default value for this command.

**Mode**

Privileged EXEC

**Usage**

Use "**show qos map**" command to show all kinds of mapping for qos remapping and remarking features.

**Example**

This example shows how to show all qos maps.

```
Switch# show qos map queue-cos
 Queue to CoS mappings
 Queue1      2      3      4      5      6      7      8
 ------------------------------------------------------------
 CoS         1      0      2      7      7      5      6      7
```

## show qos queueing

**Syntax**

**show qos queueing**

**Parameter**

**Default**

No default value for this command.

**Mode**

Privileged EXEC

**Usage**

Use "**show qos queueing**" command to show qos queueing information.

**Example**

This example shows how to check current qos queueing information.

```
Switch# show qos queueing
qid-weights          Ef - Priority
1    -      3        dis- N/A
2    -      5        dis- N/A
3    - N/A           ena- 3
4    - N/A           ena- 4
5    - N/A           ena- 5
6    - N/A           ena- 6
```

7 - N/A ena- 7
8 - N/A ena- 8

# 29.Rate Limit

## rate limit egress

### Syntax

**rate-limit egress** <16-1000000>
**no rate-limit egress**

### Parameter

| | |
|---|---|
| *<16-1000000>* | Specify the committed information rate. |

### Default

Default rate limit is disabled.

### Mode

Interface configuration

### Usage

Use the "**rate-limit egress**" command to configure the egress port shaper.
Use the **no** form of this command to disable the shaper.
You can verify your setting by entering the **show running-config interfaces** command.

### Example

The following example show how to configure ingress port rate limit and egress port shaper.
Switch(config)# **interfaces gi1**

Switch(config-if)# **rate-limit egress 2048**
Switch# **show running-config interfaces gi1**
interface gi1
rate-limit egress 2048

## rate-limit ingress

### Syntax

**rate-limit ingress <16-1000000>**
**no rate-limit ingress**

### Parameter

| | |
|---|---|
| *<16-1000000>* | Specify the ingress limit rate |
| <1-8> | Specify the egress shaper queue number |

### Default

Rate limiting is disabled.

### Mode

Interface configuration

### Usage

Use the "**rate-limit ingress**" command to limit the incoming traffic rate on a port.
Use the **no** form of this command to disable the rate limit.
You can verify your setting by entering the **show running-config interfaces** command

### Example

The following example show how to configure ingress port rate limit.

Switch(config)# **interfaces gi1**
Switch(config-if)# **rate-limit ingress 128**

Switch# **show running-config interfaces gi1**
**interface gi1**
**rate-limit ingress 128**

## rate limit egress queue

### Syntax

**rate-limit egress queue** <1-8> <16-1000000>
**no rate-limit egress queue** <1-8>

### Parameter

| | |
|---|---|
| <1-8> | Specify the egress shaper queue number |
| *<16-1000000>* | Specify the queue rate. |

### Default

Default queue rate limit is disabled.

### Mode

Interface configuration

### Usage

Use the "**rate-limit egress queue"** command to configure the egress queue shaper.
Use the **no** form of this command to disable the queue shaper.
You can verify your setting by entering the **show running-config interfaces** command.

### Example

The following example show how to configure ingress port rate limit and egress port shaper.
Switch(config)# **interfaces gi1**
Switch(config-if)# **rate-limit egress queue 3 2048**
Switch# **show running-config interfaces gi1**

```
interface gi1
rate-limit egress queue 3 2048
```

# 30.RIP

## rip

### Syntax

**rip**
**no rip**

### Parameter

### Default

### Mode

Global Configuration

### Usage

Use the command "rip" to enable the rip routing protocol.

### Example

Enable rip routing protocol

```
Switch(config)# rip
```

## network

### Syntax

**network** *A.B.C.D/M*
**nonetwork** *A.B.C.D/M*

### Parameter

| | |
|---|---|
| *A.B.C.D/M* | ip prefix < Network > / < length >, for example, 10.0.0.0/8 |

### Default

### Mode

Rip mode

### Usage

Use the command "**network**" to enable routing on the IP network.

### Example

Enable IP network routing

Switch(config)# **rip**
Switch(config-rip)# **network 12.0.0.0/8**

## version

### Syntax

**version 1 | 2**
**no version**

### Parameter

| | |
|---|---|
| 1 | Rip protocol version 1 |
| 2 | Rip protocol version 2 |

### Default

RIP protocol uses version 2 by default

**Mode**

Rip mode

**Usage**

Use the command "**version**" to configure the version of the RIP protocol.

**Example**

Configure RIP Protocol Version

Switch(config)# **rip**
Switch(config-rip)# **version 2**

## show rip

**Syntax**

**show rip**

**Parameter**

**Default**

**Mode**

Privileged EXEC

**Usage**

Use the command "show rip" to query rip information.

**Example**

Query RIP information

Switch# **show rip**

```
Rip status          : on
Rip version         : V2 (send V2, receive V1/2)
Updates time        : 30 sec
Age   time          : 180 sec
Garbage-collect time   : 120 sec
Default redistribution metric : 1
Routing for Networks:
```

# 31.SNMP

## snmp

### Syntax

**snmp**

### Parameter

### Default

SNMP is disabled by default

### Mode

Global Configuration

### Usage

To enable the SNMP on the switch, use the command **snmp** in the Global Configuration mode. Otherwise, use the **no** form of the command to disable to SNMP.

### Example

The following example enables the SNMP.

Switch(config)# snmp

## snmp view

### Syntax

**snmp view** *view-name* **subtree** *oid-tree* **oid-mask** (**all**|*oid-mask*) **view type** (included|excluded)
**no snmp view** *view-name* **subtree** (**all**|*oid-tree*)

### Parameter

| | |
|---|---|
| *view-name* | The SNMP view name. Its maximum length is 30 characters. |
| **subtree** *oid-tree* | Specify the ASN.1 subtree object identifier (OID) to be included or excluded from the SNMP view. |
| **oid-mask** (**all**|*oid- mask*) | Specify the OID family mask. It is used to define a family of view subtrees. For example, OID mask FA.80 is is 11111010.10000000. The length of the OID mask must be less than the length of subtree OID. |
| **iewtype**(**included**|**excluded**) | Include or exclude the selected MIBs in the view. |

### Default

### Mode

Global Configuration

### Usage

To configure the SNMP view, use the command **snmp view** in the Global Configuration mode; and use the **no** form of the command to delete the SNMP view.

The default SNMP view cannot be deleted and modified by users.

By default, the maximum numbers of SNMP view is limited to 16.

**Example**

The following example defines the SNMP view.

```
Switch(config)# snmp view private subtree 1.3.3.1 oid-mask all viewtype included
```

## snmp group

**Syntax**

**snmp group** *group-name* **(1 | 2c | 3) (noauth|auth|priv) read-view** *read-view* **write-view** *write-view* **[notify-view** *notify-view***]**
**no snmp group** *group-name security-mode version* **(1** | **2c** | **3)**

**Parameter**

| | |
|---|---|
| *group-name* | Specify SNMP group name, and the maximum length is 30 characters. |
| (**1**\|**2c**\|**3**) | Specify the SNMP version. |
| **noauth** | Specify that no packet authentication is performed. |
| **auth** | Specify that no packet authentication without entryption is performed. It is applicable only to the SNMPv3 security mode. |
| **priv** | Specify that no packet authentication with entryption is performed. It is applicable only to the SNMPv3 security mode. |
| **read-view** *read- view* | Set the view name that enables configuring the agent, and its maximum length is 30 characters. |
| **write-view** *write-view* | Set the view name that enables viewing only, and its maximum length is 30 characters. |
| **notify-view** *notify-view* | Sets the view name that sends only traps with contents that is included in SNMP view selected for notification.The maximum length is |

| | |
|---|---|
| | 30 characters. |

**Default**

No group entry is existed.

**Mode**

Global Configuration

**Usage**

To define the SNMP group, use the command **snmp group** in the Glocal Configuration mode, and use the **no** form of the command to delete the configuration.

SNMP group configuration is used in the command **snmp use** to map SNMP users to the SNMP group. These users would be automatically maped to the SNMP views defined in this command.

The securety level for SNMP v1 or v2 is always **noauth**.

**Example**

The following example adds SNMPv3 group

```
Switch(config)# snmp group v3 version 3 auth read-view all write-view all
notify-view all
```

## snmp community

**Syntax**

**snmp community** *community-name* [**view** *view-name*] (**ro**|**rw**)
**snmp community** *community-name* **group** *group-name*
**no snmp community** *community-name*

**Parameter**

| | |
|---|---|
| *community-name* | The SNMP community name. Its maximum length is 20 characters. |
| **view** *view-name* | Specify the SNMP view configured by the command **snmp view** to define the object available to the community. |
| **ro** | Read only access (default) |
| **rw** | Writable access |
| **group** *group-name* | Specify the SNMP group configured by the command **snmp group** to define the object available to the community. |

**Default**

No SNMP community is configured

**Mode**

Global Configuration

**Usage**

To define the SNMP community that permit access for SNMP v1 and v2, use the command **snmp community** in the Global Configuration mode.

**Example**

The following example defines the SNMP community named *private* with the default view *all*, and the access right is *read-only*.

```
Switch(config)# snmp community private ro
```

## snmp user

**Syntax**

**snmp user** *username group-name* [**auth** (**md5**|**sha**) *AUTHPASSWD*]
**snmp user** *username group-name* **auth** (**md5**|**sha**) *AUTHPASSWD* **priv** *PRIVPASSWD*
**no snmp user** *username*

**Parameter**

| | |
|---|---|
| *username* | Specify the SNMP user name on the host that connects to the SNMP agent. The max character is 30 characters. For the SNMP v1 or v2c, the user name must match the community name by the command **snmp host**. |
| *group-name* | Specify the SNMP group to which the SNMP user belongs. The SNMP group should be SNMPv3 and configured by the command **snmp group**. |
| **auth** (**md5**\|) | Specify the HMAC-MD5-96 authentication protocol as the user authentication. |
| **auth** (**sha**\|) | Specify the HMAC-SHA-96 authentication protocol as the user authentication. |
| *AUTHPASSWD* | The password for authentication and the range of length is from 8 to 32 characters. |
| **Priv** *PRIVPASSWD* | The private password for the privacy key, and the range of length is from 8 to 64 characters. |

**Default**

**Mode**

Global Configuration

**Usage**

To define a SNMP user, use the command snmp user in the Global Configuration mode; and use the no form to delete the SNMP user.

**Example**

The following example adds SNMP user *v3* into the group *v3* by the MD5 authentication.

Switch(config)# snmp user v3 v3 auth md5 12345678

## snmp engineid

### Syntax

**snmp engineid** (**default**|*ENGINEID*)

### Parameter

| | |
|---|---|
| **default** | Default engine ID generated on the basis of the switch MAC address. |
| *ENGINEID* | Specify SNMP engine ID. The engine ID is the 10 to 64 hexadecimal characters, and the hexadecimal number must be divided by 2. |

### Default

The default SNMP engine ID on the switch is based on switch MAC address.

### Mode

Global Configuration

### Usage

To define the SNMP engine on the switch, use the command s**nmp engineid** in the Global Configuration mode.

### Example

The following example configure the switch SNMP engine ID

Switch(config)# snmp engineid 00036D001122

## snmp engineid remote

### Syntax

**snmp engineid remote** (*ip-addr*|*ipv6-addr*) *ENGINEID*
**no snmp engineid remote** (*ip-addr*|*ipv6-addr*)

### Parameter

| | |
|---|---|
| *ENGINEID* | Specify SNMP engine ID. The engine ID is a 10 to 64 hexadecimal characters, and the hexadecimal number must be divided by 2. |
| *ip-addr* | IP address of the remote host |
| *ipv6-addr* | IPv6 address of the remote host |

### Default

### Mode

Global Configuration

### Usage

To define the remote host for SNMP engine, use the command **snmp engineid remote** in the Global Configuration mode; and use the **no** form of the command to delete the remote host from the SNMP engine.

### Example

The following example adds the remote *192.168.1.11* into SNMP engine

```
Switch(config)# snmp engineid remote 192.168.1.11 00036D10000A
```

## snmp trap

### Syntax

**snmp trap (auth|cold-start|linkUpDown|port-security|warm-start)**
**no snmp trap (auth|cold-start|linkUpDown|port-security|warm-start)**

### Parameter

| | |
|---|---|
| **auth** | Enable the SNMP authentication failure trap. |
| **cold-start** | Enable the SNMP cold start-up failure trap. |
| **linkUpDown** | Enable the SNMP link up and down failure trap. |
| **port-security** | Enable the SNMP port security trap. |
| **warm-start** | Enable the SNMP warm start-up failure trap. |

### Default

All the SNMP traps are enabled.

### Mode

Global Configuration

### Usage

To send the SNMP traps, use the command snmp trap in the Global Configuration mode; and use the no form of the command to disable the SNMP traps.

### Example

The following example disables and enables the SNMP link up and down traps individually.

```
Switch(config)# no snmp trap linkUpDown
Switch(config)# snmp trap linkUpDown
```

## snmp host

## Syntax

**snmp host** (*ip-addr*|*ipv6-addr*|*hostmane*) [**traps**|**informs**] [**version** (**1**|**2c**)] *community-name* [**udp-port** *udp-port*] [**timeout** *timeout*] [**retries** *retries*]
**snmp host** (*ip-addr*|*ipv6-addr*|*hostmane*) [**traps**|**informs**] **version 3** [(**auth**|**noauth**|**priv**)] *community-name* [**udp-port** *udp-port*] [**timeout***timeout*] [**retries** *retries*]
**no snmp host** (*ip-addr*|*ipv6-addr*|*hostmane*) **[traps|informs] [version (1|2c|3)]**

## Parameter

| | |
|---|---|
| *ip-addr* | The IP adderss of recipet. |
| *ipv6-addr* | The IPv6 adderss of recipet. |
| *hostname* | The host name of recipet. |
| **traps** | Send SNMP traps to the host. It is the default action. |
| **informs** | Send SNMP informs to the host. |
| **version** (**1**\|**2c**\|**3**) | Specify the SNMP version. |
| **noauth** | Specify that no packet authentication is performed. It is applicable only to the SNMPv3 security mode. |
| **auth** | Specify that no packet authentication without entryption is performed. It is applicable only to the SNMPv3 security mode. |
| **priv** | Specify that no packet authentication with entryption is performed. It is applicable only to the SNMPv3 security mode. |
| *community-name* | The SNMP community sent with the notification. |
| **udp-port** *udp-port* | Specify the UDP port number. |
| **timeout** *timeout* | Specify the SNMP informs timeout. |
| **retries** *retries* | Specify the retry counter of the SNMP informs. |

## Default

No SNMP host is configured.
The default SNMP version for the command is SNMPv1.

**Mode**

Global Configuration

**Usage**

To configure the hosts to receive SNMP notificatons, use the command **snmp host** in the Global Configuration mode; and use the **no** form of the command to delete the configuration.

**Example**

The following example adds the recipet *192.168.1.11* for the SNMP traps notification.

```
Switch(config)# snmp host 192.168.1.11 private
```

## show snmp view

**Syntax**

**show snmp view**

**Parameter**

**Default**

**Mode**

Privileged EXEC

**Usage**

To show the SNMP view defined on the switch, use the command **show snmp view** in the Privileged EXEC mode.

### Example

The following example shows the configuration of SNMP view.

```
Switch# show snmp view
View Name                Subtree OID                OID Mask          View Type
-------------------------- ----------------------------------------
all                                .1
all                            included

Total Entries: 1
```

## show snmp group

### Syntax

### show snmp group

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

To show the SNMP group configuration on the switch, use the command **show snmp group** in the Privileged EXEC mode.

### Example

The following example shows the SNMP group configuration.

```
Switch# show snmp group
Group Name                       Model   Level           ReadView
WriteView                        Not
------------------------------ ------ ----------- -----------
------------------ ------------------------------ ----
private                          v2c     noauth          all
all                              ---
v3                               v3      auth            all
all                              all
```

Total Entries: 2

## show snmp community

### Syntax

**show snmp community**

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

To show the configuration of snmp communities, use the command **show snmp community** in the Privileged EXEC mode.

### Example

The following example shows the SNMP communities configuration.

```
Switch# show snmp community
Commnunity Name                 Group Name                      View
Access
------------------- ------------------------------ ----------
------------------- ------------
private                                                         all
ro
public                                                          all
rw

Total Entries: 2
```

## show snmp user

### Syntax

### show snmp user

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

To show the SNMP users defined on the switch, use the command **show snmp user** in the Privileged EXEC mode.

### Example

The following example shows the configuration of SNMP user.

```
Switch# show snmp user
Username:                    v3
Password:                    ********
Privilege Mode:              rw
Access GroupName:            v3
Authentication Protocol: md5
Encryption Protocol:         none
Access SecLevel:             auth

Total Entries: 1
```

## show snmp engineid

### Syntax

### show snmp engineid

### Parameter

### Default

### Mode

Privileged EXEC

**Usage**

To show the SNMPv3 engine IDs defined on the switch, use the command **show snmp engineid** in the Privileged EXEC mode.

**Example**

The following example shows the SNMP engind id information.

```
Switch# show snmp engineid
Local SNMPV3 Engine id: 00036d001122

IP address                                Remote SNMP engineID
----------------------------------- ----------------------------
-------------------------------------
192.168.1.11                              00036D10000A

 Total Entries: 1
```

## show snmp trap

**Syntax**

**show snmp trap**

**Parameter**

**Default**

**Mode**

Privileged EXEC

**Usage**

To show the status of SNMP traps on the switch, use the command **show snmp trap** in the Privileged EXEC mode.

**Example**

The following example shows the status of SNMP traps.

```
Switch# show snmp trap
SNMP auth failed trap : Enable
SNMP linkUpDown trap : Enable
SNMP cold-start trap      : Enable
SNMP warm-start trap     : Enable
```

## show snmp host

### Syntax

### show snmp host

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

To show the SNMP trap notification recipients defined on the switch, use the command **show snmp host** in the Privileged EXEC mode.

### Example

The following example shows the configuration of SNMP notification recipients on the switch.

```
Switch# show snmp host
Server                  Community Name      Notification Version              Notification
Type
-------------------------------------------------------------------------------
192.168.1.11            private             v1                                trap

 Total Entries: 1
```

# 32. RMON

## rmon event

### Syntax

**rmon event <1-65535> [log] [trap COMMUNITY] [descriptionDESCRIPTION] [owner NAME]**
**no rmon event <1-65535>**

### Parameter

| | |
|---|---|
| **<1-65535>** | Specify event index to create or modify. |
| **[log]** | (Optional)Specify to show syslog. |
| **[trap COMMUNITY]** | (Optional)Specify SNMP community to show SNMP trap. |
| **[descriptionDESCRIPTION]** | (Optional)Specify description of event |
| **[owner NAME]** | (Optional)Specify owner of event. |

### Default

No default is defined.

### Mode

Global Configuration

### Usage

Use the **rmon event** command to add or modify a RMON evnet entry.
Use the **no** form of this command to delete.
You can verify settings by the **show rmon event** command.

### Example

The example shows how to add RMON event entry with log and trap action and then modify it action to log only.

switch(config)# **rmon event 1 log trap public description test owner admin**
switch(config)# **show rmon event 1**

Rmon Event Index 1
Rmon Event Type : Log and Trap Rmon Event Community : public Rmo
Rmon Event Last Sent :
Rmon Event Owner : admin

switch(config)# **rmon event 1 log description test owner admin**
switch(config)# **show rmon event 1**
Rmon Event Index 1
Rmon Event Type : Log Rmon Event Community : public Rmon Event D
Rmon Event Last Sent :
Rmon Event Owner : admin

## rmon alarm

**Syntax**

**rmon alarm <1-65535> interface IF_PORT (drop-events|octets|pkts|broadcast-pkts| multicast-pkts|crc-align-errors|undersize-pkts|oversize-pkts|fragments|jabbers|collisions |pkts64octets|pkts65to127octets|pkts128to255octets|pkts256to511octets|pkts512to1023octets |pkts1024to1518octets) <1-2147483647> (absolute|delta) rising <0-2147483647> <0-65535> falling <0-2147483647> <0-65535> startup (rising|rising-falling|falling) [owner NAME]**

**no rmon alarm <1-65535>**

**Parameter**

| | |
|---|---|
| **<1-65535>** | Specify alarm index to create or modify |
| **IF_PORT** | Specify the interface to sample |
| **(variable)** | Specify a mib object to sample |
| **<1-2147483647>** | Specify the time in seconds that the alarm monitors the MIB variable. |
| **(absolute\|delta)** | Specify absolute to compare sample counter absolutely.<br>Specify delta to compare delta counter between samples |

| | |
|---|---|
| **<0-2147483647>** | Specify a number which the alarm trigger rising event |
| **<0-65535>** | Specify event index when the rising threshold exceeds. |
| **<0-2147483647>** | Specify a number which the alarm trigger falling event |
| **<0-65535>** | Specify event index when the falling threshold exceeds. |
| **(rising\|rising-falling\|falling)** | Specify only to how rising or falling startup event. Or show either rising or falling startup event. |
| **[owner NAME]** | (Optional) Specify owner of alarm. |

**Default**

No default is defined.

**Mode**

Global Configuration

**Usage**

Use the **rmon alarm** command to add or modify a RMON alarm entry.Before add alarm entry, at least one event entry must be added. Use the **no** form of this command to delete.
You can verify settings by the **show rmon alarm** command.

**Example**

The example shows how to add RMON alarm entry that sample interface fa1 packets delta count every 300 seconds. Trigger event index 1 if over than rising threshold 10000, trigger event index 2 if lower than falling threshold.

switch(config)# **rmon event 1 log**
switch(config)# **rmon event 2 log**

Switch(config)# **rmon alarm 1 interface gi1 pkts 300 delta rising 10000 1 falling 100 1 startup rising-falling owner admin**

Rmon Alarm Index 1
Rmon Alarm Sample Interval 300

Rmon Alarm Sample Interface : gi1
Rmon Alarm Sample Variable : Pkts
Rmon Alarm Sample Type : delta
Rmon Alarm Type : Rising or Falling
Rmon Alarm Rising Threshold : 10000
Rmon Alarm Rising Event 1
Rmon Alarm Falling Threshold 100
Rmon Alarm Falling Event 1
Rmon Alarm Owner : admin

## rmon history

### Syntax

**rmon history <1-65535> interface IF_PORT [buckets <1-65535>] [interval <1-3600>] [owner NAME]**
**no rmon history <1-65535>**

### Parameter

| | |
|---|---|
| **<1-65535>** | Specify history index to create or modify. |
| **IF_PORT** | Specify the interface to sample |
| **[bucket <1-65535>]** | (Optional) Specify the maximum number of buckets. |
| **[interval <>1-3600]** | (Optional) Specify time interval for each sample |
| **[owner NAME]** | (Optional)Specify owner of history |

### Default

No default is defined.

### Mode

Global Configuration

### Usage

Use the **rmon history** command to add or modify a RMON history entry.
Use the **no** form of this command to delete.
You can verify settings by the **show rmon history** command.

**Example**

The example shows how to add RMON history entry that monitor interface gi1 every 60 seconds and then modify it to monitor every 30 seconds.

switch(config)# **rmon history 1 interface gi1 interval 60 owner admin**
switch(config)# **show rmon history 1**
Rmon History Index 1
Rmon Collection Interface: gi1
Rmon History Bucket 50
Rmon history Interval 60
Rmon History Owner : admin

switch(config)# **rmon history 1 interface gi1 interval 30 owner admin**
switch(config)# **show rmon history 1**
Rmon History Index 1
Rmon Collection Interface: gi1
Rmon History Bucket 50
Rmon history Interval 30
Rmon History Owner: admin

## clear rmon interfaces statistics

**Syntax**

**clear rmon interfaces IF_PORTS statistics**

**Parameter**

| | |
|---|---|
| **IF_PORTS** | specifies ports to clear |

**Default**

No default is defined

### Mode

Privileged EXEC

### Usage

Use the **clear rmon interfaces statistics** command to clear RMON etherStat statistics those are recorded on interface.
You can verify results by the **show rmon interface statistics** command.

### Example

The example shows how to clear RMON etherStat statistics on interface gi1.

```
switch# clear rmon interfaces gi1 statistics
switch# show rmon interfaces gi1 statistics
==== Port gi1 ==============================
etherStatsDropEvents            0
etherStatsOctets                0
etherStatsPkts                  0
etherStatsBroadcastPkts         0
etherStatsMulticastPkts         0
etherStatsCRCAlignErrors        0
etherStatsUnderSizePkts         0
etherStatsOverSizePkts          0
etherStatsFragments             0
etherStatsJabbers               0
etherStatsCollisions            0
etherStatsPkts64Octets          0
etherStatsPkts65to127Octets     0
etherStatsPkts128to255Octets    0
etherStatsPkts256to511Octets    0
etherStatsPkts512to1023Octets   0
etherStatsPkts1024to1518Octets  0
```

## show rmon interfaces statistics

### Syntax

**show rmon interfaces IF_PORTS statistics**

### Parameter

| | |
|---|---|
| **IF_PORTS** | specifies ports to show |

### Default

No default is defined

### Mode

Privileged EXEC

### Usage

Use the **show rmon interfaces statistics** command to show RMON etherStat statistics of interface.

### Example

The example shows how to show RMON etherStat statistics of interface gi1.

```
switch(config)# show rmon interfaces gi1 statistics
==== Port gi1 ==============================
etherStatsDropEvents                          0
etherStatsOctets                            : 81882
etherStatsPkts                              578
etherStatsBroadcastPkts                     10
etherStatsMulticastPkts                     0
etherStatsCRCAlignErrors                    0
etherStatsUnderSizePkts                     0
etherStatsOverSizePkts                      0
etherStatsFragments                         0
etherStatsJabbers                           0
etherStatsCollisions                        0
etherStatsPkts64Octets                      355
etherStatsPkts65to127Octets                 126
etherStatsPkts128to255Octets                0
etherStatsPkts256to511Octets                42
etherStatsPkts512to1023Octets               55
```

etherStatsPkts1024to1518Octets 0

## show rmon event

### Syntax

**show rmon event (<1-65535> | all)**

### Parameter

| | |
|---|---|
| **<1-65535>** | specifies event index to show |
| **all** | Show all existed event |

### Default

No default is defined

### Mode

Privileged EXEC

### Usage

Use the **show rmon event** command to show existed RMON event entry.

### Example

The example shows how to show rmon event entry.

switch(config)# **rmon event 1 log trap public description test owner admin**
switch(config)# **show rmon event 1**
Rmon Event Index 1
Rmon Event Type : Log and Trap
Rmon Event Community : public
Rmon Event Description : test
Rmon Event Last Sent :
Rmon Event Owner : admin

## show rmon event log

### Syntax

**show rmon event <1-65535> log**

### Parameter

| | |
|---|---|
| **<1-65535>** | specifies event index to show event log |

### Default

No entry and log is exist

### Mode

Privileged EXEC

### Usage

Use the **show rmon event log** command to show log triggered by RMON alarm.

### Example

The example shows how to show rmon event log.

switch(config)# **show rmon event 1 log**
==========
====
Index 1
Alarm Index 1
Action : Startup Falling
Time : (32918334) 3 days, 19:26:23.34
Description : fa1.Pkts=0 <= 100

## show rmon alarm

### Syntax

**show rmon alarm (<1-65535> | all)**

**Parameter**

| | |
|---|---|
| **<1-65535>** | specifies alarm index to show |
| **all** | Show all existed alarm |

**Default**

No alarm is defined

**Mode**

Privileged EXEC

**Usage**

Use the **show rmon alarm** command to show existed RMON alarm entry.

**Example**

The example shows how to show rmon alarm entry.

Switch(config)# **rmon alarm 1 interface gi1 pkts 300 delta rising 10000 1 falling 100 1 startup rising-falling owner admin**

Rmon Alarm Index 1
Rmon Alarm Sample Interval 300
Rmon Alarm Sample Interface : gi1
Rmon Alarm Sample Variable : Pkts
Rmon Alarm Sample Type : delta
Rmon Alarm Type : Rising or Falling
Rmon Alarm Rising Threshold : 10000
Rmon Alarm Rising Event 1
Rmon Alarm Falling Threshold 100
Rmon Alarm Falling Event 1
Rmon Alarm Owner : admin

## show rmon history

### Syntax

**show rmon history (<1-65535> | all)**

### Parameter

| | |
|---|---|
| **<1-65535>** | specifies history index to show |
| **all** | Show all existed history |

### Default

No history is defined

### Mode

Privileged EXEC

### Usage

Use the **show rmon history** command to show existed RMON history entry.

### Example

The example shows how to show RMON history entry.

switch(config)# **rmon history 1 interface gi1 interval 30 owner admin**
switch(config)# **show rmon history 1**
Rmon History Index 1
Rmon Collection Interface: gi1
Rmon History Bucket 50
Rmon history Interval 30
Rmon History Owner: admin

## show rmon history statistic

### Syntax

**show rmon history <1-65535> statistic**

**Parameter**

| | |
|---|---|
| **<1-65535>** | specifies history index to show history statistic |

**Default**

No history is defined

**Mode**

Privileged EXEC

**Usage**

Use the **show rmon history statistic** command to show statistics that are recorded by RMON history.

**Example**

The example shows how to show RMON history statistics

switch(config)# **show rmon history 1 statistics**

```
==================================================
====
Sample Index          2
Interval Start      : (32940466) 3 days, 19:30:04.66
DropEvents            0
Octets              : 117226
Pkts                763
BroadcastPkts         9
MulticastPkts         0
CRCAlignErrors        0
UnderSizePkts         0
OverSizePkts          0
Fragments             0
Jabbers               0
```

```
Collisions            0
Utilization           1

================================================================
====
Sample Index          1
Interval Start       : (32939462) 3 days, 19:29:54.62
DropEvents            0
Octets              220
Pkts                3
BroadcastPkts         1
MulticastPkts         0
CRCAlignErrors          0
UnderSizePkts         0
OverSizePkts          0
Fragments             0
Jabbers     0
Collisions     0
Utilization    0
```

# 33. Spanning Tree

## instance (MST)

### Syntax

**instance** *instance-id* **vlan** *vlan-list*
**no instance** *instance-id* **vlan** *vlan-list*

### Parameter

| | |
|---|---|
| *instance-id* | The MSTP instance ID from 0 to 15. |
| **vlan** *vlan-list* | Add the VLAN list to the MSTP instance. |

### Default

All VLANs are mapped to the Common and Internal Spanning Tree (CIST)instance (instance 0).

**Mode**

MST Configuration

**Usage**

To map the VLAN to the Multiple Spanning Tree (MSTP) instances, use the command instance in the MST Configuration mode; and use the no form of the command to restore its default configuration.
All VLANs that are not explicility configured to an MSTP instance are mapped to the CIST instance (instance 0).

For two or more switches in the samp MSTP regiom, their VLAN mapping, name and revision number configuration, must be the same.

**Example**

The following example maps the vlan 10-20 to the MSTP instance 1, and VLAN 100 to instance 2.

```
Switch(config)# spanning-tree mst configuration
Switch(config-mst)# instance 1 vlan 10-20
Switch(config-mst)# instance 2 vlan 100
```

## name (MST)

**Syntax**

**name** *name-str*
**no name**

**Parameter**

| | |
|---|---|
| *name-str* | The MSTP instance name. Its maximum length is 32 characters. |

### Default

The default MSTP name is the switch MAC address.

### Mode

MST Configuration

### Usage

To define the name for MSTP instance, use the command **name** in the MST Configuration mode; and use the **no** form to restore the default name configuration.

### Example

The following example configures the name of MST instance to *Valkyrie*.

```
Switch(config)# spanning-tree mst configuration
Switch(config-mst)# name Valkyrie
```

## revision (MST)

### Syntax

**revision rev**
**no revision**

### Parameter

| | |
|---|---|
| *rev* | The MSTP revision number. Its valid rage is from 0 to 65535. |

### Default

The default revision number is 0.

### Mode

MST Configuration

### Usage

To define the revision for the MSTP configuration, use the command **revision** in the MST Configuration mode; and use the **no** form of the command to restore it default configuration.

### Example

The following example defines the revision MSTP configuration to 1.

```
Switch(config)# spanning-tree mst configuration
Switch(config-mst)# revision 1
```

## spanning-tree mst configuration

### Syntax

**spanning-tree mst configuration**

### Parameter

### Default

### Mode

Global Configuration

### Usage

To enter the MST configuration mode for the MSTP configuration modification, use the command **spanning-tree mst configuration** in the Global Configuration mode.

### Example

The following example modifies the MSTP configuration in the MST Configuration mode.

```
Switch(config)# spanning-tree mst configuration
Switch(config-mst)# instance 1 vlan 10-20
Switch(config-mst)# name Valkyrie
Switch(config-mst)# revision 1
```

## spanning-tree mst cost

### Syntax

**spanning-tree mst** *instance-id* **cost** *cost*
**no spanning-tree mst** *instance-id* **cost** *cost*

### Parameter

| | |
|---|---|
| *instance-id* | Specify the instance ID. The valid range is from 0 to 15. |
| *cost* | Specify the path cost for the interfaces on the specific MSTP instance. For the long path cost method, its valid range is from 0 to 200000000; and the valid range is from 0 to 65535 for the short path cost method. The value 0 indicates AUTO, which the port path cost is determined by the port speed and the path cost method. |

### Default

The default port path cost is 0, and it is determined by the port speed and the path cost method (long or short).

| Interface | Long | Short |
|---|---|---|
| Gigabit Ethernet(1000Mbps) | 20000 | 4 |
| Fast Ethernet (100Mbps) | 200000 | 19 |
| Ethernet (10Mbps) | 2000000 | 100 |

### Mode

Interface Configuration

**Usage**

To configure the path cost for MSTP calculations, use the command **spanning-tree mst cost** in the Interface Configuration mode. If the loop occurs, the MSTP considers the path cost when selecting the interface into the Forwarding state. For the default configuration, use the no form of the command.

When configuring the path cost on the CIST (instance 0), it is equal to the command **spanning-tree cost** in the Interface Configuration mode.

**Example**

The following example configures the path cost of interface fa1 on the instance 1 to 30000

```
Switch(config)# interface gi1
Switch(config-if)# spanning-tree mst 1 cost 30000
```

## spanning-tree mst port-priority

**Syntax**

**spanning-tree mst** *instance-id* **port-priority** *priority*
**no spanning-tree mst** *instance-id* **port-priority**

**Parameter**

| | |
|---|---|
| *instance-id* | Specify the instance ID. The valid range is from 0 to 15. |
| *priority* | Specify the interface priority on the specific instance. |

**Default**

The default port priority on each instance is 128

**Mode**

Interface Configuration

**Usage**

To configure the interface priority on the specific instances, use the command **spanning-tree mst port-priority** in the Interface Configuration mode. For the default configuration, use the **no** form of the command.

The priority value must be the multiple of 16. When the port priority on the CIST (instance 0) is configured, it is equal to the command **spanning-tree port-priority** in the Interface Configuration mode.

**Example**

The following example sets the port priority of gi1 on the instance 1 to 144; and set the port priority of gi1 on the CIST (instance 0) to 96

```
Switch(config)# interface gi1
Switch(config-if)# spanning-tree mst 1 port-priority 144
Switch(config-if)# spanning-tree mst 0 port-priority 96
```

## spanning-tree mst priority

**Syntax**

**spanning-tree mst instance** *instance-id* **priority** *priority*
**no spanning-tree mst instance** *instance-id* **priority**

**Parameter**

| | |
|---|---|
| *instance-id* | Specify the instance ID. The valid range is from 0 to15. |
| *priority* | Specify the bridge priority on the specific instance. The valid range is from 0 to 61440. It nsures the probility that the switch is selected as the root bridge, and the lower values has the higher priority for the switch to be |

| | |
|---|---|
| | selected as the root bridge. |

**Default**

The default priority on each instance is 32768.

**Mode**

Global Configuration

**Usage**

To configure the bridge priority on the specific instance, use the command **spanning-tree mst priority** in the Global Configuration mode. To restore the default configuration, use the **no** form of the command.

The value of bridge priority must be the multiple of 4096. A switch with the lowest priority is the root of the STP topology. For the configuration of bridge priority on the CIST (instance 0), it is equal to the command **spanning-tree priority** in the Global Configuration mode.

**Example**

The following example modifies the bridge priority to 4096 on instance 0 and instance 1 individually.

```
Switch(config)# spanning-tree mst 0 priority 4096
Switch(config)# spanning-tree mst 1 priority 4096
```

## spanning-tree

**Syntax**

**spanning-tree**
**no spanning-tree**

**Parameter**

### Default

Spanning-Tree is enabled by default.

### Mode

Global Configuration

### Usage

To enable the spanning tree, use the command **spanning-tree** in the Global Configuration mode; and use the no form of the command to disable the spanning tree on the switch.

### Example

The following example disables and enables the spanning tree individually.

```
Switch(config)# no spanning-tree
Switch(config)# spanning-tree
```

## spanning-tree mode

### Syntax

**spanning-tree mode (mstp|rstp|stp)**
**no spanning-tree force-version**

### Parameter

| | |
|---|---|
| **mstp** | Enable the Multiple Spanning Tree (MSTP) operation. |
| **rstp** | Enable the Rapid Spanning Tree (RSTP) operation. |
| **stp** | Enable the Spanning Tree (STP) operation. |

### Default

The default mode is rstp.

**Mode**

Global Configuration

**Usage**

To specify the spanning tree operation mode, use the command of **spanning-tree mode** in the Global Configuration mode. For the default configuration, use the command **no spanning-tree force-version** in the Global Configuration mode.

When the switch is configured as MSTP mode, it can use STP and RSTP for the backward compatibility with switches working in STP and RSTP mode individually. For the RSTP configuration, the switch can also use STP for the switches working in the STP operation.

**Example**

The following example sets the STP operation to MSTP.

```
Switch(config)# spanning-tree mode mstp
```

## spanning-tree bpdu

**Syntax**

**spanning-tree bpdu (filtering|flooding)**
**no spanning-tree bpdu**

**Parameter**

| | |
|---|---|
| **filtering** | Filter the BPDU when STP is diabled. |
| **flooding** | Flood the BPDU when the STP is disabled. |

**Default**

The default configuration is flooding.

**Mode**

Global Configuration

**Usage**

To configure the action of Bridge Protocol Data Unit (BPDU) handlring when STP is disabled, use the command **spanning-tree bpdu** in the Global Configuration mode. To restore the configuration to the default action, use the no form of the command.

**Example**

The following example configures the action of BPDU handling to fliter when the STP is disabled.

```
Switch(config)# spanning-tree bpdu filtering
```

## spanning-tree bpdu-filter

**Syntax**

**spanning-tree bpdu-filter**
**no spanning-tree bpdu-filter**

**Parameter**

**Default**

BPDU filter is disabled.

**Mode**

Interface Configuration

**Usage**

To enable the BPDU filter, use the command **spanning-tree bpdu-filter** in the Interface Configuration mode; and use **no** form of the command to disable the BPDU filter.

**Example**

The following example enables the BPDU filter for interface gi1.

```
Switch(config)# interface gi1
Switch(config-if)# spanning-tree bpdu-filter
```

## spanning-tree bpdu-guard

**Syntax**

**spanning-tree bpdu-guard**
**no spanning-tree bpdu-guard**

**Parameter**

**Default**

BPDU guard is disabled

**Mode**

Interface Configuration

**Usage**

To enable the BPDU filter, use the command **spanning-tree bpdu-guard** in the Interface Configuration mode; and use **no** form of the command to disable the BPDU filter.

**Example**

The following example enables the BPDU guard for interface gi1.

```
Switch(config)# interface gi1
Switch(config-if)# spanning-tree bpdu-guard
```

## spanning-tree cost

### Syntax

**spanning-tree cost** cost
**no spanning-tree cost**

### Parameter

| | |
|---|---|
| *cost* | The port path cost. For the long path cost method, its valid range is from 0 to 200000000; and the valid range is from 0 to 65535 for the short path cost method. The value 0 indicates AUTO, which the port path cost is determined by the port speed and the path cost method. |

### Default

The default port path cost is 0, and it is determined by the port speed and the path cost method (long or short).

| Interface | Long | Short |
|---|---|---|
| Gigabit Ethernet (1000Mbps) | 20000 | 4 |
| Fast Ethernet (100Mbps) | 200000 | 19 |
| Ethernet (10Mbps) | 2000000 | 100 |

### Mode

Interface Configuration

### Usage

To configure the STP path cost for an interface, use the command **spanning-tree cost** in the Interface Configuration mode; and use the **no** form of the command to restore it to the default configuration.

### Example

The following example configures port path cost to 30000 for interface fa2.

```
Switch(config)# interface gi1
Switch(config-if)# spanning-tree cost 30000
```

## spanning-tree forward-delay

### Syntax

**spanning-tree forward-delay** *seconds*
**no spanning-tree forward-delay**

### Parameter

| | |
|---|---|
| *seconds* | STP forward delay time. Its valid range is from 4 to 30 seconds. |

### Default

The default forward delay time is 15 seconds.

### Mode

Global Configuration

### Usage

To configure the STP bridge forward delay time, which is the amount of time that a port remains in the Listening and Learning states before it enters the Forwarding state, use the command spanning-tree forward-time in the Global Configuration mode. To restore it to the default configuration, use the **no** form of the command.

When the forward delay time is configured, the following relationship shold be maintained:

2 * (forward-time - 1) >= Max-Age

**Example**

The following example configures STP forward delay time to 25.

```
Switch(config)# spanning-tree forward-time 25
```

## spanning-tree hello-time

**Syntax**

**spanning-tree hello-time** seconds
**no spanning-tree hello-time**

**Parameter**

| | |
|---|---|
| *seconds* | STP hello time in second. Its valid range is from 1 to 10 seconds. |

**Default**

The default STP hello time is 2 seconds.

**Mode**

Global Configuration

**Usage**

STP hello time is the time interval to broadcast its hello message to other bridges. To configure the STP hello time, use the command **spanning-tree hello-time** in the Global Configuration mode; and use the **no** form of the command to restore the hello time to default configuration.

When the hello time is configured, the following relationship should be maintained:

Max-Age >= 2 * (hello-time + 1)

**Example**

The following example configures BPDU hello time to 4.

```
Switch(config)# spanning-tree hello-time 4
```

## spanning-tree maximum-age

**Syntax**

**spanning-tree maximum-age** *seconds*
**no spanning-tree maximum-age**

**Parameter**

| | |
|---|---|
| *seconds* | The interval in seconds for a switch to wait the configuration messages, without attempting to redefine its own configuration. |

**Default**

The default maximum age is 20 seconds.

**Mode**

Global Configuration

**Usage**

To set the interval in seconds that the switch can wait without receiving the configuration messages, before attempting to redefine its own configuration, use the command **spanning-tree maximum-age** in the Global Configuratio mode. For the default configuration, use the **no** form of the commands.

When the maximum age is configured, the following

relationship should be maintained:
2 * (forward-time - 1)>= Max-Age >= 2 * (hello-time + 1)

**Example**

The following example configures STP maximum age to 10.

```
Switch(config)# spanning-tree maximum-age 10
```

## spanning-tree edge

**Syntax**

**spanning-tree edge**
**no spanning-tree edge**

**Parameter**

**Default**

The default configuration is disabled.

**Mode**

Interface Configuration

**Usage**

To enable the edge mode for an interface, use the command **spanning-tree edge** in the Interface Configuration mode; and use the **no** form of the command to restore it to the default configuration.

In the edge mode, the interface would be put into the Forwarding state immediately upon link up. If the edge mode is enabled for the interface and there are BPDUs received on the interface, the loop might be occurred in the short time.

**Example**

The following example enables the edge mode for the interface gi1.

```
Switch(config)# interface gi1
Switch(config-if)# spanning-tree edge
```

## spanning-tree link-type

### Syntax

**spanning-tree link-type (point-to-point|shared)**
**no spanning-tree link-type**

### Parameter

| | |
|---|---|
| **point-to-point** | Specify the port link type is point to point. |
| **shared** | Specify the port link type is shared. |

### Default

The default configuration link type is **point-to-poin**t for the ports with full duplex configuration, and **shared** for the ports with half duplex settings.

### Mode

Interface Configuration

### Usage

To set the RSTP link-type for an interface, use the command **spanning-tree link** in the Interface Configuration mode. For the default configuration, use the **no** form of the command.

### Example

The following example configures the link-type to point-to-point for the interface gi1.

```
Switch(config)# interface gi1
Switch(config-if)# spanning-tree link-type point-to-point
```

## spanning-tree max-hops

### Syntax

**spanning-tree max-hops** counts
**no spanning-tree max-hops**

### Parameter

| | |
|---|---|
| *counts* | Specify the number of hops in an MSTP regision before the BPDU is discarded. The valid range is 1 to 40. |

### Default

The default max-hops configuration is 20.

### Mode

Global Configuration

### Usage

To specify the number of hops for a BPDU to be forwarded in the MSTP region, use the command **spanning-tree max-hops** in the Global Configuration mode; and restore the setting to default configuration by the **no** form of the command.

### Example

The following example specifies the max hops for BPDU to 10.

```
Switch(config)# spanning-tree max-hops 10
```

## spanning-tree mcheck

### Syntax

**spanning-tree mechek**

### Parameter

### Default

### Mode

Interface Configuration

### Usage

To restart the Spanning Tree Protocol (STP) migration process (re-negotiate forcely with its neighborhood) on the specific interface, use the command spanning-tree mcheck in the Interface Configuration mode

### Example

The following example restarts the STP negotiation on the interface gi1.

```
Switch(config)# interface gi1
Switch(config-if)# spanning-tree mecheck
```

## spanning-tree pathcost method

### Syntax

**spanning-tree pathcost method** (**long**|**short**)

### Parameter

| | |
|---|---|
| **long** | The range for the path cost is from 1 to 200000000. |
| **short** | The range for the path cost is from 1 to 65535. |

### Default

The default path cost method is long.

### Mode

Global Configuration

### Usage

To set the spanning tree path cost method, use the command **spanning-tree pathcost method** in the Global Configuration mode.
If the short method is specified, the switch calculates the path cost in the range 1 throuth 65535; Otherwise, it calculates the path cost in the range 1 to 200000000.

### Example

The following example modifies path cost method to short.

```
Switch(config)# spanning-tree pathcost method short
```

## spanning-tree port-priority

### Syntax

**spanning-tree port-priority** *priority*
**no spanning-tree port-priority** *priority*

### Parameter

| | |
|---|---|
| *priority* | Specify the priority for an interface. The valid range is from 0 to 240. |

### Default

The default priority for each interface is 128.

### Mode

Interface Configuration

### Usage

To configure the STP priority for an interface, use the command **spanning- tree port-priority** in the Interface Configuration mode. For the default configuration, use the **no** form of the command.
The priority value must be the multiple of 16.

### Example

The following example modifies the port priority to 96 for the interface gi2 .

```
Switch(config)# interface gi2
Switch(config-if)# spanning-tree port-priority 96
```

## spanning-tree priority

### Syntax

**spanning-tree priority** *priority*
**no spanning-tree priority**

### Parameter

| | |
|---|---|
| *instance-id* | Specify the instance ID. The valid range is from 0 to 15. |
| *priority* | Specify the bridge STP priority. The valid range is from 0 to 61440. It nsures the probility that the switch is selected as the root bridge, and the lower values has the higher priority for the switch to be selected as the root bridge of the STP topology. |

### Default

The default priority for the switch 32768.

**Mode**

Global Configuration

**Usage**

To configure the bridge priority, use the command **spanning-tree mst priority** in the Global Configuration mode. To restore the default configuration, use the **no** form of the command.

The value of bridge priority must be the multiple of 4096. A switch with the lowest priority is the root of the STP topology. When swithes with the same priority configuration in the environment, the switch with lowest MAC address would be selected as the root bridge.

**Example**

The following example modifies the bridge priority to 4096.

```
Switch(config)# spanning-tree priority 4096
```

## spanning-tree tx-hold-count

**Syntax**

**spanning-tree tx-hold-count** *count*
**no spanning-tree tx-hold-count**

**Parameter**

| | |
|---|---|
| *count* | Specify the tx-hold-count used to limit the maximum numbers of packets transmission per second. The valid range is from 1 to 10. |

**Default**

The default value is 6.

### Mode

Global Configuration

### Usage

To limit the maximum numbers of packets transmission per second, use the command **spanning-tree tx-hold-count** in the Global Configuration mode. For the default configuration, use the **no** form of the command.

### Example

The following example sets the tx-hold-count to 4.

```
Switch(config)# spanning-tree tx-hold-count 4
```

## show spanning-tree

### Syntax

**show spanning-tree**

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

To display the spanning tree configuration, use the command spanning-tree in the Privileged EXEC mode

### Example

The following example shows the spanning tree configuration.

```
Switch# show spanning-tree

Spanning tree enabled mode RSTP
Default port cost method:  long

  Root ID     Priority    32768
              Address     1c:2a:a3:c4:02:92
              This switch is the root
              Hello Time  2 sec  Max Age 20 sec  Forward Delay 15 sec

  Number of topology changes 3 last change occurred 00:00:03 ago
  Times:  hold 0, topology change 0, notification 0
          hello 2, max age 20, forward delay 15

Interfaces
  Name      State    Prio.Nbr    Cost      Sts    Role EdgePort         Type
--------- -------- -------- -------- ------ ---- -------- ----------------
     gi1  enabled   128.1      20000    Frw    Desg         No P2P (RSTP)
    gi15  enabled   128.15     200000   Frw    Desg         No P2P (RSTP)
gi25  enabled   128.25     200000   Frw    Desg         No P2P (RSTP)
```

## show spanning-tree interface

### Syntax

**show spanning-tree interface** *IF_PORTS* [**statistic**]

### Parameter

| | |
|---|---|
| **interface** *IF_PORTS* | An interface ID or the list of interface IDs. |
| **statistic** | Display the STP statistic for an interface. |

### Default

### Mode

Privileged EXEC

### Usage

To show the STP configuration and statistics for an interface, use the command

show spanning-tree interface in the Privileged EXEC mode.

### Example

The following example shows the STP configuration for the interface gi1.

```
Switch# show spanning-tree interfaces gi1

Port gi1 enabled
State: forwarding                    Role: designated
Port id: 128.23                      Port cost: 19
Type: P2P (RSTP)                     Edge Port: No
Designated bridge Priority : 32768   Address: 00:11:22:33:44:55
Designated port id: 128.23           Designated path cost: 0
BPDU Filter: Disabled                BPDU guard: Disabled
BPDU: sent 21886, received 0
```

The following example shows the STP statistic for the interface gi1.

```
Switch# show spanning-tree interfaces gi1 statistic

STP Port Statistic
==================================================

Port                                 : gi1
Configuration BDPUs Received         : 0
TCN BDPUs Received                   : 0
MSTP BDPUs Received                  : 0
Configuration BDPUs Transmitted : 0
TCN BDPUs Transmitted                : 0
MSTP BDPUs Transmitted               : 21917
==================================================
```

## show spanning-tree mst

### Syntax

**show spanning-tree mst** *instace-id*

### Parameter

| | |
|---|---|
| *instance-id* | The MSTP instance ID. Its valid range is from 0 to 15. |

### Default

### Mode

Privileged EXEC

### Usage

To show the information for a specific MSTP instance, use the command **show spanning-tree mst** in the Privileged EXEC mode.

### Example

The following example displays the information for the MSTP instance 0 and 1 individually.

```
Switch# show spanning-tree mst 0

 MST Instance Information
============================================================
                Instance Type : CIST (0)
           Bridge Identifier : 32768/ 0/1C:2A:A3:C4:02:92
------------------------------------------------------------
    Designated Root Bridge : 32768/ 0/1C:2A:A3:C4:02:92
  External Root Path Cost : 0
      Regional Root Bridge : 32768/ 0/1C:2A:A3:C4:02:92
  Internal Root Path Cost : 0
          Designated Bridge : 32768/ 0/1C:2A:A3:C4:02:92
                  Root Port : 0/0
                    Max Age : 20
               Forward Delay : 15
            Topology changes : 3
      Last Topology Change : 374
------------------------------------------------------------
 VLANs mapped: 1-4094
============================================================

Interface           Role Sts Cost         Prio.Nbr Type
---------------- ---- --- --------- -------- --------------------------------
gi1                 Desg FWD 20000       128.1    P2P (RSTP)
gi15                Desg FWD 200000      128.15   P2P (RSTP)
gi25                Desg FWD 200000      128.25   P2P (RSTP)
```

## show spanning-tree mst interface

### Syntax

**show spanning-tree mst** *instance-id* **interface** *IF_PORTS*

**Parameter**

| | |
|---|---|
| *instance-id* | The MSTP instance ID. Its valid range is from 0 to 15. |
| **interface** *IF_PORTS* | An interface ID or the list of interface IDs. |

**Default**

**Mode**

Privileged EXEC

**Usage**

To show the MSTP instance information on the specific interface, use the command **show spanning-tree mst interface** in the Privileged EXEC mode.

**Example**

The following example shows the MSTP 0 and 1 information individually on the interface gi1.

```
Switch# show spanning-tree mst 0 interfaces g1

 MST Port Information
================================================================
 Instance Type : CIST (0)
----------------------------------------------------------------

        Port Identifier : 128/1
    External Path-Cost : 0            /20000
    Internal Path-Cost : 0            /20000
----------------------------------------------------------------
   Designated Root Bridge : 32768/1C:2A:A3:C4:02:92
        External Root Cost : 0
     Regional Root Bridge : 32768/1C:2A:A3:C4:02:92
        Internal Root Cost : 0
         Designated Bridge : 32768/1C:2A:A3:C4:02:92
```

```
Internal Port Path Cost : 20000
                Port Role : Designated
               Port State : Forwarding
---------------------------------------------------------------
```

## show spanning-tree mst configuration

### Syntax

### show spanning-tree mst configuration

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

To show the global MST configuration, use the command **show spanning-tree mst configuration** in the Privileged EXEC mode.

### Example

The following example shows the global MST configuration.

```
Switch# show spanning-tree mst
configuration
Name        [00:11:22:33:44:55]
Revision    0       Instances configured 2

Instance    Vlans mapped
--------    ---------------------------------------------------------------------
0           1-99,111-4094
1           100-110
---------------------------------------------------------------------------
```

# 34. Static Routing

## interface vlan (IPv4)

### Syntax

**interface vlan**
**ip address** *ipaddr mask*
**no interface vlan**
**no ip address**

### Parameter

| | |
|---|---|
| *ipaddr* | Specify IPv4 address for switch |
| *mask* | Specify net mask address for switch |

### Default

The vlan interface and ip address are not configured by default.

### Mode

Global configuration and vlan interface configuration.

### Usage

Use the **interface vlan** global configuration command to config ip interface on the device.
Use the **ip address** command in vlan interface mode to configure the device's ip address.
Use the **no ip address** command to delete the configured ip address.
Use the **no interface vlan** command to delete ip interface on the device.
You can verify your setting by entering the **show ip interface vlan** Privileged EXEC command.

### Example

The following example shows how to config ip interface.

```
Switch(config)# interface vlan 2
```

```
Switch(config-if)# ip address 192.168.3.1 255.255.255.0
Switch# show ip interface vlan 2

IP Address              I/F         I/F Status admin/oper      Type      Status
----------------- ---------- ---------- ------- ------
192.168.3.1/24      VLAN 2      UP/DOWN                    Static     Valid
```

## ip route

### Syntax

**ip route** *dest-ipaddr mask router-ipaddr*
**no ip route** *dest-ipaddr mask router-ipaddr*

### Parameter

| | |
|---|---|
| *dest-ipaddr* | Destination ip address prefix |
| *mask* | Destination ip address prefix mask |
| *router-ipaddr* | Forwarding router's ip address |

### Default

Static route is not configured by default.

### Mode

Global Configuration mode.

### Usage

Use the **ip route** command in global mode to configure a static route rule.
Use the **no ip route** command to delete a static routing rule.
You can verify your setting by entering the **show ip route** Privileged EXEC command

### Example

The following example shows how to configure a static route.

```
Switch(config)# vlan 2
Switch(config)# interface GigabitEthernet 4
Switch(config-if)# switchport trunk allowed vlan add 2
Switch(config)# interface vlan 2
Switch(config-if)# ip address 192.168.3.1 255.255.255.0
Switch(config)# ip route 1.1.1.1 255.0.0.0 192.168.3.11
Switch# show ip route
Codes: > - best, C - connected, S - static

S>    1.0.0.0/8 [1/1] via 192.168.3.11, VLAN 2
C>    192.168.0.0/24 is directly connected, MGMT VLAN
C>    192.168.3.0/24 is directly connected, VLAN 2
```

## arp

### Syntax

**arp** *ip-addr mac-addr* **vlan** *vlanid*
**no arp** *ip-addr mac-addr* **vlan** *vlanid*

### Parameter

| | |
|---|---|
| *ip-addr* | IP address of ARP entry |
| *mac-addr* | MAC address of ARP entry |
| *vlanid* | Vlan ID of this arp entry |

### Defaul

The device contains ARP entries of the vlan interface.

### Mode

Global Configuration mode

### Usage

Use the **arp** command to add a static arp entry.
Use the **no arp** command to delete a static arp entry.
You can verify your setting by entering the **show arp** Privileged EXEC command

### Example

The following example shows how to configure and view a static arp entry.

```
Switch(config)# arp 192.168.3.22 00:00:11:11:11:11 vlan 2
Switch# show arp
VLAN Interface      IP address          HW address          Status
----------------- --------------- ----------------- ----------
vlan 1              192.168.0.112     00:D0:00:00:00:01   Dynamic
vlan 2              192.168.3.22       00:00:11:11:11:11   Static
```

## interface vlan (IPv6)

### Syntax

**interface vlan** *vlanid*
**ipv6 enable**
**no interface vlan** *vlanid*
**no ipv6 enable**

### Parameter

| | |
|---|---|
| *vlanid* | Vlan id for vlan interface |

### Default

The vlan interface are not configured by default.Ipv6 is disabled.

### Mode

Global configuration and vlan interface configuration.

### Usage

Use the **interface vlan** global configuration command to config ip interface on the device.
Use the **ipv6 enable** command in vlan interface mode to enable ipv6 function.
Use the **no ipv6 enable** command to disable ipv6 function.
Use the **no interface vlan** command to delete ip interface on the device.

You can verify your setting by entering the **show ipv6 interface vlan** Privileged EXEC command.

### Example

The following example shows how to config ip interface.

```
Switch(config)# interface vlan 2
Switch(config-if)# ipv6 enable
Switch# show ipv6 interface vlan 2

VLAN 2 is up/up
IPv6 is enabled, link-local address is fe80::2e0:4cff:fe00:0
IPv6 Forwarding is enabled
No global unicast address is configured
Joined group address(es):
ff02::1:ff00:0
ff02::1
ff01::1
ND DAD is enabled, number of DAD attempts: 1
Stateless autoconfiguration is enabled
```

## ipv6 address

### Syntax

**ipv6 address** *ipv6-addr*
**no ipv6 address**

### Parameter

| | |
|---|---|
| *ipv6-addr* | Manually configured ipv6 address |

### Default

The vlan interface are not configured by default.Ipv6 is disabled.

### Mode

Global configuration and vlan interface configuration.

### Usage

Use the **ipv6 address** command in vlan interface mode to config a manual ipv6 address.
Use the **no ipv6 address** command in vlan interface mode to delete all manual ipv6 addresses on this vlan interface.
You can verify your setting by entering the **show ipv6 interface vlan** Privileged EXEC command.

### Example

The following example shows how to config ip interface.

```
Switch(config)# interface vlan 2
Switch(config-if)# ipv6 address 2001:01::01:01/64
Switch# show ipv6 interface vlan 2
VLAN 2 is up/up
IPv6 is enabled, link-local address is fe80::2e0:4cff:fe00:0
IPv6 Forwarding is enabled
Global unicast address(es):
IPv6 Global Address                    Type
2001:1::1:1/64                         Manual
Joined group address(es):
ff02::1:ff01:1
ff02::1:ff00:0
ff02::1
ff01::1
ND DAD is enabled, number of DAD attempts: 1
Stateless autoconfiguration is enabled Stateless autoconfiguration is enabled
```

## ipv6 route

### Syntax

**ipv6 route** *ipv6-addr/length route-ipv6-addr*
**no ipv6 address** *ipv6-addr/length*

### Parameter

| | |
|---|---|
| *ipv6-addr/length* | Destination ipv6 prefix and length |
| *route-ipv6-addr* | Forwarding router's ipv6 address |

### Default

The ipv6 routing entry is not configured by default.

### Mode

Global configuration and vlan interface configuration.

### Usage

Use the **ipv6 route** command to configure a static ipv6 routing entry.
Use the **no ipv6 address** command to delete a static ipv6 routing entry.
You can verify your setting by entering the **show ipv6 route static** Privileged EXEC command.

### Example

The following example shows how to configure an ipv6 routing entry.

```
Switch(config)# ipv6 route 2002:01::01:01/96 2001:01::01:02
Switch# show ipv6 route static
Codes: A - active, I - inactive

I     2002:1::/96 [1/1] via 2001:1::1:2, inactive
```

## ipv6 neighbors

### Syntax

**ipv6 neighbor** *ipv6-addr* **vlan** *vlanid macaddr*
**no ipv6 neighbor**

### Parameter

| | |
|---|---|
| *ipv6-addr* | Neighbor ipv6 address |
| *vlanid* | Vlan interface number |
| *macaddr* | MAC address of ipv6 neighbor entry |

### Default

No ipv6 neighbor address by default.

### Mode

Global configuration.

### Usage

Use the **ipv6 neighbor** command to configure a static ipv6 neighbor entry.
Use the **no ipv6 neighbor** command to delete ipv6 neighbor entry.
You can verify your setting by entering the **show ipv6 neighbors** Privileged EXEC command.

### Example

The following example shows how to configure an ipv6 neighbor entry.

```
Switch(config)# ipv6 neighbor 2001:01::01:11 vlan 2 00:00:00:11:11:12
Switch# show ipv6 neighbors
VLAN Interface              IPv6 address            HW address          Status     Router State
--------------- ---------------------------------------- ----------------- ------
---- ------ ----------
vlan 2                2001:1::1:11                00:00:00:11:11:12   Static       No

Total number of entries: 1
```

## show ip interface vlan

### Syntax

**show ip interface vlan** *vlanid*

### Parameter

| | |
|---|---|
| *vlanid* | Vlan id for vlan interface |

### Default

### Mode

Privileged EXEC

### Usage

Use the command "show IP interface VLAN" to query the interface information.

### Example

The following example shows how to show VLAN interface information.

```
Switch# show ip interface vlan 2

IP Address              I/F          I/F Status admin/oper      Type      Status
----------------------- ---------- ---------- ------- ------
192.168.3.1/24          VLAN 2       UP/DOWN                    Static    Valid
```

## show ipv6 interface vlan

### Syntax

**show ipv6 interface vlan** *vlanid*

### Parameter

| | |
|---|---|
| *vlanid* | Vlan id for vlan interface |

### Default

### Mode

Privileged EXEC

### Usage

Use the command "show IPv6 interface VLAN" to query the IPv6 information of the interface

### Example

The following example shows how to show VLAN interface ipv6 information.

```
Switch# show ipv6 interface vlan 2

VLAN 2 is up/up
IPv6 is enabled, link-local address is fe80::2e0:4cff:fe00:0
IPv6 Forwarding is enabled
No global unicast address is configured
Joined group address(es):
ff02::1:ff00:0
ff02::1
ff01::1
ND DAD is enabled, number of DAD attempts: 1
Stateless autoconfiguration is enabled
```

## show ip route

### Syntax

### show ip route

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

Use the command "show ip route" to query the system IP route table entries.

### Example

The following example shows how to show routing information

```
Switch# show ip route
Codes: > - best, C - connected, S - static

S>    1.0.0.0/8 [1/1] via 192.168.3.11, VLAN 2
C>    192.168.0.0/24 is directly connected, MGMT VLAN
C>    192.168.3.0/24 is directly connected, VLAN 2
```

## show ipv6 route

### Syntax

### show ipv6 route

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

Use the command "show IPv6 route" to query the system static IPv6 route table entries.

### Example

The following example shows how to show ipv6 static routing

```
Switch# show ipv6 route static
Codes: A - active, I - inactive

I     2002:1::/96 [1/1] via 2001:1::1:2, inactive
```

## show arp

### Syntax

**show arp**

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

Use the command "show ARP" to query static ARP table entries.

### Example

The following example shows how to show ARP table entry

```
VLAN Interface       IP address           HW address          Status
---------------- --------------- ------------------ ----------
vlan 1               192.168.0.112     00:D0:00:00:00:01    Dynamic
vlan 2               192.168.3.22       00:00:11:11:11:11    Static
```

## show ipv6 neighbors

### Syntax

**show ipv6 neighbor**

### Parameter

### Default

### Mode

Privileged EXEC

**Usage**

Use the command "show IPv6 neighbor" to query the system's IPv6 neighbor table entries.

**Example**

The following example shows how to show ipv6 neighbor entry.

```
Switch# show ipv6 neighbors
VLAN Interface              IPv6 address                HW address          Status     Router State
---------------- ---------------------------------------- ----------------- ------
---- ------ ----------
vlan 2                2001:1::1:11                00:00:00:11:11:12   Static       No

Total number of entries: 1
```

# 35. Storm Control

## storm-control

**Syntax**

**storm-control**
**no storm-control**
**storm-control (broadcast | unknown-unicast | unknown-multicast)**
**no storm-control (broadcast | unknown-unicast | unknown-multicast)**

**Parameter**

| | |
|---|---|
| **broadcast** | Select broadcast storm control type |
| **unknown-unicast** | Select unknown unicast storm control type |
| **unknown-multicast** | Select unknown multicast storm control type |

## Default

Default storm control is disabled.
Default broadcast storm control is disabled.
Default unknown multicast storm control is disabled
Default unknown unicast storm control is disabled

## Mode

Interface Configuration

## Usage

Storm control function is able to enable/disable on each single port. Use the "**storm control**" command to enable storm control feature on the selected ports. And use "**no storm control**" command to disable storm control feature. Not only port is able to enable/disable on the port. Each storm control type is also able to enable/disable on each single port.
Use the "**storm-control** (**broadcast**|**unknown-unicast**|**unknown-multicast**)" command to enable the storm control type you need and use no form to disable it.

## Example

This example shows how to enable storm control on interface gi1.

```
Switch(config)# interface gi1
Switch(config-if)# storm-control
```

This example shows how to enable broadcast storm control and configure broadcast storm control rate to 200.

```
Switch(config)# interface gi1
Switch(config-if)# storm-control broadcast
```

This example shows how to show current storm control configuration on interface gi1

```
Switch# show storm-control interfaces gi1

Port     | State | Broadcast | Unkown-Multicast | Unknown-Unicast | Action
|        |       pps      |        pps      |        pps
|
---------+-------+-----------+------------------+-----------------|--------
---
```

gi1 enable 200 Off( 10000) Off( 10000) Shutdown

## storm-control action

### Syntax

**storm-control action** (**drop** | **shutdown**)
**no storm-control action**

### Parameter

| | |
|---|---|
| **drop** | Storm control rate calculates by octet-based |
| **shutdown** | |

### Default

Default storm control action is drop.

### Mode

Interface Configuration

### Usage

Use "**storm-control action**" command to set the action when the received storm control packets exceed the maximum rate on an interface.
Use **no** form to restore to default action.

### Example

This example shows how to configure storm control action to shutdown port on interface gi1.

Switch(config)# **interface gi1**
Switch(config-if)# **storm-control action shutdown**

This example shows how to show storm control action on interface gi1.

Switch# **show storm-control interfaces gi1**

```
Port      | State | Broadcast | Unkown-Multicast | Unknown-Unicast | Action
|         |         pps      |         pps      |         pps
|
---------+-------+-----------+------------------+-----------------|--------
---
gi1         disable   Off( 10000)      Off( 10000)      Off( 10000)      Shutdown
```

## storm-control ifg

### Syntax

**storm-control ifg** (**include** | **exclude**)

### Parameter

| | |
|---|---|
| **include** | Include preamble & IFG (20 bytes) when count ingress storm control rate. |
| **exclude** | Exclude preamble & IFG (20 bytes) when count ingress storm control rate |

### Default

Default storm control inter frame gap is excluded.

### Mode

Global Configuration

### Usage

Storm control mechanism will try to calculate ingress packets is exceed configured rate or not and do corresponding action.
Use **storm-control ifg** command to include/exclude the preamble and inter frame gap into the calculating.

### Example

This example shows how to configure storm inter frame gap to include.
Switch(config)# **storm-control ifg include**

This example shows how to show storm control global configuration.

Switch# **show storm-control**
Storm control preamble and IFG: Included
Storm control unit: pps
.....

## storm-control level

### Syntax

**storm-control** (**broadcast** | **unknown-unicast** | **unknown-multicast**) **level** *<1-1000000>*
**no storm-control** (**broadcast** | **unknown-unicast** | **unknown-multicast**) **level**

### Parameter

| | |
|---|---|
| **broadcast** | Select broadcast storm control type |
| **unknown-unicast** | Select unknown unicast storm control type |
| **unknown- multicast** | Select unknown multicast storm control type |
| **level** *<1-1000000>* | Specify the storm control rate for selected type.<br>For bps, range is 16-1000000<br>For pps, range is 1-262143 |

### Default

Default broadcast storm control rate is 10000.
Default unknown multicast storm control rate is 10000.
Default unknown unicast storm control rate is 10000.

### Mode

Interface Configuration

### Usage

Each control type is allowed to have different storm control rate.

Use "**storm-control (broadcast|unknown-unicast|unknown-multicast) level**" command to configure it
Use no form to restore to default rate.

**Example**

This example shows how to enable broadcast storm control and configure broadcast storm control rate to 200.

```
Switch(config)# interface gi1
Switch(config-if)# storm-control broadcast
Switch(config-if)# storm-control broadcast level 200
```

This example shows how to show current storm control configuration on interface gi1

```
Switch# show storm-control interfaces gi1
Port     | State | Broadcast | Unkown-Multicast | Unknown-Unicast | Action
|        |       pps      |         pps      |         pps
|
---------+-------+-----------+------------------+-----------------|--------
---
gi1              enable 200          Off( 10000)        Off( 10000)          Shutdown
```

## storm-control unit

**Syntax**

**storm-control unit** (**bps** | **pps**)

**Parameter**

| | |
|---|---|
| **bps** | Storm control rate calculates by octet-based |
| **pps** | Storm control rate calculates by packet-based |

**Default**

Default storm control unit is bps.

**Mode**

Global Configuration

### Usage

Storm control mechanism will try to calculate ingress packets is
exceed configured rate or not and do corresponding action.
Use **storm-control unit** command to change the unit of calculating method.

### Example

This example shows how to configure storm control rate unit as pps.
Switch(config)# **storm-control unit pps**

This example shows how to show storm control global configuration.
Switch# **show storm-control**
Storm control preamble and IFG: Excluded
Storm control unit: pps
.....

## show storm-control

### Syntax

**show storm-control**
**show storm-control interface** *IF_PORTS*

### Parameter

| | |
|---|---|
| *IF_PORTS* | Specify port to show. |

### Default

No default value for this command

### Mode

Privileged EXEC

### Usage

Use "**show storm-control**" command to show all storm control related configurations including global configuration and per port configurations.

Use "**show storm-control interface**" command to show selected port storm control configurations.

**Example**

This example shows how to show storm control global configuration.

```
Switch# show storm-control
Storm control preamble and IFG: Excluded
Storm control unit: pps
.....
```

This example shows how to show current storm control configuration on interface gi1

```
Switch# show storm-control interfaces gi1
Port      | State | Broadcast | Unkown-Multicast | Unknown-Unicast| Action
|         |         pps       |         pps      |         pps
|
---------+-------+------------+------------------+----------------|--------
---
gi1              enable          200               Off( 10000)                  Off( 10000)
Shutdown
```

# 36. System File

## copy

**Syntax**

**copy** (**flash://** | **tftp://**) (**flash://** | **tftp://**)
**copy tftp://** (**backup-config** | **running-config** | **startup-config**)
**cop usb (backup-config | running-config | startup-config)**
**copy** (**backup-config** | **running-config** | **startup-config**) **tftp://**
**copy (backup-config | running-config | startup-config) usb**
**copy (backup-config | startup-config) running-config**
**copy (backup-config | running-config) startup-config**
**copy (running-config | startup-config) backup-config**

**Parameter**

| | |
|---|---|
| **flash://** | Specify the file stored in flash to operation. Available files are:<br>flash://startup-config<br>flash://backup-config<br>flash://rsa1 flash://rsa2<br>flash://dsa2<br>flash://image0<br>flash://image1<br>flash://ram.log<br>flash://flash.log |
| **tftp://** | Specify remote tftp server and remote file name. The format is "**tftp://192.168.1.111/remote_file_name**" |
| **usb** | USB flash drive |
| **running-config** | Running configuration file |
| **startup-config** | Startup configuration file |
| **backup-config** | Backup configuration file |

**Default**

No default value for this command.

**Mode**

Privileged EXEC

**Usage**

There are many types of files in system. These files are very important for administrator to manage the switch. The most common file operation is copy. By using these copy commands, we can upgrade, backup following type of files. When using USB flash disk, the file format of USB is FAT32.

- **Firmware Image**
- **Configuration Files**
- **Syslog Files**
- **Language Files**
- **Security Certificate**

**Example**

This example shows how to copy running configuration to startup configuration.

Switch# **copy running-config startupst-config**

This example shows how to backup running configuration to remote tftp server 192.168.111 with file name test1.cfg.

Switch# **copy running-config tftp://192.168.1.111/test1.cfg**

Uploading file...Please Wait...

Uploading Done

This example shows how to upgrade startup configuration from remote tftp server 192.168.1.111 with file name test2.cfg.

Switch# **copy tftp://192.168.1.111/test2.cfg startup-config**

Downloading file...Please Wait...

Downloading Done

Upgrade config success. Do you want to reboot now? (y/n)n

This example shows how to backup security file dsa2 to remote tftp server 192.168.1.111 with file name dsa2.

Switch# **copy flash://dsa2 tftp://192.168.1.111/dsa2**

Uploading file...Please Wait...

Uploading Done

## delete

### Syntax

**delete** (**startrup-config** | **backup-config** | **flash://**)

### Parameter

| | |
|---|---|
| **flash://** | Specify the configuration file stored in flash to delete. Available files are:<br>flash://startup-config<br>flash://backup-config |
| **startup-config** | Delete startup configuration file |
| **backup-config** | Delete backup configuration file |

### Default

No default value for this command.

### Mode

Privileged EXEC

### Usage

Use "**delete**" command to delete configuration files or use "**delete system**" command to delete firmware image stored in flash.
The "**delete startup-config**" command is using to restore factory default and it is equal to command "**restore-defaults**".

### Example

This example shows how to delete backup configuration file.

```
Switch# delete backup-config
```

This example shows how to show file status in flash.

```
Switch# show flash
File Name          File Size Modified
---------------------- --------------- ----------------------
startup-config     1191      2000-01-01 00:00:23
backup-config      1607      2000-01-01 08:36:23
rsa1                974      2000-01-01 00:00:18
rsa2               1675      2000-01-01 00:00:18
dsa2                668      2000-01-01 00:00:18
ssl_cert            993      2000-01-01 00:00:18
image0 (active)  4372401          2012-09-24 01:57:29
image1 (backup)    0
```

## restore-defaults

### Syntax

**restore-defaults** [**interfaces** *IF_PORTS*]

### Parameter

| | |
|---|---|
| **interfaces** *IF_PORTS* | Specify port to restore its ' ruuning config |

### Default

No default value for this command.

**Mode**

Privileged EXEC

**Usage**

Use "**restore-defaults**" command to restore factory default of all system. The command is equal to "**delete startup-config**"

**Example**

This example shows how to restore factory defaults.
Switch# **restore-defaults**
Restore Default Success. Do you want to reboot now? (y/n)n

## save

**Syntax**

**save**

**Parameter**

**Default**

No default value for this command.

**Mode**

Privileged EXEC

**Usage**

Use "**save**" command to save running configuration to startup configuration file. This command is equal to "**copy running-config startup-config**".

**Example**

This example shows how to save running configuration to startup configuration.
Switch# **save**
Success

## show config

### Syntax

**show** (**running-config** | **startrup-config** | **backup-config**)
**show running-config interfaces** *IF_PORTS*

### Parameter

| | |
|---|---|
| **running-config** | Show running configuration on terminal |
| **startup-config** | Show startup configuration on terminal |
| **backup-config** | Show backup configuration on terminal |
| *IF_PORTS* | Specify port to show its' ruuning config |

### Default

No default value for this command.

### Mode

Privileged EXEC

### Usage

Our configuration file is text based. Therefore, we can show the configuration on terminal and read it by this command.
Use "**show config**" command to show configuration files stored in system.
Use "**show config interfaces**" command to show specific port configurations.

### Example

This example shows how to show startup configuration
Switch# **show startup-config**
! System Description: RTK RTL8328-24FE-4GE Switch

```
! System Version: v2.5.0-beta.32811
! System Name: SwitchEF0102
! System Up Time: 0 days, 4 hours, 31 mins, 43 secs
!
!
!
!
username "" privilege user secret "dnXencJRwfIV6"
username "admin" secret "FzjrGO6vfbERY"
voice-vlan vpt 0
voice-vlan dscp 0
.....
```

This example shows how to show running configuration

```
Switch# show running-config
! System Description: RTK RTL8328-24FE-4GE Switch
! System Version: v2.5.0-beta.32811
! System Name: SwitchEF0102
! System Up Time: 0 days, 5 hours, 23 mins, 42 secs
!
!
!
!
username "" privilege user secret "dnXencJRwfIV6"
username "admin" secret "FzjrGO6vfbERY"
voice-vlan vpt 0
voice-vlan dscp 0
.....
```

This example shows how to display running configuraiton on specific port.

```
Switch# show running-config interfaces gi1
interface gi1
rate-limit ingress 128
```

## show flash

### Syntax

### show flash

### Parameter

### Default

No default value for this command.

### Mode

Privileged EXEC

**Usage**

Use "**show flash**" command to show all files' status which stored in flash.

**Example**

This example shows how to show all files status stored in flash.

```
Switch# show flash
File Name                File Size                Modified
------------------------ ---------------- ----------------------
startup-config   1191             2000-01-01 00:00:23
backup-config    1607             2000-01-01 08:36:23
rsa1              974             2000-01-01 00:00:18
rsa2             1675             2000-01-01 00:00:18
dsa2              668             2000-01-01 00:00:18
ssl_cert          993             2000-01-01 00:00:18
image0 (active)  4372401          2012-09-24 01:57:29
image1 (backup)0
```

## usb install

**Syntax**

**usb install**

**Parameter**

**Default**

**Mode**

Privileged EXEC

**Usage**

Use the command "USB install" to install the USB driver. Note that the file format of the USB flash disk should be FAT32. After the driver is successfully installed, the system configuration file may be saved and uploaded.

The USB function only supports the same series of three-layer management

switches, and the two-layer management switch does not support this function.

**Example**

This example shows how to installing the USB flash drive

Switch# **usb install**

## usb remove

**Syntax**

**usb remove**

**Parameter**

**Default**

**Mode**

Privileged EXEC

**Usage**

Use the command "USB remove" to uninstall the USB flash drive.

The USB function only supports the same series of three-layer management switches, and the two-layer management switch does not support this function.

**Example**

This example shows how to uninstall the USB flash drive

Switch# usb remove

# 37. Surveillance VLAN

## surveillance-vlan (Global)

### Syntax

**surveillance-vlan**
**no surveillance -vlan**

### Parameter

### Default

Surveillance VLAN is disabled

### Mode

Global Configuration

### Usage

Use the **surveillance vlan** global configuration command to enable the functional Surveillance VLAN on the device.
Use the **no** form of this command to disable Surveillance VLAN function. You can verify your setting by entering the **show surveillance vlan Privileged EXEC** command.

### Example

The following example shows how to enable Surveillance VLAN.

```
Switch(config)# surveillance -vlan
Switch# show surveillance -vlan
Administrate Surveillance VLAN state : disabled
Surveillance VLAN ID                 : none (disable)
Surveillance VLAN Aging              : 1440 minutes
Surveillance VLAN CoS                 6
Surveillance VLAN 1p Remark: disabled
```

## surveillance-vlan (Interface)

### Syntax

**surveillance-vlan**

**no surveillance-vlan**

**Parameter**

**Default**

Disable by default.

**Mode**

Interface Configuration

**Usage**

Use the **surveillance vlan** Interface configuration command to enable OUI surveillance VLAN configuration on an interface
Use the **no** form of this command to disable Surveillance VLAN on an interfaces
You can verify your setting by entering the **show surveillance vlan Privileged EXEC** command

**Example**

The following example how to enable Surveillance VLAN function in oui mode on an interface

```
Switch(config)#interface range gi1-3
Switch(config-if)#surveillance-vlan
Switch# show surveillance-vlan interfaces gi1-3
Surveillance VLAN Aging: 1440 minutes
Surveillance VLAN CoS              7
Surveillance VLAN 1p Remark: enabled

OUI table
OUI MAC | Description
------------------+----------------
00:01:02 | Test


Port     | State    | Port Mode | Cos Mode
---------+----------+-----------------+----------
gi1          | Disabled |   Auto     | Src
gi2          | Disabled |   Auto     | Src
gi3          | Disabled |   Auto     | Src
```

## surveillance-vlan vlan

### Syntax

**surveillance-vlan vlan** <1-4094>
**no surveillance-vlan vlan**

### Parameter

| | |
|---|---|
| <1-4094> | Specify the Surveillance VLAN ID |

### Default

The default Surveillance VLAN ID is None.

### Mode

Global Configuration

### Usage

Use the **surveillance vlan id** global configuration command to configure the VLAN identifier of the surveillance VLAN statically.
Use the **no** form of this command to restore surveillance VLAN id to default. You can verify your setting by entering the **show surveillance vlan Privileged EXEC** command

### Example

The following example shows how to set Surveillance VLAN id. The VLAN id must be created first.

```
Switch(config)# surveillance-vlan vlan 128
Switch# show surveillance-vlan
Administrate Surveillance VLAN state : enabled
Surveillance VLAN ID       128
Surveillance VLAN Aging : 1440 minutes
Surveillance VLAN CoS              6
Surveillance VLAN 1p Remark: disabled
```

## surveillance-vlan oui-table

### Syntax

**surveillance-vlan oui-table** A:B:C [DESCRIPTION]
**no surveillance-vlan oui-table** [A:B:C]

### Parameter

| | |
|---|---|
| A:B:C | Specify OUI Mac address to add or remove |
| DESCRIPTION | Specify description of the specified MAC address to the surveillance VLAN OUI table |

### Default

Default has no pre-defined OUI.

### Mode

Global Configuration

### Usage

Use the **surveillance vlan oui-table** global configuration command to add OUI mac address to OUI Table
Use the **no** form of this command to remove all or specified OUI mac address..
You can verify your setting by entering the **show surveillance vlan Privileged EXEC** command

### Example

This following example shows how to add OUI Mac.

```
Switch(config)# surveillance-vlan oui-table 00:01:02  “Test”
Switch# show surveillance-vlan interfaces gi1-3
```

```
Surveillance VLAN Aging : 1440 minutes
Surveillance VLAN CoS    : 6
Surveillance VLAN 1p Remark: disabled

OUI table
OUI MAC | Description
------------------+----------------
00:01:02 | Test


Port     | State     | Port Mode | Cos Mode
---------+-----------+-----------------+-----------
gi1| Disabled |    Auto     | Src
gi2| Disabled |    Auto     | Src
gi3| Disabled |    Auto     | Src
```

## surveillance-vlan cos (Global)

### Syntax

**surveillance-vlan cos** <0-7> [remark]
**no surveillance-vlan cos**

### Parameter

| | |
|---|---|
| <0-7> | Specify the surveillance VLAN Class of Service value in telephone OUI mode |
| remark | Specify that the L2 user priority is remarked with the CoS value |

### Default

The default cos value is 6, remark is disabled.

### Mode

Global Configuration

### Usage

Use the **surveillance vlan cos** global configurations command to configure the surveillance VLAN cos value and 1p remark function.

Use the "**no**" form to restore to default mode.
You can verify your setting by entering the **show surveillance vlan Privileged EXEC** command

**Example**

The following example show how to set cos value and enable 1p remark function

```
Switch(config)# surveillance-vlan cos 7 remark
Switch# show surveillance-vlan
Administrate Surveillance VLAN state : disabled
Surveillance VLAN ID      128
Surveillance VLAN Aging : 1440 minutes
Surveillance VLAN CoS              7
Surveillance VLAN 1p Remark: enabled
```

## surveillance-vlan cos (Interface)

**Syntax**

**surveillance-vlan cos ( src | all )**
**no surveillance-vlan cos**

**Parameter**

| | |
|---|---|
| src | Specify QoS attributes are applied to packets with OUIs in the source MAC address. |
| all | Specify QoS attributes are applied to packets that are classified to the Surveillance VLAN. |

**Default**

The default all port in Src mode.

**Mode**

Interface configuration

### Usage

Use the **surveillance vlan cos mode** Interface configuration command to configure OUI surveillance VLAN cos mode configuration on an interface. Use the "**no**" form to restore to default mode.
You can verify your setting by entering the **show surveillance-vlan interfaces Privileged EXEC** command

### Example

The following example how to configure surveillance packet QoS attributes on an interface

```
Switch(config)#interface range gi1-3
Switch(config-if)#surveillance-vlan cos all
Switch# show surveillance-vlan interfaces gi1-3
Surveillance VLAN Aging: 1440 minutes
Surveillance VLAN CoS                7
Surveillance VLAN 1p Remark: enabled

OOUI table
OUI MAC | Description
-------------------+-----------------
00:01:02 | Test


Port     | State     | Port Mode | Cos Mode
---------+-----------+-----------------+-----------
gi1        | Disabled |        Auto      | All
gi2        | Disabled |        Auto      | All
gi3        | Disabled |        Auto      | All
```

## surveillance-vlan mode

### Syntax

**surveillance-vlan mode (auto|manual)**
**no surveillance-vlan mode**

### Parameter

| | |
|---|---|
| **auto** | Specifies that the port is identified as a candidate to join the surveillance VLAN. When a packet with a source OUI MAC |

| | |
|---|---|
| | address that identifies the remote equipment as surveillance equipment is seen on the port, the port joins the surveillance VLAN as a tagged port. |
| **manual** | Specifies that the port is manually assigned to the surveillance VLAN. |

**Default**

The default is auto mode.

**Mode**

Interface Configuration

**Usage**

Use the **surveillance-vlan mode** global configuration command to configure the surveillance VLAN mode for interface.
Use the "**no**" form to restore to default mode.
You can verify your setting by entering the **show surveillance-vlan interfaces Privileged EXEC** command.

**Example**

The following example how to configure surveillance mode to manual

```
Switch(config)#interface range gi1-3
Switch(config-if)#surveillance-vlan mode manaul
Switch# show surveillance-vlan interfaces gi1-3
Surveillance VLAN Aging: 1440 minutes
Surveillance VLAN CoS              7
Surveillance VLAN 1p Remark: enabled

OUI table
OUI MAC | Description
------------------+-----------------
00:01:02 | Test


Port     | State    | Port Mode | Cos Mode
---------+----------+-----------------+-----------
gi1 | Disabled | Manual    | Src
gi2 | Disabled | Manual    | Src
```

gi3 | Disabled | Manual | Src

## surveillance-vlan aging-time

### Syntax

**surveillance-vlan aing-time** <30-65536>
**no surveillance-vlan aing-time**

### Parameter

| | |
|---|---|
| <30-65536> | Specify the Surveillance VLAN aging timeout interval in minutes |

### Default

The default aging-timeout value is 1440 minutes

### Mode

Global Configuration

### Usage

Use the **surveillance vlan aging-time** global configuration command to configure the surveillance VLAN aging timeout.
Use the "**no**" form to restore to default time.
You can verify your setting by entering the **show surveillance vlan Privileged EXEC** command

### Example

The following example shows how to set aging time.

```
Switch(config)# surveillance-vlan aging-time 720
Switch# show surveillance-vlan
Administrate Surveillance VLAN state : disabled
Surveillance VLAN ID      1
Surveillance VLAN Aging : 720 minutes
```

Surveillance VLAN CoS 5
Surveillance VLAN 1p Remark: enabled

## show surveillance-vlan

### Syntax

**show surveillance-vlan**
**show surveillance-vlan interfaces [**IF_PORTS]

### Parameter

| | |
|---|---|
| IF_PORTS | Specifies interfaces to display surveillance VLAN settings in OUI mode |

### Default

### Mode

Privileged EXEC

### Usage

Use the **show surveillance vlan** command in EXEC mode to display the surveillance VLAN status for all interfaces or for a specific interface if the surveillance VLAN type is OUI

### Example

The following example show how to display surveillance vlan OUI mode settings

```
Switch# show surveillance-vlan
Administrate Surveillance VLAN state : disabled
Surveillance VLAN ID      : none (disable)
Surveillance VLAN Aging          : 720 minutes
Surveillance VLAN CoS                6
Surveillance VLAN 1p Remark: disabled

Switch# show surveillance-vlan interfaces gi1-4
Surveillance VLAN Aging : 720 minutes
```

```
Surveillance VLAN CoS                5
Surveillance VLAN 1p Remark: enabled

OOUI table
OUI MAC | Description
------------------+----------------
00:01:02 | Test

Port     | State     | Port Mode | Cos Mode
---------+-----------+-----------------+-----------
gi1      | Disabled |       Auto     | Src
gi2      | Disabled |       Auto     | Src
gi3      | Disabled |       Auto     | Src
```

# 38. Time

## clock set

### Syntax

**clock set HH:MM:SS (jan|feb|mar|apr|may|jun|jul|aug|sep|oct|nov|dec)<1-31> <2000-2035>**

### Parameter

| | |
|---|---|
| **HH:MM:SS**<br><br>**(jan\|feb\|mar\|apr**<br><br>**\|may\|jun\|jul\|aug\|**<br>**sep\|oct\|nov\|dec)**<br>**<1-31> <2000-** | Specify static time of year, month, day, hour, minute,second |

### Default

No default is defined.

The clock set to 2000/01/01 08:00:00 by default at startup.

**Mode**

Privileged EXEC

**Usage**

Use the **clock set** command to set static time. The static time won't save to configuration file.
You can verify your setting by entering the **show clock Privileged EXEC** command.

**Example**

The example shows how to set static time of switch.

```
switch# clock set 11:03:00 sep 21 2012
11:03:00 DFL(UTC+8) Sep 21 2012

switch# show clock
11:03:21 DFL(UTC+8) Sep 21 2012
  No time source
```

## clock timezone

**Syntax**

**clock timezone ACRONYM HOUR-OFFSET [minutes <0-59>]**
**no clock timezone**

**Parameter**

| | |
|---|---|
| **ACRONYM** | Specify acronym name of time zone |
| **HOUR-OFFSET** | Specify hour offset of time zone |
| **Minutes <1-59>** | Specify minute offset of time zone |

**Default**

Default time zone is UTC+8.

**Mode**

Global Configuration

**Usage**

Use the **clock timezone** command to set timezone setting.
Use the **no** form of this command to restore to default setting.
You can verify your setting by entering the **show clock detail Privileged EXEC** command.

**Example**

The example shows how to set time zone of switch and then restore to default time zone.

```
switch(config)# clock timezone test +5
switch(config)# show clock detail
10:13:27 test(UTC+5) Sep 21 2012
No time source

Time zone: Acronym is test Offset is UTC+5

switch(config)# no clock timezone
switch(config)# show clock detail
13:14:50 DFL(UTC+8) Sep 21 2012
No time source

Time zone: Acronym is DFL Offset is UTC+8
```

## clock source

**Syntax**

**clock source (local|sntp)**

**Parameter**

| | |
|---|---|
| **local** | Specify to use static time |
| **sntp** | Specify to use sntp time |

### Default

Default is using local time.

### Mode

Global Configuration

### Usage

Use the **clock source** command to set the source of time.
Use the no form of this command to restore to default setting.
You can verify your setting by entering the **show clock detail Privileged EXEC** command.

### Example

The example shows how to set clock source of switch.

```
switch(config)# clock source sntp
switch(config)# show clock detail
08:32:12 test(UTC+5) Sep 21 2012
Time source is sntp

Time zone: Acronym is DFL Offset is UTC+8
```

## clock summer-time

### Syntax

**clock summer-time** *ACRONYM* **date** (**jan** | **feb** | **mar** | **apr** | **may** | **jun** | **jul** | **aug** | **sep** | **oct** | **nov** | **dec**) *<1-31> <2000-2037>HH:MM* (**jan** | **feb** | **mar** | **apr** | **may** | **jun** | **jul** | **aug** | **sep** | **oct** | **nov** | **dec**) *<1-31> <2000-2037> HH:MM [<1-1440>]*
**clock summer-time** *ACRONYM* **recurring (usa|eu)** [*<1-1440>*] **clock summer-time** *ACRONYM* **recurring** (*<1-5>* | **first** | **last**) (**sun** | **mon** | **tue** | **wed** | **thu** | **fri** | **sat**) (**jan** | **feb** | **mar** | **apr** | **may** | **jun** | **jul** | **aug** | **sep** | **oct** | **nov** | **dec**) *HH:MM* (*<1-5>* | **first** | **last**) (**sun** | **mon** | **tue** | **wed** | **thu** | **fri** | **sat**) (**jan** | **feb** | **mar** | **apr** | **may** | **jun** | **jul** | **aug** | **sep** | **oct** | **nov** | **dec**) *HH:MM* [*<1-1440>*]
**no clock summer-time**

### Parameter

| | |
|---|---|
| **ACRONYM** | Specify acronym name of time zone |
| **date** | Non recurring daylight saving time duration |
| **<1-1440>** | Adjust daylight saving time offset |
| **usa** | Using daylight saving time in the United States that starts on the second Sunday of March and ends on the first Sunday of November |
| **eu** | Using daylight saving time in the Europe that starts on the last Sunday in March and ending on the last Sunday in October |
| **recurring** | Specify ecurring daylight saving time duration. |

**Default**

No default daylight saving time is defined.

**Mode**

Global Configuration

**Usage**

Use the **clock summer-time** command to set daylight saving time for system time. The "**usa**" or "**eu**" means that use the global daylight saving policy which defined by international organization. In both the "**date**"and "**recurring**", the first part of the command specifies when summer time begins, and the second part specifies when it ends. All times are relative to the local time zone. The "**recurring**" means that adjust time every year within the month.
Use the no form of this command to default setting.
You can verify your setting by entering the **show clock detail Privileged EXEC** command.

**Example**

The example shows how to set clock summer time of switch. You can verify settings by the following show show clock command.

```
switch(config)# clock summer-time test recurring usa
switch(config)# show clock detail
08:32:12 test(UTC+5) Sep 21 2012
No time source
```

Time zone: Acronym is DFL Offset is UTC+8

Summertime: Acronym is test Recurring every year. Begins at 2 0 3 2:0
Ends at 1 0 11 2:0
Offset is 60 minutes.

## Sntp

### Syntax

**sntp host HOSTNAME [port <1-65535>]**
**no sntp**

### Parameter

| | |
|---|---|
| **HOSTNAME** | Specify ip address or hostname of sntp server |
| **sntp** | Specify server port of sntp server |

### Default

No default SNTP server defined. Default server port is 123 when server created.

### Mode

Global Configuration

### Usage

Use the sntp command to set remote SNTP server. Use the no form of this command to default setting.
You can verify your setting by entering the **show sntp Privileged EXEC** command.

### Example

The example shows how to set remote SNTP server of switch.

```
switch(config)# clock source sntp
switch(config)# sntp host 192.168.1.100
switch(config)# show sntp
SNTP is Enabled
SNTP Server address: 192.168.1.100
SNTP Server port: 123
```

## show clock

### Syntax

**show clock [detail]**

### Parameter

| | |
|---|---|
| detail | Show more detail information of clock |

### Default

No default is defined

### Mode

Privileged EXEC

### Usage

Use the **show clock** command to show clock of switch. The "**detail**" means that show more information of clock such as time zone and daylight saving time.

### Example

The example shows how to show clock of switch and detail information.

```
Switch334455(config)# show clock
14:34:43 DLS(UTC+9) Sep 25 2012
Time source is sntp
```

## show sntp

### Syntax

**show sntp**

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

Use the **show sntp** command to remote SNTP server information.

### Example

The example shows how to show remote SNTP server.

```
Switch334455(config)# show sntp
SNTP is Enabled
SNTP Server address: 192.168.1.100
SNTP Server port: 123
```

# 39. UDLD

## udld

### Syntax

**udld**
**no udld**

### Parameter

### Default

UDLD is disabled by default.

**Mode**

Interface Configuration

**Usage**

Use the **udld** command to enable UniDirectional Link Detection (UDLD) normal mode of interface.
Use the no form of this command to restore to default setting.You can verify your setting by entering the **show udld interface Privileged EXEC** command.

**Example**

The example shows how to enable UniDirectional Link Detection (UDLD) normal mode in interface gi1.

```
switch(config)# interface gi1
switch(config-if)# udld
switch# show udld interfaces gi1
Port enable administrative configuration setting: Enabled
Port enable operational state: Enabled
Current bidirectional state: Bidirectional
Current operational state: Advertisement - SINGLE NEIGHBOR DETECTED
```

## udld aggressive

**Syntax**

**udld aggressive**
**no udld aggressive**

**Parameter**

**Default**

UDLD aggressive mode is disabled by default.

**Mode**

Interface Configuration

**Usage**

Use the **udld aggressive** command to enable UniDirectional Link Detection (UDLD) aggressive mode of interface.
Use the no form of this command to restore to default setting.
You can verify your setting by entering the **show udld interface Privileged EXEC** command.

**Example**

The example shows how to enable udld aggressive mode in interface gi1.

```
switch(config)# interface gi1
switch(config-if)# udld
switch# show udld interfaces gi1
Port enable administrative configuration setting: Enabled / in aggressive mode
Port enable operational state: Enabled / in aggressive mode
Current bidirectional state: Bidirectional
Current operational state: Advertisement - SINGLE NEIGHBOR DETECTED
```

## udld message time

**Syntax**

**udld message time** *message-time-interval*

**Parameter**

| | |
|---|---|
| *message-time-interval* | Specify the interval for sending message.Range is 1 -90 seconds. |

**Default**

Default interval is 15 seconds.

**Mode**

Global Configuration

### Usage

Use the **udld message time** to set interval of UniDirectional Link Detection (UDLD) sent message.

### Example

The example shows how to set interval of UniDirectional Link Detection (UDLD) message.

```
switch(config)# udld message time 30
```

## udld reset

### Syntax

**udld reset**

### Parameter

### Default

No default is defined

### Mode

Privileged EXEC

### Usage

Use the **udld reset** command to reset all interfaces disabled by the UniDirectional Link Detection (UDLD) and permit traffic to begin passing through them again.
If the interface configuration is still enabled for UDLD, these ports begin to run UDLD again and are disabled for the same reason if the problem has not been corrected.

### Example

The example shows how to reset all interfaces disabled by UDLD

```
Switch# udld reset
1 ports shutdown by UDLD were reset.
```

## show udld

### Syntax

**show udld**
**show udld interfaces** *IF_NMLPORTS*

### Parameter

| | |
|---|---|
| *IF_NMLPORTS* | Specify the normal interfaces to display udld information |

### Default

No default is defined

### Mode

Privileged EXEC

### Usage

Use the **show udld** command to to display UniDirectional Link Detection (UDLD) administrative and operational status for all ports or the specified port.

### Example

The example shows how to show UniDirectional Link Detection (UDLD) settings and operational status of interface gi1.

```
Switch# show udld interfaces g1

Interface gi1
```

---
Port enable administrative configuration setting: Enabled / in aggressive mode
Port enable operational state: Enabled / in aggressive mode
Current bidirectional state: Unknown
Current operational state: Advertisement
Message interval: 7
Time out interval: 5
No neighbor cache information stored

# 40. VLAN

## vlan

### Syntax

**vlan**
**no vlan**

### Parameter

### Default

VLAN 1 created by default

### Mode

Global Configuration

### Usage

Use the **vlan** global configuration command to create VLAN. Use the **no** form of this command to remove exist VLAN.
You can verify your setting by entering the **show vlan Privileged EXEC** command.

### Example

The following example creates and removes a VLAN entry (100).

```
Switch# show vlan
VID | VLAN Name | Untagged Ports | Tagged Ports | Type
-------+---------------------------+---------------------------+-------------
-------+---------
1 |       default      | gi1-48,gi1-4,lag1-8 |                  --- | Default
100 |              VLAN0100 |       --- |      --- | Static
```

## Name (vlan)

### Syntax

### name NAME

### Parameter

| | |
|---|---|
| NAME | Specify the name of the VLAN (Max. 32 chars). |

### Default

Default name of new vlan is VLANxxxx. Xxxx is 4-digit vlan number.

### Mode

VLAN Configuration

### Usage

Use the **name** vlan configuration command to set name of vlan
You can verify your setting by entering the **show vlan Privileged EXEC** command.

### Example

This example sets the VLAN name of VLAN 100 to be `VLAN- one-hundred`.

```
SwitchEF0101(config)# vlan 100
SwitchEF0101(config-vlan)# name VLAN-one-hundred
```

```
Switch# show vlan
VID | VLAN Name | Untagged Ports | Tagged Ports | Type
-------+--------------------------+--------------------------+-----------------
---+---------
1 |       default    | fa1-48,gi1-4,lag1-8 |   --- | Default

100 | VLAN-one-hundred |         --- |     --- | Static
```

## switchport mode

### Syntax

**switchport mode ( access | hybrid | trunk [uplink] | tunnel )**

### Parameter

| | |
|---|---|
| access | Specify the VLAN mode to Access port. |
| hybrid | Specify the VLAN mode to Hybrid port. |
| trunk | Specify the VLAN mode to Trunk port. |
| uplink | Specify the Uplink property on this Trunk port. |
| tunnel | Specify the VLAN mode to Dot1Q Tunnel port. |

### Default

Default is trunk mode of all interfaces

### Mode

Port Configuration

### Usage

The VLAN mode is used to configure the port for different port role.
**Access port**: Accepts only untagged frames and join an untagged VLAN.
**Hybrid port**: Support all functions as defined in IEEE 802.1Q specification.

**Trunk port**: An untagged member of one VLAN at most, and is a tagged member of zero or more VLANs. If it is an uplink port, it can recognize double tagging on this port.
**Tunnel port**: Port-based Q-in-Q mode.

Use the **switch mode** port configuration command to set mode of interface You can verify your setting by entering the **show interfaces switchport Privileged EXEC** command.

### Example

This example sets VLAN mode to Access port.

```
Switch(config)# interface gi12
Switch(config-if)# switchport mode access
Switch# show interfaces switchport gi12
Port : gi12
Port Mode : Access
Ingress Filtering : enabled
Acceptable Frame Type : untagged-only
Ingress UnTagged VLAN ( NATIVE ) : 1
Trunking VLANs Enabled:

Port is member in:
Vlan    Name      Egress rule
------- ----------------------- -----------------
1    default        Untagged

Forbidden VLANs:
Vlan Name
------- ----------------------
```

## switchport hybrid pvid

### Syntax

**switchport hybrid pvid <1-4094>**

### Parameter

| | |
|---|---|
| <1-4094> | Specify the port-based VLAN ID on the Hybrid port. |

### Default

Default pivd is 1.

### Mode

Port Configuration

### Usage

Use the **switch hybrid pivd** port configuration command to set pvid of interface.
You can verify your setting by entering the **show interfaces switchport Privileged EXEC** command.

### Example

This example sets PVID to 100.

```
SwitchEF0101(config)# interface gi10
SwitchEF0101(config-if)# switchport mode hybrid
SwitchEF0101(config-if)# switchport hybrid pvid 100
SwitchEF0101# show interfaces switchport fa10
Port : gi10
Port Mode : Hybrid Ingress Filtering : enabled
Acceptable Frame Type : all
Ingress UnTagged VLAN ( NATIVE ) : 100
Trunking VLANs Enabled:

Port is member in:
Vlan     Name    Egress rule
------- ---------------------- -----------------
1   default        Untagged

Forbidden VLANs:
Vlan            Name
```

## switchport hybrid ingress-filtering

### Syntax

**switchport bybrid ingress-filtering**

**no switchport hybrid ingress-filtering**

**Parameter**

**Default**

Default is enabled

**Mode**

Port Configuration

**Usage**

Use the **switchport hybrid ingress-filtering** port configuration command to enable vlan ingress filter.
Use the **no** form of this command to disable.
You can verify your setting by entering thes **show interfaces switchport Privileged EXEC** command.

**Example**

This example sets ingress-filtering to disable.

```
SwitchEF0101(config)# interface gi10
SwitchEF0101(config-if)# switchport mode hybrid
SwitchEF0101(config-if)#no switchport hybrid ingress-filtering
SwitchEF0101# show interfaces switchport gi10
Port : gi10
Port Mode : Hybrid Ingress Filtering : disabled
Acceptable Frame Type : all
Ingress UnTagged VLAN ( NATIVE ) : 100
Trunking VLANs Enabled:

Port is member in:
Vlan     Name    Egress rule
------- ---------------------- -----------------
1   default        Untagged

Forbidden VLANs:
Vlan Name
```

## switchport hybrid acceptable-frame-type

## Syntax

**switchport hybrid acceptable-frame-type ( all | tagged-only | untagged-only )**

## Parameter

| | |
|---|---|
| all | Specify to accept all frames. |
| tagged-only | Specify to only accept tagged frames. |
| untagged-only | Specify to only accept untagged frames. |

## Default

Default is accept all frames

## Mode

Port Configuration

## Usage

Use the **switchport hybrid accept-frame-type** port configuration command to choose which type of frame can be accepted.
You can verify your setting by entering the **s show interfaces switchport Privileged EXEC** command

## Example

This example sets acceptable-frame-type to tagged-only.

SwitchEF0101(config)# interface fa10
SwitchEF0101(config-if)# switchport mode hybrid
SwitchEF0101(config-if)# switchport hybrid acceptable-frame-type tagged- only
SwitchEF0101# show interfaces switchport fa10 Port : fa10
Port Mode : Nybrid Ingress Filtering : disabled
Acceptable Frame Type : tagged-only
Ingress UnTagged VLAN ( NATIVE ) : 100
Trunking VLANs Enabled:

Port is member in:

```
Vlan     Name    Egress rule
------- ---------------------- ----------------
1   default        Untagged

Forbidden VLANs:
Vlan             Name
```

## switchport hybrid allowed vlan

### Syntax

**switchport hybrid allowed vlan add** *VLAN-LIST* **[(tagged|untagged)]**
**switchport hybrid allowed vlan remove** *VLAN-LIST*

### Parameter

| | |
|---|---|
| *VLAN-LIST* | Specifies the VLAN list to be added or remove. |
| ( tagged \|untagged ) | Specifies the member type is tagged or untagged. |

### Default

Only vlan 1 is untagged member by default. Default is tagged member when added.

### Mode

Port Configuration

### Usage

Use the **switchport hybrid allow vlan add** port configuration command to allow vlan on interface.
Use the **switchport hybrid allow vlan remove** port configuration command to remove vlan on interface.
You can verify your setting by entering the **s show interfaces switchport Privileged EXEC** command.

### Example

This example sets port fa10 VLAN to join the VLAN 100 as tagged member.

```
Switch(config)# interface gi10
Switch(config-if)# switchport hybrid allowed vlan add 100-105
Switch(config-if)# switchport hybrid allowed vlan remove 105
Switch# show interfaces switchport gi10
Port : gi10
Port Mode : Hybrid Ingress Filtering : disabled
Acceptable Frame Type : tagged-only
Ingress UnTagged VLAN ( NATIVE ) : 100
Trunking VLANs Enabled:

Port is member in:
Vlan      Name    Egress rule
------- ---------------------------------- -----------------
1         default  Untagged
      VLAN-one-hundred Tagged
VLAN0101        Tagged
VLAN0102        Tagged
VLAN0103        Tagged
VLAN0104        Tagged

Forbidden VLANs:
Vlan      Name
------- ----------------------
```

## switchport access vlan

### Syntax

**switchport access vlan <1-4094>**
**No switchport access vlan**

### Parameter

| | |
|---|---|
| <1-4094> | Specifies the access VLAN ID. |

### Default

Default is vlan 1

### Mode

Port Configuration

### Usage

Use the **switchport access vlan** port configuration command to set native vlan on interface. The vlan will be pvid on interface as well.
Use the **no** form of this command to restore to default vlan
You can verify your setting by entering the **s show interfaces switchport Privileged EXEC** command.

### Example

This example sets Access port gi10 native VLAN ID to 100.

```
Switch(config)# interface gi10
Switch(config-if)# switchport mode access
Switch(config-if)# switchport access vlan 100
Switch# show interfaces switchport gi10
Port : gi10
Port Mode : Access Ingress Filtering : enabled
Acceptable Frame Type : untagged-only
Ingress UnTagged VLAN ( NATIVE ) : 100
Trunking VLANs Enabled:

Port is member in:
Vlan Name         Egress rule
------- ----------------------        -----------------
100 VLAN-one-hundred Untagged

Forbidden VLANs:
Vlan       Name
------- ----------------------
```

## switchport tunnel vlan

### Syntax

**switchport tunnel vlan <1-4094>**
**no switchport tunnel vlan**

### Parameter

| | |
|---|---|
| <1-4094> | Specifies the tunnel VLAN ID. |

**Default**

Default is vlan 1

**Mode**

Port Configuration

**Usage**

Use the **switchport tunnel vlan** port configuration command to set dot1q tunnel vlan on interface. The vlan will be pvid on interface as well.
Use the **no** form of this command to remove vlan on interface. The tunnel vlan id will set to reserve vlan 4095.
You can verify your setting by entering the **s show interfaces switchport Privileged EXEC** command.

**Example**

This example sets Tunnel port gi10 native VLAN to 100.

```
Switch(config)# interface gi10
Switch(config-if)# switchport mode tunnel
Switch(config-if)# switchport tunnel vlan 100
Switch# show interfaces switchport gi10
Port : gi10
Port Mode : Tunnel Ingress Filtering : enabled
Acceptable Frame Type : all
Ingress UnTagged VLAN ( NATIVE ) : 100
Trunking VLANs Enabled:

Port is member in:
Vlan Name         Egress rule
------- ----------------------        -----------------
100 VLAN-one-hundred Untagged

Forbidden VLANs:
Vlan      Name
 ------- ----------------------
```

## switchport trunk native vlan

## Syntax

**switchport trunk native vlan <1-4094>**
**no switchport trunk native vlan**

## Parameter

| | |
|---|---|
| <1-4094> | Specifies the native VLAN ID. |

## Default

Default is vlan 1

## Mode

Port Configuration

## Usage

Use the **switchport trunk native vlan** port configuration command to set native vlan on interface.
Use the **no** form of this command to restore to default vlan.
You can verify your setting by entering the **s show interfaces switchport Privileged EXEC** command.

## Example

This example sets Trunk port gi10 native VLAN to 100.

```
Switch(config)# interface gi10
Switch(config-if)# switchport mode trunk
Switch(config-if)# switchport trunk native vlan 100
Switch# show interfaces switchport gi10
Port : gi10
Port Mode : Trunk Ingress Filtering : enabled
   Acceptable Frame Type : all
Ingress UnTagged VLAN ( NATIVE ) : 100
Trunking VLANs Enabled:

Port is member in:
Vlan Name        Egress rule
```

------- ---------------------- ----------------
100 VLAN-one-hundred Untagged

Forbidden VLANs:
Vlan Name

## switchport trunk allowed vlan

### Syntax

**switchport trunk allowed vlan ( add | remove ) ( VLAN-LIST | all )**

### Parameter

| | |
|---|---|
| ( add \| remove ) | Specify the action to add or remove the allowed VLAN list. |
| ( VLAN-LIST \| all ) | Specify the VLAN list or all VLANs to be added or removed. |

### Default

Default is vlan 1

### Mode

Port Configuration

### Usage

Use the **switchport trunk allow vlan add** port configuration command to allow vlan on interface.
Use the **switchport trunk allow vlan remove** port configuration command to remove vlan on interface.
You can verify your setting by entering the **s show interfaces switchport Privileged EXEC** command.

### Example

This example sets Trunk port gi10 to add the allowed VLAN 100.

```
Switch(config)# interface gi10
Switch(config-if)# switchport trunk allowed vlan add 100
Switch# show interfaces switchport gi10
Port : gi10
Port Mode : Trunk
Ingress Filtering : enabled
Acceptable Frame Type : all
Ingress UnTagged VLAN ( NATIVE ) : 1
Trunking VLANs Enabled: 100

Port is member in:
Vlan Name        Egress rule
------- ---------------------- -----------------
1 default          Untagged
100 VLAN-one-hundred Tagged

Forbidden VLANs:
Vlan     Name
  ------- ----------------------
```

## switchport default-vlan tagged

### Syntax

**switchport default-vlan tagged**
**no switchport default-vlan tagged**

### Parameter

### Default

Default is untagged

### Mode

Port Configuration

### Usage

Use the **switchport default vlan tagged** port configuration command to become default vlantaggedmember.
Use the **no switchport default vlan tagged** port configuration command to restore to default

You can verify your setting by entering the **s show interfaces switchport Privileged EXEC** command

**Example**

This example sets Trunk port gi10 membership with the default VLAN to tag.

```
Switch(config)# interface gi10
Switch(config-if)# switchport default-vlan tagged
Switch# show interfaces switchport gi10
Port : gi10
Port Mode : Hybrid Ingress Filtering : enabled
Acceptable Frame Type : all
Ingress UnTagged VLAN ( NATIVE ) : 1
Trunking VLANs Enabled:

Port is member in:
Vlan    Name      Egress rule
------- ---------------------- -----------------
1    default        Tagged

Forbidden VLANs:
Vlan Name
   ------- ----------------------
```

## switchport forbidden default-vlan

**Syntax**

**switchport forbidden default-vlan**

**no switchport forbidden default-vlan**

**Parameter**

**Default**

Default is allowed

**Mode**

Port Configuration

### Usage

Use the **switchport forbidden default-vlan** port configuration command to forbid default-vlan on interface.
Use the **no switchport forbidden default-vlan** port configuration command to restore to default
You can verify your setting by entering the **s show interfaces switchport Privileged EXEC** command

### Example

This example sets the membership of the default VLAN with port gi10 to forbidden.

```
Switch(config)# interface gi10
Switch(config-if)# switchport forbidden default-vlan
Switch# show interfaces switchport gi10
Port : gi10
Port Mode : Trunk Ingress Filtering : enabled
Acceptable Frame Type : all
Ingress UnTagged VLAN ( NATIVE ) : 4095
Trunking VLANs Enabled:

Port is member in:
Vlan     Name    Egress rule
------- ---------------------- ----------------

Forbidden VLANs:
Vlan     Name
------- ----------------------
1        default
```

## switchport forbidden vlan

### Syntax

**switchport forbidden vlan ( add | remove )** *VLAN-LIST*

### Parameter

| | |
|---|---|
| (add \| remove) | Add or remove forbidden membership. |
| *VLAN-LIST* | Specify the VLAN list. |

### Default

No vlan is forbidden by default

### Mode

Port Configuration

### Usage

Use the **switchport forbidden vlan add** port configuration command to forbid vlan on interface.
Use the **switchport forbidden vlan remove** port configuration command to accpet vlan on interface.
You can verify your setting by entering the **s show interfaces switchport Privileged EXEC** command

### Example

This example sets the membership of the VLAN 100 with port gi10 to forbidden.

```
Switch(config)# interface gi10
Switch(config-if)# switchport forbidden vlan add 100
Switch# show interfaces switchport gi10
Port : gi10
Port Mode : Trunk Ingress Filtering : enabled
Acceptable Frame Type : all
Ingress UnTagged VLAN ( NATIVE ) : 1
Trunking VLANs Enabled: 100

Port is member in:
Vlan      Name    Egress rule
------- ---------------------- -----------------
1         default  Untagged

Forbidden VLANs:
Vlan Name
------- -----------------------
100 VLAN-one-hundred
```

## switchport vlan tpid

### Syntax

**switchport vlan tpid (0x8100|0x88a8|0x9100|0x9200)**

### Parameter

| | |
|---|---|
| (0x8100\|0x88a8\|0x9100\|0x9200) | Select TPID to set. |

### Default

Default TPID is 0x8100

### Mode

Port Configuration

### Usage

Use the **switchport vlan tpid** port configuration command to set TPID on interface.
You can verify your setting by entering the **s show running-config Privileged EXEC** command

### Example

This example sets the TPID to 0x9100 on interface gi10.

```
Switch(config)# interface gi10
Switch(config-if)# switchport vlan tpid 0x9100
```

## management-vlan

### Syntax

**management-vlan vlan <1-4094>**
**no management-vlan**

### Parameter

| | |
|---|---|
| <1-4094> | Specify the VLAN ID of management-vlan. |

**Default**

Default management vlan is 1.

**Mode**

Global Configuration

**Usage**

Use the **management vlan** Global Configuration mode command to set management vlan id. Vlan id must be created first.
Use the **no** form of this command to restore to default setting.
You can verify your setting by entering the **show management-vlan Privileged EXEC** command

**Example**

The following example specifies that management vlan 2 is created

```
Switch(config)#vlan 2
Switch(config)# management-vlan vlan 2
```

The following example specifies that management-vlan is restored to be default VLAN.

```
Switch(config)# no management-vlan
```

## show vlan

**Syntax**

**show vlan [(***VLAN-LIST***|dynamic|static)]**

**Parameter**

| | |
|---|---|
| (*VLAN-LIST*\|dynamic\|static) | Specify vlan id to show information or show all static or dynamic vlan entries. |

**Default**

**Mode**

Privileged EXEC

**Usage**

Display information about vlan entry

**Example**

The following example specifies that show vlan

```
Switch# show vlan
VID | VLAN Name | Untagged Port | Tagged Port | Type
-------+-------------------------+-------------------------+---------------+---
------
1 |default  | fa1-8,fa10-48,lag1-8 |--- | Default
100 | VLAN-one-hundred |     --- |     --- | Static
101 |      VLAN0101 |         --- |    --- | Static
102 |      VLAN0102 |       --- |      --- | Static
```

## show vlan interface membership

**Syntax**

**show vlan VLAN-LIST interfaces IF_PORTS membership**

**Parameter**

| | |
|---|---|
| <VLAN-List> | Specify vlan to show |
| IF_PORTS | Specify interface is to show |

### Default

### Mode

Privileged EXEC

### Usage

Display information about vlan membership on interfaces.

### Example

The following example specifies that show vlan interface membership

```
Switch# show vlan 100 interfaces gi10 membership
VLAN ID : 100
VLAN Type : Static
---------+--------------
Port     | Membership
---------+--------------
gi10 | Excluded
---------+--------------
```

## show interface switchport

### Syntax

**show interface switchport interfaces** *IF_PORTS*

### Parameter

| | |
|---|---|
| IF_PORTS | Specify interfaces protocol vlan to display |

### Default

### Mode

Privileged EXEC

### Usage

Display information about default vlan

### Example

The following example specifies that show interfacce switchport.

```
Switch(config)# interface gi10
Switch(config-if)# switchport trunk allowed vlan add 100
Switch# show interfaces switchport gi10
Port : gi10
Port Mode : Trunk
Ingress Filtering : enabled
Acceptable Frame Type : all
Ingress UnTagged VLAN ( NATIVE ) : 1
Trunking VLANs Enabled: 100

Port is member in:
Vlan    Name      Egress rule
------- ----------------------        ---------------
1   default        Untagged
100   VLAN-one-hundred          Tagged

Forbidden VLANs:
Vlan      Name
```

## show management-vlan

### Syntax

### show management-vlan

### Parameter

### Default

### Mode

Privileged EXEC

### Usage

Display information about management vlan

**Example**

The following example specifies that show management vlan

```
Switch(config)# show management-vlan
Management VLAN-ID : default(1)
```

# 41. Voice VLAN

## voice-vlan (Global)

**Syntax**

**voice-vlan**
**no voice-vlan**

**Parameter**

**Default**

Voice VLAN is disabled

**Mode**

Global Configuration

**Usage**

Use the **voice vlan** global configuration command to enable the functional Voice VLAN on the device.
Use the **no** form of this command to disable voice vlan function.
You can verify your setting by entering the **show voice vlan Privileged EXEC** command.

**Example**

The following example shows how to enable voice vlan.

```
Switch(config)# voice-vlan
Switch# show voice-vlan
Administrate Voice VLAN state : disabled
Voice VLAN ID   : none (disable)
Voice VLAN Aging          : 1440 minutes
Voice VLAN CoS            6
Voice VLAN 1p Remark: disabled
```

## voice-vlan (Interface)

### Syntax

**voice-vlan**
**no voice-vlan**

### Parameter

### Default

The default all port admin-staus is disabled.

### Mode

Interface Configuration

### Usage

Use the **voice vlan** Interface configuration command to enable OUI voice VLAN configuration on an interface
Use the **no** form of this command to disable voice vlan on an interfaces You can verify your setting by entering the **show voice vlan Privileged EXEC** command

### Example

The following example how to enable voice VLAN function in oui mode on an interface

```
Switch(config)#interface range gi1-3
Switch(config-if)#voice-vlan
```

```
Switch# show voice-vlan interfaces gi1-8
Voice VLAN Aging          : 1440 minutes
Voice VLAN CoS            7
Voice VLAN 1p Remark: enabled

OUI table
OUI MAC | Description
--------------------+----------------
00:E0:BB | 3COM
00:03:6B | Cisco
00:E0:75 | Veritel
00:D0:1E | Pingtel
00:01:E3 | Siemens
00:60:B9 | NEC/Philips
00:0F:E2 | H3C
00:09:6E | Avaya

   Port | State       | Port Mode     | Cos Mode
-------+-----------+-------------+-----------
gi1      | Disabled |      Auto       | Src
gi2      | Disabled |      Auto       | Src
gi3      | Disabled |      Auto       | Src
gi4      | Disabled |      Auto       | Src
gi5      | Disabled |      Auto       | Src
gi6      | Disabled |      Auto       | Src
gi7      | Disabled |      Auto       | Src
gi8      | Disabled |      Auto       | Src
```

## voice-vlan vlan

### Syntax

**voice-vlan vlan** <1-4094>
**no voice-vlan vlan**

### Parameter

| | |
|---|---|
| <1-4094> | Specify the voice VLAN ID |

### Default

The default Voice VLAN ID is None.

### Mode

Global Configuration

### Usage

Use the **voice vlan id** global configuration command to configure the VLAN identifier of the voice VLAN statically.
Use the **no** form of this command to restore voice vlan id to default. You can verify your setting by entering the **show voice vlan Privileged EXEC** command

### Example

The following example shows how to set Voice vlan id. The vlan id must be created first.

```
Switch(config)# voice-vlan vlan 128
Switch# show voice-vlan
Administrate Voice VLAN state : enabled
Voice VLAN ID   128
Voice VLAN Aging        : 1440 minutes
Voice VLAN CoS          6
Voice VLAN 1p Remark: disabled
```

## voice-vlan oui-table

### Syntax

**voice-vlan oui-table** *A:B:C* [*DESCRIPTION*]
**no voice-vlan oui-table** [*A:B:C*]

### Parameter

| | |
|---|---|
| A:B:C | Specify OUI Mac address to add or remove |
| DESCRIPTION | Specify description of the specified MAC address to the voice VLAN OUI table |

### Default

The system default has 8 oui addresses.

**Mode**

Global Configuration

**Usage**

Use the **voice vlan oui-table** global configuration command to add oui mac address to OUI Table
Use the **no** form of this command to remove all or specified oui mac address..
You can verify your setting by entering the **show voice vlan Privileged EXEC** command

**Example**

This following example shows how to add OUI Mac.

```
Switch(config)# voice-vlan oui-table 00:01:02  “Test”
Switch# show voice-vlan interfaces all
Voice VLAN Aging          : 1440 minutes
Voice VLAN CoS            6
Voice VLAN 1p Remark: disabled

OUI table
OUI MAC | Description
-------------------+-----------------
00:E0:BB | 3COM
00:03:6B | Cisco
00:E0:75 | Veritel
00:D0:1E | Pingtel
00:01:E3 | Siemens
00:60:B9 | NEC/Philips
00:0F:E2 | H3C
00:09:6E | Avaya
00:01:02 | Test

Port    | State      | Port Mode | Cos Mode
---------+-----------+------------------+-----------
gi1    | Disabled |     Auto     | Src
fa2    | Disabled |     Auto     | Src
fa3 | Disabled | Auto | Src
   ……
```

## voice-vlan cos (Global)

### Syntax

**voice-vlan cos** <0-7> [remark]
**no voice-vlan cos**

### Parameter

| | |
|---|---|
| <0-7> | Specify the voice VLAN Class of Service value in telephone oui mode |
| remark | Specify that the L2 user priority is remarked with the CoS value |

### Default

The default cos value is 6, remark is disabled.

### Mode

Global Configuration

### Usage

Use the **voice vlan cos** global configuration command to configure the voice VLAN cos value and 1p remark function
Use the "**no**" form to restore to default mode.
You can verify your setting by entering the **show voice vlan Privileged EXEC** command

### Example

The following example show how to set cos value and enable 1p remark function

```
Switch(config)# voice-vlan cos 7 remark
Switch# show voice-vlan
Administrate Voice VLAN state : disabled
Voice VLAN ID           128
Voice VLAN Aging        : 1440 minutes
Voice VLAN CoS          7
Voice VLAN 1p Remark: enabled
```

## voice-vlan cos (Interface)

### Syntax

**voice-vlan cos ( src | all )**
**no voice-vlan cos**

### Parameter

| | |
|---|---|
| src | Specify QoS attributes are applied to packets with OUIs in the source MAC address. |
| All | Specify QoS attributes are applied to packets that are classified to the Voice VLAN. |

### Default

The default all port in Src mode.

### Mode

Interface configuration

### Usage

Use the **voice vlan cos** Interface configuration command to configure OUI voice VLAN cos mode configuration on an interface
Use the "**no**" form to restore to default mode.
You can verify your setting by entering the **show voice-vlan interfaces Privileged EXEC** command

### Example

The following example how to configure voice packet QoS attributes on an interface

```
Switch(config)#interface range gi1-3
Switch(config-if)#voice-vlan cos all
Switch# show voice-vlan interfaces gi1-8
Voice VLAN Aging       : 1440 minutes
```

```
Voice VLAN CoS          : 6
Voice VLAN 1p Remark: disabled

OUI table
    OUI MAC       |     Description
--------------+-----------------
    00:E0:BB     | 3COM
    00:03:6B     | Cisco
    00:E0:75     | Veritel
    00:D0:1E     | Pingtel
    00:01:E3     | Siemens
    00:60:B9     | NEC/Philips
    00:0F:E2     | H3C
    00:09:6E     | Avaya

   Port | State       | Port Mode     | Cos Mode
-------+----------+-------------+-----------
gi1      | Disabled |      Auto       | All
gi2      | Disabled |      Auto       | All
gi3      | Disabled |      Auto       | All
gi4      | Disabled |      Auto       | Src
gi5      | Disabled |      Auto       | Src
gi6      | Disabled |      Auto       | Src
gi7      | Disabled |      Auto       | Src
gi8      | Disabled |      Auto       | Src
```

## voice-vlan mode

### Syntax

**voice-vlan mode (auto|manual)**
**no voice-vlan mode**

### Parameter

| | |
|---|---|
| **auto** | Specifies that the port is identified as a candidate to join the voice VLAN. When a packet with a source OUI MAC address that identifies the remote equipment as voice equipment is seen on the port, the port joins the voice VLAN as a tagged port. |
| **manual** | Specifies that the port is manually assigned to the voice VLAN. |

**Default**

The default is auto mode.

**Mode**

Interface Configuration

**Usage**

Use the **voice-vlan mode** global configuration command to configure the voice VLAN mode for interface.
Use the "**no**" form to restore to default mode.
You can verify your setting by entering the **show voice-vlan interfaces Privileged EXEC** command.

**Example**

The following example how to configure voice mode to manual

```
Switch(config)#interface range gi1-3
Switch(config-if)#voice-vlan mode manaul
Switch# show voice-vlan interfaces gi1-8
Voice VLAN Aging       : 1440 minutes
Voice VLAN CoS         : 6
Voice VLAN 1p Remark: disabled

OUI table
    OUI MAC       |     Description
-------------+-----------------
    00:E0:BB     | 3COM
    00:03:6B     | Cisco
    00:E0:75     | Veritel
    00:D0:1E     | Pingtel
    00:01:E3     | Siemens
    00:60:B9     | NEC/Philips
    00:0F:E2     | H3C
    00:09:6E     | Avaya

   Port | State       | Port Mode     | Cos Mode
-------+----------+-------------+-----------
gi1      | Disabled |      manaul        | All
gi2      | Disabled |      manaul        | All
gi3      | Disabled |      manaul        | All
gi4      | Disabled |      Auto        | Src
```

gi5 | Disabled | Auto | Src
gi6 | Disabled | Auto | Src
gi7 | Disabled | Auto | Src
gi8 | Disabled | Auto | Src

## voice-vlan aging-time

### Syntax

**voice-vlan aing-time** <30-65536>
**no voice-vlan aing-time**

### Parameter

| | |
|---|---|
| <30-65536> | Specify the voice VLAN aging timeout interval in minutes |

### Default

The default aging-timeout value is 1440 minutes

### Mode

Global Configuration

### Usage

Use the **voice vlan aging-time** global configuration command to configure the voice VLAN aging timeout.
Use the "**no**" form to restore to default time.
You can verify your setting by entering the **show voice vlan Privileged EXEC** command

### Example

The following example shows how to set aging time.

```
Switch(config)# voice-vlan aging-time 720
Switch# show voice-vlan
```

Administrate Voice VLAN state : disabled
Voice VLAN ID 1
Voice VLAN Aging : 720 minutes
Voice VLAN CoS 5
Voice VLAN 1p Remark: enabled

## show voice-vlan

### Syntax

**show voice-vlan**
**show voice-vlan interfaces [**IF_PORTS]

### Parameter

| | |
|---|---|
| IF_PORTS | Specifies intefaces to display voice VLAN settings in oui mode |

### Default

### Mode

Privileged EXEC

### Usage

Use the **show voice vlan** command in EXEC mode to display the voice VLAN status for all interfaces or for a specific interface if the voice VLAN type is OUI

### Example

The following example show how to display voice vlan oui mode settings

Switch# **show voice-vlan**

Administrate Voice VLAN state : disabled

Voice VLAN ID : none (disable)
Voice VLAN Aging : 720 minutes
Voice VLAN CoS 6
Voice VLAN 1p Remark: disabled

Switch# **show voice-vlan interfaces**
**gi1-4** Voice VLAN Aging : 720 minutes Voice VLAN CoS 5
Voice VLAN 1p Remark: enabled

OUI table
OUI MAC | Description
---
---
00:E0:BB | 3COM
00:03:6B | Cisco
00:E0:75 | Veritel
00:D0:1E | Pingtel
00:01:E3 | Siemens
00:60:B9 | NEC/Philips
00:0F:E2 | H3C
00:09:6E | Avaya

Port | State | Port Mode | Cos Mode
---
gi1 | Disabled | Auto |
Src
gi2 | Disabled | Auto |
Src
gi3 | Disabled | Auto
| Src
gi4 | Disabled | Auto | Src