




NOTE:

1. Electrical test:

- (1). 100% open short & miss wire test
- (2). Insulation resistance: DC 300V 10M ohm
- (3). Contactor resistance: 3 ohm
- (4). Dielectric strength: 150V AC/Sec, 1mA
- (5). HD-TV test 4k*2k 60Hz

2. Printing: High Speed HDMI® Cable with Ethernet

MATERIAL LIST:

④	OUTER MOLD	PVC 88A Black	2	
③	INNER MOLD	LD-PE	2	
②	CONNOCOTR	19P A/M Crimping type, Gold Plated Pin, Gold Plated Shell	2	
①	CABLE	HDMI (1/30AWG CCS*1P+E+A+MYLAR)*5+1/30AWG CCS*4C+AE PVC/Black OD: 6.0±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	Q'TY	REMARK

Item No.	Length (mm)
S3700	1000 ± 30
S3701	2000 ± 50
S3702	3000 ± 70

DESC. STANDARD Ultra HDMI Cable + Ethernet, AM/AM, black

SECOMP

BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.
	Fergus	NEW	2016-06-03	A